



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE5005SM thru NTE5031SM Zener Diode, 300mW $\pm 5\%$ Tolerance

Features:

- Zener Voltage 3.3V to 24V
- SOT-23 Type Surface Mount Package

Absolute Maximum Ratings:

Maximim Repetitive Peak Forward Current, I_{FPM}	250mA
Maximim Repetitive Peak Working Current, I_{ZRM}	250mA
Forward Voltage ($I_F = 10\text{mA}$, $T_J = +25^\circ\text{C}$), V_F	900mV
Total Power Dissipation ($T_A \leq +25^\circ\text{C}$, Note 1), P_{tot}	350mW
Maximum Junction Temperature, T_J	+175°C
Storage Temperature Range, T_{stg}	-65° to +175°C

Thermal Characteristics: ($T_J = P \times (R_{thJT} + R_{thSA}) + T_A$)

Thermal Resistance

Junction-to-Tab, R_{thJT}	50K/W
Tab-to-Soldering Points, R_{thTS}	280K/W
Soldering Points-to-Ambient (Note 1), R_{thSA}	90K/W

Note 1. Device mounted on a ceramic substrate of 8mm x 10mm x 0.7mm.

Electrical Characteristics: ($T_J = +25^\circ\text{C}$, unless otherwise specified)

NTE Type No.	Nominal Zener Voltage $V_z @ I_{zt}$	Zener Test Current I_{zt}	Reverse Current $I_R @ V_R$	Typical Differential Resistance $r_{diff} @ I_{zt}$	Typical Temperature Coefficient $S_z @ I_{zt}$	Typical Diode Capacitance C_d (Note 2)
	V	mA		Ω	mV/K	pF
5005SM	3.3	5	5 μA	1V	85	-2.4
5006SM	3.6	5	5 μA	1V	85	-2.4
5007SM	3.9	5	3 μA	1V	85	-2.5
5008SM	4.3	5	3 μA	1V	80	-2.5
5010SM	5.1	5	2 μA	2V	40	-0.8
5011SM	5.6	5	1 μA	2V	15	1.2
5013SM	6.2	5	3 μA	4V	10	0.4
5014SM	6.8	5	2 μA	4V	15	1.2
5015SM	7.5	5	1 μA	5V	6	4.0
5018SM	9.1	5	500nA	6V	6	5.5
5021SM	12.0	5	100nA	0.7V _{Znom}	10	8.4
5024SM	15.0	5	50nA	0.7V _{Znom}	10	11.4
5027SM	18.0	5	50nA	0.7V _{Znom}	10	14.4
5031SM	24.0	5	50nA	0.7V _{Znom}	25	20.4
						33

Note 2. $V_R = 0$, $f = 1\text{MHz}$.

