

PTB 20249



2.5 Watts, 1465–1513 MHz

Cellular Radio RF Power Transistor

Description

The 20249 is a class AB, NPN, common emitter RF power transistor intended for 26 Vdc operation from 1465 to 1513 MHz. Rated at 2.5 watts minimum output power, it may be used for both CW and PEP applications. Ion implantation, nitride surface passivation and gold metallization are used to ensure excellent device reliability. 100% lot traceability is standard.

- 2.5 Watts, 26 Vdc
- Class AB Characteristics
- Surface Mountable
- Available in Tape and Reel
- Gold Metallization
- Silicon Nitride Passivated



Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CER}	55	Vdc
Collector-Base Voltage	V_{CBO}	55	Vdc
Emitter-Base Voltage (collector open)	V_{EBO}	4	Vdc
Collector Current (continuous)	I_C	0.5	Adc
Total Device Dissipation at $T_{flange} = 25^\circ\text{C}$ Above 25°C derate by	P_D	10 0.057	Watts W/°C
Storage Temperature Range	T_{STG}	-40 to +150	°C
Thermal Resistance ($T_{flange} = 70^\circ\text{C}$)	$R_{\theta JC}$	17.5	°C/W

Electrical Characteristics (100% Tested)


Characteristic	Conditions	Symbol	Min	Typ	Max	Units
Breakdown Voltage C to E	$I_B = 0\text{ A}, I_C = 5\text{ mA}, R_{BE} = 22\ \Omega$	$V_{(BR)CER}$	55	—	—	Volts
Breakdown Voltage C to E	$V_{BE} = 0\text{ V}, I_C = 5\text{ mA}$	$V_{(BR)CES}$	55	—	—	Volts
Breakdown Voltage E to B	$I_C = 0\text{ A}, I_E = 5\text{ mA}$	$V_{(BR)EBO}$	4	5	—	Volts
DC Current Gain	$V_{CE} = 5\text{ V}, I_C = 250\text{ mA}$	h_{FE}	20	—	—	—

RF Specifications (100% Tested)

Characteristic	Symbol	Min	Typ	Max	Units
Gain ($V_{CC} = 26\text{ Vdc}, P_{out} = 1\text{ W}, I_{CQ} = 25\text{ mA}, f = 1513\text{ MHz}$)	G_{pe}	9.5	11.5	—	dB
Power Output at 1 dB Compression ($V_{CC} = 26\text{ Vdc}, I_{CQ} = 25\text{ mA}, f = 1513\text{ MHz}$)	P-1dB	2.5	3.5	—	Watts
Load Mismatch Tolerance ($V_{CC} = 26\text{ Vdc}, P_{out} = 5\text{ W}, I_{CQ} = 25\text{ mA}, f = 1513\text{ MHz}$ —all phase angles at frequency of test)	Ψ	—	—	5:1	—

Impedance Data (data shown for fixed-tuned broadband circuit)

($V_{CC} = 26\text{ Vdc}, P_{out} = 2.5\text{ W}, I_{CQ} = 25\text{ mA}$)



Frequency MHz	Z Source		Z Load	
	R	jX	R	jX
1465	17.90	12.50	10.50	25.40
1489	17.60	12.90	10.40	26.10
1513	17.30	13.40	10.40	26.70

