

LOW-NOISE DUAL OPERATIONAL AMPLIFIER


■ GENERAL DESCRIPTION

The NJM2041 is a bipolar operational amplifier which is designed as low noise version of the NJM4558 with high output current and fast slew rate ($3V/\mu s$) and wide unity gain bandwidth (7MHz) constructed using New JRC Planar epitaxial process.


■ FEATURES

- Operating Voltage $(\pm 4V \sim \pm 22V)$
- High Onput Current $(25mA.)$
- Slew Rate $(3V/\mu s \text{ typ.})$
- Unity Gain Bandwidth $(7MHz \text{ typ.})$
- Package Outline DIP8, DMP8, SIP8
- Bipolar Technology

■ PIN CONFIGURATION




■ PACKAGE OUTLINE



PIN FUNCTION

1. A OUTPUT
2. A-INPUT
3. A+INPUT
4. V-
5. B+INPUT
6. B-INPUT
7. B OUTPUT
8. V+

■ EQUIVALENT CIRCUIT (1/2 Shown)



■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

| PARAMETER | SYMBOL | RATINGS | UNIT |
|-----------------------------|--------------------------------|--|------|
| Supply Voltage | V ⁺ /V ⁻ | ±22 | V |
| Differential Input Voltage | V _{ID} | ±30 | V |
| Input Voltage | V _{IC} | ±15 (note) | V |
| Power Dissipation | P _D | (DIP8) 500 (DIM8) 300 (SIP8) 800 | mW |
| Operating Temperature Range | T _{opr} | -20~+75 | °C |
| Storage Temperature Range | T _{stg} | -40~+125 | °C |

(note) For supply voltage less than ±15V, the absolute maximum input voltage is equal to the supply voltage.

■ ELECTRICAL CHARACTERISTICS

(Ta=25°C, V⁺/V⁻=±15V)

| PARAMETER | SYMBOL | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|---------------------------------|------------------|---|------|-------|------|-------|
| Input Offset Voltage | V _{IO} | R _S ≤10kΩ | — | 0.3 | 3 | mV |
| Input Offset Current | I _{IO} | — | — | 10 | 200 | nA |
| Input Bias Current | I _B | — | — | 200 | 500 | nA |
| Input Resistance | R _{IN} | — | 50 | 200 | — | kΩ |
| Large signal Voltage Gain | A _V | R _L ≥2kΩ, V _O =±10V | 86 | 110 | — | dB |
| Maximum Output Voltage Swing 1 | V _{OM1} | R _L ≥10kΩ | ±12 | ±14 | — | V |
| Maximum Output Voltage Swing 2 | V _{OM2} | I _O =25mA | ±10 | ±11.5 | — | V |
| Input Common Mode Voltage Range | V _{ICM} | — | ±12 | ±14 | — | V |
| Common Mode Rejection Ratio | CMR | R _S ≤10kΩ | 70 | 100 | — | dB |
| Supply Voltage Rejection Ratio | SVR | R _S ≤10kΩ | 76 | 100 | — | dB |
| Operating Current | I _{CC} | — | — | 6 | 8 | mA |
| Slew Rate | SR | — | — | 3 | — | V/μs |
| Gain Bandwidth Product | GB | — | — | 7 | — | MHz |
| Equivalent Input Noise Voltage | V _{NI} | FLAT+JISA R _S =300Ω | — | 0.48 | 0.61 | μVrms |


(note) : New JRC's general selected products D-rank are also prepared for the noise standard (R_S=2.2kΩ, RIAA, V_{NI}=1.4μV Max.)

■ TYPICAL CHARACTERISTICS

Large Signal Voltage Gain


vs. Frequency

($V^+/V^- = \pm 15V$, $R_L = 2k\Omega$, $T_a = 25^\circ C$)



Equivalent Input Noise Voltage


($V^+/V^- = \pm 15V$, $T_a = 25^\circ C$)



Maximum Output Voltage Swing

vs. Load Resistance


($V^+/V^- = \pm 15V$, $T_a = 25^\circ C$)



Maximum Output Voltage Swing


vs. Output Current

($T_a = 25^\circ C$)



Operating Current vs. Temperature


($V^+/V^- = \pm 15V$)



Maximum Output Voltage Swing


vs. Temperature

($V^+/V^- = \pm 15V$, $R_L = 10k\Omega$)




■ TYPICAL CHARACTERISTICS


Input Offset Voltage vs. Temperature




Input Bias Current vs. Temperature




Maximum Output Voltage Swing vs. Operating Voltage




Maximum Output Voltage Swing vs. Operating Voltage



Operating Current vs. Operating Voltage



Maximum Output Voltage Swing vs. Frequency



MEMO

[CAUTION]

The specifications on this databook are only given for information , without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.