


B40C1500G THRU B380C1500G

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

Reverse Voltage - 65 to 600 Volts Forward Current - 1.5 Amperes


Case Style WOG



Dimensions in inches and (millimeters)

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated chip junctions
- High case dielectric strength
- Typical I_{R} less than 0.1 μ A
- High surge current capability
- Ideal for printed circuit boards
- High temperature soldering guaranteed:
260°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension



MECHANICAL DATA

Case: Molded plastic body over passivated junctions

Terminals: Plated leads solderable per MIL-STD-750,

Method 2026

Mounting Position: Any

Weight: 0.04 ounce, 1.1 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	B40 C1500G	B80 C1500G	B125 C1500G	B250 C1500G	B380 C1500G	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	65	125	200	400	600	Volts
Maximum RMS input voltage R + C-load	V _{RMS}	40	80	125	250	380	Volts
Maximum DC blocking voltage	V _{DC}	65	125	200	400	600	Volts
Maximum peak working voltage	V _{RWM}	90	180	300	600	800	Volts
Maximum non-repetitive peak voltage	V _{RSR}	100	200	350	650	1000	Volts
Maximum repetitive peak forward surge current	I _{FRM}			10.0			Amps
Maximum average forward output current for free air operation at T _A =45°C R + L-load C-load	I _(AV)			1.6			Amps
1.5							
Peak forward surge current single sine wave on rated load at T _J =125°C	I _{FSM}			50.0			Amps
Rating for fusing at T _J =125°C (t<100ms)	I ² t			12.5			A ² sec
Min. series resistor C-load at V _{RMS} = ±10%	R _t	1.0	2.0	4.0	8.0	12.0	Ohms
Maximum load capacitance +50% -10%	C _L	5000	2500	1000	500	200	μF
Maximum instantaneous forward voltage drop per leg at 1.5A	V _F			1.0			Volts
Maximum reverse current at rated repetitive peak voltage per leg T _A =25°C	I _R			10.0			μA
Typical thermal resistance per leg (NOTE 1)	R _{θJA} R _{θJL}			36.0			°C/W
Operating junction temperature range	T _J			-40 to +125			°C
Storage temperature range	T _{TSG}			-40 to +150			°C

NOTES:

1. Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. at 0.375" (9.5mm) lead lengths with 0.2 x 0.2"

RATINGS AND CHARACTERISTICS CURVES B40C1500G THRU B380C1500G

