


LTA-Series




The LTA-Series Mini Tippette Snap-in rocker switches are illuminated, single pole and double-insulated. These switches are AC rated and are also suitable for low voltage DC applications. A variety of actuators, colors and terminations can be specified with ratings up to 20 amps.

Specifications

- Certifications*: UL, CSA
- Dielectric Strength: 1,000V (minimum)
- Insulation Resistance: 100 Megohms (minimum)
- Base Material: Nylon
- Actuator Material: Nylon or Polycarbonate
- Bezel Material: Nylon


* Due to ongoing technological advances, consult factory for certification specifics.

Dimensional Specifications: in. [mm]




.069[1.75] DIA	.156[3.96] DIA	.055[1.40] DIA	
.250[6.35]	.375[9.52]	.250[6.35]	6.000[152.40]
	.250[6.35]	.187[4.74]	.500[12.70]
.250 TAB (Q.C.)	SOLDER LUG	.187 TAB (Q.C.)	INTEGRATED WIRE LEAD (no exposed conductors)


TERMINAL TYPE



PADDLE



SHORT PADDLE



MOUNTING HOLE
Panel Thickness:
.020[.508] min. to
.250[6.35] max.

SERIES	RATING	TERMINATION	ACTUATOR COLOR	LENS COLOR ^{2,3}
LTA	20	1	T	R
LTA OFF-NONE-ON SINGLE POLE	10 5A 250VAC 10A 125VAC 1/2HP 125-250VAC	0 SOLDER LUG 1 .250 TAB (QC) 3 .187 TAB (QC) 5 WIRE LEAD	ROCKER A AMBER C CLEAR G GREEN³ R RED	A AMBER C CLEAR G GREEN LU BLUE R RED
	11 5A 250VAC 10A 125VAC 5A (TUNGSTEN) 125VAC L	ACTUATOR STYLE	PADDLE¹ B BLACK W WHITE	LAMP VOLTAGE
	20 10A 250VAC 15A 125VAC 3/4HP 125-250VAC	P PADDLE PS PADDLE - SHORT T LIGHTED ROCKER	BASE COLOR¹	NEON 125N 125 VOLT 250N 250 VOLT
	21 10A 250VAC 15A 125VAC		B BLACK W WHITE	INCANDESCENT 6V 6 VOLT 12V 12 VOLT 18V 18 VOLT 24V 24 VOLT 28V 28 VOLT
	22 10A 250VAC 15A 125VAC 20A 125-250VAC H 3/4HP 125-250VAC			

NOTES:

Shading indicates standard configurations. Stainless steel bezels are available. Add suffix "BEZEL" to the end of the catalog number. (ex.) LTA201-TR-B/12V/BEZEL. Imprinting is available. Please specify when ordering.

Panel Cut-Out Recommendations: For sheet metal panels, switch must enter panel in same direction as the punch. (Burr on bottom.) Test cut hole in actual material.

1 Custom colors are available. Consult factory.

2 Neon lamps (125 volt or 250 volt) not recommended with green or blue colored indicators.

3 Specify lens color only if actuator style is P or PS.