




10A Bridge Rectifier

Features

- Diffused junction
- High current capability
- Surge overload rating to 150A peak
- High case dielectric strength of 1500V
- Ideal for printed circuit board applications
- Plastic material has underwriters laboratory flammability classification 94V-0
- UL Listed under recognized component index, file number E95060



Absolute Maximum Ratings

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Value	Unit
Repetitive peak reverse voltage =Working peak reverse voltage =DC Blocking voltage		PBPC1001	V_{RRM} $=V_{RWM}$ $=V_R$	50	V
		PBPC1002		100	V
		PBPC1003		200	V
		PBPC1004		400	V
		PBPC1005		600	V
		PBPC1006		800	V
		PBPC1007		1000	V
Peak forward surge current			I_{FSM}	150	A
Average forward current	$T_C=50^\circ\text{C}$, mounted on metal chassis		I_{FAV}	10	A
	$T_C=50^\circ\text{C}$, mounted on PC board FR-4 material		I_{FAV}	8	A
Junction and storage temperature range			$T_j=T_{stg}$	-65...+125	$^\circ\text{C}$

Electrical Characteristics

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F=5\text{A}$		V_F			1.1	V
Reverse current	$T_C=25^\circ\text{C}$		I_R			10	μA
	$T_C=100^\circ\text{C}$		I_R			1	mA
I^2t Rating for fusing			I^2t			64	A^2s
Diode capacitance	$V_R=4\text{V}$, $f=1\text{MHz}$		C_D		110		pF
Thermal resistance junction to case			R_{thJC}		7.5		K/W



Characteristics ($T_j = 25^\circ\text{C}$ unless otherwise specified)




Figure 1. Max. Average Forward Current vs. Ambient Temperature




Figure 3. Max. Peak Forward Surge Current vs. Number of Cycles




Figure 2. Typ. Forward Current vs. Forward Voltage





Figure 4. Typ. Reverse Current vs. Percent of Rated Peak Reverse Voltage





PBPC1001–PBPC1007

Vishay Lite-On Power Semiconductor

Dimensions in mm



PBPC-8		
Dim	Min	Max
A	18.54	19.56
B	6.35	7.60
C	22.20	-
D	Ø1.27 Typical	
E	5.33	7.37
G	Ø3.60	Ø4.00
H	12.70 Typical	
J	2.38x45° Typical	
All Dimensions in mm		



technical drawings
according to DIN
specifications

14479

- Case: molded plastic body
- Polarity: marked on body
- Approx. weight: 3.8 grams
- Mounting: through hole for #6 screw
- Mounting torque: 5.0 Inch-pounds maximum
- Mounting position: any
- Marking: type number



Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Telefunken products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Telefunken against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423