

**KVR133X64C2/128**  
**128MB 16M x 64-Bit PC133**  
**CL2 168-Pin DIMM**

**DESCRIPTION:**

This document describes ValueRAM's 16M x 64-bit (128MB) PC133 CL2 SDRAM (Synchronous DRAM) memory module. The components on this module include four 16M x 16-bit (4M x 16-bit x 4 Bank) PC133 SDRAM in TSOP packages. This 168-pin DIMM uses gold contact fingers and requires +3.3V. The electrical and mechanical specifications are as follows:

**FEATURES:**

- |                          |  |
|--------------------------|--|
| ✓ CLK Cycle Time (tCC)   | min. = 7.5ns (CAS Latency = 2) / max. = 1000ns |
| ✓ Row Cycle Time (tRC)   | 60ns   |
| ✓ CLK to Output (tSAC)   | max. = 5.4ns (CAS Latency = 2)                 |
| ✓ Single Power Supply of | +3.3V (+/- .3V)                                |
| ✓ Power                  | 1.188 W (operating)                            |
| ✓ UL Rating              | 94 V - 0                                       |

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.375" (34.92mm).




Figure 1: KVR133X64C2/128 168-Pin DIMM