


**Applications**

- Switch-mode power supplies
- Soft-start motors, e.g. in vacuum cleaners

**Features**

- Useable in series connections up to 265 V<sub>rms</sub>
- Coated thermistor disk
- Kinked leads of tinned copper wire
- Wide resistance range
- UL approval (E69802)


**Options**

Resistance tolerance < 20 % available on request

Dimensions in mm  
Approx. weight 2 g

**Delivery mode**

Bulk (standard), cardboard tape, reeled or in Ammo pack

Climatic category (IEC 60068-1)		55/170/56	
Max. power at 25 °C	$P_{\max}$	3,1	W
Resistance tolerance	$\Delta R_N/R_N$	± 20 %	
Rated temperature	$T_N$	25	°C
B value tolerance	$\Delta B/B$	± 3 %	
Dissipation factor (in air)	$\delta_{\text{th}}$	approx. 17	mW/K
Thermal cooling time constant (in air)	$\tau_c$	approx. 90	s
Heat capacity	$C_{\text{th}}$	approx. 1530	mJ/K

$R_{25}$ Ω	$I_{\max}$ (25 °C) A	No. of R/T char- acteristic	$B_{25/100}$ K	$C_T^{(1)}$ 230 V μF	$C_T^{(1)}$ 110 V μF	Parameters for		Ordering code
						$R(I)^{(1)}$ k	n	
1,0	9,0	1201	2700	700	2800	0,622	- 1,27	B57237S0109M000
2,2	7,0	1202	2800	700	2800	0,806	- 1,30	B57237S0229M000
2,5	6,5	1202	2800	700	2800	0,843	- 1,30	B57237S0259M000
4,7	5,1	1203	2900	700	2800	1,03	- 1,32	B57237S0479M000
5,0	5,0	1203	2900	700	2800	1,05	- 1,32	B57237S0509M000
7,0	4,2	1302	3060	700	2800	1,16	- 1,33	B57237S0709M000
10	3,7	1308	3060	700	2800	1,29	- 1,34	B57237S0100M000
15	3,0	1302	3000	700	2800	1,49	- 1,33	B57237S0150M000
22	2,8	1304	3300	700	2800	1,57	- 1,37	B57237S0220M000
33	2,5	1304	3300	900	3600	1,78	- 1,37	B57237S0330M000

1) For details on the capacitance  $C_T$  as well as on the parameters  $k$  and  $n$  refer to "Application Notes", pages 40–42.

**Reliability data**

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature $T: 170\text{ °C}$ $t: 1000\text{ h}$	< 10 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 21 days	< 5 %	No visible damage
Rapid temperature cycling	IEC 60068-2-14	Lower test temperature: – 55 °C Upper test temperature: 170 °C Number of cycles: 10	< 10 %	No visible damage
Endurance		$I = I_{\max}$ $t: 1000\text{ h}$	< 10 %	No visible damage
Cyclic endurance		$I = I_{\max}$ , 1000 cycles On-time = 1 min Cooling time = 6 min	< 10 %	No visible damage
Transient load		Capacitance = $C_T$ Number of cycles: 1000	< 5 %	No visible damage

**Herausgegeben von EPCOS AG**

**Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND**

**☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

**Published by EPCOS AG**

**Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY**

**☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.