

TOSHIBA BI-DIRECTIONAL TRIODE THYRISTOR SILICON PLANAR TYPE

SM2GZ47, SM2GZ47A, SM2JZ47, SM2JZ47A


AC POWER CONTROL APPLICATIONS

Unit in mm

- $I_T(\text{RMS}) = 1\text{A}$ ($T_a = 65^\circ\text{C}$ without radiator)
- Gate Trigger Current : $I_{GT} = 5\text{mA}$ Max. (TYPE "A")
- Repetitive Peak Off-State Voltage : $V_{DRM} = 400\text{V}, 600\text{V}$
- R.M.S On-State Current : $I_T(\text{RMS}) = 2\text{A}$ ($T_c = 110^\circ\text{C}$)
- Isolation Voltage : $V_{ISOL} = 1500\text{V}$ (AC, $t = 60\text{s}$)


MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
Repetitive Peak Off-State Voltage and Repetitive Peak Reverse Voltage	SM2GZ47	V_{DRM}	400	V
	SM2GZ47A			
	SM2JZ47		600	
	SM2JZ47A			
R.M.S On-State Current (Full Sine Waveform)	$T_c = 110^\circ\text{C}$	$I_T(\text{RMS})$	2	A
	$T_a = 65^\circ\text{C}$		1	
Peak One Cycle Surge On-State Current (Non-Repetitive)		I_{TSM}	8 (50Hz)	A
			8.8 (60Hz)	
I^2t Limit Value		I^2t	0.32	A^2s
Peak Gate Power Dissipation		P_{GM}	3	W
Average Gate Power Dissipation		$P_G(\text{AV})$	0.3	W
Peak Gate Voltage		V_{FGM}	10	V
Peak Gate Current		I_{GM}	1.6	A
Junction Temperature		T_j	$-40 \sim 125$	$^\circ\text{C}$
Storage Temperature Range		T_{stg}	$-40 \sim 125$	$^\circ\text{C}$
Isolation Voltage (AC, $t = 1\text{min.}$)		V_{ISOL}	1500	V



Weight : 1.7g (Typ.)

MARKING









NUMBER	SYMBOL		MARK
※1	TYPE	SM2GZ47, SM2GZ47A	M2GZ47
		SM2JZ47, SM2JZ47A	M2JZ47
※2		SM2GZ47A, SM2JZ47A	A
※3	Lot Number Month (Starting from 		



961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Repetitive Peak Off-State Current		I_{DRM}	$V_{\text{DRM}} = \text{Rated}$		—	—	20	μA
Gate Trigger Voltage	I	V_{GT}	$V_{\text{D}} = 12\text{V}$ $R_{\text{L}} = 20\Omega$	T2 (+), Gate (+)	—	—	1.5	V
	II			T2 (+), Gate (—)	—	—	1	
	III			T2 (—), Gate (—)	—	—	1	
	IV			T2 (—), Gate (+)	—	—	—	
Gate Trigger Current	I	I_{GT}	$V_{\text{D}} = 12\text{V}$ $R_{\text{L}} = 20\Omega$	T2 (+), Gate (+)	—	—	8	mA
	II			T2 (+), Gate (—)	—	—	8	
	III			T2 (—), Gate (—)	—	—	8	
	IV			T2 (—), Gate (+)	—	—	—	
	I			T2 (+), Gate (+)	—	—	5	
	II			T2 (+), Gate (—)	—	—	5	
	III			T2 (—), Gate (—)	—	—	5	
	IV			T2 (—), Gate (+)	—	—	—	
Peak On-State Voltage		V_{TM}	$I_{\text{TM}} = 3\text{A}$		—	—	1.7	V
Gate Non-Trigger Voltage		V_{GD}	$V_{\text{D}} = \text{Rated}$, $T_{\text{c}} = 125^{\circ}\text{C}$		0.2	—	—	V
Holding Current		I_{H}	$R_{\text{L}} = 100\Omega$		—	—	10	mA
Thermal Resistance		$R_{\text{th(j-a)}}$	Junction to Ambient, AC		—	—	55	$^{\circ}\text{C} / \text{W}$

GATE TRIGGER CHARACTERISTIC
(SM2GZ47, SM2JZ47)GATE TRIGGER CHARACTERISTIC
(SM2GZ47A, SM2JZ47A) $I_{GT}(T_c)/I_{GT}(T_c=25^\circ C) - T_c$ (TYPICAL) $V_{GT}(T_c)/V_{GT}(T_c=25^\circ C) - T_c$ (TYPICAL) $I_H(T_c)/I_H(T_c=25^\circ C) - T_c$ (TYPICAL)TRANSIENT THERMAL IMPEDANCE
(JUNCTION TO AMBIENT)



<CONDITION>

- ◆ NO HEAT SINK
- ◆ LEAD FORMING : LB182
- ◆ PRINT BOARD

$\left(\begin{array}{l} t = 1.6\text{mm} \\ \text{SOLDER LAND : } 2\text{mm}\phi \end{array} \right)$