

TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995


- Low $r_{DS(on)}$. . . 0.3 Ω Typ
- High-Voltage Outputs . . . 60 V
- Pulsed Current . . . 7 A Per Channel
- Fast Commutation Speed

description


The TPIC5302 is a monolithic power DMOS array that consists of three electrically isolated independent N-channel enhancement-mode DMOS transistors. The TPIC5302 is offered in a standard 16-pin small-outline surface-mount (D) package.

The TPIC5302 is characterized for operation over the case temperature range of -40°C to 125°C .

D PACKAGE
(TOP VIEW)



schematic



absolute maximum ratings over operating case temperature range (unless otherwise noted)[†]

Drain-to-source voltage, V_{DS}	60 V
Source-to-GND voltage	100 V
Drain-to-GND voltage	100 V
Gate-to-source voltage, V_{GS}	± 20 V
Continuous drain current, each output, all outputs on, $T_C = 25^{\circ}\text{C}$	1.4 A
Continuous source-to-drain diode current	1.4 A
Pulsed drain current, each output, $T_C = 25^{\circ}\text{C}$ (see Note 1 and Figure 6)	7 A
Single-pulse avalanche energy, E_{AS} , $T_C = 25^{\circ}\text{C}$ (see Figure 4)	10.5 mJ
Continuous total power dissipation at (or below) $T_C = 25^{\circ}\text{C}$	1087 mW
Operating virtual junction temperature range, T_J	-40°C to 150°C
Operating case temperature range, T_C	-40°C to 125°C
Storage temperature range, T_{stg}	-65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: Pulse duration = 10 ms and duty cycle = 2%

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1995, Texas Instruments Incorporated

TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995

electrical characteristics, $T_C = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(BR)DSX}$ Drain-to-source breakdown voltage	$I_D = 250\ \mu\text{A}$, $V_{GS} = 0$	60			V
$V_{GS(th)}$ Gate-to-source threshold voltage	$I_D = 1\ \text{mA}$, $V_{DS} = V_{GS}$	1.5	1.85	2.2	V
$V_{(BR)}$ Reverse drain-to-GND breakdown voltage (across D1, D2, and D3)	Drain-to-GND current = $250\ \mu\text{A}$	100			V
$V_{DS(on)}$ Drain-to-source on-state voltage	$I_D = 1.4\ \text{A}$, $V_{GS} = 10\ \text{V}$, See Notes 2 and 3		0.42	0.49	V
$V_{F(SD)}$ Forward on-state voltage, source-to-drain	$I_S = 1.4\ \text{A}$, $V_{GS} = 0$ (Z1, Z2, Z3), See Notes 2 and 3		0.9	1.1	V
V_F Forward on-state voltage, GND-to-drain	$I_D = 1.4\ \text{A}$		4.8		V
I_{DSS} Zero-gate-voltage drain current	$V_{DS} = 48\ \text{V}$, $V_{GS} = 0$	$T_C = 25^\circ\text{C}$	0.05	1	μA
		$T_C = 125^\circ\text{C}$	0.5	10	
I_{GSSF} Forward gate current, drain short circuited to source	$V_{GS} = 16\ \text{V}$, $V_{DS} = 0$		10	100	nA
I_{GSSR} Reverse gate current, drain short circuited to source	$V_{SG} = 16\ \text{V}$, $V_{DS} = 0$		10	100	nA
I_{lkg} Leakage current, drain-to-GND	$V_R = 48\ \text{V}$	$T_C = 25^\circ\text{C}$	0.05	1	μA
		$T_C = 125^\circ\text{C}$	0.5	10	
$r_{DS(on)}$ Static drain-to-source on-state resistance	$V_{GS} = 10\ \text{V}$, $I_D = 1.4\ \text{A}$, See Notes 2 and 3 and Figures 6 and 7	$T_C = 25^\circ\text{C}$	0.3	0.35	Ω
		$T_C = 125^\circ\text{C}$	0.41	0.5	
g_{fs} Forward transconductance	$V_{DS} = 10\ \text{V}$, $I_D = 0.7\ \text{A}$, See Notes 2 and 3	1.15	1.41		S
C_{iss} Short-circuit input capacitance, common source	$V_{DS} = 25\ \text{V}$, $V_{GS} = 0$, $f = 1\ \text{MHz}$		135	170	pF
C_{oss} Short-circuit output capacitance, common source			80	100	
C_{rss} Short-circuit reverse-transfer capacitance, common source			30	40	

NOTES: 2. Technique should limit $T_J - T_C$ to 10°C maximum and pulse duration $\leq 5\ \text{ms}$.
3. These parameters are measured with voltage-sensing contacts separate from the current-carrying contacts.

source-to-drain diode characteristics, $T_C = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$t_{rr(SD)}$ Reverse-recovery time	$I_S = 0.5\ \text{A}$, $V_{GS} = 0$, $V_{DS} = 48\ \text{V}$, $di/dt = 100\ \text{A}/\mu\text{s}$, See Figure 1		35		ns
Q_{RR} Total diode charge			0.04		μC

GND-to-drain diode characteristics, $T_C = 25^\circ\text{C}$ (see schematic, D1, D2, and D3)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_{rr} Reverse-recovery time	$I_F = 0.5\ \text{A}$, $V_{DS} = 48\ \text{V}$, $di/dt = 100\ \text{A}/\mu\text{s}$, See Figure 1		130		ns
Q_{RR} Total diode charge			0.4		μC



TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995

resistive-load switching characteristics, $T_C = 25^\circ\text{C}$


PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$t_{d(on)}$ Turn-on delay time	$V_{DD} = 25\text{ V}$, $R_L = 50\ \Omega$, $t_{r1} = 10\text{ ns}$, $t_{f1} = 10\text{ ns}$, See Figure 2		23	46	ns
$t_{d(off)}$ Turn-off delay time			25	50	
t_{r2} Rise time			5	10	
t_{f2} Fall time			17	34	
Q_g Total gate charge	$V_{DS} = 48\text{ V}$, $I_D = 0.5\text{ A}$, $V_{GS} = 10\text{ V}$, See Figure 3		8	9.8	nC
$Q_{gs(th)}$ Threshold gate-to-source charge			0.5	0.63	
Q_{gd} Gate-to-drain charge			1.5	1.85	
L_D Internal drain inductance			5		nH
L_S Internal source inductance			5		
R_g Internal gate resistance			0.25		Ω

thermal resistance

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$R_{\theta JA}$ Junction-to-ambient thermal resistance	All outputs with equal power, See Note 4		115		$^\circ\text{C/W}$
$R_{\theta JP}$ Junction-to-pin thermal resistance			32		

NOTE 4: Package mounted on an FR4 printed-circuit board with no heat sink

PARAMETER MEASUREMENT INFORMATION



$^\dagger I_{RM}$ = maximum recovery current


Figure 1. Reverse-Recovery-Current Waveform of Source-to-Drain Diode

TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995

PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT

NOTE A: C_L includes probe and jig capacitance.





Figure 2. Resistive-Switching Test Circuit and Voltage Waveforms



TEST CIRCUIT





Figure 3. Gate-Charge Test Circuit and Voltage Waveform

PARAMETER MEASUREMENT INFORMATION





- NOTES: A. The pulse generator has the following characteristics: $t_r \leq 10$ ns, $t_f \leq 10$ ns, $Z_O = 50 \Omega$.
 B. Input pulse duration (t_w) is increased until peak current $I_{AS} = 7$ A, where t_{av} = avalanche time.

$$\text{Energy test level is defined as } E_{AS} = \frac{I_{AS} \times V_{(BR)DSX} \times t_{av}}{2} = 10.5 \text{ mJ}$$

Figure 4. Single-Pulse Avalanche-Energy Test Circuit and Waveforms

TYPICAL CHARACTERISTICS



TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995

TYPICAL CHARACTERISTICS




Figure 7




Figure 8




Figure 9








Figure 10

TYPICAL CHARACTERISTICS




TPIC5302

3-CHANNEL INDEPENDENT POWER DMOS ARRAY

SLIS029B – APRIL 1994 – REVISED SEPTEMBER 1995

THERMAL INFORMATION



[†] Less than 0.1 duty cycle

Figure 15





Figure 16

THERMAL INFORMATION

D PACKAGE[†] NORMALIZED JUNCTION-TO-AMBIENT THERMAL RESISTANCE VS PULSE DURATION



[†] Device mounted on FR4 printed-circuit board with no heat sink

NOTE A: $Z_{\theta A}(t) = r(t) R_{\theta JA}$
 t_W = pulse duration
 t_C = cycle time
 d = duty cycle = t_W/t_C

Figure 17

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.