

- Designed to comply with the requirements of GR1089, UL1950, EN60950, BABT and CSA950 to provide a supplementary insulation barrier with a working voltage of 250V
- UL File Number E150991
- Minimum interwinding breakdown voltage of 1500 Vrms
- Operating and storage temperature range: -40° to +85° C
- Meets IEC 695, 2-2 flammability requirements
- PWB Process Capability: standard printed wiring board assembly techniques, total-immersion cleaning
- Reliability testing: shock, vibration, temperature cycling, temperature - humidity - bias

ELECTRICAL SPECIFICATIONS AT 25° C

| Part Number | Turns Ratio ±2% | Inductance ¹ mH ±5% | Leakage Inductance ² µH max | DCR Ω max | | Longitudinal Balance dB min | Insertion Loss dB max | Harmonic Distortion ³ dB max |
|--------------|--------------------|-----------------------------------|---|--------------|-----------|--------------------------------|--------------------------|--|
| | Chip : Line | Line Side | Line Side | Chip Side | Line Side | 100 kHz - 300 kHz | 100 kHz | 5 kHz Fundamental |
| 0560-6600-N2 | 1 : 2.2 | 3 | 10 | 2.0 | 4.0 | 55 | 1.5 | -75 |

All measurements are made with pins 2 and 4 connected


1. Inductance measured at 10 kHz, 0.1 Vac

2. Measured at 100 kHz, 0.1 Vac

3. Measurements made with 100Ω source and 27.9Ω load impedance, 2 Vrms

SCHEMATIC


0560-6600-N2



TM01377

MECHANICAL

0560-6600-N2



Dimensions are in inches [millimeters].
Standard dimension tolerance is ± 0.005 [0.13] unless otherwise noted.

©2001 Bel Fuse Inc. Specifications subject to change without notice. 09.01

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com