

DSP56364

24-Bit Audio Digital Signal Processor

1 Overview

The DSP56364 supports digital audio applications requiring sound field processing, acoustic equalization, and other digital audio algorithms. The DSP56364 uses the high performance, single-clock-per-cycle DSP56300 core family of programmable CMOS digital signal processors (DSPs) combined with the audio signal processing capability of the Freescale Symphony™ DSP family, as shown in [Figure 1-1](#). This design provides a two-fold performance increase over Freescale's popular Symphony family of DSPs while retaining code compatibility. Significant architectural enhancements include a barrel shifter, 24-bit addressing, instruction cache, and direct memory access (DMA). The DSP56364 offers 100 million instructions per second (MIPS) using an internal 100 MHz clock at 3.3 V.

Contents

| | |
|---|------------|
| 1 Overview | 1-1 |
| 2 Signal/Connection Descriptions | 2-1 |
| 3 Specifications | 3-1 |
| 4 Packaging | 4-1 |
| 5 Design Considerations | 5-1 |
| 6 Ordering Information | 6-1 |
| A IBIS Model | A-1 |

This document contains information on a new product. Specifications and information herein are subject to change without notice.

© Freescale Semiconductor, Inc., 2006. All rights reserved.



Data Sheet Conventions

This data sheet uses the following conventions:

OVERBAR Used to indicate a signal that is active when pulled low (For example, the **RESET** pin is active when low.)

“asserted” Means that a high true (active high) signal is high or that a low true (active low) signal is low

“deasserted” Means that a high true (active high) signal is low or that a low true (active low) signal is high

| Examples: | Signal/Symbol | Logic State | Signal State | Voltage* |
|-----------|------------------|-------------|--------------|-------------------|
| | \overline{PIN} | True | Asserted | V_{IL} / V_{OL} |
| | \overline{PIN} | False | Deasserted | V_{IH} / V_{OH} |
| | PIN | True | Asserted | V_{IH} / V_{OH} |
| | PIN | False | Deasserted | V_{IL} / V_{OL} |

Note: *Values for V_{IL} , V_{OL} , V_{IH} , and V_{OH} are defined by individual product specifications.




Figure 1-1 DSP56364 Block Diagram

1.1 Features

1.1.1 Digital Signal Processing Core

- 100 Million Instructions Per Second (MIPS) with an 100 MHz clock at 3.3V.
- Object Code Compatible with the 56000 core.
- Data ALU with a 24 x 24 bit multiplier-accumulator and a 56-bit barrel shifter. 16-bit arithmetic support.
- Program Control with position independent code support and instruction cache support.
- Six-channel DMA controller.
- PLL based clocking with a wide range of frequency multiplications (1 to 4096), predivider factors (1 to 16) and power saving clock divider (2^i : $i=0$ to 7). Reduces clock noise.
- Internal address tracing support and OnCE™ for Hardware/Software debugging.
- JTAG port.
- Very low-power CMOS design, fully static design with operating frequencies down to DC.
- STOP and WAIT low-power standby modes.

1.1.2 On-chip Memory Configuration

- 1.5Kx24 Bit Y-Data RAM.
- 1Kx24 Bit X-Data RAM.
- 8Kx24 Bit Program ROM.
- 0.5Kx24 Bit Program RAM and 192x24 Bit Bootstrap ROM.
- 0.75Kx24 Bit from Y Data RAM can be switched to Program RAM resulting in up to 1.25Kx24 Bit of Program RAM.

1.1.3 Off-chip memory expansion

- External Memory Expansion Port with 8-bit data bus.
- Off-chip expansion up to 2 x 16M x 8-bit word of Data/Program memory when using DRAM.
- Off-chip expansion up to 2 x 256k x 8-bit word of Data/Program memory when using SRAM.
- Simultaneous glueless interface to SRAM and DRAM.

1.1.4 Peripheral modules

- Enhanced Serial Audio Interface (ESAI): 6 serial lines, 4 selectable as receive or transmit and 2 transmit only, master or slave. I²S, Sony, AC97, network and other programmable protocols. Unused pins of ESAI may be used as GPIO lines.
- Serial Host Interface (SHI): SPI and I²C protocols, 10-word receive FIFO, support for 8, 16 and 24-bit words.
- Four dedicated GPIO lines.

1.1.5 Packaging

- 100-pin plastic TQFP package.

1.2 Documentation

Table 1-1 lists the documents that provide a complete description of the DSP56364 and are required to design properly with the part. Documentation is available from a local Freescale distributor, a Freescale semiconductor sales office, a Freescale Literature Distribution Center, or through the Freescale DSP home page on the Internet (the source for the latest information).

Table 1-1 DSP56364 Documentation

| Document Name | Description | Order Number |
|---|---|--------------|
| DSP56300 Family Manual | Detailed description of the 56000-family architecture and the 24-bit core processor and instruction set | DSP56300FM |
| DSP56364 User's Manual | Detailed description of memory, peripherals, and interfaces | DSP56364UM |
| DSP56364 Product Brief | Brief description of the chip | DSP56364P |
| DSP56364 Technical Data Sheet (this document) | Electrical and timing specifications; pin and package descriptions | DSP56364 |

2 Signal/Connection Descriptions

2.1 Signal Groupings

The input and output signals of the DSP56364 are organized into functional groups, which are listed in [Table 2-1](#) and illustrated in [Figure 2-1](#).

The DSP56364 is operated from a 3.3 V supply; however, some of the inputs can tolerate 5 V. A special notice for this feature is added to the signal descriptions of those inputs.

Table 2-1 DSP56364 Functional Signal Groupings

| Functional Group | | Number of Signals | Detailed Description |
|----------------------------|---------------------|-------------------|----------------------------|
| Power (V_{CC}) | | 18 | Table 2-2 |
| Ground (GND) | | 14 | Table 2-3 |
| Clock and PLL | | 3 | Table 2-4 |
| Address bus | Port A ¹ | 18 | Table 2-5 |
| Data bus | | 8 | Table 2-6 |
| Bus control | | 6 | Table 2-7 |
| Interrupt and mode control | | 4 | Table 2-8 |
| General Purpose I/O | Port B ² | 4 | Table 2-12 |
| SHI | | 5 | Table 2-9 |
| ESAI | Port C ³ | 12 | Table 2-10 |
| JTAG/OnCE Port | | 4 | Table 2-11 |

¹ Port A is the external memory interface port, including the external address bus, data bus, and control signals.

² Port B signals are the GPIO signals.

³ Port C signals are the ESAI port signals multiplexed with the GPIO signals.




Figure 2-1 Signals Identified by Functional Group

2.2 Power

Table 2-2 Power Inputs

| Power Name | Description |
|----------------|---|
| V_{CCP} | PLL Power — V_{CCP} is V_{CC} dedicated for PLL use. The voltage should be well-regulated and the input should be provided with an extremely low impedance path to the V_{CC} power rail. There is one V_{CCP} input. |
| V_{CCQL} (4) | Quiet Core (Low) Power — V_{CCQL} is an isolated power for the internal processing logic. This input must be tied externally to all other chip power inputs. The user must provide adequate external decoupling capacitors. There are four V_{CCQL} inputs. |
| V_{CCQH} (4) | Quiet External (High) Power — V_{CCQH} is a quiet power source for I/O lines. This input must be tied externally to all other chip power inputs. The user must provide adequate decoupling capacitors. There are four V_{CCQH} inputs. |
| V_{CCA} (4) | Address Bus Power — V_{CCA} is an isolated power for sections of the address bus I/O drivers. This input must be tied externally to all other chip power inputs. The user must provide adequate external decoupling capacitors. There are four V_{CCA} inputs. |
| V_{CCD} (1) | Data Bus Power — V_{CCD} is an isolated power for sections of the data bus I/O drivers. This input must be tied externally to all other chip power inputs. The user must provide adequate external decoupling capacitors. There is one V_{CCD} inputs. |
| V_{CCC} (1) | Bus Control Power — V_{CCC} is an isolated power for the bus control I/O drivers. This input must be tied externally to all other chip power inputs. The user must provide adequate external decoupling capacitors. There is one V_{CCC} inputs. |
| V_{CCS} (3) | SHI and ESAI — V_{CCS} is an isolated power for the SHI and ESAI. This input must be tied externally to all other chip power inputs _L . The user must provide adequate external decoupling capacitors. There are three V_{CCS} inputs. |

2.3 Ground

Table 2-3 Grounds

| Ground Name | Description |
|-------------|---|
| GND_P | PLL Ground — GND_P is ground-dedicated for PLL use. The connection should be provided with an extremely low-impedance path to ground. V_{CCP} should be bypassed to GND_P by a 0.47 μ F capacitor located as close as possible to the chip package. There is one GND_P connection. |
| GND_Q (4) | Quiet Ground — GND_Q is an isolated ground for the internal processing logic. This connection must be tied externally to all other chip ground connections. The user must provide adequate external decoupling capacitors. There are four GND_Q connections. |
| GND_A (4) | Address Bus Ground — GND_A is an isolated ground for sections of the address bus I/O drivers. This connection must be tied externally to all other chip ground connections. The user must provide adequate external decoupling capacitors. There are four GND_A connections. |
| GND_D (1) | Data Bus Ground — GND_D is an isolated ground for sections of the data bus I/O drivers. This connection must be tied externally to all other chip ground connections. The user must provide adequate external decoupling capacitors. There is one GND_D connections. |

Table 2-3 Grounds (continued)

| Ground Name | Description |
|----------------------|--|
| GND _C (1) | Bus Control Ground —GND _C is an isolated ground for the bus control I/O drivers. This connection must be tied externally to all other chip ground connections. The user must provide adequate external decoupling capacitors. There is one GND _C connections. |
| GND _S (3) | SHI and ESAI —GND _S is an isolated ground for the SHI and ESAI. This connection must be tied externally to all other chip ground connections. The user must provide adequate external decoupling capacitors. There are three GND _S connections. |

2.4 Clock and PLL

Table 2-4 Clock and PLL Signals

| Signal Name | Type | State during Reset | Signal Description |
|--------------------------------|-------|--------------------|---|
| EXTAL | Input | Input | External Clock Input —An external clock source must be connected to EXTAL in order to supply the clock to the internal clock generator and PLL. |
| PCAP | Input | Input | PLL Capacitor —PCAP is an input connecting an off-chip capacitor to the PLL filter. Connect one capacitor terminal to PCAP and the other terminal to V _{CCP} . If the PLL is not used, PCAP may be tied to V _{CC} , GND, or left floating. |
| PINIT/ $\overline{\text{NMI}}$ | Input | Input | PLL Initial/Nonmaskable Interrupt —During assertion of $\overline{\text{RESET}}$, the value of PINIT/ $\overline{\text{NMI}}$ is written into the PLL Enable (PEN) bit of the PLL control register, determining whether the PLL is enabled or disabled. After $\overline{\text{RESET}}$ deassertion and during normal instruction processing, the PINIT/ $\overline{\text{NMI}}$ Schmitt-trigger input is a negative-edge-triggered nonmaskable interrupt (NMI) request internally synchronized to internal system clock. <i>This input is 5 V tolerant.</i> |

2.5 External Memory Expansion Port (Port A)

When the DSP56364 enters a low-power standby mode (stop or wait), it tri-states the relevant port A signals: D0–D7, AA0, AA1, $\overline{\text{RD}}$, $\overline{\text{WR}}$, $\overline{\text{CAS}}$.

2.5.1 External Address Bus

Table 2-5 External Address Bus Signals

| Signal Name | Type | State during Reset | Signal Description |
|-------------|--------|--------------------|---|
| A0–A17 | Output | Keeper active | Address Bus —A0–A17 are active-high outputs that specify the address for external program and data memory accesses. Otherwise, the signals are kept to their previous values by internal weak keepers. To minimize power dissipation, A0–A17 do not change state when external memory spaces are not being accessed. |

2.5.2 External Data Bus

Table 2-6 External Data Bus Signals

| Signal Name | Type | State during Reset | Signal Description |
|-------------|--------------|--------------------|---|
| D0–D7 | Input/Output | Tri-stated | Data Bus —D0–D7 are active-high, bidirectional input/outputs that provide the bidirectional data bus for external program and data memory accesses. D0–D7 are tri-stated during hardware reset and when the DSP is in the stop or wait low-power standby mode. |

2.5.3 External Bus Control

Table 2-7 External Bus Control Signals

| Signal Name | Type | State during Reset | Signal Description |
|---|--------|--------------------|---|
| AA0–AA1/ $\overline{\text{RAS0}}\text{--}\overline{\text{RAS1}}$ | Output | Tri-stated | Address Attribute or Row Address Strobe —When defined as AA, these signals can be used as chip selects or additional address lines. When defined as $\overline{\text{RAS}}$, these signals can be used as $\overline{\text{RAS}}$ for DRAM interface. These signals are tri-statable outputs with programmable polarity. These signals are tri-stated during hardware reset and when the DSP is in the stop or wait low-power standby mode. |
| CAS | Output | Tri-stated | Column Address Strobe — $\overline{\text{CAS}}$ is an active-low output used by DRAM to strobe the column address. This signal is tri-stated during hardware reset and when the DSP is in the stop or wait low-power standby mode. |
| RD | Output | Tri-stated | Read Enable — $\overline{\text{RD}}$ is an active-low output that is asserted to read external memory on the data bus. This signal is tri-stated during hardware reset and when the DSP is in the stop or wait low-power standby mode. |
| WR | Output | Tri-stated | Write Enable — $\overline{\text{WR}}$ is an active-low output that is asserted to write external memory on the data bus. This signal is tri-stated during hardware reset and when the DSP is in the stop or wait low-power standby mode. |
| TA | Input | Ignored Input | Transfer Acknowledge —If there is no external bus activity, the $\overline{\text{TA}}$ input is ignored. The $\overline{\text{TA}}$ input is a data transfer acknowledge (DTACK) function that can extend an external bus cycle indefinitely. Any number of wait states (1, 2, . . . infinity) may be added to the wait states inserted by the BCR by keeping $\overline{\text{TA}}$ deasserted. In typical operation, $\overline{\text{TA}}$ is deasserted at the start of a bus cycle, is asserted to enable completion of the bus cycle, and is deasserted before the next bus cycle. The current bus cycle completes one clock period after $\overline{\text{TA}}$ is asserted synchronous to the internal system clock. The number of wait states is determined by the $\overline{\text{TA}}$ input or by the bus control register (BCR), whichever is longer. The BCR can be used to set the minimum number of wait states in external bus cycles. In order to use the $\overline{\text{TA}}$ functionality, the BCR must be programmed to at least one wait state. A zero wait state access cannot be extended by $\overline{\text{TA}}$ deassertion, otherwise improper operation may result. $\overline{\text{TA}}$ can operate synchronously or asynchronously, depending on the setting of the TAS bit in the operating mode register (OMR). $\overline{\text{TA}}$ functionality may not be used while performing DRAM type accesses, otherwise improper operation may result. |

2.6 Interrupt and Mode Control

The interrupt and mode control signals select the chip's operating mode as it comes out of hardware reset. After $\overline{\text{RESET}}$ is deasserted, these inputs are hardware interrupt request lines.

Table 2-8 Interrupt and Mode Control

| Signal Name | Type | State during Reset | Signal Description |
|--------------------------------------|-------|--------------------|---|
| $\text{MODA}/\overline{\text{IRQA}}$ | Input | Input | <p>Mode Select A/External Interrupt Request A—$\text{MODA}/\overline{\text{IRQA}}$ is an active-low Schmitt-trigger input, internally synchronized to the internal system clock. $\text{MODA}/\overline{\text{IRQA}}$ selects the initial chip operating mode during hardware reset and becomes a level-sensitive or negative-edge-triggered, maskable interrupt request input during normal instruction processing. MODA, MODB, and MODD select one of 8 initial chip operating modes, latched into the OMR when the $\overline{\text{RESET}}$ signal is deasserted. If $\overline{\text{IRQA}}$ is asserted synchronous to the internal system clock, multiple processors can be re-synchronized using the WAIT instruction and asserting $\overline{\text{IRQA}}$ to exit the wait state. If the processor is in the stop standby state and $\overline{\text{IRQA}}$ is asserted, the processor will exit the stop state.</p> <p><i>This input is 5 V tolerant.</i></p> |
| $\text{MODB}/\overline{\text{IRQB}}$ | Input | Input | <p>Mode Select B/External Interrupt Request B—$\text{MODB}/\overline{\text{IRQB}}$ is an active-low Schmitt-trigger input, internally synchronized to the internal system clock. $\text{MODB}/\overline{\text{IRQB}}$ selects the initial chip operating mode during hardware reset and becomes a level-sensitive or negative-edge-triggered, maskable interrupt request input during normal instruction processing. MODA, MODB, and MODD select one of 8 initial chip operating modes, latched into OMR when the $\overline{\text{RESET}}$ signal is deasserted. If $\overline{\text{IRQB}}$ is asserted synchronous to the internal system clock, multiple processors can be re-synchronized using the WAIT instruction and asserting $\overline{\text{IRQB}}$ to exit the wait state.</p> <p>This input is 5 V tolerant.</p> |
| $\text{MODD}/\overline{\text{IRQD}}$ | Input | Input | <p>Mode Select D/External Interrupt Request D—$\text{MODD}/\overline{\text{IRQD}}$ is an active-low Schmitt-trigger input, internally synchronized to the internal system clock. $\text{MODD}/\overline{\text{IRQD}}$ selects the initial chip operating mode during hardware reset and becomes a level-sensitive or negative-edge-triggered, maskable interrupt request input during normal instruction processing. MODA, MODB, and MODD select one of 8 initial chip operating modes, latched into OMR when the $\overline{\text{RESET}}$ signal is deasserted. If $\overline{\text{IRQD}}$ is asserted synchronous to the internal system clock, multiple processors can be re-synchronized using the WAIT instruction and asserting $\overline{\text{IRQD}}$ to exit the wait state.</p> <p>This input is 5 V tolerant.</p> |
| $\overline{\text{RESET}}$ | Input | Input | <p>Reset—$\overline{\text{RESET}}$ is an active-low, Schmitt-trigger input. When asserted, the chip is placed in the reset state and the internal phase generator is reset. The Schmitt-trigger input allows a slowly rising input (such as a capacitor charging) to reset the chip reliably. When the $\overline{\text{RESET}}$ signal is deasserted, the initial chip operating mode is latched from the MODA, MODB, and MODD inputs. The $\overline{\text{RESET}}$ signal must be asserted during power up. A stable EXTAL signal must be supplied before deassertion of $\overline{\text{RESET}}$.</p> <p><i>This input is 5 V tolerant.</i></p> |

2.7 Serial Host Interface

The SHI has five I/O signals that can be configured to allow the SHI to operate in either SPI or I²C mode.

Table 2-9 Serial Host Interface Signals

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------|----------------------------|--------------------|--|
| SCK | Input or output | Tri-stated | SPI Serial Clock —The SCK signal is an output when the SPI is configured as a master and a Schmitt-trigger input when the SPI is configured as a slave. When the SPI is configured as a master, the SCK signal is derived from the internal SHI clock generator. When the SPI is configured as a slave, the SCK signal is an input, and the clock signal from the external master synchronizes the data transfer. The SCK signal is ignored by the SPI if it is defined as a slave and the slave select (\overline{SS}) signal is not asserted. In both the master and slave SPI devices, data is shifted on one edge of the SCK signal and is sampled on the opposite edge where data is stable. Edge polarity is determined by the SPI transfer protocol. |
| SCL | Input or output | Tri-stated | I²C Serial Clock —SCL carries the clock for I ² C bus transactions in the I ² C mode. SCL is a Schmitt-trigger input when configured as a slave and an open-drain output when configured as a master. SCL should be connected to V _{CC} through a pull-up resistor. This signal is tri-stated during hardware, software, and individual reset. Thus, there is no need for an external pull-up in this state. This input is 5 V tolerant. |
| MISO | Input or output | Tri-stated | SPI Master-In-Slave-Out —When the SPI is configured as a master, MISO is the master data input line. The MISO signal is used in conjunction with the MOSI signal for transmitting and receiving serial data. This signal is a Schmitt-trigger input when configured for the SPI Master mode, an output when configured for the SPI Slave mode, and tri-stated if configured for the SPI Slave mode when \overline{SS} is deasserted. An external pull-up resistor is not required for SPI operation. |
| SDA | Input or open-drain output | Tri-stated | I²C Data and Acknowledge —In I ² C mode, SDA is a Schmitt-trigger input when receiving and an open-drain output when transmitting. SDA should be connected to V _{CC} through a pull-up resistor. SDA carries the data for I ² C transactions. The data in SDA must be stable during the high period of SCL. The data in SDA is only allowed to change when SCL is low. When the bus is free, SDA is high. The SDA line is only allowed to change during the time SCL is high in the case of start and stop events. A high-to-low transition of the SDA line while SCL is high is a unique situation, and is defined as the start event. A low-to-high transition of SDA while SCL is high is a unique situation defined as the stop event. This signal is tri-stated during hardware, software, and individual reset. Thus, there is no need for an external pull-up in this state. This input is 5 V tolerant. |
| MOSI | Input or output | Tri-stated | SPI Master-Out-Slave-In —When the SPI is configured as a master, MOSI is the master data output line. The MOSI signal is used in conjunction with the MISO signal for transmitting and receiving serial data. MOSI is the slave data input line when the SPI is configured as a slave. This signal is a Schmitt-trigger input when configured for the SPI Slave mode. |

Table 2-9 Serial Host Interface Signals (continued)

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------------|-----------------|--------------------|--|
| HA0 | Input | Tri-stated | <p>I²C Slave Address 0—This signal uses a Schmitt-trigger input when configured for the I²C mode. When configured for I²C slave mode, the HA0 signal is used to form the slave device address. HA0 is ignored when configured for the I²C master mode.</p> <p>This signal is tri-stated during hardware, software, and individual reset. Thus, there is no need for an external pull-up in this state.</p> <p>This input is 5 V tolerant.</p> |
| \overline{SS} | Input | Input | <p>SPI Slave Select—This signal is an active low Schmitt-trigger input when configured for the SPI mode. When configured for the SPI Slave mode, this signal is used to enable the SPI slave for transfer. When configured for the SPI master mode, this signal should be kept deasserted (pulled high). If it is asserted while configured as SPI master, a bus error condition is flagged. If \overline{SS} is deasserted, the SHI ignores SCK clocks and keeps the MISO output signal in the high-impedance state.</p> |
| HA2 | Input | Input | <p>I²C Slave Address 2—This signal uses a Schmitt-trigger input when configured for the I²C mode. When configured for the I²C Slave mode, the HA2 signal is used to form the slave device address. HA2 is ignored in the I²C master mode.</p> <p>This signal is tri-stated during hardware, software, and individual reset. Thus, there is no need for an external pull-up in this state.</p> <p><i>This input is 5 V tolerant.</i></p> |
| \overline{HREQ} | Input or Output | Tri-stated | <p>Host Request—This signal is an active low Schmitt-trigger input when configured for the master mode but an active low output when configured for the slave mode.</p> <p>When configured for the slave mode, \overline{HREQ} is asserted to indicate that the SHI is ready for the next data word transfer and deasserted at the first clock pulse of the new data word transfer. When configured for the master mode, \overline{HREQ} is an input. When asserted by the external slave device, it will trigger the start of the data word transfer by the master. After finishing the data word transfer, the master will await the next assertion of \overline{HREQ} to proceed to the next transfer.</p> <p>This signal is tri-stated during hardware, software, personal reset, or when the HREQ1–HREQ0 bits in the HCSR are cleared. There is no need for external pull-up in this state.</p> <p><i>This input is 5 V tolerant.</i></p> |

2.8 Enhanced Serial Audio Interface

Table 2-10 Enhanced Serial Audio Interface Signals

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------|--------------------------------|--------------------|---|
| HCKR | Input or output | GPIO disconnected | High Frequency Clock for Receiver —When programmed as an input, this signal provides a high frequency clock source for the ESAI receiver as an alternate to the DSP core clock. When programmed as an output, this signal can serve as a high-frequency sample clock (e.g., for external digital to analog converters [DACs]) or as an additional system clock. |
| PC2 | Input, output, or disconnected | GPIO disconnected | Port C 2 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. <i>This input is 5 V tolerant.</i> |
| HCKT | Input or output | GPIO disconnected | High Frequency Clock for Transmitter —When programmed as an input, this signal provides a high frequency clock source for the ESAI transmitter as an alternate to the DSP core clock. When programmed as an output, this signal can serve as a high frequency sample clock (e.g., for external DACs) or as an additional system clock. |
| PC5 | Input, output, or disconnected | GPIO disconnected | Port C 5 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. <i>This input is 5 V tolerant.</i> |
| FSR | Input or output | GPIO disconnected | Frame Sync for Receiver —This is the receiver frame sync input/output signal. In the asynchronous mode (SYN=0), the FSR pin operates as the frame sync input or output used by all the enabled receivers. In the synchronous mode (SYN=1), it operates as either the serial flag 1 pin (TEBE=0), or as the transmitter external buffer enable control (TEBE=1, RFSD=1). When this pin is configured as serial flag pin, its direction is determined by the RFSD bit in the RCCR register. When configured as the output flag OF1, this pin will reflect the value of the OF1 bit in the SAICR register, and the data in the OF1 bit will show up at the pin synchronized to the frame sync in normal mode or the slot in network mode. When configured as the input flag IF1, the data value at the pin will be stored in the IF1 bit in the SAISR register, synchronized by the frame sync in normal mode or the slot in network mode. |
| PC1 | Input, output, or disconnected | GPIO disconnected | Port C 1 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. <i>This input is 5 V tolerant.</i> |
| FST | Input or output | GPIO disconnected | Frame Sync for Transmitter —This is the transmitter frame sync input/output signal. For synchronous mode, this signal is the frame sync for both transmitters and receivers. For asynchronous mode, FST is the frame sync for the transmitters only. The direction is determined by the transmitter frame sync direction (TFSD) bit in the ESAI transmit clock control register (TCCR). |

Table 2-10 Enhanced Serial Audio Interface Signals (continued)

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------|--------------------------------|--------------------|--|
| PC4 | Input, output, or disconnected | GPIO disconnected | Port C 4 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SCKR | Input or output | GPIO disconnected | Receiver Serial Clock —SCKR provides the receiver serial bit clock for the ESAI. The SCKR operates as a clock input or output used by all the enabled receivers in the asynchronous mode (SYN=0), or as serial flag 0 pin in the synchronous mode (SYN=1). When this pin is configured as serial flag pin, its direction is determined by the RCKD bit in the RCCR register. When configured as the output flag OF0, this pin will reflect the value of the OF0 bit in the SAICR register, and the data in the OF0 bit will show up at the pin synchronized to the frame sync in normal mode or the slot in network mode. When configured as the input flag IF0, the data value at the pin will be stored in the IF0 bit in the SAISR register, synchronized by the frame sync in normal mode or the slot in network mode. |
| PC0 | Input, output, or disconnected | GPIO disconnected | Port C 0 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SCKT | Input or output | GPIO disconnected | Transmitter Serial Clock —This signal provides the serial bit rate clock for the ESAI. SCKT is a clock input or output used by all enabled transmitters and receivers in synchronous mode, or by all enabled transmitters in asynchronous mode. |
| PC3 | Input, output, or disconnected | GPIO disconnected | Port C 3 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO5 | Output | GPIO disconnected | Serial Data Output 5 —When programmed as a transmitter, SDO5 is used to transmit data from the TX5 serial transmit shift register. |
| SDI0 | Input | GPIO disconnected | Serial Data Input 0 —When programmed as a receiver, SDI0 is used to receive serial data into the RX0 serial receive shift register. |
| PC6 | Input, output, or disconnected | GPIO disconnected | Port C 6 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO4 | Output | GPIO disconnected | Serial Data Output 4 —When programmed as a transmitter, SDO4 is used to transmit data from the TX4 serial transmit shift register. |

Table 2-10 Enhanced Serial Audio Interface Signals (continued)

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------|--------------------------------|--------------------|---|
| SDI1 | Input | GPIO disconnected | Serial Data Input 1 —When programmed as a receiver, SDI1 is used to receive serial data into the RX1 serial receive shift register. |
| PC7 | Input, output, or disconnected | GPIO disconnected | Port C 7 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO3 | Output | GPIO disconnected | Serial Data Output 3 —When programmed as a transmitter, SDO3 is used to transmit data from the TX3 serial transmit shift register. |
| SDI2 | Input | GPIO disconnected | Serial Data Input 2 —When programmed as a receiver, SDI2 is used to receive serial data into the RX2 serial receive shift register. |
| PC8 | Input, output, or disconnected | GPIO disconnected | Port C 8 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO2 | Output | GPIO disconnected | Serial Data Output 2 —When programmed as a transmitter, SDO2 is used to transmit data from the TX2 serial transmit shift register |
| SDI3 | Input | GPIO disconnected | Serial Data Input 3 —When programmed as a receiver, SDI3 is used to receive serial data into the RX3 serial receive shift register. |
| PC9 | Input, output, or disconnected | GPIO disconnected | Port C 9 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO1 | Output | GPIO disconnected | Serial Data Output 1 —SDO1 is used to transmit data from the TX1 serial transmit shift register. |
| PC10 | Input, output, or disconnected | GPIO disconnected | Port C 10 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |
| SDO0 | Output | GPIO disconnected | Serial Data Output 0 —SDO0 is used to transmit data from the TX0 serial transmit shift register. |
| PC11 | Input, output, or disconnected | GPIO disconnected | Port C 11 —When the ESAI is configured as GPIO, this signal is individually programmable as input, output, or internally disconnected. The default state after reset is GPIO disconnected. This input is 5 V tolerant. |

2.9 JTAG/OnCE Interface

Table 2-11 JTAG/OnCE Interface

| Signal Name | Signal Type | State during Reset | Signal Description |
|-------------|-------------|--------------------|--|
| TCK | Input | Input | Test Clock —TCK is a test clock input signal used to synchronize the JTAG test logic. It has an internal pull-up resistor. <i>This input is 5 V tolerant.</i> |
| TDI | Input | Input | Test Data Input —TDI is a test data serial input signal used for test instructions and data. TDI is sampled on the rising edge of TCK and has an internal pull-up resistor. This input is 5 V tolerant. |
| TDO | Output | Tri-stated | Test Data Output —TDO is a test data serial output signal used for test instructions and data. TDO is tri-statable and is actively driven in the shift-IR and shift-DR controller states. TDO changes on the falling edge of TCK. |
| TMS | Input | Input | Test Mode Select —TMS is an input signal used to sequence the test controller’s state machine. TMS is sampled on the rising edge of TCK and has an internal pull-up resistor. <i>This input is 5 V tolerant.</i> |

Table 2-12 GPIO Signals

| Signal Name | Signal Type | State during Reset | Signal Description |
|--------------|-------------------------------|--------------------|--|
| GPIO0-GP IO3 | Input, output or disconnected | Disconnected | GPIO0-3- The General Purpose I/O pins are used for control and handshake functions between the DSP and external circuitry. Each Port B GPIO pin may be individually programmed as an input, output or disconnected |

3 Specifications

3.1 Introduction

The DSP56364 is a high density CMOS device with Transistor-Transistor Logic (TTL) compatible inputs and outputs. The DSP56364 specifications are preliminary and are from design simulations, and may not be fully tested or guaranteed. Finalized specifications will be published after full characterization and device qualifications are complete.

3.2 Maximum Ratings

CAUTION

This device contains circuitry protecting against damage due to high static voltage or electrical fields. However, normal precautions should be taken to avoid exceeding maximum voltage ratings. Reliability of operation is enhanced if unused inputs are pulled to an appropriate logic voltage level (e.g., either GND or V_{CC}). The suggested value for a pullup or pulldown resistor is 10 k Ω .

NOTE

In the calculation of timing requirements, adding a maximum value of one specification to a minimum value of another specification does not yield a reasonable sum. A maximum specification is calculated using a worst case variation of process parameter values in one direction. The minimum specification is calculated using the worst case for the same parameters in the opposite direction. Therefore, a “maximum” value for a specification will never occur in the same device that has a “minimum” value for another specification; adding a maximum to a minimum represents a condition that can never exist.

Table 3-1 Maximum Ratings

| Rating ¹ | Symbol | Value ^{1, 2} | Unit |
|---|-----------|------------------------------|------|
| Supply Voltage | V_{CC} | -0.3 to +4.0 | V |
| All input voltages excluding “5 V tolerant” inputs ³ | V_{IN} | GND -0.3 to $V_{CC} + 0.3$ | V |
| All “5 V tolerant” input voltages ³ | V_{IN5} | GND - 0.3 to $V_{CC} + 3.95$ | V |
| Current drain per pin excluding V_{CC} and GND | I | 10 | mA |
| Operating temperature range | T_J | -40 to +105 | °C |
| Storage temperature | T_{STG} | -55 to +125 | °C |

¹ GND = 0 V, $V_{CC} = 3.3 \text{ V} \pm 0.16 \text{ V}$, $T_J = -0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50 \text{ pF}$

² Absolute maximum ratings are stress ratings only, and functional operation at the maximum is not guaranteed. Stress beyond the maximum rating may affect device reliability or cause permanent damage to the device.

³ **CAUTION:** All “5 V Tolerant” input voltages must not be more than 3.95 V greater than the supply voltage; this restriction applies to “power on”, as well as during normal operation. In any case, the input voltages cannot be more than 5.75 V. “5 V Tolerant” inputs are inputs that tolerate 5 V.

3.3 Thermal Characteristics

Table 3-2 Thermal Characteristics

| Characteristic | Symbol | TQFP Value | Unit |
|---|----------------------------------|------------|------|
| Junction-to-ambient thermal resistance ¹ | $R_{\theta JA}$ or θ_{JA} | 49.87 | °C/W |
| Junction-to-case thermal resistance ² | $R_{\theta JC}$ or θ_{JC} | 9.26 | °C/W |
| Thermal characterization parameter | Ψ_{JT} | 2.0 | °C/W |

¹ Junction-to-ambient thermal resistance is based on measurements on a horizontal single-sided printed circuit board per SEMI G38-87 in natural convection. (SEMI is Semiconductor Equipment and Materials International, 805 East Middlefield Rd., Mountain View, CA 94043, (415) 964-5111.)

Measurements were done with parts mounted on thermal test boards conforming to specification EIA/JESD51-3.

² Junction-to-case thermal resistance is based on measurements using a cold plate per SEMI G30-88, with the exception that the cold plate temperature is used for the case temperature.

3.4 DC Electrical Characteristics

Table 3-3 DC Electrical Characteristics¹

| Characteristics | Symbol | Min | Typ | Max | Unit |
|--|-----------|---------------------|-----|---------------------|---------|
| Supply voltage | V_{CC} | 3.14 | 3.3 | 3.46 | V |
| Input high voltage | | | | | V |
| • D(0:7), \overline{TA} | V_{IH} | 2.0 | — | V_{CC} | |
| • $MOD^2/\overline{IRQ^2}$, \overline{RESET} , $PINIT/\overline{NMI}$ and all JTAG/ESAI/GPIO/SHI (SPI mode)pins | V_{IHP} | 2.0 | — | $V_{CC} + 3.95$ | |
| • SHI (I2C mode) pins | V_{IHP} | 1.5 | — | $V_{CC} + 3.95$ | |
| • EXTAL ³ | V_{IHx} | $0.8 \times V_{CC}$ | — | V_{CC} | |
| Input low voltage | | | | | V |
| • D(0:7), \overline{TA} , $MOD^2/\overline{IRQ^2}$, \overline{RESET} , $PINIT$ | V_{IL} | -0.3 | — | 0.8 | |
| • JTAG/ESAI/GPIO/SHI (SPI mode)pins | V_{ILP} | -0.3 | — | 0.8 | |
| • SHI (I2C mode) pins | V_{ILP} | -0.3 | — | $0.3 \times V_{CC}$ | |
| • EXTAL ³ | V_{ILx} | -0.3 | — | $0.2 \times V_{CC}$ | |
| Input leakage current | I_{IN} | -10 | — | 10 | μA |
| High impedance (off-state) input current (@ 2.4 V / 0.4 V) | I_{TSI} | -10 | — | 10 | μA |
| Output high voltage | | | | | V |
| • TTL ($I_{OH} = -0.4 \text{ mA}$) ^{4,5} | V_{OH} | 2.4 | — | — | V |
| • CMOS ($I_{OH} = -10 \mu A$) ⁴ | V_{OH} | $V_{CC} - 0.01$ | — | — | V |
| Output low voltage | | | | | V |
| • TTL ($I_{OL} = 3.0 \text{ mA}$, open-drain pins $I_{OL} = 6.7 \text{ mA}$) ^{4,5} | V_{OL} | — | — | 0.4 | V |
| • CMOS ($I_{OL} = 10 \mu A$) ⁴ | V_{OL} | — | — | 0.01 | V |
| Internal supply current ⁶ at internal clock of 100Mhz | | | | | |
| • In Normal mode | I_{CCI} | — | 127 | 181 | mA |
| • In Wait mode ⁷ | I_{CCW} | — | 7.5 | 11 | mA |
| • In Stop mode ⁸ | I_{CCS} | — | 100 | 150 | μA |
| PLL supply current | | — | 1 | 2.5 | mA |
| Input capacitance ⁴ | C_{IN} | — | — | 10 | pF |

¹ $V_{CC} = 3.3 \text{ V} \pm .16 \text{ V}$; $T_J = 0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50 \text{ pF}$

² Refers to $MODA/\overline{IRQA}$, $MODB/\overline{IRQB}$, and $MODD/\overline{IRQD}$ pins

³ Driving EXTAL to the low V_{IHx} or the high V_{ILx} value may cause additional power consumption (DC current). To minimize power consumption, the minimum V_{IHx} should be no lower than $0.9 \times V_{CC}$ and the maximum V_{ILx} should be no higher than $0.1 \times V_{CC}$.

⁴ Periodically sampled and not 100% tested

AC Electrical Characteristics

- ⁵ This characteristic does not apply to PCAP.
- ⁶ [Section 5, "Design Considerations"](#) provides a formula to compute the estimated current requirements in Normal mode. In order to obtain these results, all inputs must be terminated (i.e., not allowed to float). Measurements are based on synthetic intensive DSP benchmarks. The power consumption numbers in this specification are 90% of the measured results of this benchmark. This reflects typical DSP applications. Typical internal supply current is measured with $V_{CC} = 3.3\text{ V}$ at $T_J = 105^\circ\text{C}$. Maximum internal supply current is measured with $V_{CC} = 3.46\text{ V}$ at $T_J = 105^\circ\text{C}$.
- ⁷ In order to obtain these results, all inputs must be terminated (i.e., not allowed to float). PLL signal is disabled during Stop state.
- ⁸ In order to obtain these results, all inputs, which are not disconnected at Stop mode, must be terminated (i.e., not allowed to float).

3.5 AC Electrical Characteristics

The timing waveforms shown in the AC electrical characteristics section are tested with a V_{IL} maximum of 0.3 V and a V_{IH} minimum of 2.4 V for all pins except EXTAL, which is tested using the input levels shown in [Note 8](#) of the previous table. AC timing specifications, which are referenced to a device input signal, are measured in production with respect to the 50% point of the respective input signal's transition. DSP56364 output levels are measured with the production test machine V_{OL} and V_{OH} reference levels set at 0.4 V and 2.4 V, respectively.

NOTE

Although the minimum value for the frequency of EXTAL is 0 MHz, the device AC test conditions are 15 MHz and rated speed.

3.6 Internal Clocks

Table 3-4 Internal Clocks

| Characteristics | Symbol | Expression ^{1, 2} | | |
|--|--------|--|-------------------------------------|--|
| | | Min | Typ | Max |
| Internal operation frequency with PLL enabled | f | — | $(E_f \times MF) / (PDF \times DF)$ | — |
| Internal operation frequency with PLL disabled | f | — | $E_f/2$ | — |
| Internal clock high period | T_H | | | |
| • With PLL disabled | | — | ET_C | — |
| • With PLL enabled and $MF \leq 4$ | | $0.49 \times ET_C \times PDF \times DF/MF$ | — | $0.51 \times ET_C \times PDF \times DF/MF$ |
| • With PLL enabled and $MF > 4$ | | $0.47 \times ET_C \times PDF \times DF/MF$ | — | $0.53 \times ET_C \times PDF \times DF/MF$ |

Table 3-4 Internal Clocks (continued)


| Characteristics | Symbol | Expression ^{1, 2} | | |
|---|-----------|---|--------------------------------|---|
| | | Min | Typ | Max |
| Internal clock low period <ul style="list-style-type: none"> • With PLL disabled • With PLL enabled and $MF \leq 4$ • With PLL enabled and $MF > 4$ | T_L | — $0.49 \times ET_C \times PDF \times DF/MF$ $0.47 \times ET_C \times PDF \times DF/MF$ | ET_C — — | — $0.51 \times ET_C \times PDF \times DF/MF$ $0.53 \times ET_C \times PDF \times DF/MF$ |
| Internal clock cycle time with PLL enabled | T_C | — | $ET_C \times PDF \times DF/MF$ | — |
| Internal clock cycle time with PLL disabled | T_C | — | $2 \times ET_C$ | — |
| Instruction cycle time | I_{CYC} | — | T_C | — |

¹ DF = Division Factor
Ef = External frequency
 ET_C = External clock cycle
MF = Multiplication Factor
PDF = Predivision Factor
 T_C = internal clock cycle

² See the *PLL and Clock Generation* section in the *DSP56300 Family Manual* for a detailed discussion of the PLL.

3.7 EXTERNAL CLOCK OPERATION

The DSP56364 system clock is an externally supplied square wave voltage source connected to EXTAL(See [Figure 3-1](#)).



Note: The midpoint is $0.5 (V_{IHC} + V_{ILC})$.

Figure 3-1 External Clock Timing

Phase Lock Loop (PLL) Characteristics

Table 3-5 Clock Operation

| No. | Characteristics | Symbol | Min | Max |
|-----|--|--------|----------------------|---------------------------|
| 1 | Frequency of EXTAL (EXTAL Pin Frequency) The rise and fall time of this external clock should be 3 ns maximum. | E_f | 0 | 100.0 |
| 2 | EXTAL input high ^{1, 2} <ul style="list-style-type: none"> With PLL disabled (46.7%–53.3% duty cycle⁶) With PLL enabled (42.5%–57.5% duty cycle⁶) | ET_H | 4.67 ns 4.25 ns | ∞ 157.0 μ s |
| 3 | EXTAL input low ^{1, 2} <ul style="list-style-type: none"> With PLL disabled (46.7%–53.3% duty cycle⁶) With PLL enabled (42.5%–57.5% duty cycle⁶) | ET_L | 4.67 ns 4.25 ns | ∞ 157.0 μ s |
| 4 | EXTAL cycle time ² <ul style="list-style-type: none"> With PLL disabled With PLL enabled | ET_C | 10.00 ns 10.00 ns | ∞ 273.1 μ s |

¹ Measured at 50% of the input transition.

² The maximum value for PLL enabled is given for minimum V_{CO} and maximum MF.

3.8 Phase Lock Loop (PLL) Characteristics

Table 3-6 PLL Characteristics

| Characteristics | Min | Max | Unit |
|--|--|---|------|
| V_{CO} frequency when PLL enabled ($MF \times E_f \times 2/PDF$) | 30 | 200 | MHz |
| PLL external capacitor (PCAP pin to V_{CCP}) (C_{PCAP} ¹) <ul style="list-style-type: none"> @ $MF \leq 4$ @ $MF > 4$ | $(MF \times 580) - 100$ $MF \times 830$ | $(MF \times 780) - 140$ $MF \times 1470$ | pF |

¹ C_{PCAP} is the value of the PLL capacitor (connected between the P_{CAP} pin and V_{CCP}). The recommended value in pF for C_{PCAP} can be computed from one of the following equations:
 $(MF \times 680) - 120$, for $MF \leq 4$, or
 $MF \times 1100$, for $MF > 4$.

3.9 Reset, Stop, Mode Select, and Interrupt Timing

Table 3-7 Reset, Stop, Mode Select, and Interrupt Timing¹

| No. | Characteristics | Expression ² | Min | Max | Unit |
|-----|---|--|---|----------------------------|---|
| 8 | Delay from $\overline{\text{RESET}}$ assertion to all pins at reset value ³ | — | — | 26.0 | ns |
| 9 | Required $\overline{\text{RESET}}$ duration ⁴ <ul style="list-style-type: none"> • Power on, external clock generator, PLL disabled • Power on, external clock generator, PLL enabled • Power on, internal oscillator • During STOP, XTAL disabled (PCTL Bit 16 = 0) • During STOP, XTAL enabled (PCTL Bit 16 = 1) • During normal operation | $50 \times \text{ET}_C$ $1000 \times \text{ET}_C$ $75000 \times \text{ET}_C$ $75000 \times \text{ET}_C$ $2.5 \times \text{T}_C$ $2.5 \times \text{T}_C$ | 500.0 10.0 0.75 0.75 25.0 25.0 | — — — — — — | ns ns μs ms ms ns |
| 10 | Delay from asynchronous $\overline{\text{RESET}}$ deassertion to first external address output (internal reset deassertion) ⁵ <ul style="list-style-type: none"> • Minimum • Maximum | $3.25 \times \text{T}_C + 2.0$ $20.25 \text{T}_C + 7.50$ | 34.5 — | — 211.5 | ns ns |
| 13 | Mode select setup time | | 30.0 | — | ns |
| 14 | Mode select hold time | | 0.0 | — | ns |
| 15 | Minimum edge-triggered interrupt request assertion width | | 6.6 | — | ns |
| 16 | Minimum edge-triggered interrupt request deassertion width | | 6.6 | — | ns |
| 17 | Delay from $\overline{\text{IRQA}}$, $\overline{\text{IRQB}}$, $\overline{\text{IRQD}}$, $\overline{\text{NMI}}$ assertion to external memory access address out valid <ul style="list-style-type: none"> • Caused by first interrupt instruction fetch • Caused by first interrupt instruction execution | $4.25 \times \text{T}_C + 2.0$ $7.25 \times \text{T}_C + 2.0$ | 44.5 74.5 | — — | ns ns |
| 18 | Delay from $\overline{\text{IRQA}}$, $\overline{\text{IRQB}}$, $\overline{\text{IRQD}}$, $\overline{\text{NMI}}$ assertion to general-purpose transfer output valid caused by first interrupt instruction execution | $10 \times \text{T}_C + 5.0$ | 105.0 | — | ns |
| 19 | Delay from address output valid caused by first interrupt instruction execute to interrupt request deassertion for level sensitive fast interrupts ^{6, 7} | $3.75 \times \text{T}_C + \text{WS} \times \text{T}_C - 10.94$ | — | — | ns |
| 20 | Delay from $\overline{\text{RD}}$ assertion to interrupt request deassertion for level sensitive fast interrupts ^{6, 7} | $3.25 \times \text{T}_C + \text{WS} \times \text{T}_C - 10.94$ | — | — | ns |

Table 3-7 Reset, Stop, Mode Select, and Interrupt Timing¹ (continued)

| No. | Characteristics | Expression ² | Min | Max | Unit |
|-----|---|--|------|-------|------|
| 21 | Delay from \overline{WR} assertion to interrupt request deassertion for level sensitive fast interrupts ^{6, 7} <ul style="list-style-type: none"> • DRAM for all WS • SRAM WS = 1 • SRAM WS = 2, 3 • SRAM WS \geq 4 | $(WS + 3.5) \times T_C - 10.94$ $(WS + 3.5) \times T_C - 10.94$ $(WS + 3) \times T_C - 10.94$ $(WS + 2.5) \times T_C - 10.94$ | — | — | ns |
| 24 | Duration for \overline{IRQA} assertion to recover from Stop state | | 5.9 | — | |
| 25 | Delay from \overline{IRQA} assertion to fetch of first instruction (when exiting Stop) ^{3, 8} <ul style="list-style-type: none"> • PLL is not active during Stop (PCTL Bit 17 = 0) and Stop delay is enabled (OMR Bit 6 = 0) • PLL is not active during Stop (PCTL Bit 17 = 0) and Stop delay is not enabled (OMR Bit 6 = 1) • PLL is active during Stop (PCTL Bit 17 = 1) (Implies No Stop Delay) | $PLC \times ET_C \times PDF + (128K - PLC/2) \times T_C$ $PLC \times ET_C \times PDF + (23.75 \pm 0.5) \times T_C$ $(8.25 \pm 0.5) \times T_C$ | 1.3 | 13.6 | ms |
| 26 | Duration of level sensitive \overline{IRQA} assertion to ensure interrupt service (when exiting Stop) ^{3, 8} <ul style="list-style-type: none"> • PLL is not active during Stop (PCTL Bit 17 = 0) and Stop delay is enabled (OMR Bit 6 = 0) • PLL is not active during Stop (PCTL Bit 17 = 0) and Stop delay is not enabled (OMR Bit 6 = 1) • PLL is active during Stop (PCTL Bit 17 = 1) (implies no Stop delay) | $PLC \times ET_C \times PDF + (128K - PLC/2) \times T_C$ $PLC \times ET_C \times PDF + (20.5 \pm 0.5) \times T_C$ $5.5 \times T_C$ | 13.6 | — | ms |
| 27 | Interrupt Requests Rate <ul style="list-style-type: none"> • ESAI, SCI • DMA • \overline{IRQ}, \overline{NMI} (edge trigger) • \overline{IRQ}, \overline{NMI} (level trigger) | $12T_C$ $8T_C$ $8T_C$ $12T_C$ | — | 120.0 | ns |
| 28 | DMA Requests Rate <ul style="list-style-type: none"> • Data read from ESAI, SCI • Data write to ESAI, SCI • \overline{IRQ}, \overline{NMI} (edge trigger) | $6T_C$ $7T_C$ $3T_C$ | — | 60.0 | ns |

Table 3-7 Reset, Stop, Mode Select, and Interrupt Timing¹ (continued)

| No. | Characteristics | Expression ² | Min | Max | Unit |
|-----|--|-------------------------|------|-----|------|
| 29 | Delay from \overline{IRQA} , \overline{IRQB} , \overline{IRQD} , \overline{NMI} assertion to external memory (DMA source) access address out valid | $4.25 \times T_C + 2.0$ | 44.0 | — | ns |

¹ $V_{CC} = 3.3 \text{ V} \pm 0.16 \text{ V}$; $T_J = 0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50 \text{ pF}$

² Use expression to compute maximum value.

³ Periodically sampled and not 100% tested

⁴ For an external clock generator, \overline{RESET} duration is measured during the time in which \overline{RESET} is asserted, V_{CC} is valid, and the EXTAL input is active and valid.

For internal oscillator, \overline{RESET} duration is measured during the time in which \overline{RESET} is asserted and V_{CC} is valid. The specified timing reflects the crystal oscillator stabilization time after power-up. This number is affected both by the specifications of the crystal and other components connected to the oscillator and reflects worst case conditions.

When the V_{CC} is valid, but the other “required \overline{RESET} duration” conditions (as specified above) have not been yet met, the device circuitry will be in an uninitialized state that can result in significant power consumption and heat-up. Designs should minimize this state to the shortest possible duration.

⁵ For an external clock generator, \overline{RESET} duration is measured during the time in which \overline{RESET} is asserted, V_{CC} is valid, and the EXTAL input is active and valid.

For internal oscillator, \overline{RESET} duration is measured during the time in which \overline{RESET} is asserted and V_{CC} is valid. The specified timing reflects the crystal oscillator stabilization time after power-up. This number is affected both by the specifications of the crystal and other components connected to the oscillator and reflects worst case conditions.

When the V_{CC} is valid, but the other “required \overline{RESET} duration” conditions (as specified above) have not been yet met, the device circuitry will be in an uninitialized state that can result in significant power consumption and heat-up. Designs should minimize this state to the shortest possible duration.

⁶ When using fast interrupts and \overline{IRQA} , \overline{IRQB} , and \overline{IRQD} are defined as level-sensitive, timings 19 through 21 apply to prevent multiple interrupt service. To avoid these timing restrictions, the deasserted Edge-triggered mode is recommended when using fast interrupts. Long interrupts are recommended when using Level-sensitive mode.

⁷ WS = number of wait states (measured in clock cycles, number of T_C)

⁸ This timing depends on several settings:

For PLL disable, using internal oscillator (PLL Control Register (PCTL) Bit 16 = 0) and oscillator disabled during Stop (PCTL Bit 17 = 0), a stabilization delay is required to assure the oscillator is stable before executing programs. In that case, resetting the Stop delay (OMR Bit 6 = 0) will provide the proper delay. While it is possible to set OMR Bit 6 = 1, it is not recommended and these specifications do not guarantee timings for that case.

For PLL disable, using internal oscillator (PCTL Bit 16 = 0) and oscillator enabled during Stop (PCTL Bit 17=1), no stabilization delay is required and recovery time will be minimal (OMR Bit 6 setting is ignored).

For PLL disable, using external clock (PCTL Bit 16 = 1), no stabilization delay is required and recovery time will be defined by the PCTL Bit 17 and OMR Bit 6 settings.

For PLL enable, if PCTL Bit 17 is 0, the PLL is shutdown during Stop. Recovering from Stop requires the PLL to get locked. The PLL lock procedure duration, PLL Lock Cycles (PLC), may be in the range of 0 to 1000 cycles. This procedure occurs in parallel with the stop delay counter, and stop recovery will end when the last of these two events occurs. The stop delay counter completes count or PLL lock procedure completion.

PLC value for PLL disable is 0.

The maximum value for ET_C is 4096 (maximum MF) divided by the desired internal frequency (i.e., for 100 MHz it is $4096/100 \text{ MHz} = 40 \mu\text{s}$). During the stabilization period, T_C , T_H , and T_L will not be constant, and their width may vary, so timing may vary as well.

9. If PLL does not lose lock.






Figure 3-2 Reset Timing




a) First Interrupt Instruction Execution



b) General Purpose I/O


AA0462

Figure 3-3 External Fast Interrupt Timing




AA0463

Figure 3-4 External Interrupt Timing (Negative Edge-Triggered)



AA0465

Figure 3-5 Operating Mode Select Timing



AA0466

Figure 3-6 Recovery from Stop State Using $\overline{\text{IRQA}}$

External Memory Expansion Port (Port A)




Figure 3-7 Recovery from Stop State Using $\overline{\text{IRQA}}$ Interrupt Service




Figure 3-8 External Memory Access (DMA Source) Timing

3.10 External Memory Expansion Port (Port A)

3.10.1 SRAM Timing

Table 3-8 SRAM Read and Write Accesses¹

| No. | Characteristics | Symbol | Expression ² | Min | Max | Unit |
|-----|--|---------------------|---|-------|-----|------|
| 100 | Address valid and AA assertion pulse width | t_{RC} , t_{WC} | $(WS + 1) \times T_C - 4.0$ [$1 \leq WS \leq 3$] | 16.0 | — | ns |
| | | | $(WS + 2) \times T_C - 4.0$ [$4 \leq WS \leq 7$] | 56.0 | — | ns |
| | | | $(WS + 3) \times T_C - 4.0$ [$WS \geq 8$] | 106.0 | — | ns |

Table 3-8 SRAM Read and Write Accesses¹ (continued)

| No. | Characteristics | Symbol | Expression ² | Min | Max | Unit |
|-----|--|------------------|---|------|------|------|
| 101 | Address and AA valid to \overline{WR} assertion | t_{AS} | $0.25 \times T_C - 2.0$ [WS = 1] | 0.5 | — | ns |
| | | | $0.75 \times T_C - 2.0$ [2 ≤ WS ≤ 3] | 5.5 | — | ns |
| | | | $1.25 \times T_C - 2.0$ [WS ≥ 4] | 10.5 | — | ns |
| 102 | \overline{WR} assertion pulse width | t_{WP} | $1.5 \times T_C - 4.0$ [WS = 1] | 11.0 | — | ns |
| | | | All frequencies: $WS \times T_C - 4.0$ [2 ≤ WS ≤ 3] | 16.0 | — | ns |
| | | | $(WS - 0.5) \times T_C - 4.0$ [WS ≥ 4] | 31.0 | — | ns |
| 103 | \overline{WR} deassertion to address not valid | t_{WR} | $0.25 \times T_C - 2.0$ [1 ≤ WS ≤ 3] | 0.5 | — | ns |
| | | | $1.25 \times T_C - 2.0$ [4 ≤ WS ≤ 7] | 10.5 | — | ns |
| | | | $2.25 \times T_C - 2.0$ [WS ≥ 8] | 20.5 | — | ns |
| | | | All frequencies: $1.25 \times T_C - 4.0$ [4 ≤ WS ≤ 7] | 8.5 | — | ns |
| | | | $2.25 \times T_C - 4.0$ [WS ≥ 8] | 18.5 | — | ns |
| 104 | Address and AA valid to input data valid | t_{AA}, t_{AC} | $(WS + 0.75) \times T_C - 7.0$ [WS ≥ 1] | — | 10.5 | ns |
| 105 | \overline{RD} assertion to input data valid | t_{OE} | $(WS + 0.25) \times T_C - 7.0$ [WS ≥ 1] | — | 5.5 | ns |
| 106 | \overline{RD} deassertion to data not valid (data hold time) | t_{OHZ} | | 0.0 | — | ns |
| 107 | Address valid to \overline{WR} deassertion ³ | t_{AW} | $(WS + 0.75) \times T_C - 4.0$ [WS ≥ 1] | 13.5 | — | ns |

Table 3-8 SRAM Read and Write Accesses¹ (continued)

| No. | Characteristics | Symbol | Expression ² | Min | Max | Unit |
|-----|---|-----------------------|---|------|-----|------|
| 108 | Data valid to \overline{WR} deassertion (data setup time) | t_{DS} (t_{DW}) | $(WS - 0.25) \times T_C - 3.0$ [$WS \geq 1$] | 4.5 | — | ns |
| 109 | Data hold time from \overline{WR} deassertion | t_{DH} | $0.25 \times T_C - 2.0$ [$1 \leq WS \leq 3$] | 0.5 | — | ns |
| | | | $1.25 \times T_C - 2.0$ [$4 \leq WS \leq 7$] | 10.5 | — | ns |
| | | | $2.25 \times T_C - 2.0$ [$WS \geq 8$] | 20.5 | — | ns |
| 113 | \overline{RD} deassertion time | | $0.75 \times T_C - 4.0$ [$1 \leq WS \leq 3$] | 3.5 | — | ns |
| | | | $1.75 \times T_C - 4.0$ [$4 \leq WS \leq 7$] | 13.5 | — | ns |
| | | | $2.75 \times T_C - 4.0$ [$WS \geq 8$] | 23.5 | — | ns |
| 114 | \overline{WR} deassertion time | | $0.5 \times T_C - 4.0$ [$WS = 1$] | 1.0 | — | ns |
| | | | $T_C - 2.0$ [$2 \leq WS \leq 3$] | 6.0 | — | ns |
| | | | $2.5 \times T_C - 4.0$ [$4 \leq WS \leq 7$] | 21.0 | — | ns |
| | | | $3.5 \times T_C - 4.0$ [$WS \geq 8$] | 31.0 | — | ns |
| 115 | Address valid to \overline{RD} assertion | | $0.5 \times T_C - 4.0$ | 1.0 | — | ns |
| 116 | \overline{RD} assertion pulse width | | $(WS + 0.25) \times T_C - 4.0$ | 8.5 | — | ns |
| 117 | \overline{RD} deassertion to address not valid | | $0.25 \times T_C - 2.0$ [$1 \leq WS \leq 3$] | 0.5 | — | ns |
| | | | $1.25 \times T_C - 2.0$ [$4 \leq WS \leq 7$] | 10.5 | — | ns |
| | | | $2.25 \times T_C - 2.0$ [$WS \geq 8$] | 20.5 | — | ns |

Table 3-8 SRAM Read and Write Accesses¹ (continued)

| No. | Characteristics | Symbol | Expression ² | Min | Max | Unit |
|-----|--|--------|-------------------------|-----|-----|------|
| 118 | \overline{TA} setup before \overline{RD} or \overline{WR} deassertion ⁴ | | $0.25 \times T_C + 2.0$ | 4.5 | — | ns |
| 119 | \overline{TA} hold after \overline{RD} or \overline{WR} deassertion | | | 0 | — | ns |

¹ All timings for 100 MHz are measured from $0.5 \cdot V_{CC}$ to $.05 \cdot V_{CC}$

² WS is the number of wait states specified in the BCR.

³ Timings 100, 107 are guaranteed by design, not tested.

⁴ In the case of \overline{TA} negation: timing 118 is relative to the deassertion edge of \overline{RD} or \overline{WR} were \overline{TA} to remain active.




Figure 3-9 SRAM Read Access




Figure 3-10 SRAM Write Access

3.10.2 DRAM Timing

The selection guides provided in [Figure 3-11](#) and [Figure 3-14](#) should be used for primary selection only. Final selection should be based on the timing provided in the following tables. As an example, the selection guide suggests that 4 wait states must be used for 100 MHz operation when using Page Mode DRAM. However, by using the information in the appropriate table, a designer may choose to evaluate whether fewer wait states might be used by determining which timing prevents operation at 100 MHz, running the chip at a slightly lower frequency (e.g., 95 MHz), using faster DRAM (if it becomes available), and control factors such as capacitive and resistive load to improve overall system performance.




Figure 3-11 DRAM Page Mode Wait States Selection Guide

Table 3-9 DRAM Page Mode Timings, One Wait State (Low-Power Applications)^{1, 2, 3}

| No. | Characteristics | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|---|-----------|------------------------|---------------------|------|---------------------|------|------|
| | | | | Min | Max | Min | Max | |
| 131 | Page mode cycle time for two consecutive accesses of the same direction | t_{PC} | $2 \times T_C$ | 100.0 | — | 66.7 | — | ns |
| | Page mode cycle time for mixed (read and write) accesses | | $1.25 \times T_C$ | 62.5 | — | 41.7 | — | |
| 132 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $T_C - 7.5$ | — | 42.5 | — | 25.8 | ns |
| 133 | Column address valid to data valid (read) | t_{AA} | $1.5 \times T_C - 7.5$ | — | 67.5 | — | 42.5 | ns |

Table 3-9 DRAM Page Mode Timings, One Wait State (Low-Power Applications)^{1, 2, 3} (continued)

| No. | Characteristics | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|--|-------------------|----------------------------------|---------------------|-----|---------------------|-----|------|
| | | | | Min | Max | Min | Max | |
| 134 | $\overline{\text{CAS}}$ deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | 0.0 | — | ns |
| 135 | Last $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RSH} | $0.75 \times T_{\text{C}} - 4.0$ | 33.5 | — | 21.0 | — | ns |
| 136 | Previous $\overline{\text{CAS}}$ deassertion to $\overline{\text{RAS}}$ deassertion | t_{RHCP} | $2 \times T_{\text{C}} - 4.0$ | 96.0 | — | 62.7 | — | ns |
| 137 | $\overline{\text{CAS}}$ assertion pulse width | t_{CAS} | $0.75 \times T_{\text{C}} - 4.0$ | 33.5 | — | 21.0 | — | ns |
| 138 | Last $\overline{\text{CAS}}$ deassertion to $\overline{\text{RAS}}$ deassertion ⁵ BRW[1:0] = 00 • BRW[1:0] = 01 • BRW[1:0] = 10 • BRW[1:0] = 11 | t_{CRP} | $1.75 \times T_{\text{C}} - 6.0$ | 81.5 | — | 52.3 | — | ns |
| | | | $3.25 \times T_{\text{C}} - 6.0$ | 156.5 | — | 102.2 | — | ns |
| | | | $4.25 \times T_{\text{C}} - 6.0$ | 206.5 | — | 135.5 | — | ns |
| | | | $6.25 \times T_{\text{C}} - 6.0$ | 306.5 | — | 202.1 | — | ns |
| 139 | $\overline{\text{CAS}}$ deassertion pulse width | t_{CP} | $0.5 \times T_{\text{C}} - 4.0$ | 21.0 | — | 12.7 | — | ns |
| 140 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $0.5 \times T_{\text{C}} - 4.0$ | 21.0 | — | 12.7 | — | ns |
| 141 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $0.75 \times T_{\text{C}} - 4.0$ | 33.5 | — | 21.0 | — | ns |
| 142 | Last column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $2 \times T_{\text{C}} - 4.0$ | 96.0 | — | 62.7 | — | ns |
| 143 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $0.75 \times T_{\text{C}} - 3.8$ | 33.7 | — | 21.2 | — | ns |
| 144 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}$ assertion | t_{RCH} | $0.25 \times T_{\text{C}} - 3.7$ | 8.8 | — | 4.6 | — | ns |
| 145 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $0.5 \times T_{\text{C}} - 4.2$ | 20.8 | — | 12.5 | — | ns |
| 146 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $1.5 \times T_{\text{C}} - 4.5$ | 70.5 | — | 45.5 | — | ns |
| 147 | Last $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $1.75 \times T_{\text{C}} - 4.3$ | 83.2 | — | 54.0 | — | ns |
| 148 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $1.75 \times T_{\text{C}} - 4.3$ | 83.2 | — | 54.0 | — | ns |
| 149 | Data valid to $\overline{\text{CAS}}$ assertion (Write) | t_{DS} | $0.25 \times T_{\text{C}} - 4.0$ | 8.5 | — | 4.3 | — | ns |
| 150 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $0.75 \times T_{\text{C}} - 4.0$ | 33.5 | — | 21.0 | — | ns |
| 151 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{WCS} | $T_{\text{C}} - 4.3$ | 45.7 | — | 29.0 | — | ns |

Table 3-9 DRAM Page Mode Timings, One Wait State (Low-Power Applications)^{1, 2, 3} (continued)

| No. | Characteristics | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|--|-----------|-------------------------|---------------------|------|---------------------|------|------|
| | | | | Min | Max | Min | Max | |
| 152 | Last \overline{RD} assertion to \overline{RAS} deassertion | t_{ROH} | $1.5 \times T_C - 4.0$ | 71.0 | — | 46.0 | — | ns |
| 153 | \overline{RD} assertion to data valid | t_{GA} | $T_C - 7.5$ | — | 42.5 | — | 25.8 | ns |
| 154 | \overline{RD} deassertion to data not valid ⁶ | t_{GZ} | | 0.0 | — | 0.0 | — | ns |
| 155 | \overline{WR} assertion to data active | | $0.75 \times T_C - 0.3$ | 37.2 | — | 24.7 | — | ns |
| 156 | \overline{WR} deassertion to data high impedance | | $0.25 \times T_C$ | — | 12.5 | — | 8.3 | ns |

¹ The number of wait states for Page mode access is specified in the DCR.

² The refresh period is specified in the DCR.

³ All the timings are calculated for the worst case. Some of the timings are better for specific cases (e.g., t_{PC} equals $2 \times T_C$ for read-after-read or write-after-write sequences).

⁴ Reduced DSP clock speed allows use of Page Mode DRAM with one Wait state (See [Figure 3-14](#)).

⁵ BRW[1:0] (DRAM control register bits) defines the number of wait states that should be inserted in each DRAM out-of-page access.

⁶ \overline{RD} deassertion will always occur after \overline{CAS} deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

Table 3-10 DRAM Page Mode Timings, Two Wait States^{1, 2, 3, 4}

| No. | Characteristics | Symbol | Expression ⁵ | 66 MHz | | 80 MHz | | Unit |
|-----|--|------------|-------------------------|--------|------|--------|------|------|
| | | | | Min | Max | Min | Max | |
| 131 | Page mode cycle time for two consecutive accesses of the same direction | t_{PC} | $2 \times T_C$ | 45.4 | — | 37.5 | — | ns |
| | Page mode cycle time for mixed (read and write) accesses | | $1.25 \times T_C$ | 41.1 | — | 34.4 | — | ns |
| 132 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $1.5 \times T_C - 7.5$ | — | 15.2 | — | — | ns |
| | | | $1.5 \times T_C - 6.5$ | — | — | — | 12.3 | ns |
| 133 | Column address valid to data valid (read) | t_{AA} | $2.5 \times T_C - 7.5$ | — | 30.4 | — | — | ns |
| | | | $2.5 \times T_C - 6.5$ | — | — | — | 24.8 | ns |
| 134 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | 0.0 | — | ns |
| 135 | Last \overline{CAS} assertion to \overline{RAS} deassertion | t_{RSH} | $1.75 \times T_C - 4.0$ | 22.5 | — | 17.9 | — | ns |
| 136 | Previous \overline{CAS} deassertion to \overline{RAS} deassertion | t_{RHCP} | $3.25 \times T_C - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 137 | \overline{CAS} assertion pulse width | t_{CAS} | $1.5 \times T_C - 4.0$ | 18.7 | — | 14.8 | — | ns |
| 138 | Last \overline{CAS} deassertion to \overline{RAS} deassertion ⁶ • BRW[1:0] = 00 • BRW[1:0] = 01 • BRW[1:0] = 10 • BRW[1:0] = 11 | t_{CRP} | $2.0 \times T_C - 6.0$ | 24.4 | — | 19.0 | — | ns |
| | | | $3.5 \times T_C - 6.0$ | 47.2 | — | 37.8 | — | ns |
| | | | $4.5 \times T_C - 6.0$ | 62.4 | — | 50.3 | — | ns |
| | | | $6.5 \times T_C - 6.0$ | 92.8 | — | 75.3 | — | ns |
| 139 | \overline{CAS} deassertion pulse width | t_{CP} | $1.25 \times T_C - 4.0$ | 14.9 | — | 11.6 | — | ns |
| 140 | Column address valid to \overline{CAS} assertion | t_{ASC} | $T_C - 4.0$ | 11.2 | — | 8.5 | — | ns |
| 141 | \overline{CAS} assertion to column address not valid | t_{CAH} | $1.75 \times T_C - 4.0$ | 22.5 | — | 17.9 | — | ns |
| 142 | Last column address valid to \overline{RAS} deassertion | t_{RAL} | $3 \times T_C - 4.0$ | 41.5 | — | 33.5 | — | ns |
| 143 | \overline{WR} deassertion to \overline{CAS} assertion | t_{RCS} | $1.25 \times T_C - 3.8$ | 15.1 | — | 11.8 | — | ns |
| 144 | \overline{CAS} deassertion to \overline{WR} assertion | t_{RCH} | $0.5 \times T_C - 3.7$ | 3.9 | — | 2.6 | — | ns |
| 145 | \overline{CAS} assertion to \overline{WR} deassertion | t_{WCH} | $1.5 \times T_C - 4.2$ | 18.5 | — | 14.6 | — | ns |
| 146 | \overline{WR} assertion pulse width | t_{WP} | $2.5 \times T_C - 4.5$ | 33.5 | — | 26.8 | — | ns |

Table 3-10 DRAM Page Mode Timings, Two Wait States^{1, 2, 3, 4} (continued)

| No. | Characteristics | Symbol | Expression ⁵ | 66 MHz | | 80 MHz | | Unit |
|-----|--|-----------|-------------------------|--------|------|--------|------|------|
| | | | | Min | Max | Min | Max | |
| 147 | Last \overline{WR} assertion to \overline{RAS} deassertion | t_{RWL} | $2.75 \times T_C - 4.3$ | 33.4 | — | 26.8 | — | ns |
| 148 | \overline{WR} assertion to \overline{CAS} deassertion | t_{CWL} | $2.5 \times T_C - 4.3$ | 33.6 | — | 27.0 | — | ns |
| 149 | Data valid to \overline{CAS} assertion (write) | t_{DS} | $0.25 \times T_C - 3.7$ | 0.1 | — | — | — | ns |
| | | | $0.25 \times T_C - 3.0$ | — | — | 0.1 | — | ns |
| 150 | \overline{CAS} assertion to data not valid (write) | t_{DH} | $1.75 \times T_C - 4.0$ | 22.5 | — | 17.9 | — | ns |
| 151 | \overline{WR} assertion to \overline{CAS} assertion | t_{WCS} | $T_C - 4.3$ | 10.9 | — | 8.2 | — | ns |
| 152 | Last \overline{RD} assertion to \overline{RAS} deassertion | t_{ROH} | $2.5 \times T_C - 4.0$ | 33.9 | — | 27.3 | — | ns |
| 153 | \overline{RD} assertion to data valid | t_{GA} | $1.75 \times T_C - 7.5$ | — | 19.0 | — | — | ns |
| | | | $1.75 \times T_C - 6.5$ | — | — | — | 15.4 | ns |
| 154 | \overline{RD} deassertion to data not valid ⁷ | t_{GZ} | | 0.0 | — | 0.0 | — | ns |
| 155 | \overline{WR} assertion to data active | | $0.75 \times T_C - 0.3$ | 11.1 | — | 9.1 | — | ns |
| 156 | \overline{WR} deassertion to data high impedance | | $0.25 \times T_C$ | — | 3.8 | — | 3.1 | ns |

¹ The number of wait states for Page mode access is specified in the DCR.

² The refresh period is specified in the DCR.

³ The asynchronous delays specified in the expressions are valid for DSP56364.

⁴ There are no DRAMs fast enough to fit to two wait states Page mode @ 100MHz (See [Figure 3-11](#))

⁵ All the timings are calculated for the worst case. Some of the timings are better for specific cases (e.g., t_{PC} equals $3 \times T_C$ for read-after-read or write-after-write sequences).

⁶ BRW[1:0] (DRAM Control Register bits) defines the number of wait states that should be inserted in each DRAM out-of-page access.

⁷ \overline{RD} deassertion will always occur after \overline{CAS} deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

Table 3-11 DRAM Page Mode Timings, Three Wait States^{1, 2, 3}

| No. | Characteristics | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|------------|-------------------------|------|------|------|
| 131 | Page mode cycle time for two consecutive accesses of the same direction | t_{PC} | $2 \times T_C$ | 40.0 | — | ns |
| | Page mode cycle time for mixed (read and write) accesses | | $1.25 \times T_C$ | 35.0 | — | |
| 132 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $2 \times T_C - 7.0$ | — | 13.0 | ns |
| 133 | Column address valid to data valid (read) | t_{AA} | $3 \times T_C - 7.0$ | — | 23.0 | ns |
| 134 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | ns |
| 135 | Last \overline{CAS} assertion to \overline{RAS} deassertion | t_{RSH} | $2.5 \times T_C - 4.0$ | 21.0 | — | ns |
| 136 | Previous \overline{CAS} deassertion to \overline{RAS} deassertion | t_{RHCP} | $4.5 \times T_C - 4.0$ | 41.0 | — | ns |
| 137 | \overline{CAS} assertion pulse width | t_{CAS} | $2 \times T_C - 4.0$ | 16.0 | — | ns |
| 138 | Last \overline{CAS} deassertion to \overline{RAS} assertion ⁵ <ul style="list-style-type: none"> • BRW[1:0] = 00 • BRW[1:0] = 01 • BRW[1:0] = 10 • BRW[1:0] = 11 | t_{CRP} | $2.25 \times T_C - 6.0$ | — | — | ns |
| | | | $3.75 \times T_C - 6.0$ | — | — | ns |
| | | | $4.75 \times T_C - 6.0$ | 41.5 | — | ns |
| | | | $6.75 \times T_C - 6.0$ | 61.5 | — | ns |
| 139 | \overline{CAS} deassertion pulse width | t_{CP} | $1.5 \times T_C - 4.0$ | 11.0 | — | ns |
| 140 | Column address valid to \overline{CAS} assertion | t_{ASC} | $T_C - 4.0$ | 6.0 | — | ns |
| 141 | \overline{CAS} assertion to column address not valid | t_{CAH} | $2.5 \times T_C - 4.0$ | 21.0 | — | ns |
| 142 | Last column address valid to \overline{RAS} deassertion | t_{RAL} | $4 \times T_C - 4.0$ | 36.0 | — | ns |
| 143 | \overline{WR} deassertion to \overline{CAS} assertion | t_{RCS} | $1.25 \times T_C - 4.0$ | 8.5 | — | ns |
| 144 | \overline{CAS} deassertion to \overline{WR} assertion | t_{RCH} | $0.75 \times T_C - 4.0$ | 3.5 | — | ns |
| 145 | \overline{CAS} assertion to \overline{WR} deassertion | t_{WCH} | $2.25 \times T_C - 4.2$ | 18.3 | — | ns |
| 146 | \overline{WR} assertion pulse width | t_{WP} | $3.5 \times T_C - 4.5$ | 30.5 | — | ns |
| 147 | Last \overline{WR} assertion to \overline{RAS} deassertion | t_{RWL} | $3.75 \times T_C - 4.3$ | 33.2 | — | ns |
| 148 | \overline{WR} assertion to \overline{CAS} deassertion | t_{CWL} | $3.25 \times T_C - 4.3$ | 28.2 | — | ns |
| 149 | Data valid to \overline{CAS} assertion (write) | t_{DS} | $0.5 \times T_C - 4.0$ | 1.0 | — | ns |
| 150 | \overline{CAS} assertion to data not valid (write) | t_{DH} | $2.5 \times T_C - 4.0$ | 21.0 | — | ns |
| 151 | \overline{WR} assertion to \overline{CAS} assertion | t_{WCS} | $1.25 \times T_C - 4.3$ | 8.2 | — | ns |

Table 3-11 DRAM Page Mode Timings, Three Wait States^{1, 2, 3} (continued)

| No. | Characteristics | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|-----------|-------------------------|------|------|------|
| 152 | Last \overline{RD} assertion to \overline{RAS} deassertion | t_{ROH} | $3.5 \times T_C - 4.0$ | 31.0 | — | ns |
| 153 | \overline{RD} assertion to data valid | t_{GA} | $2.5 \times T_C - 7.0$ | — | 18.0 | ns |
| 154 | \overline{RD} deassertion to data not valid ⁶ | t_{GZ} | | 0.0 | — | ns |
| 155 | \overline{WR} assertion to data active | | $0.75 \times T_C - 0.3$ | 7.2 | — | ns |
| 156 | \overline{WR} deassertion to data high impedance | | $0.25 \times T_C$ | — | 2.5 | ns |

¹ The number of wait states for Page mode access is specified in the DCR.

² The refresh period is specified in the DCR.

³ The asynchronous delays specified in the expressions are valid for DSP56364.

⁴ All the timings are calculated for the worst case. Some of the timings are better for specific cases (e.g., t_{PC} equals $4 \neq T_C$ for read-after-read or write-after-write sequences).

⁵ BRW[1:0] (DRAM control register bits) defines the number of wait states that should be inserted in each DRAM out-of-page-access.

⁶ \overline{RD} deassertion will always occur after \overline{CAS} deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

Table 3-12 DRAM Page Mode Timings, Four Wait States^{1, 2, 3}

| No. | Characteristics | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|---|------------|-------------------------|------|------|------|
| 131 | Page mode cycle time for two consecutive accesses of the same direction. | t_{PC} | $2 \times T_C$ | 50.0 | — | ns |
| | Page mode cycle time for mixed (read and write) accesses. | | $1.25 \times T_C$ | 45.0 | — | ns |
| 132 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $2.75 \times T_C - 7.0$ | — | 20.5 | ns |
| 133 | Column address valid to data valid (read) | t_{AA} | $3.75 \times T_C - 7.0$ | — | 30.5 | ns |
| 134 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | ns |
| 135 | Last \overline{CAS} assertion to \overline{RAS} deassertion | t_{RSH} | $3.5 \times T_C - 4.0$ | 31.0 | — | ns |
| 136 | Previous \overline{CAS} deassertion to \overline{RAS} deassertion | t_{RHCP} | $6 \times T_C - 4.0$ | 56.0 | — | ns |
| 137 | \overline{CAS} assertion pulse width | t_{CAS} | $2.5 \times T_C - 4.0$ | 21.0 | — | ns |
| 138 | Last \overline{CAS} deassertion to \overline{RAS} assertion ⁵ <ul style="list-style-type: none"> • BRW[1:0] = 00 • BRW[1:0] = 01 • BRW[1:0] = 10 • BRW[1:0] = 11 | t_{CRP} | $2.75 \times T_C - 6.0$ | — | — | ns |
| | | | $4.25 \times T_C - 6.0$ | — | — | ns |
| | | | $5.25 \times T_C - 6.0$ | 46.5 | — | ns |
| | | | $7.25 \times T_C - 6.0$ | 66.5 | — | ns |
| 139 | \overline{CAS} deassertion pulse width | t_{CP} | $2 \times T_C - 4.0$ | 16.0 | — | ns |

Table 3-12 DRAM Page Mode Timings, Four Wait States^{1, 2, 3} (continued)

| No. | Characteristics | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|------------------|----------------------------------|------|------|------|
| 140 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $T_{\text{C}} - 4.0$ | 6.0 | — | ns |
| 141 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $3.5 \times T_{\text{C}} - 4.0$ | 31.0 | — | ns |
| 142 | Last column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $5 \times T_{\text{C}} - 4.0$ | 46.0 | — | ns |
| 143 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $1.25 \times T_{\text{C}} - 4.0$ | 8.5 | — | ns |
| 144 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}$ assertion | t_{RCH} | $1.25 \times T_{\text{C}} - 4.0$ | 8.5 | — | ns |
| 145 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $3.25 \times T_{\text{C}} - 4.2$ | 28.3 | — | ns |
| 146 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $4.5 \times T_{\text{C}} - 4.5$ | 40.5 | — | ns |
| 147 | Last $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $4.75 \times T_{\text{C}} - 4.3$ | 43.2 | — | ns |
| 148 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $3.75 \times T_{\text{C}} - 4.3$ | 33.2 | — | ns |
| 149 | Data valid to $\overline{\text{CAS}}$ assertion (write) | t_{DS} | $0.5 \times T_{\text{C}} - 4.0$ | 1.0 | — | ns |
| 150 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $3.5 \times T_{\text{C}} - 4.0$ | 31.0 | — | ns |
| 151 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{WCS} | $1.25 \times T_{\text{C}} - 4.3$ | 8.2 | — | ns |
| 152 | Last $\overline{\text{RD}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{ROH} | $4.5 \times T_{\text{C}} - 4.0$ | 41.0 | — | ns |
| 153 | $\overline{\text{RD}}$ assertion to data valid | t_{GA} | $3.25 \times T_{\text{C}} - 7.0$ | — | 25.5 | ns |
| 154 | $\overline{\text{RD}}$ deassertion to data not valid ⁶ | t_{GZ} | | 0.0 | — | ns |
| 155 | $\overline{\text{WR}}$ assertion to data active | | $0.75 \times T_{\text{C}} - 0.3$ | 7.2 | — | ns |
| 156 | $\overline{\text{WR}}$ deassertion to data high impedance | | $0.25 \times T_{\text{C}}$ | — | 2.5 | ns |

¹ The number of wait states for Page mode access is specified in the DCR.


² The refresh period is specified in the DCR.

³ The asynchronous delays specified in the expressions are valid for DSP56364.

⁴ All the timings are calculated for the worst case. Some of the timings are better for specific cases (e.g., t_{PC} equals $3 \times T_{\text{C}}$ for read-after-read or write-after-write sequences).

⁵ BRW[1:0] (DRAM control register bits) defines the number of wait states that should be inserted in each DRAM out-of-page access.

⁶ $\overline{\text{RD}}$ deassertion will always occur after $\overline{\text{CAS}}$ deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .



AA0473

Figure 3-12 DRAM Page Mode Write Accesses

External Memory Expansion Port (Port A)





Figure 3-13 DRAM Page Mode Read Accesses



AA0475

Figure 3-14 DRAM Out-of-Page Wait States Selection Guide

Table 3-13 DRAM Out-of-Page and Refresh Timings, Four Wait States^{1, 2}

| No. | Characteristics ³ | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|---|-----------|-------------------------|---------------------|-------|---------------------|------|------|
| | | | | Min | Max | Min | Max | |
| 157 | Random read or write cycle time | t_{RC} | $5 \times T_C$ | 250.0 | — | 166.7 | — | ns |
| 158 | \overline{RAS} assertion to data valid (read) | t_{RAC} | $2.75 \times T_C - 7.5$ | — | 130.0 | — | 84.2 | ns |
| 159 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $1.25 \times T_C - 7.5$ | — | 55.0 | — | 34.2 | ns |
| 160 | Column address valid to data valid (read) | t_{AA} | $1.5 \times T_C - 7.5$ | — | 67.5 | — | 42.5 | ns |
| 161 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | 0.0 | — | ns |
| 162 | \overline{RAS} deassertion to \overline{RAS} assertion | t_{RP} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |
| 163 | \overline{RAS} assertion pulse width | t_{RAS} | $3.25 \times T_C - 4.0$ | 158.5 | — | 104.3 | — | ns |
| 164 | \overline{CAS} assertion to \overline{RAS} deassertion | t_{RSH} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |

Table 3-13 DRAM Out-of-Page and Refresh Timings, Four Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|--|------------------|-------------------------|---------------------|------|---------------------|------|------|
| | | | | Min | Max | Min | Max | |
| 165 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CSH} | $2.75 \times T_C - 4.0$ | 133.5 | — | 87.7 | — | ns |
| 166 | $\overline{\text{CAS}}$ assertion pulse width | t_{CAS} | $1.25 \times T_C - 4.0$ | 58.5 | — | 37.7 | — | ns |
| 167 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{RCD} | $1.5 \times T_C \pm 2$ | 73.0 | 77.0 | 48.0 | 52.0 | ns |
| 168 | $\overline{\text{RAS}}$ assertion to column address valid | t_{RAD} | $1.25 \times T_C \pm 2$ | 60.5 | 64.5 | 39.7 | 43.7 | ns |
| 169 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{RAS}}$ assertion | t_{CRP} | $2.25 \times T_C - 4.0$ | 108.5 | — | 71.0 | — | ns |
| 170 | $\overline{\text{CAS}}$ deassertion pulse width | t_{CP} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |
| 171 | Row address valid to $\overline{\text{RAS}}$ assertion | t_{ASR} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |
| 172 | $\overline{\text{RAS}}$ assertion to row address not valid | t_{RAH} | $1.25 \times T_C - 4.0$ | 58.5 | — | 37.7 | — | ns |
| 173 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $0.25 \times T_C - 4.0$ | 8.5 | — | 4.3 | — | ns |
| 174 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |
| 175 | $\overline{\text{RAS}}$ assertion to column address not valid | t_{AR} | $3.25 \times T_C - 4.0$ | 158.5 | — | 104.3 | — | ns |
| 176 | Column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $2 \times T_C - 4.0$ | 96.0 | — | 62.7 | — | ns |
| 177 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $1.5 \times T_C - 3.8$ | 71.2 | — | 46.2 | — | ns |
| 178 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}$ assertion | t_{RCH} | $0.75 \times T_C - 3.7$ | 33.8 | — | 21.3 | — | ns |
| 179 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{WR}}$ assertion | t_{RRH} | $0.25 \times T_C - 3.7$ | 8.8 | — | 4.6 | — | ns |
| 180 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $1.5 \times T_C - 4.2$ | 70.8 | — | 45.8 | — | ns |
| 181 | $\overline{\text{RAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCR} | $3 \times T_C - 4.2$ | 145.8 | — | 95.8 | — | ns |
| 182 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $4.5 \times T_C - 4.5$ | 220.5 | — | 145.5 | — | ns |
| 183 | $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $4.75 \times T_C - 4.3$ | 233.2 | — | 154.0 | — | ns |
| 184 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $4.25 \times T_C - 4.3$ | 208.2 | — | 137.4 | — | ns |
| 185 | Data valid to $\overline{\text{CAS}}$ assertion (write) | t_{DS} | $2.25 \times T_C - 4.0$ | 108.5 | — | 71.0 | — | ns |
| 186 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $1.75 \times T_C - 4.0$ | 83.5 | — | 54.3 | — | ns |
| 187 | $\overline{\text{RAS}}$ assertion to data not valid (write) | t_{DHR} | $3.25 \times T_C - 4.0$ | 158.5 | — | 104.3 | — | ns |

Table 3-13 DRAM Out-of-Page and Refresh Timings, Four Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression | 20 MHz ⁴ | | 30 MHz ⁴ | | Unit |
|-----|--|-----------|-------------------------|---------------------|-------|---------------------|-------|------|
| | | | | Min | Max | Min | Max | |
| 188 | \overline{WR} assertion to \overline{CAS} assertion | t_{WCS} | $3 \times T_C - 4.3$ | 145.7 | — | 95.7 | — | ns |
| 189 | \overline{CAS} assertion to \overline{RAS} assertion (refresh) | t_{CSR} | $0.5 \times T_C - 4.0$ | 21.0 | — | 12.7 | — | ns |
| 190 | \overline{RAS} deassertion to \overline{CAS} assertion (refresh) | t_{RPC} | $1.25 \times T_C - 4.0$ | 58.5 | — | 37.7 | — | ns |
| 191 | \overline{RD} assertion to \overline{RAS} deassertion | t_{ROH} | $4.5 \times T_C - 4.0$ | 221.0 | — | 146.0 | — | ns |
| 192 | \overline{RD} assertion to data valid | t_{GA} | $4 \times T_C - 7.5$ | — | 192.5 | — | 125.8 | ns |
| 193 | \overline{RD} deassertion to data not valid ³ | t_{GZ} | | 0.0 | — | 0.0 | — | ns |
| 194 | \overline{WR} assertion to data active | | $0.75 \times T_C - 0.3$ | 37.2 | — | 24.7 | — | ns |
| 195 | \overline{WR} deassertion to data high impedance | | $0.25 \times T_C$ | — | 12.5 | — | 8.3 | ns |

¹ The number of wait states for out of page access is specified in the DCR.

² The refresh period is specified in the DCR.

³ \overline{RD} deassertion will always occur after \overline{CAS} deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

⁴ Reduced DSP clock speed allows use of DRAM out-of-page access with four Wait states (See [Figure 3-17](#)).

Table 3-14 DRAM Out-of-Page and Refresh Timings, Eight Wait States^{1, 2}

| No. | Characteristics ³ | Symbol | Expression ⁴ | 66 MHz | | 80 MHz | | Unit |
|-----|---|-----------|-------------------------|--------|------|--------|------|------|
| | | | | Min | Max | Min | Max | |
| 157 | Random read or write cycle time | t_{RC} | $9 \times T_C$ | 136.4 | — | 112.5 | — | ns |
| 158 | \overline{RAS} assertion to data valid (read) | t_{RAC} | $4.75 \times T_C - 7.5$ | — | 64.5 | — | — | ns |
| | | | $4.75 \times T_C - 6.5$ | — | — | — | 52.9 | ns |
| 159 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $2.25 \times T_C - 7.5$ | — | 26.6 | — | — | ns |
| | | | $2.25 \times T_C - 6.5$ | — | — | — | 21.6 | ns |
| 160 | Column address valid to data valid (read) | t_{AA} | $3 \times T_C - 7.5$ | — | 40.0 | — | — | ns |
| | | | $3 \times T_C - 6.5$ | — | — | — | 31.0 | ns |
| 161 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | 0.0 | — | ns |
| 162 | \overline{RAS} deassertion to \overline{RAS} assertion | t_{RP} | $3.25 \times T_C - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 163 | \overline{RAS} assertion pulse width | t_{RAS} | $5.75 \times T_C - 4.0$ | 83.1 | — | 67.9 | — | ns |

Table 3-14 DRAM Out-of-Page and Refresh Timings, Eight Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression ⁴ | 66 MHz | | 80 MHz | | Unit |
|-----|---|------------------|-------------------------|--------|------|--------|------|------|
| | | | | Min | Max | Min | Max | |
| 164 | $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RSH} | $3.25 \times T_C - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 165 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CSH} | $4.75 \times T_C - 4.0$ | 68.0 | — | 55.5 | — | ns |
| 166 | $\overline{\text{CAS}}$ assertion pulse width | t_{CAS} | $2.25 \times T_C - 4.0$ | 30.1 | — | 24.1 | — | ns |
| 167 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{RCD} | $2.5 \times T_C \pm 2$ | 35.9 | 39.9 | 29.3 | 33.3 | ns |
| 168 | $\overline{\text{RAS}}$ assertion to column address valid | t_{RAD} | $1.75 \times T_C \pm 2$ | 24.5 | 28.5 | 19.9 | 23.9 | ns |
| 169 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{RAS}}$ assertion | t_{CRP} | $4.25 \times T_C - 4.0$ | 59.8 | — | 49.1 | — | ns |
| 170 | $\overline{\text{CAS}}$ deassertion pulse width | t_{CP} | $2.75 \times T_C - 4.0$ | 37.7 | — | 30.4 | — | ns |
| 171 | Row address valid to $\overline{\text{RAS}}$ assertion | t_{ASR} | $3.25 \times T_C - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 172 | $\overline{\text{RAS}}$ assertion to row address not valid | t_{RAH} | $1.75 \times T_C - 4.0$ | 22.5 | — | 17.9 | — | ns |
| 173 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $0.75 \times T_C - 4.0$ | 7.4 | — | 5.4 | — | ns |
| 174 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $3.25 \times T_C - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 175 | $\overline{\text{RAS}}$ assertion to column address not valid | t_{AR} | $5.75 \times T_C - 4.0$ | 83.1 | — | 67.9 | — | ns |
| 176 | Column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $4 \times T_C - 4.0$ | 56.6 | — | 46.0 | — | ns |
| 177 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $2 \times T_C - 3.8$ | 26.5 | — | 21.2 | — | ns |
| 178 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}^5$ assertion | t_{RCH} | $1.25 \times T_C - 3.7$ | 15.2 | — | 11.9 | — | ns |
| 179 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{WR}}^5$ assertion | t_{RRH} | $0.25 \times T_C - 3.7$ | 0.1 | — | — | — | ns |
| | | | $0.25 \times T_C - 3.0$ | — | — | 0.1 | — | ns |
| 180 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $3 \times T_C - 4.2$ | 41.3 | — | 33.3 | — | ns |
| 181 | $\overline{\text{RAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCR} | $5.5 \times T_C - 4.2$ | 79.1 | — | 64.6 | — | ns |
| 182 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $8.5 \times T_C - 4.5$ | 124.3 | — | 101.8 | — | ns |
| 183 | $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $8.75 \times T_C - 4.3$ | 128.3 | — | 105.1 | — | ns |
| 184 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $7.75 \times T_C - 4.3$ | 113.1 | — | 92.6 | — | ns |
| 185 | Data valid to $\overline{\text{CAS}}$ assertion (write) | t_{DS} | $4.75 \times T_C - 4.0$ | 68.0 | — | 55.4 | — | ns |

Table 3-14 DRAM Out-of-Page and Refresh Timings, Eight Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression ⁴ | 66 MHz | | 80 MHz | | Unit |
|-----|--|------------------|----------------------------------|--------|-------|--------|------|------|
| | | | | Min | Max | Min | Max | |
| 186 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $3.25 \times T_{\text{C}} - 4.0$ | 45.2 | — | 36.6 | — | ns |
| 187 | $\overline{\text{RAS}}$ assertion to data not valid (write) | t_{DHR} | $5.75 \times T_{\text{C}} - 4.0$ | 83.1 | — | 67.9 | — | ns |
| 188 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{WCS} | $5.5 \times T_{\text{C}} - 4.3$ | 79.0 | — | 64.5 | — | ns |
| 189 | $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ assertion (refresh) | t_{CSR} | $1.5 \times T_{\text{C}} - 4.0$ | 18.7 | — | 14.8 | — | ns |
| 190 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{CAS}}$ assertion (refresh) | t_{RPC} | $1.75 \times T_{\text{C}} - 4.0$ | 22.5 | — | 17.9 | — | ns |
| 191 | $\overline{\text{RD}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{ROH} | $8.5 \times T_{\text{C}} - 4.0$ | 124.8 | — | 102.3 | — | ns |
| 192 | $\overline{\text{RD}}$ assertion to data valid | t_{GA} | $7.5 \times T_{\text{C}} - 7.5$ | — | 106.1 | — | — | ns |
| | | | | — | — | — | 87.3 | ns |
| 193 | $\overline{\text{RD}}$ deassertion to data not valid ³ | t_{GZ} | 0.0 | 0.0 | — | 0.0 | — | ns |
| 194 | $\overline{\text{WR}}$ assertion to data active | | $0.75 \times T_{\text{C}} - 0.3$ | 11.1 | — | 9.1 | — | ns |
| 195 | $\overline{\text{WR}}$ deassertion to data high impedance | | $0.25 \times T_{\text{C}}$ | — | 3.8 | — | 3.1 | ns |

¹ The number of wait states for out-of-page access is specified in the DCR.

² The refresh period is specified in the DCR.

³ $\overline{\text{RD}}$ deassertion will always occur after $\overline{\text{CAS}}$ deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

⁴ The asynchronous delays specified in the expressions are valid for DSP56364.

⁵ Either t_{RCH} or t_{RRH} must be satisfied for read cycles.

Table 3-15 DRAM Out-of-Page and Refresh Timings, Eleven Wait States^{1, 2}

| No. | Characteristics ³ | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|------------------|----------------------------------|-------|------|------|
| 157 | Random read or write cycle time | t_{RC} | $12 \times T_{\text{C}}$ | 120.0 | — | ns |
| 158 | $\overline{\text{RAS}}$ assertion to data valid (read) | t_{RAC} | $6.25 \times T_{\text{C}} - 7.0$ | — | 55.5 | ns |
| 159 | $\overline{\text{CAS}}$ assertion to data valid (read) | t_{CAC} | $3.75 \times T_{\text{C}} - 7.0$ | — | 30.5 | ns |
| 160 | Column address valid to data valid (read) | t_{AA} | $4.5 \times T_{\text{C}} - 7.0$ | — | 38.0 | ns |
| 161 | $\overline{\text{CAS}}$ deassertion to data not valid (read hold time) | t_{OFF} | | 0.0 | — | ns |
| 162 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{RAS}}$ assertion | t_{RP} | $4.25 \times T_{\text{C}} - 4.0$ | 38.5 | — | ns |
| 163 | $\overline{\text{RAS}}$ assertion pulse width | t_{RAS} | $7.75 \times T_{\text{C}} - 4.0$ | 73.5 | — | ns |

Table 3-15 DRAM Out-of-Page and Refresh Timings, Eleven Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|------------------|---------------------------|-------|------|------|
| 164 | $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RSH} | $5.25 \times T_C - 4.0$ | 48.5 | — | ns |
| 165 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CSH} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 166 | $\overline{\text{CAS}}$ assertion pulse width | t_{CAS} | $3.75 \times T_C - 4.0$ | 33.5 | — | ns |
| 167 | $\overline{\text{RAS}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{RCD} | $2.5 \times T_C \pm 4.0$ | 21.0 | 29.0 | ns |
| 168 | $\overline{\text{RAS}}$ assertion to column address valid | t_{RAD} | $1.75 \times T_C \pm 4.0$ | 13.5 | 21.5 | ns |
| 169 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{RAS}}$ assertion | t_{CRP} | $5.75 \times T_C - 4.0$ | 53.5 | — | ns |
| 170 | $\overline{\text{CAS}}$ deassertion pulse width | t_{CP} | $4.25 \times T_C - 4.0$ | 38.5 | — | ns |
| 171 | Row address valid to $\overline{\text{RAS}}$ assertion | t_{ASR} | $4.25 \times T_C - 4.0$ | 38.5 | — | ns |
| 172 | $\overline{\text{RAS}}$ assertion to row address not valid | t_{RAH} | $1.75 \times T_C - 4.0$ | 13.5 | — | ns |
| 173 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $0.75 \times T_C - 4.0$ | 3.5 | — | ns |
| 174 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $5.25 \times T_C - 4.0$ | 48.5 | — | ns |
| 175 | $\overline{\text{RAS}}$ assertion to column address not valid | t_{AR} | $7.75 \times T_C - 4.0$ | 73.5 | — | ns |
| 176 | Column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $6 \times T_C - 4.0$ | 56.0 | — | ns |
| 177 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $3.0 \times T_C - 4.0$ | 26.0 | — | ns |
| 178 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}^5$ assertion | t_{RCH} | $1.75 \times T_C - 4.0$ | 13.5 | — | ns |
| 179 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{WR}}^5$ assertion | t_{RRH} | $0.25 \times T_C - 2.0$ | 0.5 | — | ns |
| 180 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $5 \times T_C - 4.2$ | 45.8 | — | ns |
| 181 | $\overline{\text{RAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCR} | $7.5 \times T_C - 4.2$ | 70.8 | — | ns |
| 182 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $11.5 \times T_C - 4.5$ | 110.5 | — | ns |
| 183 | $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $11.75 \times T_C - 4.3$ | 113.2 | — | ns |
| 184 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $10.25 \times T_C - 4.3$ | 103.2 | — | ns |
| 185 | Data valid to $\overline{\text{CAS}}$ assertion (write) | t_{DS} | $5.75 \times T_C - 4.0$ | 53.5 | — | ns |
| 186 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $5.25 \times T_C - 4.0$ | 48.5 | — | ns |
| 187 | $\overline{\text{RAS}}$ assertion to data not valid (write) | t_{DHR} | $7.75 \times T_C - 4.0$ | 73.5 | — | ns |
| 188 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{WCS} | $6.5 \times T_C - 4.3$ | 60.7 | — | ns |
| 189 | $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ assertion (refresh) | t_{CSR} | $1.5 \times T_C - 4.0$ | 11.0 | — | ns |
| 190 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{CAS}}$ assertion (refresh) | t_{RPC} | $2.75 \times T_C - 4.0$ | 23.5 | — | ns |

Table 3-15 DRAM Out-of-Page and Refresh Timings, Eleven Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression ⁴ | Min | Max | Unit |
|-----|--|-----------|-------------------------|-------|------|------|
| 191 | \overline{RD} assertion to \overline{RAS} deassertion | t_{ROH} | $11.5 \times T_C - 4.0$ | 111.0 | — | ns |
| 192 | \overline{RD} assertion to data valid | t_{GA} | $10 \times T_C - 7.0$ | — | 93.0 | ns |
| 193 | \overline{RD} deassertion to data not valid ³ | t_{GZ} | | 0.0 | — | ns |
| 194 | \overline{WR} assertion to data active | | $0.75 \times T_C - 0.3$ | 7.2 | — | ns |
| 195 | \overline{WR} deassertion to data high impedance | | $0.25 \times T_C$ | — | 2.5 | ns |

¹ The number of wait states for out-of-page access is specified in the DCR.

² The refresh period is specified in the DCR.

³ \overline{RD} deassertion will always occur after \overline{CAS} deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

⁴ The asynchronous delays specified in the expressions are valid for DSP56364.

⁵ Either t_{RCH} or t_{RRH} must be satisfied for read cycles.

Table 3-16 DRAM Out-of-Page and Refresh Timings, Fifteen Wait States^{1, 2}

| No. | Characteristics ³ | Symbol | Expression | Min | Max | Unit |
|-----|---|-----------|-------------------------|-------|------|------|
| 157 | Random read or write cycle time | t_{RC} | $16 \times T_C$ | 160.0 | — | ns |
| 158 | \overline{RAS} assertion to data valid (read) | t_{RAC} | $8.25 \times T_C - 5.7$ | — | 76.8 | ns |
| 159 | \overline{CAS} assertion to data valid (read) | t_{CAC} | $4.75 \times T_C - 5.7$ | — | 41.8 | ns |
| 160 | Column address valid to data valid (read) | t_{AA} | $5.5 \times T_C - 5.7$ | — | 49.3 | ns |
| 161 | \overline{CAS} deassertion to data not valid (read hold time) | t_{OFF} | 0.0 | 0.0 | — | ns |
| 162 | \overline{RAS} deassertion to \overline{RAS} assertion | t_{RP} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 163 | \overline{RAS} assertion pulse width | t_{RAS} | $9.75 \times T_C - 4.0$ | 93.5 | — | ns |
| 164 | \overline{CAS} assertion to \overline{RAS} deassertion | t_{RSH} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 165 | \overline{RAS} assertion to \overline{CAS} deassertion | t_{CSH} | $8.25 \times T_C - 4.0$ | 78.5 | — | ns |
| 166 | \overline{CAS} assertion pulse width | t_{CAS} | $4.75 \times T_C - 4.0$ | 43.5 | — | ns |
| 167 | \overline{RAS} assertion to \overline{CAS} assertion | t_{RCD} | $3.5 \times T_C \pm 2$ | 33.0 | 37.0 | ns |
| 168 | \overline{RAS} assertion to column address valid | t_{RAD} | $2.75 \times T_C \pm 2$ | 25.5 | 29.5 | ns |
| 169 | \overline{CAS} deassertion to \overline{RAS} assertion | t_{CRP} | $7.75 \times T_C - 4.0$ | 73.5 | — | ns |
| 170 | \overline{CAS} deassertion pulse width | t_{CP} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 171 | Row address valid to \overline{RAS} assertion | t_{ASR} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 172 | \overline{RAS} assertion to row address not valid | t_{RAH} | $2.75 \times T_C - 4.0$ | 23.5 | — | ns |

Table 3-16 DRAM Out-of-Page and Refresh Timings, Fifteen Wait States^{1, 2} (continued)

| No. | Characteristics ³ | Symbol | Expression | Min | Max | Unit |
|-----|--|------------------|--------------------------|-------|-------|------|
| 173 | Column address valid to $\overline{\text{CAS}}$ assertion | t_{ASC} | $0.75 \times T_C - 4.0$ | 3.5 | — | ns |
| 174 | $\overline{\text{CAS}}$ assertion to column address not valid | t_{CAH} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 175 | $\overline{\text{RAS}}$ assertion to column address not valid | t_{AR} | $9.75 \times T_C - 4.0$ | 93.5 | — | ns |
| 176 | Column address valid to $\overline{\text{RAS}}$ deassertion | t_{RAL} | $7 \times T_C - 4.0$ | 66.0 | — | ns |
| 177 | $\overline{\text{WR}}$ deassertion to $\overline{\text{CAS}}$ assertion | t_{RCS} | $5 \times T_C - 3.8$ | 46.2 | — | ns |
| 178 | $\overline{\text{CAS}}$ deassertion to $\overline{\text{WR}}$ ⁴ assertion | t_{RCH} | $1.75 \times T_C - 3.7$ | 13.8 | — | ns |
| 179 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{WR}}$ ⁴ assertion | t_{RRH} | $0.25 \times T_C - 2.0$ | 0.5 | — | ns |
| 180 | $\overline{\text{CAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCH} | $6 \times T_C - 4.2$ | 55.8 | — | ns |
| 181 | $\overline{\text{RAS}}$ assertion to $\overline{\text{WR}}$ deassertion | t_{WCR} | $9.5 \times T_C - 4.2$ | 90.8 | — | ns |
| 182 | $\overline{\text{WR}}$ assertion pulse width | t_{WP} | $15.5 \times T_C - 4.5$ | 150.5 | — | ns |
| 183 | $\overline{\text{WR}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{RWL} | $15.75 \times T_C - 4.3$ | 153.2 | — | ns |
| 184 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ deassertion | t_{CWL} | $14.25 \times T_C - 4.3$ | 138.2 | — | ns |
| 185 | Data valid to $\overline{\text{CAS}}$ assertion (write) | t_{DS} | $8.75 \times T_C - 4.0$ | 83.5 | — | ns |
| 186 | $\overline{\text{CAS}}$ assertion to data not valid (write) | t_{DH} | $6.25 \times T_C - 4.0$ | 58.5 | — | ns |
| 187 | $\overline{\text{RAS}}$ assertion to data not valid (write) | t_{DHR} | $9.75 \times T_C - 4.0$ | 93.5 | — | ns |
| 188 | $\overline{\text{WR}}$ assertion to $\overline{\text{CAS}}$ assertion | t_{WCS} | $9.5 \times T_C - 4.3$ | 90.7 | — | ns |
| 189 | $\overline{\text{CAS}}$ assertion to $\overline{\text{RAS}}$ assertion (refresh) | t_{CSR} | $1.5 \times T_C - 4.0$ | 11.0 | — | ns |
| 190 | $\overline{\text{RAS}}$ deassertion to $\overline{\text{CAS}}$ assertion (refresh) | t_{RPC} | $4.75 \times T_C - 4.0$ | 43.5 | — | ns |
| 191 | $\overline{\text{RD}}$ assertion to $\overline{\text{RAS}}$ deassertion | t_{ROH} | $15.5 \times T_C - 4.0$ | 151.0 | — | ns |
| 192 | $\overline{\text{RD}}$ assertion to data valid | t_{GA} | $14 \times T_C - 5.7$ | — | 134.3 | ns |
| 193 | $\overline{\text{RD}}$ deassertion to data not valid ³ | t_{GZ} | | 0.0 | — | ns |
| 194 | $\overline{\text{WR}}$ assertion to data active | | $0.75 \times T_C - 0.3$ | 7.2 | — | ns |
| 195 | $\overline{\text{WR}}$ deassertion to data high impedance | | $0.25 \times T_C$ | — | 2.5 | ns |

¹ The number of wait states for out-of-page access is specified in the DCR.

² The refresh period is specified in the DCR.

³ $\overline{\text{RD}}$ deassertion will always occur after $\overline{\text{CAS}}$ deassertion; therefore, the restricted timing is t_{OFF} and not t_{GZ} .

⁴ Either t_{RCH} or t_{RRH} must be satisfied for read cycles.




Figure 3-15 DRAM Out-of-Page Read Access

External Memory Expansion Port (Port A)




Figure 3-16 DRAM Out-of-Page Write Access




Figure 3-17 DRAM Refresh Access

3.11 Serial Host Interface SPI Protocol Timing

Table 3-17 Serial Host Interface SPI Protocol Timing

| No. | Characteristics | Mode | Filter Mode | Expression | Min | Max | Unit |
|-----|---|--------|-------------|-----------------------------|-----|-----|------|
| 140 | Tolerable spike width on clock or data in | — | Bypassed | — | — | 0 | ns |
| | | | Narrow | — | — | 50 | ns |
| | | | Wide | — | — | 100 | ns |
| 141 | Minimum serial clock cycle = $t_{SPICC(min)}$ | Master | Bypassed | $6 \times T_C + 46$ | 106 | — | ns |
| | | | Narrow | $6 \times T_C + 152$ | 212 | — | ns |
| | | | Wide | $6 \times T_C + 223$ | 283 | — | ns |
| 142 | Serial clock high period | Master | Bypassed | $0.5 \times t_{SPICC} - 10$ | 43 | — | ns |
| | | | Narrow | $0.5 \times t_{SPICC} - 10$ | 96 | — | ns |
| | | | Wide | $0.5 \times t_{SPICC} - 10$ | 131 | — | ns |
| | | Slave | Bypassed | $2.5 \times T_C + 12$ | 37 | — | ns |
| | | | Narrow | $2.5 \times T_C + 102$ | 127 | — | ns |
| | | | Wide | $2.5 \times T_C + 189$ | 214 | — | ns |


Table 3-17 Serial Host Interface SPI Protocol Timing (continued)

| No. | Characteristics | Mode | Filter Mode | Expression | Min | Max | Unit |
|-----|---|------------------|-------------|-------------------------------|-----|------|------|
| 143 | Serial clock low period | Master | Bypassed | $0.5 \times t_{SPICC} - 10$ | 43 | — | ns |
| | | | Narrow | $0.5 \times t_{SPICC} - 10$ | 96 | — | ns |
| | | | Wide | $0.5 \times t_{SPICC} - 10$ | 131 | — | ns |
| | | Slave | Bypassed | $2.5 \times T_C + 12$ | 37 | — | ns |
| | | | Narrow | $2.5 \times T_C + 102$ | 127 | — | ns |
| | | | Wide | $2.5 \times T_C + 189$ | 214 | — | ns |
| 144 | Serial clock rise/fall time | Master | — | — | — | 10 | ns |
| | | Slave | — | — | — | 2000 | ns |
| 146 | \overline{SS} assertion to first SCK edge CPHA = 0 | Slave | Bypassed | $3.5 \times T_C + 15$ | 50 | — | ns |
| | | | Narrow | 0 | 0 | — | ns |
| | | | Wide | 0 | 0 | — | ns |
| | CPHA = 1 | Slave | Bypassed | 10 | 10 | — | ns |
| | | | Narrow | 0 | 0 | — | ns |
| | | | Wide | 0 | 0 | — | ns |
| 147 | Last SCK edge to \overline{SS} not asserted | Slave | Bypassed | 12 | 12 | — | ns |
| | | | Narrow | 102 | 102 | — | ns |
| | | | Wide | 189 | 189 | — | ns |
| 148 | Data input valid to SCK edge (data input set-up time) | Master/ Slave | Bypassed | 0 | 0 | — | ns |
| | | | Narrow | $\text{MAX}\{(20 - T_C), 0\}$ | 10 | — | ns |
| | | | Wide | $\text{MAX}\{(40 - T_C), 0\}$ | 30 | — | ns |
| 149 | SCK last sampling edge to data input not valid | Master/ Slave | Bypassed | $2.5 \times T_C + 10$ | 35 | — | ns |
| | | | Narrow | $2.5 \times T_C + 30$ | 55 | — | ns |
| | | | Wide | $2.5 \times T_C + 50$ | 75 | — | ns |
| 150 | \overline{SS} assertion to data out active | Slave | — | 2 | 2 | — | ns |
| 151 | \overline{SS} deassertion to data high impedance | Slave | — | 9 | — | 9 | ns |

Table 3-17 Serial Host Interface SPI Protocol Timing (continued)


| No. | Characteristics | Mode | Filter Mode | Expression | Min | Max | Unit |
|--|---|---------------|-------------|--|-----|-----|------|
| 152 | SCK edge to data out valid (data out delay time) | Master/ Slave | Bypassed | $2 \times T_C + 33$ | — | 53 | ns |
| | | | Narrow | $2 \times T_C + 123$ | — | 143 | ns |
| | | | Wide | $2 \times T_C + 210$ | — | 230 | ns |
| 153 | SCK edge to data out not valid (data out hold time) | Master/ Slave | Bypassed | $T_C + 5$ | 15 | — | ns |
| | | | Narrow | $T_C + 55$ | 65 | — | ns |
| | | | Wide | $T_C + 106$ | 116 | — | ns |
| 154 | \overline{SS} assertion to data out valid (CPHA = 0) | Slave | — | $T_C + 33$ | — | 43 | ns |
| 157 | First SCK sampling edge to \overline{HREQ} output deassertion | Slave | Bypassed | $2.5 \times T_C + 30$ | — | 55 | ns |
| | | | Narrow | $2.5 \times T_C + 120$ | — | 145 | ns |
| | | | Wide | $2.5 \times T_C + 217$ | — | 242 | ns |
| 158 | Last SCK sampling edge to \overline{HREQ} output not deasserted (CPHA = 1) | Slave | Bypassed | $2.5 \times T_C + 30$ | 55 | — | ns |
| | | | Narrow | $2.5 \times T_C + 80$ | 105 | — | ns |
| | | | Wide | $2.5 \times T_C + 136$ | 161 | — | ns |
| 159 | \overline{SS} deassertion to \overline{HREQ} output not deasserted (CPHA = 0) | Slave | — | $2.5 \times T_C + 30$ | 55 | — | ns |
| 160 | \overline{SS} deassertion pulse width (CPHA = 0) | Slave | — | $T_C + 6$ | 16 | — | ns |
| 161 | \overline{HREQ} in assertion to first SCK edge | Master | Bypassed | $0.5 \times t_{SPICC} + 2.5 \times T_C + 43$ | 121 | — | ns |
| | | | Narrow | $0.5 \times t_{SPICC} + 2.5 \times T_C + 43$ | 174 | — | ns |
| | | | Wide | $0.5 \times t_{SPICC} + 2.5 \times T_C + 43$ | 209 | — | ns |
| 162 | \overline{HREQ} in deassertion to last SCK sampling edge (\overline{HREQ} in set-up time) (CPHA = 1) | Master | — | 0 | 0 | — | ns |
| 163 | First SCK edge to \overline{HREQ} in not asserted (\overline{HREQ} in hold time) | Master | — | 0 | 0 | — | ns |
| Note: Periodically sampled, not 100% tested | | | | | | | |

Serial Host Interface SPI Protocol Timing



AA0271


Figure 3-18 SPI Master Timing (CPHA = 0)



AA0272


Figure 3-19 SPI Master Timing (CPHA = 1)

Serial Host Interface SPI Protocol Timing



AA0273

Figure 3-20 SPI Slave Timing (CPHA = 0)



AA0274

Figure 3-21 SPI Slave Timing (CPHA = 1)

3.12 Serial Host Interface (SHI) I²C Protocol Timing

Table 3-18 SHI I²C Protocol Timing

| Standard I ² C ¹ | | | | | | | |
|--|---|-----------------------|---------------|------|---------------------------|-----|------|
| No. | Characteristics | Symbol/ Expression | Standard-Mode | | Fast-Mode | | Unit |
| | | | Min | Max | Min | Max | |
| | Tolerable spike width on SCL or SDA | — | | | | | |
| | • Filters bypassed | | — | 0 | — | 0 | ns |
| | • Narrow filters enabled | | — | 50 | — | 50 | ns |
| | • Wide filters enabled | | — | 100 | — | 100 | ns |
| 171 | SCL clock frequency | F _{SCL} | — | 100 | — | 400 | kHz |
| 172 | Bus free time | T _{BUF} | 4.7 | — | 1.3 | — | μs |
| 173 | Start condition set-up time | T _{SU;STA} | 4.7 | — | 0.6 | — | μs |
| 174 | Start condition hold time | T _{HD;STA} | 4.0 | — | 0.6 | — | μs |
| 175 | SCL low period | T _{LOW} | 4.7 | — | 1.3 | — | μs |
| 176 | SCL high period | T _{HIGH} | 4.0 | — | 1.3 | — | μs |
| 177 | SCL and SDA rise time | T _R | — | 1000 | 20 + 0.1 × C _b | 300 | ns |
| 178 | SCL and SDA fall time | T _F | — | 300 | 20 + 0.1 × C _b | 300 | ns |
| 179 | Data set-up time | T _{SU;DAT} | 250 | — | 100 | — | ns |
| 180 | Data hold time | T _{HD;DAT} | 0.0 | — | 0.0 | 0.9 | μs |
| 181 | Stop condition set-up time | T _{SU;STO} | 4.0 | — | 0.6 | — | μs |
| 182 | Capacitive load for each line | C _b | — | 400 | — | 400 | pF |
| 183 | DSP clock frequency | F _{DSP} | | | | | |
| | • Filters bypassed | | 10.6 | — | 28.5 | — | MHz |
| | • Narrow filters enabled | | 11.8 | — | 39.7 | — | MHz |
| | • Wide filters enabled | | 13.1 | — | 61.0 | — | MHz |
| 184 | $\overline{\text{HREQ}}$ in deassertion to last SCL edge (HREQ in set-up time) | t _{SU;RQI} | 0.0 | — | 0.0 | — | ns |

Table 3-18 SHI I²C Protocol Timing (continued)

| Standard I ² C ¹ | | | | | | | |
|--|--|---|---------------|-----|-----------|-----|------|
| No. | Characteristics | Symbol/ Expression | Standard-Mode | | Fast-Mode | | Unit |
| | | | Min | Max | Min | Max | |
| 186 | First SCL sampling edge to $\overline{\text{HREQ}}$ output deassertion | $T_{\text{NG;RQO}}$ | | | | | ns |
| | • Filters bypassed | $2 \times T_C + 30$ | — | 50 | — | 50 | ns |
| | • Narrow filters enabled | $2 \times T_C + 120$ | — | 140 | — | 140 | ns |
| | • Wide filters enabled | $2 \times T_C + 208$ | — | 228 | — | 228 | ns |
| 187 | Last SCL edge to HREQ output not deasserted | $T_{\text{AS;RQO}}$ | | | | | ns |
| | • Filters bypassed | $2 \times T_C + 30$ | 50 | — | 50 | — | ns |
| | • Narrow filters enabled | $2 \times T_C + 80$ | 100 | — | 100 | — | ns |
| | • Wide filters enabled | $2 \times T_C + 135$ | 155 | — | 155 | — | ns |
| 188 | HREQ in assertion to first SCL edge | $T_{\text{AS;RQI}}$ | | | | | ns |
| | • Filters bypassed | $0.5 \times T_{\text{I}^2\text{CCP}} - 0.5 \times T_C - 21$ | 4327 | — | 927 | — | ns |
| | • Narrow filters enabled | | 4282 | — | 882 | — | ns |
| | • Wide filters enabled | | 4238 | — | 838 | — | ns |

¹ $R_P(\text{min}) = 1.5 \text{ k}^{3/4}$

3.12.1 Programming the Serial Clock

The programmed serial clock cycle, $T_{\text{I}^2\text{CCP}}$, is specified by the value of the HDM[5:0] and HRS bits of the HCKR (SHI clock control register).

The expression for $T_{\text{I}^2\text{CCP}}$ is

$$T_{\text{I}^2\text{CCP}} = [T_C \times 2 \times (\text{HDM}[7:0] + 1) \times (7 \times (1 - \text{HRS}) + 1)]$$

where

HRS is the prescaler rate select bit. When HRS is cleared, the fixed divide-by-eight prescaler is operational. When HRS is set, the prescaler is bypassed.

HDM[7:0] are the divider modulus select bits.

A divide ratio from 1 to 64 ($\text{HDM}[5:0] = 0$ to $\$3\text{F}$) may be selected.

Serial Host Interface (SHI) I²C Protocol Timing

In I²C mode, the user may select a value for the programmed serial clock cycle from

$$6 \times T_C (\text{if HDMS}[5:0] = \$02 \text{ and HRS} = 1)$$

to

$$4096 \times T_C (\text{if HDMS}[7:0] = \$FF \text{ and HRS} = 0)$$

The programmed serial clock cycle (T_{I^2CCP}), SCL rise time (T_R), and the filters selected should be chosen in order to achieve the desired SCL frequency, as shown in Table 3-19.

Table 3-19 SCL Serial Clock Cycle generated as Master

| | |
|------------------------|--|
| Filters bypassed | $T_{I^2CCP} + 2.5 \times T_C + 45\text{ns} + T_R$ |
| Narrow filters enabled | $T_{I^2CCP} + 2.5 \times T_C + 135\text{ns} + T_R$ |
| Wide filters enabled | $T_{I^2CCP} + 2.5 \times T_C + 223\text{ns} + T_R$ |

EXAMPLE:

For DSP clock frequency of 100 MHz (i.e. $T_C = 10\text{ns}$), operating in a standard-mode I²C environment ($F_{SCL} = 100\text{ KHz}$ (i.e. $T_{SCL} = 10\mu\text{s}$), $T_R = 1000\text{ns}$), with filters bypassed

$$T_{I^2CCP} = 10\mu\text{s} - 2.5 \times 10\text{ns} - 45\text{ns} - 1000\text{ns} = 893\text{ns}$$

Choosing HRS = 0 gives

$$\text{HDM}[7:0] = (893\text{ns}) / (2 \times 10\text{ns} \times 8) - 1 = 55.8$$

Thus the HDM[7:0] value should be programmed to \$38 (=56).




Figure 3-22 I²C Timing

3.13 Enhanced Serial Audio Interface Timing

Table 3-20 Enhanced Serial Audio Interface Timing

| No. | Characteristics ^{1, 2, 3} | Symbol | Expression | Min | Max | Condition ⁴ | Unit |
|-----|--|-------------|------------------------|--------|--------------|------------------------|------|
| 430 | Clock cycle ⁵ | t_{SSICC} | $4 \times T_C$ | 40.0 | — | i ck | ns |
| | | | $3 \times T_C$ | 30.0 | — | x ck | |
| | | | $TXC:\max[3*tc; t454]$ | 40.0 | — | x ck | |
| 431 | Clock high period • For internal clock • For external clock | — | $2 \times T_C - 10.0$ | 10.0 | — | | ns |
| | | | $1.5 \times T_C$ | 15.0 | — | | |
| 432 | Clock low period • For internal clock • For external clock | — | $2 \times T_C - 10.0$ | 10.0 | — | | ns |
| | | | $1.5 \times T_C$ | 15.0 | — | | |
| 433 | RXC rising edge to FSR out (bl) high | — | — | — — | 37.0 22.0 | x ck i ck a | ns |
| 434 | RXC rising edge to FSR out (bl) low | — | — | — — | 37.0 22.0 | x ck i ck a | ns |
| 435 | RXC rising edge to FSR out (wr) high ⁶ | — | — | — | 39.0 | x ck | ns |
| | | | | — | 24.0 | i ck a | |
| 436 | RXC rising edge to FSR out (wr) low ⁶ | — | — | — | 39.0 | x ck | ns |
| | | | | — | 24.0 | i ck a | |
| 437 | RXC rising edge to FSR out (wl) high | — | — | — | 36.0 | x ck | ns |
| | | | | — | 21.0 | i ck a | |
| 438 | RXC rising edge to FSR out (wl) low | — | — | — | 37.0 | x ck | ns |
| | | | | — | 22.0 | i ck a | |
| 439 | Data in setup time before RXC (SCK in synchronous mode) falling edge | — | — | 0.0 | — | x ck | ns |
| | | | | 19.0 | — | i ck | |
| 440 | Data in hold time after RXC falling edge | — | — | 5.0 | — | x ck | ns |
| | | | | 3.0 | — | i ck | |
| 441 | FSR input (bl, wr) high before RXC falling edge ⁶ | — | — | 23.0 | — | x ck | ns |
| | | | | 1.0 | — | i ck a | |
| 442 | FSR input (wl) high before RXC falling edge | — | — | 1.0 | — | x ck | ns |
| | | | | 23.0 | — | i ck a | |

Table 3-20 Enhanced Serial Audio Interface Timing (continued)

| No. | Characteristics ^{1, 2, 3} | Symbol | Expression | Min | Max | Condition ⁴ | Unit |
|-----|---|--------|-------------------------------|-------------|--------------|------------------------|------|
| 443 | FSR input hold time after RXC falling edge | — | — | 3.0 0.0 | — — | x ck i ck a | ns |
| 444 | Flags input setup before RXC falling edge | — | — | 0.0 19.0 | — — | x ck i ck s | ns |
| 445 | Flags input hold time after RXC falling edge | — | — | 6.0 0.0 | — — | x ck i ck s | ns |
| 446 | TXC rising edge to FST out (bl) high | — | — | — — | 29.0 15.0 | x ck i ck | ns |
| 447 | TXC rising edge to FST out (bl) low | — | — | — — | 31.0 17.0 | x ck i ck | ns |
| 448 | TXC rising edge to FST out (wr) high ⁶ | — | — | — — | 31.0 17.0 | x ck i ck | ns |
| 449 | TXC rising edge to FST out (wr) low ⁶ | — | — | — — | 33.0 19.0 | x ck i ck | ns |
| 450 | TXC rising edge to FST out (wl) high | — | — | — — | 30.0 16.0 | x ck i ck | ns |
| 451 | TXC rising edge to FST out (wl) low | — | — | — — | 31.0 17.0 | x ck i ck | ns |
| 452 | TXC rising edge to data out enable from high impedance | — | — | — — | 31.0 17.0 | x ck i ck | ns |
| 453 | TXC rising edge to transmitter #0 drive enable assertion | — | — | — — | 34.0 20.0 | x ck i ck | ns |
| 454 | TXC rising edge to data out valid | — | $23 + 0.5 \times T_C$ 21.0 | — — | 28.0 21.0 | x ck i ck | ns |
| 455 | TXC rising edge to data out high impedance ⁷ | — | — | — — | 31.0 16.0 | x ck i ck | ns |
| 456 | TXC rising edge to transmitter #0 drive enable deassertion ⁷ | — | — | — — | 34.0 20.0 | x ck i ck | ns |
| 457 | FST input (bl, wr) setup time before TXC falling edge ⁶ | — | — | 2.0 21.0 | — — | x ck i ck | ns |
| 458 | FST input (wl) to data out enable from high impedance | — | — | — | 27.0 | — | ns |

Table 3-20 Enhanced Serial Audio Interface Timing (continued)

| No. | Characteristics ^{1, 2, 3} | Symbol | Expression | Min | Max | Condition ⁴ | Unit |
|-----|---|--------|------------|-------------|--------------|------------------------|------|
| 459 | FST input (wl) to transmitter #0 drive enable assertion | — | — | — | 31.0 | — | ns |
| 460 | FST input (wl) setup time before TXC falling edge | — | — | 2.0 21.0 | — — | x ck i ck | ns |
| 461 | FST input hold time after TXC falling edge | — | — | 4.0 0.0 | — — | x ck i ck | ns |
| 462 | Flag output valid after TXC rising edge | — | — | — — | 32.0 18.0 | x ck i ck | ns |
| 463 | HCKR/HCKT clock cycle | — | — | 40.0 | — | | ns |
| 464 | HCKT input rising edge to TXC output | — | — | — | 27.5 | | ns |
| 465 | HCKR input rising edge to RXC output | — | — | — | 27.5 | | ns |

¹ $V_{CC} = 3.16 \text{ V} \pm 0.16 \text{ V}$; $T_J = 0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50 \text{ pF}$.

² i ck = internal clock

x ck = external clock

i ck a = internal clock, asynchronous mode (asynchronous implies that TXC and RXC are two different clocks)

i ck s = internal clock, synchronous mode (synchronous implies that TXC and RXC are the same clock)

³ bl = bit length

wl = word length

wr = word length relative

⁴ TXC(SCKT pin) = transmit clock

RXC(SCKR pin) = receive clock

FST(FST pin) = transmit frame sync

FSR(FSR pin) = receive frame sync

HCKT(HCKT pin) = transmit high speed clock


HCKR(HCKR pin) = receive high speed clock

⁵ For the internal clock, the external clock cycle is defined by I_{cyc} and the ESAI control register.

⁶ The word-relative frame sync signal waveform relative to the clock operates in the same manner as the bit-length frame sync signal waveform, but spreads from one serial clock before first bit clock (same as bit length frame sync signal), until the one before last bit clock of the first word in frame.

⁷ Periodically sampled and not 100% tested

Enhanced Serial Audio Interface Timing



Note: In network mode, output flag transitions can occur at the start of each time slot within the frame. In normal mode, the output flag state is asserted for the entire frame period.

AA0490

Figure 3-23 ESAS Transmitter Timing




Figure 3-24 ESAI Receiver Timing




Figure 3-25 ESAI HCKT Timing




Figure 3-26 ESAI HCKR Timing

3.14 GPIO Timing

Table 3-21 GPIO Timing

| No. | Characteristics ¹ | Expression | Min | Max | Unit |
|------------------|---|-------------------------|------|------|------|
| 490 ² | EXTAL edge to GPIO out valid (GPIO out delay time) | | — | 32.8 | ns |
| 491 | EXTAL edge to GPIO out not valid (GPIO out hold time) | | 4.8 | — | ns |
| 492 | GPIO In valid to EXTAL edge (GPIO in set-up time) | | 10.2 | — | ns |
| 493 | EXTAL edge to GPIO in not valid (GPIO in hold time) | | 1.8 | — | ns |
| 494 ² | Fetch to EXTAL edge before GPIO change | $6.75 \times T_C - 1.8$ | 65.7 | — | ns |
| 495 | GPIO out rise time | — | — | 13 | ns |
| 496 | GPIO out fall time | — | — | 13 | ns |

¹ $V_{CC} = 3.3 \text{ V} \pm 0.16 \text{ V}$; $T_J = 0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50 \text{ pF}$

² Valid only when PLL enabled with multiplication factor equal to one.




Figure 3-27 GPIO Timing

3.15 JTAG Timing

Table 3-22 JTAG Timing^{1, 2}

| No. | Characteristics | All frequencies | | Unit |
|-----|---|-----------------|------|------|
| | | Min | Max | |
| 500 | TCK frequency of operation ($1/(T_C \times 3)$; maximum 22 MHz) | 0.0 | 22.0 | MHz |
| 501 | TCK cycle time in Crystal mode | 45.0 | — | ns |
| 502 | TCK clock pulse width measured at 1.5 V | 20.0 | — | ns |
| 503 | TCK rise and fall times | 0.0 | 3.0 | ns |
| 504 | Boundary scan input data setup time | 5.0 | — | ns |
| 505 | Boundary scan input data hold time | 24.0 | — | ns |
| 506 | TCK low to output data valid | 0.0 | 40.0 | ns |
| 507 | TCK low to output high impedance | 0.0 | 40.0 | ns |
| 508 | TMS, TDI data setup time | 5.0 | — | ns |

Table 3-22 JTAG Timing^{1, 2} (continued)

| No. | Characteristics | All frequencies | | Unit |
|-----|-------------------------------|-----------------|------|------|
| | | Min | Max | |
| 509 | TMS, TDI data hold time | 25.0 | — | ns |
| 510 | TCK low to TDO data valid | 0.0 | 44.0 | ns |
| 511 | TCK low to TDO high impedance | 0.0 | 44.0 | ns |

¹ $V_{CC} = 3.3\text{ V} \pm 0.16\text{ V}$; $T_J = 0^\circ\text{C}$ to $+105^\circ\text{C}$, $C_L = 50\text{ pF}$

² All timings apply to OnCE module data transfers because it uses the JTAG port as an interface.




Figure 3-28 Test Clock Input Timing Diagram





Figure 3-29 Boundary Scan (JTAG) Timing Diagram



AA0498

Figure 3-30 Test Access Port Timing Diagram

NOTES

4 Packaging

4.1 Pin-out and Package Information

This section provides information about the available package for this product, including diagrams of the package pinouts and tables describing how the signals described in [Section 2, "Signal/Connection Descriptions"](#) are allocated for the package. The DSP56364 is available in a 100-pin TQFP package. [Table 4-1](#) and [Table 4-2](#) show the pin/name assignments for the packages.

4.1.1 TQFP Package Description

Top view of the 100-pin TQFP package is shown in [Figure 4-1](#) with its pin-outs. The 100-pin TQFP package mechanical drawing is shown in [Figure 4-2](#).

Pin-out and Package Information

| | 100 | 99 | 98 | 97 | 96 | 95 | 94 | 93 | 92 | 91 | 90 | 89 | 88 | 87 | 86 | 85 | 84 | 83 | 82 | 81 | 80 | 79 | 78 | 77 | 76 | | | |
|-----------|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-------|
| MODD | 1 | | | | | | | | | | | | | | | | | | | | | | | | | 75 | D0 | |
| MODB | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | 74 | A17 |
| MODA | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | 73 | A16 |
| FST | 4 | | | | | | | | | | | | | | | | | | | | | | | | | | 72 | GND A |
| FSR | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | 71 | VCCA |
| SCKT | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | 70 | A15 |
| SCKR | 7 | | | | | | | | | | | | | | | | | | | | | | | | | | 69 | A14 |
| VCCS | 8 | | | | | | | | | | | | | | | | | | | | | | | | | | 68 | A13 |
| GNDS | 9 | | | | | | | | | | | | | | | | | | | | | | | | | | 67 | A12 |
| HCKT | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | 66 | VCCLQ |
| VCCLQ | 11 | | | | | | | | | | | | | | | | | | | | | | | | | | 65 | GNDQ |
| GNDQ | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | 64 | GND A |
| HCKR | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | 63 | VCCA |
| SDO0 | 14 | | | | | | | | | | | | | | | | | | | | | | | | | | 62 | A11 |
| VCCHQ | 15 | | | | | | | | | | | | | | | | | | | | | | | | | | 61 | VCCQH |
| SDO1 | 16 | | | | | | | | | | | | | | | | | | | | | | | | | | 60 | A10 |
| SDO2/SDI3 | 17 | | | | | | | | | | | | | | | | | | | | | | | | | | 59 | A9 |
| SDO3/SDI2 | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | 58 | A8 |
| SDO4/SDI1 | 19 | | | | | | | | | | | | | | | | | | | | | | | | | | 57 | A7 |
| SDO5/SDI0 | 20 | | | | | | | | | | | | | | | | | | | | | | | | | | 56 | GND A |
| VCCS | 21 | | | | | | | | | | | | | | | | | | | | | | | | | | 55 | VCCA |
| GNDS | 22 | | | | | | | | | | | | | | | | | | | | | | | | | | 54 | A6 |
| SS/HA2 | 23 | | | | | | | | | | | | | | | | | | | | | | | | | | 53 | A5 |
| MOSI/HA0 | 24 | | | | | | | | | | | | | | | | | | | | | | | | | | 52 | A4 |
| MISO/SDA | 25 | | | | | | | | | | | | | | | | | | | | | | | | | | 51 | A3 |
| | 26 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SCK/SCL | | 27 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HREQ | | 28 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PINIT/NMI | | 29 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RESET | | 30 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NC | | 31 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VCCP | | 32 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PCAP | | 33 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GNDP | | 34 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| EXTAL | | 35 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VCCHQ | | 36 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GNDQ | | 37 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VCCQL | | 38 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TA | | 39 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CAS | | 40 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WR | | 41 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RD | | 42 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VCCC | | 43 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GND C | | 44 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AA1 | | 45 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AA0 | | 46 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A0 | | 47 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A1 | | 48 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VCCA | | 49 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GND A | | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Figure 4-1 DSP56364 100-Pin Thin Quad Flat Pack (TQFP), Top View

Table 4-1 DSP56364 100-Pin TQFP Signal Identification by Pin Number


| Pin No. | Signal Name | Pin No. | Signal Name | Pin No. | Signal Name | Pin No. | Signal Name |
|---------|-----------------------------------|---------|--------------------------------|---------|-------------|---------|-------------|
| 1 | MODD/ $\overline{\text{IRQD}}$ | 26 | SCK/SCL | 51 | A3 | 76 | D1 |
| 2 | MODB/ $\overline{\text{IRQB}}$ | 27 | $\overline{\text{HREQ}}$ | 52 | A4 | 77 | D2 |
| 3 | MODA/ $\overline{\text{IRQA}}$ | 28 | PINIT/ $\overline{\text{NMI}}$ | 53 | A5 | 78 | D3 |
| 4 | FST | 29 | RESET | 54 | A6 | 79 | VCCD |
| 5 | FSR | 30 | No Connect | 55 | VCCA | 80 | GNDD |
| 6 | SCKT | 31 | VCCP | 56 | GNDA | 81 | D4 |
| 7 | SCKR | 32 | PCAP | 57 | A7 | 82 | D5 |
| 8 | VCCS | 33 | GNDP | 58 | A8 | 83 | D6 |
| 9 | GNDS | 34 | EXTAL | 59 | A9 | 84 | D7 |
| 10 | HCKT | 35 | VCCHQ | 60 | A10 | 85 | No Connect |
| 11 | VCCLQ | 36 | GNDQ | 61 | VCCHQ | 86 | No Connect |
| 12 | GNDQ | 37 | VCCLQ | 62 | A11 | 87 | VCCLQ |
| 13 | HCKR | 38 | TA | 63 | VCCA | 88 | GNDQ |
| 14 | SDO0 | 39 | $\overline{\text{CAS}}$ | 64 | GNDA | 89 | VCCHQ |
| 15 | VCCHQ | 40 | WR | 65 | GNDQ | 90 | No Connect |
| 16 | SDO1 | 41 | RD | 66 | VCCLQ | 91 | GPIO0 |
| 17 | SDO2/SDI3 | 42 | VCCC | 67 | A12 | 92 | VCCS |
| 18 | SDO3/SDI2 | 43 | GNDC | 68 | A13 | 93 | GNDS |
| 19 | SDO4/SDI1 | 44 | AA1/ $\overline{\text{RAS1}}$ | 69 | A14 | 94 | GPIO1 |
| 20 | SDO5/SDI0 | 45 | AA0/ $\overline{\text{RAS0}}$ | 70 | A15 | 95 | GPIO2 |
| 21 | VCCS | 46 | A0 | 71 | VCCA | 96 | GPIO3 |
| 22 | GNDS | 47 | A1 | 72 | GNDA | 97 | TDO |
| 23 | $\overline{\text{SS}}/\text{HA2}$ | 48 | VCCQ | 73 | A16 | 98 | TDI |
| 24 | MOSI/HA0 | 49 | GNDQ | 74 | A17 | 99 | TCK |
| 25 | MISO/SDA | 50 | A2 | 75 | D0 | 100 | TMS |

Note: Signal names are based on configured functionality. Most pins supply a single signal. Some pins provide a signal with dual functionality, such as the MODx/ $\overline{\text{IRQx}}$ pins that select an operating mode after $\overline{\text{RESET}}$ is deasserted, but act as interrupt lines during operation.

Table 4-2 DSP56364 100-Pin TQFP Signal Identification by Name

| Signal Name | Pin No. | Signal Name | Pin No. | Signal Name | Pin No. | Signal Name | Pin No. |
|-------------------------|---------|-------------|---------|-----------------------------------|---------|------------------------|---------|
| A0 | 46 | D4 | 81 | HCKR | 13 | SDO4/SDI1 | 19 |
| A1 | 47 | D5 | 82 | HCKT | 10 | TA | 38 |
| A10 | 60 | D6 | 83 | $\overline{\text{HREQ}}$ | 27 | TCK | 99 |
| A11 | 62 | D7 | 84 | MISO/SDA | 25 | TDI | 98 |
| A12 | 67 | EXTAL | 34 | MODA/ $\overline{\text{IRQA}}$ | 3 | TD0 | 97 |
| A13 | 68 | FSR | 5 | MODB/ $\overline{\text{IRQB}}$ | 2 | TMS | 100 |
| A14 | 69 | FST | 4 | MODD/ $\overline{\text{IRQD}}$ | 1 | VCCA | 48 |
| A15 | 70 | GNDA | 49 | MOSI/HA0 | 24 | VCCA | 55 |
| A16 | 73 | GNDA | 56 | No Connect | 30 | VCCA | 63 |
| A17 | 74 | GNDA | 64 | No Connect | 85 | VCCA | 71 |
| A2 | 50 | GNDA | 72 | No Connect | 86 | VCCC | 42 |
| A3 | 51 | GNDC | 43 | No Connect | 90 | VCCD | 79 |
| A4 | 52 | GNDD | 80 | PCAP | 32 | VCCHQ | 15 |
| A5 | 53 | GNDP | 33 | PINIT/ $\overline{\text{NMI}}$ | 28 | VCCHQ | 35 |
| A6 | 54 | GNDQ | 12 | $\overline{\text{RD}}$ | 41 | VCCHQ | 61 |
| A7 | 57 | GNDQ | 36 | $\overline{\text{RESET}}$ | 29 | VCCHQ | 89 |
| A8 | 58 | GNDQ | 65 | SCK/SCL | 26 | VCCLQ | 11 |
| A9 | 59 | GNDQ | 88 | SCKR | 7 | VCCLQ | 37 |
| AA0 | 45 | GNDS | 9 | SCKT | 6 | VCCLQ | 66 |
| AA1 | 44 | GNDS | 22 | SDO0 | 14 | VCCLQ | 87 |
| $\overline{\text{CAS}}$ | 39 | GNDS | 93 | SDO1 | 16 | VCCP | 31 |
| D0 | 75 | GPIO0 | 91 | SDO5/SDI0 | 20 | VCCS | 8 |
| D1 | 76 | GPIO1 | 94 | $\overline{\text{SS}}/\text{HA2}$ | 23 | VCCS | 21 |
| D2 | 77 | GPIO2 | 95 | SDO2/SDI3 | 17 | VCCS | 92 |
| D3 | 78 | GPIO3 | 96 | SDO3/SDI2 | 18 | $\overline{\text{WR}}$ | 40 |

4.1.2 TQFP Package Mechanical Drawing



CASE 983±02
ISSUE E

DATE 01/30/96

Figure 4-2 DSP56364 100-pin TQFP Package

5 Design Considerations

5.1 Thermal Design Considerations

An estimation of the chip junction temperature, T_J , in °C can be obtained from the following equation:

$$T_J = T_A + (P_D \times R_{\theta JA})$$

Where: T_A = ambient temperature °C
 $R_{\theta JA}$ = package junction-to-ambient thermal resistance °C/W
 P_D = power dissipation in package W

Historically, thermal resistance has been expressed as the sum of a junction-to-case thermal resistance and a case-to-ambient thermal resistance.

$$R_{\theta JA} = R_{\theta JC} + R_{\theta CA}$$

Where: $R_{\theta JA}$ = package junction-to-ambient thermal resistance °C/W
 $R_{\theta JC}$ = package junction-to-case thermal resistance °C/W
 $R_{\theta CA}$ = package case-to-ambient thermal resistance °C/W

$R_{\theta JC}$ is device-related and cannot be influenced by the user. The user controls the thermal environment to change the case-to-ambient thermal resistance, $R_{\theta CA}$. For example, the user can change the air flow around the device, add a heat sink, change the mounting arrangement on the printed circuit board (PCB), or otherwise change the thermal dissipation capability of the area surrounding the device on a PCB. This model is most useful for ceramic packages with heat sinks; some 90% of the heat flow is dissipated through the case to the heat sink and out to the ambient environment. For ceramic packages, in situations where the heat flow is split between a path to the case and an alternate path through the PCB, analysis of the device thermal performance may need the additional modeling capability of a system level thermal simulation tool.

The thermal performance of plastic packages is more dependent on the temperature of the PCB to which the package is mounted. Again, if the estimations obtained from $R_{\theta JA}$ do not satisfactorily answer whether the thermal performance is adequate, a system level model may be appropriate.

A complicating factor is the existence of three common ways for determining the junction-to-case thermal resistance in plastic packages.

- To minimize temperature variation across the surface, the thermal resistance is measured from the junction to the outside surface of the package (case) closest to the chip mounting area when that surface has a proper heat sink.

Electrical Design Considerations

- To define a value approximately equal to a junction-to-board thermal resistance, the thermal resistance is measured from the junction to where the leads are attached to the case.
- If the temperature of the package case (T_T) is determined by a thermocouple, the thermal resistance is computed using the value obtained by the equation:

$$(T_J - T_T)/P_D$$

As noted above, the junction-to-case thermal resistances quoted in this data sheet are determined using the first definition. From a practical standpoint, that value is also suitable for determining the junction temperature from a case thermocouple reading in forced convection environments. In natural convection, using the junction-to-case thermal resistance to estimate junction temperature from a thermocouple reading on the case of the package will estimate a junction temperature slightly hotter than actual temperature. Hence, the new thermal metric, thermal characterization parameter or Ψ_{JT} , has been defined to be $(T_J - T_T)/P_D$. This value gives a better estimate of the junction temperature in natural convection when using the surface temperature of the package. Remember that surface temperature readings of packages are subject to significant errors caused by inadequate attachment of the sensor to the surface and to errors caused by heat loss to the sensor. The recommended technique is to attach a 40-gauge thermocouple wire and bead to the top center of the package with thermally conductive epoxy.

5.2 Electrical Design Considerations

CAUTION

This device contains circuitry protecting against damage due to high static voltage or electrical fields. However, normal precautions should be taken to avoid exceeding maximum voltage ratings. Reliability of operation is enhanced if unused inputs are tied to an appropriate logic voltage level (e.g., either GND or V_{CC}). The suggested value for a pullup or pulldown resistor is 10 k ohm.

Use the following list of recommendations to assure correct DSP operation:

- Provide a low-impedance path from the board power supply to each V_{CC} pin on the DSP and from the board ground to each GND pin.
- Use at least six 0.01–0.1 μF bypass capacitors positioned as close as possible to the four sides of the package to connect the V_{CC} power source to GND.
- Ensure that capacitor leads and associated printed circuit traces that connect to the chip V_{CC} and GND pins are less than 1.2 cm (0.5 inch) per capacitor lead.
- Use at least a four-layer PCB with two inner layers for V_{CC} and GND.
- Because the DSP output signals have fast rise and fall times, PCB trace lengths should be minimal. This recommendation particularly applies to the address and data buses as well as the $\overline{\text{IRQA}}$, $\overline{\text{IRQB}}$, $\overline{\text{IRQD}}$, and $\overline{\text{TA}}$ pins. Maximum PCB trace lengths on the order of 15 cm (6 inches) are recommended.
- Consider all device loads as well as parasitic capacitance due to PCB traces when calculating capacitance. This is especially critical in systems with higher capacitive loads that could create higher transient currents in the V_{CC} and GND circuits.

- All inputs must be terminated (i.e., not allowed to float) using CMOS levels, except for the three pins with internal pull-up resistors (TMS, TDI, TCK).
- Take special care to minimize noise levels on the V_{CCP} and GND_P pins.
- If multiple DSP56364 devices are on the same board, check for cross-talk or excessive spikes on the supplies due to synchronous operation of the devices.
- RESET must be asserted when the chip is powered up. A stable EXTAL signal must be supplied before deassertion of RESET.
- At power-up, ensure that the voltage difference between the 5 V tolerant pins and the chip V_{CC} never exceeds 3.95 V.

5.3 Power Consumption Considerations

Power dissipation is a key issue in portable DSP applications. Some of the factors which affect current consumption are described in this section. Most of the current consumed by CMOS devices is alternating current (ac), which is charging and discharging the capacitances of the pins and internal nodes.

Current consumption is described by the following formula:

$$I = C \times V \times f$$

where

| | | |
|---|---|------------------------------|
| C | = | node/pin capacitance |
| V | = | voltage swing |
| f | = | frequency of node/pin toggle |

Example 1. Current Consumption

For a Port A address pin loaded with 50 pF capacitance, operating at 3.3 V, and with a 100 MHz clock, toggling at its maximum possible rate (50 MHz), the current consumption is

$$I = 50 \times 10^{-12} \times 3.3 \times 50 \times 10^6 = 8.25 \text{ mA}$$

The maximum internal current ($I_{CC1\text{max}}$) value reflects the typical possible switching of the internal buses on best-case operation conditions, which is not necessarily a real application case. The typical internal current ($I_{CC1\text{typ}}$) value reflects the average switching of the internal buses on typical operating conditions.

For applications that require very low current consumption, do the following:

- Set the EBD bit when not accessing external memory.
- Minimize external memory accesses and use internal memory accesses.
- Minimize the number of pins that are switching.
- Minimize the capacitive load on the pins.
- Connect the unused inputs to pull-up or pull-down resistors.
- Disable unused peripherals.

One way to evaluate power consumption is to use a current per MIPS measurement methodology to minimize specific board effects (i.e., to compensate for measured board current not caused by the DSP).

PLL Performance Issues

A benchmark power consumption test algorithm is listed in [Appendix A, "IBIS Model"](#). Use the test algorithm, specific test current measurements, and the following equation to derive the current per MIPS value.

$$I/\text{MIPS} = I/\text{MHz} = (I_{\text{typF2}} - I_{\text{typF1}})/(F2 - F1)$$

where: I_{typF2} = current at F2
 I_{typF1} = current at F1
F2 = high frequency (any specified operating frequency)
F1 = low frequency (any specified operating frequency lower than F2)

NOTE

F1 should be significantly less than F2. For example, F2 could be 66 MHz and F1 could be 33 MHz. The degree of difference between F1 and F2 determines the amount of precision with which the current rating can be determined for an application.

5.4 PLL Performance Issues

The following explanations should be considered as general observations on expected PLL behavior. There is no testing that verifies these exact numbers. These observations were measured on a limited number of parts and were not verified over the entire temperature and voltage ranges.

5.4.1 Input (EXTAL) Jitter Requirements

The allowed jitter on the frequency of EXTAL is 0.5%. If the rate of change of the frequency of EXTAL is slow (i.e., it does not jump between the minimum and maximum values in one cycle) or the frequency of the jitter is fast (i.e., it does not stay at an extreme value for a long time), then the allowed jitter can be 2%. The phase and frequency jitter performance results are only valid if the input jitter is less than the prescribed values.

6 Ordering Information

Consult a Freescale Semiconductor sales office or authorized distributor to determine product availability and to place an order.

Table 6-1 Ordering Information^{1, 2}

| Part | Supply Voltage | Package Type | Pin Count | Frequency (MHz) | Order Number |
|----------|----------------|----------------------------|-----------|-----------------|---------------|
| DSP56364 | 3.3 V | Thin quad flat pack (TQFP) | 100 | 100 | XCB56364FU100 |
| | | Quad flat pack (QFP) | 112 | 100 | XCB56364PV100 |

¹ The DSP56364 can include factory-programmed ROM. The listed 'B' ROM code is a generic unused ROM available to any customer. Variations will be supported for Dolby digital (AC-3), DTS, MPEG2, and other features. These products are only available to authorized licensees of those technologies. Please consult the web site at www.dsppaudio.freescale.com for current availability.

² Future products in the DSP56364 family may include other ROM-based options. For additional information on future part development, or to request customer-specific ROM-based support, call your local Freescale Semiconductor sales office or authorized distributor.



NOTES

Appendix A IBIS Model

```

IBIS Model
[IBIS Ver]          3.2
[File name]        56364_e.ibs
[File Rev]         e
[Date]             Feb 13, 2002
[Component]        56364
[Manufacturer]     Freescale SEMI CONDUCTOR Ltd.
[Package]
| variable          typ          min          max
R_pkg              45.0m        22.0m        75.0m
L_pkg              2.5nH         1.1nH         4.3nH
C_pkg              1.3pF         1.2pF         1.4pF
[Pin]             signal_name      model_name    R_pin        L_pin        C_pin
1                 irqd_          ipad5v_io
2                 irqb_          ipad5v_io
3                 irqa_          ipad5v_io
4                 fst           ipad5v_io
5                 fsr           ipad5v_io
6                 sckt          ipad5v_io
7                 sckr          ipad5v_io
8                 vccs          power
9                 gnnds         gnd
10                hckt          ipad5v_io
11                vcclq        power
12                gndq          gnd
13                hckr          ipad5v_io
14                sdo0          ipad5v_io
15                vcchq        power
16                sdo1          ipad5v_io
17                sdo2/sdi3    ipad5v_io
18                sdo3/sdi2    ipad5v_io
19                sdo4/sdi1    ipad5v_io
20                sdo5/sdi0    ipad5v_io
21                vccs          power
22                gnnds         gnd
23                ss_/ha2       ipad5v_io
24                mosi/ha0      ipad5v_io
25                miso/sda      ipad5i_io
26                sck/scl       ipad5i_io
27                hreq_         ipad5i_io
28                pinit/nmi_   ipad5v_io
29                reset_        ipad5v_io
31                vccp          power
32                pcap          power
33                gndp          gnd
34                extal         ipadx_i
35                vcchq        power

```

| | | |
|----|-----------|-----------|
| 36 | gndq | gnd |
| 37 | vcclq | power |
| 38 | ta_ | ipadn_io |
| 39 | cas_ | ipadm_3st |
| 40 | wr_ | ipadn_io |
| 41 | rd_ | ipadn_io |
| 42 | vccc | power |
| 43 | gndc | gnd |
| 44 | aa1/ras1_ | ipado_3st |
| 45 | aa0/ras0_ | ipado_3st |
| 46 | a0 | ipada_3st |
| 47 | a1 | ipada_3st |
| 48 | vccq | power |
| 49 | gndq | gnd |
| 50 | a2 | ipada_3st |
| 51 | a3 | ipada_3st |
| 52 | a4 | ipada_3st |
| 53 | a5 | ipada_3st |
| 54 | a6 | ipada_3st |
| 55 | vcca | power |
| 56 | gnda | gnd |
| 57 | a7 | ipada_3st |
| 58 | a8 | ipada_3st |
| 59 | a9 | ipada_3st |
| 60 | a10 | ipada_3st |
| 61 | vcchq | power |
| 62 | a11 | ipada_3st |
| 63 | vcca | power |
| 64 | gnda | gnd |
| 65 | gndq | gnd |
| 66 | vcclq | power |
| 67 | a12 | power |
| 68 | a13 | ipada_3st |
| 69 | a14 | ipada_3st |
| 70 | a15 | ipada_3st |
| 71 | vcca | power |
| 72 | gnda | gnd |
| 73 | a16 | ipada_3st |
| 74 | a17 | ipada_3st |
| 75 | d0 | ipadd_io |
| 76 | d1 | ipadd_io |
| 77 | d2 | ipadd_io |
| 78 | d3 | ipadd_io |
| 79 | vccd | power |
| 80 | gndd | gnd |
| 81 | d4 | ipadd_io |
| 82 | d5 | ipadd_io |
| 83 | d6 | ipadd_io |
| 84 | d7 | ipadd_io |
| 87 | vcclq | power |
| 88 | gndq | gnd |
| 89 | vcchq | power |
| 91 | gpio0 | ipad5v_io |
| 92 | vccs | power |
| 93 | gn ds | gnd |

```

94          gpio1          ipad5v_io
95          gpio2          ipad5v_io
96          gpio3          ipad5v_io
97          tdo            ipad5f_io
98          tdi            ipad5f_io
99          tck            ipad5f_io
100         tms            ipad5f_io

```

```

[Model]          ipad5f_io          | ""
Model_type      I/O
Vinl = 0.8
Vinh = 2
| variable      typ          min          max
C_comp          1.96p        1.87p        2.06p
| variable      typ          min          max
[Temperature Range] 40.0          0.0          120.0
| variable      typ          min          max
[Voltage Range]  3.30V        3.00V        3.60V
|
[Pulldown]
| pulldown in the table = pulldown subtract gnd_clamp
|Voltage        I (typ)          I (min)          I (max)
|
-3.30V          -142.303u       -76.239u       -215.182u
-3.20V          -149.700u       -80.226u       -226.432u
-3.10V          -157.861u       -84.616u       -238.866u
-3.00V          -166.908u       -89.472u       -252.678u
-2.90V          -176.992u       -94.869u       -268.107u
-2.80V          -188.295u       -100.900u      -285.446u
-2.70V          -201.049u       -107.679u      -305.068u
-2.60V          -215.545u       -115.349u      -327.446u
-2.50V          -232.155u       -124.094u      -353.191u
-2.40V          -251.367u       -134.145u      -383.107u
-2.30V          -273.825u       -145.808u      -418.273u
-2.20V          -300.403u       -159.488u      -460.167u
-2.10V          -332.314u       -175.737u      -510.874u
-2.00V          -371.286u       -195.318u      -573.418u
-1.90V          -419.868u       -219.325u      -652.360u
-1.80V          -481.968u       -249.369u      -754.892u
-1.70V          -563.882u       -287.925u      -893.013u
-1.60V          -676.382u       -338.973u      -1.088m
-1.50V          -839.410u       -409.300u      -1.383m
-1.40V          -1.094m         -511.367u      -1.873m
-1.30V          -1.537m         -670.350u      -2.819m
-1.20V          -2.451m         -943.845u      -5.162m
-1.10V          -4.857m         -1.486m        -12.214m
-1.00V          -10.606m        -2.746m        -20.764m
-0.90V          -14.267m        -5.259m        -21.749m
-0.80V          -13.851m        -7.108m        -20.142m
-0.70V          -12.481m        -7.168m        -18.211m
-0.60V          -10.883m        -6.348m        -15.981m
-0.50V          -9.156m         -5.339m        -13.503m
-0.40V          -7.378m         -4.288m        -10.922m
-0.30V          -5.572m         -3.224m        -8.282m
-0.20V          -3.741m         -2.154m        -5.584m

```

| | | | |
|--------|---------|---------|----------|
| -0.10V | -1.885m | -1.080m | -2.825m |
| 0.00V | 1.898p | 1.419p | 1.871p |
| 0.10V | 1.857m | 1.057m | 2.800m |
| 0.20V | 3.630m | 2.064m | 5.482m |
| 0.30V | 5.323m | 3.023m | 8.052m |
| 0.40V | 6.936m | 3.935m | 10.508m |
| 0.50V | 8.467m | 4.798m | 12.849m |
| 0.60V | 9.915m | 5.611m | 15.073m |
| 0.70V | 11.275m | 6.371m | 17.176m |
| 0.80V | 12.546m | 7.078m | 19.155m |
| 0.90V | 13.723m | 7.726m | 21.011m |
| 1.00V | 36.925m | 20.745m | 56.704m |
| 1.10V | 39.391m | 22.074m | 60.708m |
| 1.20V | 41.612m | 23.244m | 64.383m |
| 1.30V | 43.585m | 24.247m | 67.726m |
| 1.40V | 45.305m | 25.079m | 70.735m |
| 1.50V | 46.773m | 25.741m | 73.414m |
| 1.60V | 47.997m | 26.251m | 75.766m |
| 1.70V | 48.985m | 26.633m | 77.783m |
| 1.80V | 49.733m | 26.905m | 79.441m |
| 1.90V | 50.257m | 27.092m | 80.724m |
| 2.00V | 50.612m | 27.223m | 81.651m |
| 2.10V | 50.858m | 27.321m | 82.294m |
| 2.20V | 51.040m | 27.399m | 82.744m |
| 2.30V | 51.182m | 27.465m | 83.074m |
| 2.40V | 51.302m | 27.522m | 83.332m |
| 2.50V | 51.405m | 27.572m | 83.543m |
| 2.60V | 51.497m | 27.618m | 83.724m |
| 2.70V | 51.581m | 27.657m | 83.884m |
| 2.80V | 51.658m | 27.674m | 84.030m |
| 2.90V | 51.727m | 27.587m | 84.165m |
| 3.00V | 51.757m | 27.577m | 84.290m |
| 3.10V | 51.229m | 28.700m | 84.409m |
| 3.20V | 49.190m | 30.042m | 84.515m |
| 3.30V | 49.441m | 31.171m | 84.491m |
| 3.40V | 51.034m | 32.199m | 81.077m |
| 3.50V | 54.363m | 33.153m | 79.736m |
| 3.60V | 57.165m | 34.039m | 80.276m |
| 3.70V | 58.834m | 34.872m | 82.430m |
| 3.80V | 60.328m | 35.686m | 85.482m |
| 3.90V | 61.725m | 36.495m | 91.743m |
| 4.00V | 63.035m | 37.291m | 94.219m |
| 4.10V | 64.319m | 38.051m | 96.276m |
| 4.20V | 65.598m | 38.755m | 98.249m |
| 4.30V | 66.836m | 39.394m | 100.059m |
| 4.40V | 67.999m | 39.962m | 101.849m |
| 4.50V | 69.069m | 40.453m | 103.628m |
| 4.60V | 70.046m | 40.840m | 105.345m |
| 4.70V | 70.938m | 41.065m | 106.956m |
| 4.80V | 71.751m | 40.952m | 108.448m |
| 4.90V | 72.476m | 40.067m | 109.826m |
| 5.00V | 73.089m | 39.395m | 111.106m |
| 5.10V | 73.531m | 39.313m | 112.297m |
| 5.20V | 73.651m | 39.358m | 113.400m |
| 5.30V | 72.901m | 39.410m | 114.401m |

| | | | |
|---|-----------|-----------|-----------|
| 5.40V | 71.005m | 39.460m | 115.267m |
| 5.50V | 70.389m | 39.508m | 115.917m |
| 5.60V | 70.321m | 39.552m | 116.139m |
| 5.70V | 70.361m | 39.595m | 114.582m |
| 5.80V | 70.422m | 39.634m | 111.344m |
| 5.90V | 70.489m | 39.672m | 110.612m |
| 6.00V | 70.557m | 39.708m | 110.449m |
| 6.10V | 70.624m | 39.743m | 110.455m |
| 6.20V | 70.690m | 39.777m | 110.515m |
| 6.30V | 70.753m | 39.812m | 110.595m |
| 6.40V | 70.817m | 39.848m | 110.686m |
| 6.50V | 70.881m | 39.886m | 110.783m |
| 6.60V | 70.949m | 39.929m | 110.885m |
| | | | |
| [Pullup] | | | |
| pullup in the table = pullup subtract power_clamp | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | 75.797u | 7.914u | 161.477u |
| -3.20V | 90.464u | 17.699u | 181.779u |
| -3.10V | 105.160u | 27.445u | 202.314u |
| -3.00V | 119.836u | 37.119u | 223.007u |
| -2.90V | 134.451u | 46.694u | 243.785u |
| -2.80V | 148.966u | 56.144u | 264.581u |
| -2.70V | 163.342u | 65.447u | 285.332u |
| -2.60V | 177.543u | 74.582u | 305.982u |
| -2.50V | 191.536u | 83.527u | 326.474u |
| -2.40V | 205.285u | 92.262u | 346.757u |
| -2.30V | 218.754u | 100.766u | 366.776u |
| -2.20V | 231.907u | 109.016u | 386.478u |
| -2.10V | 244.706u | 116.988u | 405.807u |
| -2.00V | 257.106u | 124.659u | 424.699u |
| -1.90V | 269.061u | 131.998u | 443.089u |
| -1.80V | 280.519u | 138.978u | 460.899u |
| -1.70V | 291.423u | 145.565u | 478.046u |
| -1.60V | 301.710u | 151.723u | 494.457u |
| -1.50V | 311.348u | 157.417u | 521.406u |
| -1.40V | 729.899u | 162.626u | 1.612m |
| -1.30V | 10.510m | 445.517u | 14.832m |
| -1.20V | 9.629m | 6.444m | 13.576m |
| -1.10V | 8.670m | 5.833m | 12.231m |
| -1.00V | 7.693m | 5.190m | 10.854m |
| -0.90V | 6.732m | 4.551m | 9.483m |
| -0.80V | 5.825m | 3.942m | 8.169m |
| -0.70V | 5.004m | 3.382m | 6.971m |
| -0.60V | 4.261m | 2.869m | 5.921m |
| -0.50V | 3.549m | 2.381m | 4.953m |
| -0.40V | 2.841m | 1.902m | 3.978m |
| -0.30V | 2.135m | 1.426m | 2.987m |
| -0.20V | 1.437m | 951.489u | 2.003m |
| -0.10V | 722.340u | 478.341u | 1.005m |
| -0.00V | 22.329p | 3.311p | 24.081p |
| 0.10V | -708.556u | -465.927u | -990.647u |
| 0.20V | -1.377m | -903.637u | -1.943m |
| 0.30V | -2.007m | -1.319m | -2.832m |

| | | | |
|-------|----------|----------|----------|
| 0.40V | -2.614m | -1.710m | -3.702m |
| 0.50V | -3.192m | -2.079m | -4.537m |
| 0.60V | -3.738m | -2.423m | -5.336m |
| 0.70V | -4.253m | -2.742m | -6.096m |
| 0.80V | -4.736m | -3.037m | -6.817m |
| 0.90V | -5.185m | -3.305m | -7.499m |
| 1.00V | -5.600m | -3.547m | -8.139m |
| 1.10V | -5.980m | -3.762m | -8.737m |
| 1.20V | -6.324m | -3.948m | -9.292m |
| 1.30V | -6.631m | -17.709m | -9.802m |
| 1.40V | -29.730m | -18.279m | -10.265m |
| 1.50V | -30.749m | -18.747m | -45.983m |
| 1.60V | -31.630m | -19.131m | -47.620m |
| 1.70V | -32.393m | -19.454m | -49.086m |
| 1.80V | -33.055m | -19.730m | -50.392m |
| 1.90V | -33.632m | -19.973m | -51.551m |
| 2.00V | -34.135m | -20.188m | -52.571m |
| 2.10V | -34.575m | -20.381m | -53.463m |
| 2.20V | -34.960m | -20.556m | -54.240m |
| 2.30V | -35.302m | -20.715m | -54.917m |
| 2.40V | -35.608m | -20.861m | -55.510m |
| 2.50V | -35.884m | -20.997m | -56.035m |
| 2.60V | -36.137m | -21.123m | -56.505m |
| 2.70V | -36.370m | -21.241m | -56.932m |
| 2.80V | -36.586m | -21.352m | -57.322m |
| 2.90V | -36.788m | -21.457m | -57.683m |
| 3.00V | -36.978m | -21.556m | -58.019m |
| 3.10V | -37.157m | -21.650m | -58.334m |
| 3.20V | -37.327m | -21.741m | -58.631m |
| 3.30V | -37.489m | -21.827m | -58.913m |
| 3.40V | -37.643m | -21.909m | -59.181m |
| 3.50V | -37.791m | -21.989m | -59.436m |
| 3.60V | -37.933m | -22.067m | -59.681m |
| 3.70V | -38.070m | -22.143m | -59.916m |
| 3.80V | -38.202m | -22.216m | -60.142m |
| 3.90V | -38.332m | -22.284m | -60.361m |
| 4.00V | -38.460m | -22.352m | -60.573m |
| 4.10V | -38.590m | -22.420m | -60.780m |
| 4.20V | -38.714m | -22.490m | -60.986m |
| 4.30V | -38.828m | -22.561m | -61.194m |
| 4.40V | -38.949m | -22.635m | -61.406m |
| 4.50V | -39.076m | -22.713m | -61.623m |
| 4.60V | -39.211m | -22.798m | -61.819m |
| 4.70V | -39.357m | -22.892m | -62.024m |
| 4.80V | -39.516m | -22.997m | -62.254m |
| 4.90V | -39.693m | -23.116m | -62.506m |
| 5.00V | -39.893m | -23.253m | -62.785m |
| 5.10V | -40.121m | -23.411m | -63.098m |
| 5.20V | -40.384m | -23.595m | -63.453m |
| 5.30V | -40.689m | -23.801m | -63.860m |
| 5.40V | -41.043m | -24.032m | -64.330m |
| 5.50V | -41.444m | -24.288m | -64.874m |
| 5.60V | -41.886m | -24.570m | -65.505m |
| 5.70V | -42.370m | -24.880m | -66.214m |
| 5.80V | -42.899m | -25.217m | -66.983m |

| | | | |
|-------------|-----------|-----------|-----------|
| 5.90V | -43.473m | -25.585m | -67.815m |
| 6.00V | -44.095m | -25.983m | -68.711m |
| 6.10V | -44.769m | -26.415m | -69.678m |
| 6.20V | -45.498m | -26.884m | -70.721m |
| 6.30V | -46.287m | -27.390m | -71.848m |
| 6.40V | -47.140m | -27.929m | -73.065m |
| 6.50V | -48.049m | -28.487m | -74.374m |
| 6.60V | -48.990m | -29.080m | -75.748m |
| | | | |
| [GND_clamp] | | | |
| | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | -1.875 | -1.074 | -2.155 |
| -3.20V | -1.793 | -1.029 | -2.059 |
| -3.10V | -1.711 | -983.765m | -1.963 |
| -2.90V | -1.548 | -893.931m | -1.771 |
| -2.80V | -1.466 | -849.071m | -1.675 |
| -2.70V | -1.385 | -804.256m | -1.579 |
| -2.60V | -1.303 | -759.489m | -1.483 |
| -2.50V | -1.221 | -714.777m | -1.388 |
| -2.40V | -1.140 | -670.127m | -1.292 |
| -2.30V | -1.059 | -625.548m | -1.197 |
| -2.20V | -977.735m | -581.048m | -1.102 |
| -2.10V | -896.773m | -536.642m | -1.007 |
| -1.90V | -735.446m | -448.177m | -817.634m |
| -1.80V | -655.171m | -404.164m | -723.409m |
| -1.70V | -575.242m | -360.342m | -629.587m |
| -1.60V | -495.760m | -316.758m | -536.295m |
| -1.50V | -416.878m | -273.482m | -443.730m |
| -1.40V | -338.839m | -230.618m | -352.222m |
| -1.30V | -262.067m | -188.327m | -262.384m |
| -1.20V | -187.395m | -146.891m | -175.533m |
| -1.10V | -116.756m | -106.839m | -95.231m |
| -0.90V | -16.024m | -37.029m | -6.612m |
| -0.80V | -2.254m | -14.319m | -2.370m |
| -0.70V | -476.015u | -2.883m | -845.181u |
| -0.60V | -85.877u | -295.354u | -147.930u |
| -0.50V | -8.033u | -33.637u | -9.999u |
| -0.40V | -432.304n | -3.576u | -310.975n |
| -0.30V | -20.874n | -340.944n | -8.593n |
| -0.20V | -964.564p | -30.895n | -258.649p |
| -0.10V | -72.583p | -2.560n | -43.910p |
| 0.00V | -33.685p | -210.508p | -34.610p |
| 0.10V | -27.665p | -30.628p | -29.748p |
| 0.20V | -22.754p | 13.546p | -25.110p |
| 0.30V | -18.303p | 48.356p | -20.906p |
| 0.40V | -14.129p | 81.869p | -16.971p |
| 0.50V | -9.979p | 114.849p | -13.050p |
| 0.60V | -5.833p | 147.499p | -9.130p |
| 0.70V | -1.689p | 179.924p | -5.210p |
| 0.80V | 2.454p | 212.188p | -1.291p |
| 0.90V | 6.596p | 244.335p | 2.628p |
| 1.10V | 14.877p | 308.388p | 10.466p |
| 1.20V | 19.017p | 340.335p | 14.384p |

| | | | |
|-------|----------|----------|---------|
| 1.30V | 23.157p | 372.250p | 18.302p |
| 1.40V | 27.297p | 404.143p | 22.221p |
| 1.50V | 31.436p | 436.027p | 26.139p |
| 1.60V | 35.576p | 467.910p | 30.057p |
| 1.70V | 39.715p | 499.805p | 33.974p |
| 1.80V | 43.855p | 531.722p | 37.892p |
| 1.90V | 47.995p | 563.675p | 41.810p |
| 2.10V | 56.277p | 627.761p | 49.646p |
| 2.20V | 60.418p | 659.933p | 53.564p |
| 2.30V | 64.561p | 692.106p | 57.482p |
| 2.40V | 68.706p | 723.142p | 61.400p |
| 2.50V | 72.847p | 751.973p | 65.319p |
| 2.60V | 76.869p | 780.264p | 69.237p |
| 2.70V | 80.074p | 808.442p | 73.156p |
| 2.80V | 82.499p | 835.513p | 77.065p |
| 2.90V | 84.837p | 860.391p | 80.794p |
| 3.10V | 89.018p | 1.265n | 86.195p |
| 3.20V | 89.573p | 1.305n | 88.344p |
| 3.30V | 103.108p | 1.593n | 90.478p |

|
[POWER_clamp]
|

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -33.685p | -340.944n | -20.906p |
| 3.40V | -72.583p | -3.576u | -25.110p |
| 3.50V | -964.564p | -33.637u | -29.748p |
| 3.60V | -20.874n | -295.354u | -34.610p |
| 3.70V | -432.304n | -2.883m | -43.910p |
| 3.80V | -8.033u | -14.319m | -258.649p |
| 3.90V | -85.877u | -37.029m | -8.593n |
| 4.10V | -2.254m | -106.839m | -9.999u |
| 4.20V | -16.024m | -146.891m | -147.930u |
| 4.30V | -55.636m | -188.327m | -845.181u |
| 4.40V | -116.756m | -230.618m | -2.370m |
| 4.50V | -187.395m | -273.482m | -6.612m |
| 4.60V | -262.067m | -316.758m | -33.199m |
| 4.70V | -338.839m | -360.342m | -95.231m |
| 4.80V | -416.878m | -404.164m | -175.533m |
| 4.90V | -495.760m | -448.177m | -262.384m |
| 5.10V | -655.171m | -536.642m | -443.730m |
| 5.20V | -735.446m | -581.048m | -536.295m |
| 5.30V | -815.997m | -625.548m | -629.587m |
| 5.40V | -896.773m | -670.127m | -723.409m |
| 5.50V | -977.735m | -714.777m | -817.634m |
| 5.60V | -1.059 | -759.489m | -912.174m |
| 5.70V | -1.140 | -804.256m | -1.007 |
| 5.80V | -1.221 | -849.071m | -1.102 |
| 5.90V | -1.303 | -893.931m | -1.197 |
| 6.10V | -1.466 | -983.765m | -1.388 |
| 6.20V | -1.548 | -1.029 | -1.483 |
| 6.30V | -1.630 | -1.074 | -1.579 |
| 6.40V | -1.711 | -1.119 | -1.675 |
| 6.50V | -1.793 | -1.164 | -1.771 |
| 6.60V | -1.875 | -1.209 | -1.867 |

```

|
[Ramp]
|Voltage          I (typ)      I (min)      I (max)
|
dV/dt_f          2.04/136.004p 1.86/237.542p 2.23/85.504p
|
dV/dt_r          2.05/194.744p 1.86/343.805p 2.23/118.850p
R_load=10000ohms
| R_load was connected to ground for Ramp_up test and power for Ramp_dn test
|
|End model
[Model]          ipad5i_io          | ""
Model_type       I/O
Vinl = 0.8
Vinh = 2
| variable       typ          min          max
C_comp           4.44p          3.89p          4.56p
| variable       typ          min          max
[Temperature Range] 40.0          0.0          120.0
| variable       typ          min          max
[Voltage Range]   3.30V          3.00V          3.60V
|
[Pulldown]
| pulldown in the table = pulldown subtract gnd_clamp
|Voltage          I (typ)      I (min)      I (max)
|
-3.30V           -142.303u    -76.239u    -215.182u
-3.20V           -149.700u    -80.226u    -226.432u
-3.10V           -157.861u    -84.616u    -238.866u
-3.00V           -166.908u    -89.472u    -252.678u
-2.90V           -176.992u    -94.869u    -268.107u
-2.80V           -188.295u    -100.900u   -285.446u
-2.70V           -201.049u    -107.679u   -305.068u
-2.60V           -215.545u    -115.349u   -327.446u
-2.50V           -232.155u    -124.094u   -353.191u
-2.40V           -251.367u    -134.145u   -383.107u
-2.30V           -273.825u    -145.808u   -418.273u
-2.20V           -300.403u    -159.488u   -460.167u
-2.10V           -332.314u    -175.737u   -510.874u
-2.00V           -371.286u    -195.318u   -573.418u
-1.90V           -419.868u    -219.325u   -652.360u
-1.80V           -481.968u    -249.369u   -754.892u
-1.70V           -563.882u    -287.925u   -893.013u
-1.60V           -676.382u    -338.973u   -1.088m
-1.50V           -839.410u    -409.300u   -1.383m
-1.40V           -1.094m      -511.367u   -1.873m
-1.30V           -1.537m      -670.350u   -2.819m
-1.20V           -2.451m      -943.845u   -5.162m
-1.10V           -4.857m      -1.486m     -12.214m
-1.00V           -10.606m     -2.746m     -20.764m
-0.90V           -14.267m     -5.259m     -21.749m
-0.80V           -13.851m     -7.108m     -20.142m
-0.70V           -12.481m     -7.168m     -18.211m
-0.60V           -10.883m     -6.348m     -15.981m
-0.50V           -9.156m      -5.339m     -13.503m

```

| | | | |
|--------|---------|---------|----------|
| -0.40V | -7.378m | -4.288m | -10.922m |
| -0.30V | -5.572m | -3.224m | -8.282m |
| -0.20V | -3.741m | -2.154m | -5.584m |
| -0.10V | -1.885m | -1.080m | -2.825m |
| 0.00V | 1.898p | 1.419p | 1.871p |
| 0.10V | 1.857m | 1.057m | 2.800m |
| 0.20V | 3.630m | 2.064m | 5.482m |
| 0.30V | 5.323m | 3.023m | 8.052m |
| 0.40V | 6.936m | 3.935m | 10.508m |
| 0.50V | 8.467m | 4.798m | 12.849m |
| 0.60V | 9.915m | 5.611m | 15.073m |
| 0.70V | 11.275m | 6.371m | 17.176m |
| 0.80V | 12.546m | 7.078m | 19.155m |
| 0.90V | 13.723m | 7.726m | 21.011m |
| 1.00V | 36.925m | 20.745m | 56.704m |
| 1.10V | 39.391m | 22.074m | 60.708m |
| 1.20V | 41.612m | 23.244m | 64.383m |
| 1.30V | 43.585m | 24.247m | 67.726m |
| 1.40V | 45.305m | 25.079m | 70.735m |
| 1.50V | 46.773m | 25.741m | 73.414m |
| 1.60V | 47.997m | 26.251m | 75.766m |
| 1.70V | 48.985m | 26.633m | 77.783m |
| 1.80V | 49.733m | 26.905m | 79.441m |
| 1.90V | 50.257m | 27.092m | 80.724m |
| 2.00V | 50.612m | 27.223m | 81.651m |
| 2.10V | 50.858m | 27.321m | 82.294m |
| 2.20V | 51.040m | 27.399m | 82.744m |
| 2.30V | 51.182m | 27.465m | 83.074m |
| 2.40V | 51.302m | 27.522m | 83.332m |
| 2.50V | 51.405m | 27.572m | 83.543m |
| 2.60V | 51.497m | 27.618m | 83.724m |
| 2.70V | 51.581m | 27.658m | 83.884m |
| 2.80V | 51.658m | 27.683m | 84.030m |
| 2.90V | 51.729m | 27.643m | 84.165m |
| 3.00V | 51.781m | 27.704m | 84.290m |
| 3.10V | 51.640m | 28.793m | 84.409m |
| 3.20V | 50.282m | 30.065m | 84.519m |
| 3.30V | 50.273m | 31.174m | 84.574m |
| 3.40V | 51.871m | 32.200m | 83.365m |
| 3.50V | 55.121m | 33.153m | 80.948m |
| 3.60V | 57.228m | 34.039m | 81.423m |
| 3.70V | 58.838m | 34.872m | 83.424m |
| 3.80V | 60.328m | 35.687m | 87.158m |
| 3.90V | 61.725m | 36.498m | 91.951m |
| 4.00V | 63.035m | 37.296m | 94.228m |
| 4.10V | 64.321m | 38.059m | 96.276m |
| 4.20V | 65.602m | 38.767m | 98.249m |
| 4.30V | 66.844m | 39.409m | 100.060m |
| 4.40V | 68.012m | 39.982m | 101.853m |
| 4.50V | 69.088m | 40.478m | 103.638m |
| 4.60V | 70.072m | 40.871m | 105.361m |
| 4.70V | 70.973m | 41.102m | 106.982m |
| 4.80V | 71.794m | 40.996m | 108.484m |
| 4.90V | 72.529m | 40.118m | 109.875m |
| 5.00V | 73.152m | 39.453m | 111.168m |

| | | | |
|---|----------|----------|----------|
| 5.10V | 73.605m | 39.379m | 112.374m |
| 5.20V | 73.737m | 39.432m | 113.492m |
| 5.30V | 72.999m | 39.492m | 114.510m |
| 5.40V | 71.115m | 39.551m | 115.392m |
| 5.50V | 70.512m | 39.608m | 116.061m |
| 5.60V | 70.457m | 39.661m | 116.301m |
| 5.70V | 70.511m | 39.713m | 114.763m |
| 5.80V | 70.586m | 39.762m | 111.545m |
| 5.90V | 70.667m | 39.809m | 110.833m |
| 6.00V | 70.749m | 39.855m | 110.689m |
| 6.10V | 70.831m | 39.899m | 110.716m |
| 6.20V | 70.911m | 39.944m | 110.796m |
| 6.30V | 70.989m | 39.988m | 110.897m |
| 6.40V | 71.068m | 40.034m | 111.009m |
| 6.50V | 71.148m | 40.083m | 111.127m |
| 6.60V | 71.230m | 40.136m | 111.250m |
| | | | |
| [Pullup] | | | |
| pullup in the table = pullup subtract power_clamp | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | 357.190u | 184.381u | 591.381u |
| -3.20V | 356.622u | 184.121u | 590.188u |
| -3.10V | 356.193u | 183.920u | 589.287u |
| -3.00V | 355.875u | 183.765u | 588.617u |
| -2.90V | 355.641u | 183.645u | 588.129u |
| -2.80V | 355.468u | 183.550u | 587.779u |
| -2.70V | 355.340u | 183.472u | 587.528u |
| -2.60V | 355.242u | 183.405u | 587.349u |
| -2.50V | 355.163u | 183.345u | 587.218u |
| -2.40V | 355.097u | 183.288u | 587.118u |
| -2.30V | 355.036u | 183.233u | 587.036u |
| -2.20V | 354.978u | 183.177u | 586.964u |
| -2.10V | 354.920u | 183.119u | 586.896u |
| -2.00V | 354.860u | 183.060u | 586.829u |
| -1.90V | 354.799u | 182.997u | 586.762u |
| -1.80V | 354.734u | 182.931u | 586.692u |
| -1.70V | 354.666u | 182.862u | 586.621u |
| -1.60V | 354.595u | 182.788u | 586.574u |
| -1.50V | 354.559u | 182.711u | 597.934u |
| -1.40V | 764.198u | 182.650u | 1.674m |
| -1.30V | 10.536m | 460.815u | 14.880m |
| -1.20V | 9.648m | 6.455m | 13.612m |
| -1.10V | 8.683m | 5.841m | 12.257m |
| -1.00V | 7.701m | 5.195m | 10.870m |
| -0.90V | 6.737m | 4.554m | 9.492m |
| -0.80V | 5.827m | 3.944m | 8.173m |
| -0.70V | 5.004m | 3.383m | 6.972m |
| -0.60V | 4.262m | 2.870m | 5.921m |
| -0.50V | 3.549m | 2.382m | 4.953m |
| -0.40V | 2.841m | 1.902m | 3.978m |
| -0.30V | 2.134m | 1.426m | 2.985m |
| -0.20V | 1.434m | 951.249u | 2.002m |
| -0.10V | 721.882u | 477.946u | 1.005m |
| -0.00V | 23.094p | 36.805p | 24.891p |

| | | | |
|-------|-----------|-----------|-----------|
| 0.10V | -708.040u | -465.659u | -990.277u |
| 0.20V | -1.374m | -903.549u | -1.941m |
| 0.30V | -2.007m | -1.319m | -2.832m |
| 0.40V | -2.614m | -1.710m | -3.702m |
| 0.50V | -3.192m | -2.079m | -4.537m |
| 0.60V | -3.738m | -2.423m | -5.336m |
| 0.70V | -4.253m | -2.742m | -6.096m |
| 0.80V | -4.736m | -3.037m | -6.817m |
| 0.90V | -5.185m | -3.305m | -7.499m |
| 1.00V | -5.600m | -3.547m | -8.139m |
| 1.10V | -5.980m | -3.762m | -8.737m |
| 1.20V | -6.324m | -3.948m | -9.292m |
| 1.30V | -6.631m | -17.709m | -9.802m |
| 1.40V | -29.730m | -18.279m | -10.265m |
| 1.50V | -30.749m | -18.747m | -45.983m |
| 1.60V | -31.630m | -19.131m | -47.620m |
| 1.70V | -32.393m | -19.454m | -49.086m |
| 1.80V | -33.055m | -19.730m | -50.392m |
| 1.90V | -33.632m | -19.973m | -51.551m |
| 2.00V | -34.135m | -20.188m | -52.571m |
| 2.10V | -34.575m | -20.381m | -53.463m |
| 2.20V | -34.960m | -20.556m | -54.240m |
| 2.30V | -35.302m | -20.715m | -54.917m |
| 2.40V | -35.608m | -20.861m | -55.510m |
| 2.50V | -35.884m | -20.997m | -56.035m |
| 2.60V | -36.137m | -21.123m | -56.505m |
| 2.70V | -36.370m | -21.241m | -56.932m |
| 2.80V | -36.586m | -21.352m | -57.322m |
| 2.90V | -36.788m | -21.457m | -57.683m |
| 3.00V | -36.978m | -21.556m | -58.019m |
| 3.10V | -37.157m | -21.650m | -58.334m |
| 3.20V | -37.327m | -21.741m | -58.631m |
| 3.30V | -37.489m | -21.827m | -58.913m |
| 3.40V | -37.643m | -21.909m | -59.181m |
| 3.50V | -37.791m | -21.989m | -59.436m |
| 3.60V | -37.933m | -22.067m | -59.681m |
| 3.70V | -38.070m | -22.143m | -59.916m |
| 3.80V | -38.202m | -22.216m | -60.142m |
| 3.90V | -38.332m | -22.284m | -60.361m |
| 4.00V | -38.460m | -22.352m | -60.573m |
| 4.10V | -38.590m | -22.420m | -60.780m |
| 4.20V | -38.714m | -22.490m | -60.986m |
| 4.30V | -38.828m | -22.561m | -61.194m |
| 4.40V | -38.949m | -22.635m | -61.406m |
| 4.50V | -39.076m | -22.713m | -61.623m |
| 4.60V | -39.211m | -22.798m | -61.819m |
| 4.70V | -39.357m | -22.892m | -62.024m |
| 4.80V | -39.516m | -22.997m | -62.254m |
| 4.90V | -39.693m | -23.116m | -62.506m |
| 5.00V | -39.893m | -23.253m | -62.785m |
| 5.10V | -40.121m | -23.411m | -63.098m |
| 5.20V | -40.384m | -23.595m | -63.453m |
| 5.30V | -40.689m | -23.801m | -63.860m |
| 5.40V | -41.043m | -24.032m | -64.330m |
| 5.50V | -41.444m | -24.288m | -64.874m |

| | | | |
|-------|----------|----------|----------|
| 5.60V | -41.886m | -24.570m | -65.505m |
| 5.70V | -42.370m | -24.880m | -66.214m |
| 5.80V | -42.899m | -25.217m | -66.983m |
| 5.90V | -43.473m | -25.585m | -67.815m |
| 6.00V | -44.095m | -25.983m | -68.711m |
| 6.10V | -44.769m | -26.415m | -69.678m |
| 6.20V | -45.498m | -26.884m | -70.721m |
| 6.30V | -46.287m | -27.390m | -71.848m |
| 6.40V | -47.140m | -27.929m | -73.065m |
| 6.50V | -48.049m | -28.487m | -74.374m |
| 6.60V | -48.990m | -29.080m | -75.748m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -1.875 | -1.074 | -2.155 |
| -3.20V | -1.793 | -1.029 | -2.059 |
| -3.10V | -1.711 | -983.769m | -1.963 |
| -2.90V | -1.548 | -893.934m | -1.771 |
| -2.80V | -1.466 | -849.075m | -1.675 |
| -2.70V | -1.385 | -804.259m | -1.579 |
| -2.60V | -1.303 | -759.493m | -1.483 |
| -2.50V | -1.221 | -714.781m | -1.388 |
| -2.40V | -1.140 | -670.131m | -1.292 |
| -2.30V | -1.059 | -625.551m | -1.197 |
| -2.20V | -977.740m | -581.052m | -1.102 |
| -2.10V | -896.779m | -536.646m | -1.007 |
| -1.90V | -735.452m | -448.180m | -817.639m |
| -1.80V | -655.177m | -404.167m | -723.415m |
| -1.70V | -575.247m | -360.345m | -629.593m |
| -1.60V | -495.766m | -316.761m | -536.300m |
| -1.50V | -416.883m | -273.485m | -443.735m |
| -1.40V | -338.844m | -230.621m | -352.227m |
| -1.30V | -262.072m | -188.330m | -262.388m |
| -1.20V | -187.399m | -146.893m | -175.537m |
| -1.10V | -116.760m | -106.842m | -95.235m |
| -0.90V | -16.027m | -37.031m | -6.614m |
| -0.80V | -2.255m | -14.321m | -2.370m |
| -0.70V | -476.049u | -2.884m | -845.183u |
| -0.60V | -85.878u | -295.501u | -147.930u |
| -0.50V | -8.033u | -33.646u | -9.999u |
| -0.40V | -432.308n | -3.576u | -310.979n |
| -0.30V | -20.878n | -340.971n | -8.597n |
| -0.20V | -968.068p | -30.900n | -262.449p |
| -0.10V | -75.987p | -2.564n | -47.610p |
| 0.00V | -36.990p | -214.009p | -38.210p |
| 0.10V | -30.869p | -34.018p | -33.249p |
| 0.20V | -25.858p | 10.263p | -28.510p |
| 0.30V | -21.307p | 45.181p | -24.206p |
| 0.40V | -17.033p | 78.801p | -20.171p |
| 0.50V | -12.783p | 111.888p | -16.150p |
| 0.60V | -8.537p | 144.645p | -12.130p |
| 0.70V | -4.293p | 177.177p | -8.110p |
| 0.80V | -49.635f | 209.548p | -4.091p |

| | | | |
|-------|----------|----------|----------|
| 0.90V | 4.192p | 241.802p | -71.907f |
| 1.10V | 12.674p | 306.070p | 7.965p |
| 1.20V | 16.914p | 338.124p | 11.984p |
| 1.30V | 21.154p | 370.146p | 16.002p |
| 1.40V | 25.393p | 402.147p | 20.020p |
| 1.50V | 29.633p | 434.138p | 24.038p |
| 1.60V | -31.788p | 466.129p | 28.056p |
| 1.70V | 38.112p | 498.131p | -33.622p |
| 1.80V | 42.352p | 530.156p | 36.092p |
| 1.90V | 46.592p | 562.217p | 40.110p |
| 2.10V | 55.074p | 626.519p | 48.146p |
| 2.20V | 59.316p | 658.799p | 52.164p |
| 2.30V | 63.559p | 691.080p | 56.182p |
| 2.40V | 67.803p | 722.224p | 60.200p |
| 2.50V | 72.044p | 751.129p | 64.219p |
| 2.60V | 76.162p | 779.443p | 68.237p |
| 2.70V | 79.409p | 807.731p | 72.256p |
| 2.80V | 81.838p | 835.534p | 76.265p |
| 2.90V | 84.178p | 864.770p | 80.080p |
| 3.10V | 88.733p | 1.234n | 85.501p |
| 3.20V | 90.025p | 1.247n | 87.652p |
| 3.30V | 96.129p | 1.274n | 89.793p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| | | | |
| 3.30V | -36.990p | -340.971n | -24.206p |
| 3.40V | -75.987p | -3.576u | -28.510p |
| 3.50V | -968.068p | -33.646u | -33.249p |
| 3.60V | -20.878n | -295.501u | -38.210p |
| 3.70V | -432.308n | -2.884m | -47.610p |
| 3.80V | -8.033u | -14.321m | -262.449p |
| 3.90V | -85.878u | -37.031m | -8.597n |
| 4.10V | -2.255m | -106.842m | -9.999u |
| 4.20V | -16.027m | -146.893m | -147.930u |
| 4.30V | -55.640m | -188.330m | -845.183u |
| 4.40V | -116.760m | -230.621m | -2.370m |
| 4.50V | -187.399m | -273.485m | -6.614m |
| 4.60V | -262.072m | -316.761m | -33.203m |
| 4.70V | -338.844m | -360.345m | -95.235m |
| 4.80V | -416.883m | -404.167m | -175.537m |
| 4.90V | -495.766m | -448.180m | -262.388m |
| 5.10V | -655.177m | -536.646m | -443.735m |
| 5.20V | -735.452m | -581.052m | -536.300m |
| 5.30V | -816.003m | -625.551m | -629.593m |
| 5.40V | -896.779m | -670.131m | -723.415m |
| 5.50V | -977.740m | -714.781m | -817.639m |
| 5.60V | -1.059 | -759.493m | -912.179m |
| 5.70V | -1.140 | -804.259m | -1.007 |
| 5.80V | -1.221 | -849.075m | -1.102 |
| 5.90V | -1.303 | -893.934m | -1.197 |
| 6.10V | -1.466 | -983.769m | -1.388 |
| 6.20V | -1.548 | -1.029 | -1.483 |
| 6.30V | -1.630 | -1.074 | -1.579 |

| | | | |
|-------|--------|--------|--------|
| 6.40V | -1.711 | -1.119 | -1.675 |
| 6.50V | -1.793 | -1.164 | -1.771 |
| 6.60V | -1.875 | -1.209 | -1.867 |

```

|
[Ramp]
|Voltage          I (typ)          I (min)          I (max)
|
dV/dt_f          2.01/129.093p 1.83/223.594p 2.20/79.668p
|
dV/dt_r          2.02/200.492p 1.83/352.515p 2.20/122.321p
R_load=10000ohms
| R_load was connected to ground for Ramp_up test and power for Ramp_dn test
|
|End model
[Model]          ipad5v_io          | ""
Model_type       I/O
Vinl = 0.8
Vinh = 2
| variable       typ          min          max
C_comp          1.96p          1.87p          2.06p
| variable       typ          min          max
[Temperature Range] 40.0          0.0          120.0
| variable       typ          min          max
[Voltage Range]   3.30V          3.00V          3.60V
|
|
[Pulldown]
| pulldown in the table = pulldown subtract gnd_clamp
|Voltage          I (typ)          I (min)          I (max)
|
-3.30V          -142.303u       -76.239u       -215.182u
-3.20V          -149.700u       -80.226u       -226.432u
-3.10V          -157.861u       -84.616u       -238.866u
-3.00V          -166.908u       -89.472u       -252.678u
-2.90V          -176.992u       -94.869u       -268.107u
-2.80V          -188.295u       -100.900u      -285.446u
-2.70V          -201.049u       -107.679u      -305.068u
-2.60V          -215.545u       -115.349u      -327.446u
-2.50V          -232.155u       -124.094u      -353.191u
-2.40V          -251.367u       -134.145u      -383.107u
-2.30V          -273.825u       -145.808u      -418.273u
-2.20V          -300.403u       -159.488u      -460.167u
-2.10V          -332.314u       -175.737u      -510.874u
-2.00V          -371.286u       -195.318u      -573.418u
-1.90V          -419.868u       -219.325u      -652.360u
-1.80V          -481.968u       -249.369u      -754.892u
-1.70V          -563.882u       -287.925u      -893.013u
-1.60V          -676.382u       -338.973u      -1.088m
-1.50V          -839.410u       -409.300u      -1.383m
-1.40V          -1.094m         -511.367u      -1.873m
-1.30V          -1.537m         -670.350u      -2.819m
-1.20V          -2.451m         -943.845u      -5.162m
-1.10V          -4.857m         -1.486m         -12.214m
-1.00V          -10.606m        -2.746m         -20.764m
-0.90V          -14.267m        -5.259m         -21.749m
-0.80V          -13.851m        -7.108m         -20.142m

```

| | | | |
|--------|----------|---------|----------|
| -0.70V | -12.481m | -7.168m | -18.211m |
| -0.60V | -10.883m | -6.348m | -15.981m |
| -0.50V | -9.156m | -5.339m | -13.503m |
| -0.40V | -7.378m | -4.288m | -10.922m |
| -0.30V | -5.572m | -3.224m | -8.282m |
| -0.20V | -3.741m | -2.154m | -5.584m |
| -0.10V | -1.885m | -1.080m | -2.825m |
| 0.00V | 1.898p | 1.419p | 1.871p |
| 0.10V | 1.857m | 1.057m | 2.800m |
| 0.20V | 3.630m | 2.064m | 5.482m |
| 0.30V | 5.323m | 3.023m | 8.052m |
| 0.40V | 6.936m | 3.935m | 10.508m |
| 0.50V | 8.467m | 4.798m | 12.849m |
| 0.60V | 9.915m | 5.611m | 15.073m |
| 0.70V | 11.275m | 6.371m | 17.176m |
| 0.80V | 12.546m | 7.078m | 19.155m |
| 0.90V | 13.723m | 7.726m | 21.011m |
| 1.00V | 36.925m | 20.745m | 56.704m |
| 1.10V | 39.391m | 22.074m | 60.708m |
| 1.20V | 41.612m | 23.244m | 64.383m |
| 1.30V | 43.585m | 24.247m | 67.726m |
| 1.40V | 45.305m | 25.079m | 70.735m |
| 1.50V | 46.773m | 25.741m | 73.414m |
| 1.60V | 47.997m | 26.251m | 75.766m |
| 1.70V | 48.985m | 26.633m | 77.783m |
| 1.80V | 49.733m | 26.905m | 79.441m |
| 1.90V | 50.257m | 27.092m | 80.724m |
| 2.00V | 50.612m | 27.223m | 81.651m |
| 2.10V | 50.858m | 27.321m | 82.294m |
| 2.20V | 51.040m | 27.399m | 82.744m |
| 2.30V | 51.182m | 27.465m | 83.074m |
| 2.40V | 51.302m | 27.522m | 83.332m |
| 2.50V | 51.405m | 27.572m | 83.543m |
| 2.60V | 51.497m | 27.618m | 83.724m |
| 2.70V | 51.581m | 27.657m | 83.884m |
| 2.80V | 51.658m | 27.674m | 84.030m |
| 2.90V | 51.727m | 27.587m | 84.165m |
| 3.00V | 51.757m | 27.577m | 84.290m |
| 3.10V | 51.229m | 28.700m | 84.409m |
| 3.20V | 49.190m | 30.042m | 84.515m |
| 3.30V | 49.441m | 31.171m | 84.491m |
| 3.40V | 51.034m | 32.199m | 81.077m |
| 3.50V | 54.363m | 33.153m | 79.736m |
| 3.60V | 57.165m | 34.039m | 80.276m |
| 3.70V | 58.834m | 34.872m | 82.430m |
| 3.80V | 60.328m | 35.686m | 85.482m |
| 3.90V | 61.725m | 36.495m | 91.743m |
| 4.00V | 63.035m | 37.291m | 94.219m |
| 4.10V | 64.319m | 38.051m | 96.276m |
| 4.20V | 65.598m | 38.755m | 98.249m |
| 4.30V | 66.836m | 39.394m | 100.059m |
| 4.40V | 67.999m | 39.962m | 101.849m |
| 4.50V | 69.069m | 40.453m | 103.628m |
| 4.60V | 70.046m | 40.840m | 105.345m |
| 4.70V | 70.938m | 41.065m | 106.956m |

| | | | |
|-------|---------|---------|----------|
| 4.80V | 71.751m | 40.952m | 108.448m |
| 4.90V | 72.476m | 40.067m | 109.826m |
| 5.00V | 73.089m | 39.395m | 111.106m |
| 5.10V | 73.531m | 39.313m | 112.297m |
| 5.20V | 73.651m | 39.358m | 113.400m |
| 5.30V | 72.901m | 39.410m | 114.401m |
| 5.40V | 71.005m | 39.460m | 115.267m |
| 5.50V | 70.389m | 39.508m | 115.917m |
| 5.60V | 70.321m | 39.552m | 116.139m |
| 5.70V | 70.361m | 39.595m | 114.582m |
| 5.80V | 70.422m | 39.634m | 111.344m |
| 5.90V | 70.489m | 39.672m | 110.612m |
| 6.00V | 70.557m | 39.708m | 110.449m |
| 6.10V | 70.624m | 39.743m | 110.455m |
| 6.20V | 70.690m | 39.777m | 110.515m |
| 6.30V | 70.753m | 39.812m | 110.595m |
| 6.40V | 70.817m | 39.848m | 110.686m |
| 6.50V | 70.881m | 39.886m | 110.783m |
| 6.60V | 70.949m | 39.929m | 110.885m |

| | | | |
|---|----------|----------|----------|
| | | | |
| [Pullup] | | | |
| pullup in the table = pullup subtract power_clamp | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | 75.797u | 7.914u | 161.477u |
| -3.20V | 90.464u | 17.699u | 181.779u |
| -3.10V | 105.160u | 27.445u | 202.314u |
| -3.00V | 119.836u | 37.119u | 223.007u |
| -2.90V | 134.451u | 46.694u | 243.785u |
| -2.80V | 148.966u | 56.144u | 264.581u |
| -2.70V | 163.342u | 65.447u | 285.332u |
| -2.60V | 177.543u | 74.582u | 305.982u |
| -2.50V | 191.536u | 83.527u | 326.474u |
| -2.40V | 205.285u | 92.262u | 346.757u |
| -2.30V | 218.754u | 100.766u | 366.776u |
| -2.20V | 231.907u | 109.016u | 386.478u |
| -2.10V | 244.706u | 116.988u | 405.807u |
| -2.00V | 257.106u | 124.659u | 424.699u |
| -1.90V | 269.061u | 131.998u | 443.089u |
| -1.80V | 280.519u | 138.978u | 460.899u |
| -1.70V | 291.423u | 145.565u | 478.046u |
| -1.60V | 301.710u | 151.723u | 494.457u |
| -1.50V | 311.348u | 157.417u | 521.406u |
| -1.40V | 729.899u | 162.626u | 1.612m |
| -1.30V | 10.510m | 445.517u | 14.832m |
| -1.20V | 9.629m | 6.444m | 13.576m |
| -1.10V | 8.670m | 5.833m | 12.231m |
| -1.00V | 7.693m | 5.190m | 10.854m |
| -0.90V | 6.732m | 4.551m | 9.483m |
| -0.80V | 5.825m | 3.942m | 8.169m |
| -0.70V | 5.004m | 3.382m | 6.971m |
| -0.60V | 4.261m | 2.869m | 5.921m |
| -0.50V | 3.549m | 2.381m | 4.953m |

| | | | |
|--------|-----------|-----------|-----------|
| -0.40V | 2.841m | 1.902m | 3.978m |
| -0.30V | 2.135m | 1.426m | 2.987m |
| -0.20V | 1.437m | 951.489u | 2.003m |
| -0.10V | 722.340u | 478.341u | 1.005m |
| -0.00V | 22.329p | 36.936p | 24.081p |
| 0.10V | -708.556u | -465.927u | -990.647u |
| 0.20V | -1.377m | -903.637u | -1.943m |
| 0.30V | -2.007m | -1.319m | -2.832m |
| 0.40V | -2.614m | -1.710m | -3.702m |
| 0.50V | -3.192m | -2.079m | -4.537m |
| 0.60V | -3.738m | -2.423m | -5.336m |
| 0.70V | -4.253m | -2.742m | -6.096m |
| 0.80V | -4.736m | -3.037m | -6.817m |
| 0.90V | -5.185m | -3.305m | -7.499m |
| 1.00V | -5.600m | -3.547m | -8.139m |
| 1.10V | -5.980m | -3.762m | -8.737m |
| 1.20V | -6.324m | -3.948m | -9.292m |
| 1.30V | -6.631m | -17.709m | -9.802m |
| 1.40V | -29.730m | -18.279m | -10.265m |
| 1.50V | -30.749m | -18.747m | -45.983m |
| 1.60V | -31.630m | -19.131m | -47.620m |
| 1.70V | -32.393m | -19.454m | -49.086m |
| 1.80V | -33.055m | -19.730m | -50.392m |
| 1.90V | -33.632m | -19.973m | -51.551m |
| 2.00V | -34.135m | -20.188m | -52.571m |
| 2.10V | -34.575m | -20.381m | -53.463m |
| 2.20V | -34.960m | -20.556m | -54.240m |
| 2.30V | -35.302m | -20.715m | -54.917m |
| 2.40V | -35.608m | -20.861m | -55.510m |
| 2.50V | -35.884m | -20.997m | -56.035m |
| 2.60V | -36.137m | -21.123m | -56.505m |
| 2.70V | -36.370m | -21.241m | -56.932m |
| 2.80V | -36.586m | -21.352m | -57.322m |
| 2.90V | -36.788m | -21.457m | -57.683m |
| 3.00V | -36.978m | -21.556m | -58.019m |
| 3.10V | -37.157m | -21.650m | -58.334m |
| 3.20V | -37.327m | -21.741m | -58.631m |
| 3.30V | -37.489m | -21.827m | -58.913m |
| 3.40V | -37.643m | -21.909m | -59.181m |
| 3.50V | -37.791m | -21.989m | -59.436m |
| 3.60V | -37.933m | -22.067m | -59.681m |
| 3.70V | -38.070m | -22.143m | -59.916m |
| 3.80V | -38.202m | -22.216m | -60.142m |
| 3.90V | -38.332m | -22.284m | -60.361m |
| 4.00V | -38.460m | -22.352m | -60.573m |
| 4.10V | -38.590m | -22.420m | -60.780m |
| 4.20V | -38.714m | -22.490m | -60.986m |
| 4.30V | -38.828m | -22.561m | -61.194m |
| 4.40V | -38.949m | -22.635m | -61.406m |
| 4.50V | -39.076m | -22.713m | -61.623m |
| 4.60V | -39.211m | -22.798m | -61.819m |
| 4.70V | -39.357m | -22.892m | -62.024m |
| 4.80V | -39.516m | -22.997m | -62.254m |
| 4.90V | -39.693m | -23.116m | -62.506m |
| 5.00V | -39.893m | -23.253m | -62.785m |

| | | | |
|-------|----------|----------|----------|
| 5.10V | -40.121m | -23.411m | -63.098m |
| 5.20V | -40.384m | -23.595m | -63.453m |
| 5.30V | -40.689m | -23.801m | -63.860m |
| 5.40V | -41.043m | -24.032m | -64.330m |
| 5.50V | -41.444m | -24.288m | -64.874m |
| 5.60V | -41.886m | -24.570m | -65.505m |
| 5.70V | -42.370m | -24.880m | -66.214m |
| 5.80V | -42.899m | -25.217m | -66.983m |
| 5.90V | -43.473m | -25.585m | -67.815m |
| 6.00V | -44.095m | -25.983m | -68.711m |
| 6.10V | -44.769m | -26.415m | -69.678m |
| 6.20V | -45.498m | -26.884m | -70.721m |
| 6.30V | -46.287m | -27.390m | -71.848m |
| 6.40V | -47.140m | -27.929m | -73.065m |
| 6.50V | -48.049m | -28.487m | -74.374m |
| 6.60V | -48.990m | -29.080m | -75.748m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -1.875 | -1.074 | -2.155 |
| -3.20V | -1.793 | -1.029 | -2.059 |
| -3.10V | -1.711 | -983.765m | -1.963 |
| -2.90V | -1.548 | -893.931m | -1.771 |
| -2.80V | -1.466 | -849.071m | -1.675 |
| -2.70V | -1.385 | -804.256m | -1.579 |
| -2.60V | -1.303 | -759.489m | -1.483 |
| -2.50V | -1.221 | -714.777m | -1.388 |
| -2.40V | -1.140 | -670.127m | -1.292 |
| -2.30V | -1.059 | -625.548m | -1.197 |
| -2.20V | -977.735m | -581.048m | -1.102 |
| -2.10V | -896.773m | -536.642m | -1.007 |
| -1.90V | -735.446m | -448.177m | -817.634m |
| -1.80V | -655.171m | -404.164m | -723.409m |
| -1.70V | -575.242m | -360.342m | -629.587m |
| -1.60V | -495.760m | -316.758m | -536.295m |
| -1.50V | -416.878m | -273.482m | -443.730m |
| -1.40V | -338.839m | -230.618m | -352.222m |
| -1.30V | -262.067m | -188.327m | -262.384m |
| -1.20V | -187.395m | -146.891m | -175.533m |
| -1.10V | -116.756m | -106.839m | -95.231m |
| -0.90V | -16.024m | -37.029m | -6.612m |
| -0.80V | -2.254m | -14.319m | -2.370m |
| -0.70V | -476.015u | -2.883m | -845.181u |
| -0.60V | -85.877u | -295.354u | -147.930u |
| -0.50V | -8.033u | -33.637u | -9.999u |
| -0.40V | -432.304n | -3.576u | -310.975n |
| -0.30V | -20.874n | -340.944n | -8.593n |
| -0.20V | -964.564p | -30.895n | -258.649p |
| -0.10V | -72.583p | -2.560n | -43.910p |
| 0.00V | -33.685p | -210.508p | -34.610p |
| 0.10V | -27.665p | -30.628p | -29.748p |
| 0.20V | -22.754p | 13.546p | -25.110p |
| 0.30V | -18.303p | 48.356p | -20.906p |

| | | | |
|-------|----------|----------|----------|
| 0.40V | -14.129p | 81.869p | -16.971p |
| 0.50V | -9.979p | 114.849p | -13.050p |
| 0.60V | -5.833p | 147.499p | -9.130p |
| 0.70V | -1.689p | 179.924p | -5.210p |
| 0.80V | 2.454p | 212.188p | -1.291p |
| 0.90V | 6.596p | 244.335p | 2.628p |
| 1.10V | 14.877p | 308.388p | 10.466p |
| 1.20V | 19.017p | 340.335p | 14.384p |
| 1.30V | 23.157p | 372.250p | 18.302p |
| 1.40V | 27.297p | 404.143p | 22.221p |
| 1.50V | 31.436p | 436.027p | 26.139p |
| 1.60V | 35.576p | 467.910p | 30.057p |
| 1.70V | 39.715p | 499.805p | 33.974p |
| 1.80V | 43.855p | 531.722p | 37.892p |
| 1.90V | 47.995p | 563.675p | 41.810p |
| 2.10V | 56.277p | 627.761p | 49.646p |
| 2.20V | 60.418p | 659.933p | 53.564p |
| 2.30V | 64.561p | 692.106p | 57.482p |
| 2.40V | 68.706p | 723.142p | 61.400p |
| 2.50V | 72.847p | 751.973p | 65.319p |
| 2.60V | 76.869p | 780.264p | 69.237p |
| 2.70V | 80.074p | 808.442p | 73.156p |
| 2.80V | 82.499p | 835.513p | 77.065p |
| 2.90V | 84.837p | 860.391p | 80.794p |
| 3.10V | 89.018p | 1.265n | 86.195p |
| 3.20V | 89.573p | 1.305n | 88.344p |
| 3.30V | 103.108p | 1.593n | 90.478p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -33.685p | -340.944n | -20.906p |
| 3.40V | -72.583p | -3.576u | -25.110p |
| 3.50V | -964.564p | -33.637u | -29.748p |
| 3.60V | -20.874n | -295.354u | -34.610p |
| 3.70V | -432.304n | -2.883m | -43.910p |
| 3.80V | -8.033u | -14.319m | -258.649p |
| 3.90V | -85.877u | -37.029m | -8.593n |
| 4.10V | -2.254m | -106.839m | -9.999u |
| 4.20V | -16.024m | -146.891m | -147.930u |
| 4.30V | -55.636m | -188.327m | -845.181u |
| 4.40V | -116.756m | -230.618m | -2.370m |
| 4.50V | -187.395m | -273.482m | -6.612m |
| 4.60V | -262.067m | -316.758m | -33.199m |
| 4.70V | -338.839m | -360.342m | -95.231m |
| 4.80V | -416.878m | -404.164m | -175.533m |
| 4.90V | -495.760m | -448.177m | -262.384m |
| 5.10V | -655.171m | -536.642m | -443.730m |
| 5.20V | -735.446m | -581.048m | -536.295m |
| 5.30V | -815.997m | -625.548m | -629.587m |
| 5.40V | -896.773m | -670.127m | -723.409m |
| 5.50V | -977.735m | -714.777m | -817.634m |
| 5.60V | -1.059 | -759.489m | -912.174m |
| 5.70V | -1.140 | -804.256m | -1.007 |

| | | | |
|-------|--------|-----------|--------|
| 5.80V | -1.221 | -849.071m | -1.102 |
| 5.90V | -1.303 | -893.931m | -1.197 |
| 6.10V | -1.466 | -983.765m | -1.388 |
| 6.20V | -1.548 | -1.029 | -1.483 |
| 6.30V | -1.630 | -1.074 | -1.579 |
| 6.40V | -1.711 | -1.119 | -1.675 |
| 6.50V | -1.793 | -1.164 | -1.771 |
| 6.60V | -1.875 | -1.209 | -1.867 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|---------------|---------------|---------------|
| dV/dt_f | 2.04/134.002p | 1.86/235.405p | 2.23/85.874p |
| dV/dt_r | 2.05/194.838p | 1.86/341.412p | 2.23/118.822p |

R_load=10000ohms

| R_load was connected to ground for Ramp_up test and power for Ramp_dn test

|

[End model]

[Model] ipada_3st | ""

| Model_type | 3-state | | |
|---------------------|---------|-------|-------|
| variable | typ | min | max |
| C_comp | 2.32p | 2.17p | 2.48p |
| variable | typ | min | max |
| [Temperature Range] | 40.0 | 0.0 | 120.0 |
| variable | typ | min | max |
| [Voltage Range] | 3.30V | 3.00V | 3.60V |

|

[Pulldown]

| pulldown in the table = pulldown subtract gnd_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -157.134u | -99.256u | -219.000u |
| -3.20V | -165.037u | -104.127u | -230.250u |
| -3.10V | -173.749u | -109.479u | -242.685u |
| -3.00V | -183.400u | -115.386u | -256.500u |
| -2.90V | -194.148u | -121.936u | -271.934u |
| -2.80V | -206.189u | -129.240u | -289.286u |
| -2.70V | -219.766u | -137.431u | -308.933u |
| -2.60V | -235.190u | -146.680u | -331.355u |
| -2.50V | -252.856u | -157.199u | -357.176u |
| -2.40V | -273.283u | -169.265u | -387.219u |
| -2.30V | -297.162u | -183.236u | -422.595u |
| -2.20V | -325.427u | -199.590u | -464.837u |
| -2.10V | -359.384u | -218.976u | -516.117u |
| -2.00V | -400.901u | -242.299u | -579.623u |
| -1.90V | -452.750u | -270.851u | -660.217u |
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |

| | | | |
|--------|------------|------------|----------|
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.871e-18 | 18.541e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 64.562m | 22.817m |
| 1.50V | 117.094m | 66.208m | 23.575m |
| 1.60V | 119.708m | 67.513m | 184.138m |
| 1.70V | 121.667m | 68.498m | 187.874m |
| 1.80V | 123.055m | 69.206m | 190.647m |
| 1.90V | 124.020m | 69.710m | 192.621m |
| 2.00V | 124.711m | 70.083m | 194.017m |
| 2.10V | 125.232m | 70.374m | 195.034m |
| 2.20V | 125.650m | 70.612m | 195.815m |
| 2.30V | 126.000m | 70.814m | 196.447m |
| 2.40V | 126.305m | 70.992m | 196.983m |
| 2.50V | 126.577m | 71.151m | 197.453m |
| 2.60V | 126.823m | 71.296m | 197.876m |
| 2.70V | 127.050m | 71.428m | 198.263m |
| 2.80V | 127.260m | 71.551m | 198.622m |
| 2.90V | 127.457m | 71.666m | 198.958m |
| 3.00V | 127.643m | 71.774m | 199.275m |
| 3.10V | 127.818m | 71.876m | 199.576m |
| 3.20V | 127.986m | 71.973m | 199.863m |
| 3.30V | 128.147m | 72.066m | 200.138m |
| 3.40V | 128.304m | 72.156m | 200.405m |
| 3.50V | 128.458m | 72.245m | 200.667m |
| 3.60V | 128.614m | 72.335m | 200.928m |
| 3.70V | 128.776m | 72.428m | 201.194m |
| 3.80V | 128.948m | 72.527m | 201.472m |
| 3.90V | 129.140m | 72.638m | 201.774m |
| 4.00V | 129.361m | 72.764m | 202.113m |
| 4.10V | 129.621m | 72.914m | 202.503m |
| 4.20V | 129.934m | 73.093m | 202.966m |
| 4.30V | 130.316m | 73.311m | 203.524m |
| 4.40V | 130.784m | 73.579m | 204.203m |

| | | | |
|---|----------|----------|----------|
| 4.50V | 131.358m | 73.906m | 205.033m |
| 4.60V | 132.060m | 74.304m | 206.045m |
| 4.70V | 132.912m | 74.787m | 207.276m |
| 4.80V | 133.939m | 75.368m | 208.763m |
| 4.90V | 135.166m | 76.060m | 210.544m |
| 5.00V | 136.619m | 76.878m | 212.659m |
| 5.10V | 138.324m | 77.836m | 215.149m |
| 5.20V | 140.308m | 78.948m | 218.056m |
| 5.30V | 142.597m | 80.230m | 221.419m |
| 5.40V | 145.217m | 81.694m | 225.277m |
| 5.50V | 148.192m | 83.355m | 229.669m |
| 5.60V | 151.545m | 85.224m | 234.630m |
| 5.70V | 155.300m | 87.316m | 240.194m |
| 5.80V | 159.478m | 89.640m | 246.393m |
| 5.90V | 164.097m | 92.208m | 253.255m |
| 6.00V | 169.177m | 95.029m | 260.806m |
| 6.10V | 174.734m | 98.112m | 269.070m |
| 6.20V | 180.781m | 101.465m | 278.065m |
| 6.30V | 187.333m | 105.096m | 287.810m |
| 6.40V | 194.400m | 109.009m | 298.319m |
| 6.50V | 201.993m | 113.211m | 309.602m |
| 6.60V | 210.118m | 117.705m | 321.670m |
| | | | |
| [Pullup] | | | |
| pullup in the table = pullup subtract power_clamp | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |
| -2.00V | 303.830u | 217.155u | 404.033u |
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |
| -1.30V | 960.395u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |

| | | | |
|--------|------------|------------|-------------|
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -65.539m | -13.798m |
| 1.40V | -110.103m | -67.611m | -154.438m |
| 1.50V | -113.807m | -69.311m | -170.370m |
| 1.60V | -117.010m | -70.713m | -176.323m |
| 1.70V | -119.783m | -71.893m | -181.647m |
| 1.80V | -122.195m | -72.910m | -186.387m |
| 1.90V | -124.297m | -73.804m | -190.581m |
| 2.00V | -126.131m | -74.599m | -194.261m |
| 2.10V | -127.733m | -75.311m | -197.468m |
| 2.20V | -129.139m | -75.954m | -200.255m |
| 2.30V | -130.384m | -76.540m | -202.683m |
| 2.40V | -131.498m | -77.077m | -204.814m |
| 2.50V | -132.504m | -77.575m | -206.704m |
| 2.60V | -133.423m | -78.037m | -208.399m |
| 2.70V | -134.270m | -78.470m | -209.937m |
| 2.80V | -135.057m | -78.877m | -211.346m |
| 2.90V | -135.792m | -79.261m | -212.650m |
| 3.00V | -136.483m | -79.625m | -213.864m |
| 3.10V | -137.136m | -79.971m | -215.004m |
| 3.20V | -137.756m | -80.302m | -216.079m |
| 3.30V | -138.345m | -80.617m | -217.098m |
| 3.40V | -138.908m | -80.920m | -218.067m |
| 3.50V | -139.447m | -81.210m | -218.993m |
| 3.60V | -139.964m | -81.490m | -219.880m |
| 3.70V | -140.462m | -81.761m | -220.732m |
| 3.80V | -140.943m | -82.022m | -221.552m |
| 3.90V | -141.408m | -82.277m | -222.344m |
| 4.00V | -141.860m | -82.525m | -223.112m |
| 4.10V | -142.300m | -82.769m | -223.858m |
| 4.20V | -142.733m | -83.010m | -224.586m |
| 4.30V | -143.159m | -83.250m | -225.300m |
| 4.40V | -143.585m | -83.493m | -226.006m |
| 4.50V | -144.013m | -83.740m | -226.709m |
| 4.60V | -144.449m | -83.996m | -227.417m |
| 4.70V | -144.899m | -84.265m | -228.137m |
| 4.80V | -145.370m | -84.551m | -228.879m |
| 4.90V | -145.871m | -84.861m | -229.656m |

| | | | |
|-------|-----------|-----------|-----------|
| 5.00V | -146.411m | -85.200m | -230.481m |
| 5.10V | -147.001m | -85.575m | -231.368m |
| 5.20V | -147.652m | -85.993m | -232.336m |
| 5.30V | -148.379m | -86.464m | -233.404m |
| 5.40V | -149.195m | -86.995m | -234.592m |
| 5.50V | -150.115m | -87.597m | -235.924m |
| 5.60V | -151.157m | -88.280m | -237.426m |
| 5.70V | -152.339m | -89.054m | -239.124m |
| 5.80V | -153.678m | -89.930m | -241.046m |
| 5.90V | -155.194m | -90.921m | -243.223m |
| 6.00V | -156.907m | -92.038m | -245.685m |
| 6.10V | -158.839m | -93.294m | -248.465m |
| 6.20V | -161.011m | -94.701m | -251.595m |
| 6.30V | -163.444m | -96.273m | -255.109m |
| 6.40V | -166.160m | -98.023m | -259.041m |
| 6.50V | -169.182m | -99.963m | -263.425m |
| 6.60V | -172.531m | -102.106m | -268.293m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -2.637 | -1.514 | -3.063 |
| -3.20V | -2.521 | -1.451 | -2.926 |
| -3.10V | -2.406 | -1.387 | -2.789 |
| -2.90V | -2.174 | -1.259 | -2.515 |
| -2.80V | -2.059 | -1.195 | -2.378 |
| -2.70V | -1.943 | -1.132 | -2.242 |
| -2.60V | -1.828 | -1.068 | -2.105 |
| -2.50V | -1.713 | -1.004 | -1.969 |
| -2.40V | -1.598 | -941.073m | -1.833 |
| -2.30V | -1.483 | -877.750m | -1.697 |
| -2.20V | -1.368 | -814.544m | -1.561 |
| -2.10V | -1.254 | -751.475m | -1.425 |
| -1.90V | -1.026 | -625.847m | -1.155 |
| -1.80V | -912.311m | -563.357m | -1.021 |
| -1.70V | -799.377m | -501.149m | -886.904m |
| -1.60V | -687.103m | -439.297m | -753.859m |
| -1.50V | -575.715m | -377.904m | -621.897m |
| -1.40V | -465.583m | -317.129m | -491.519m |
| -1.30V | -357.354m | -257.221m | -363.667m |
| -1.20V | -252.314m | -198.614m | -240.395m |
| -1.10V | -153.494m | -142.138m | -127.373m |
| -0.90V | -19.457m | -45.305m | -11.215m |
| -0.80V | -3.535m | -16.226m | -4.650m |
| -0.70V | -877.640u | -3.288m | -1.613m |
| -0.60V | -156.838u | -397.909u | -271.662u |
| -0.50V | -14.514u | -53.601u | -18.044u |
| -0.40V | -780.351n | -6.086u | -560.308n |
| -0.30V | -37.668n | -598.098n | -15.437n |
| -0.20V | -1.699n | -55.739n | -411.332p |
| -0.10V | -92.071p | -5.410n | -29.683p |
| 0.00V | -27.709p | -1.212n | -18.939p |
| 0.10V | -22.802p | -890.771p | -16.163p |
| 0.20V | -19.598p | -810.054p | -13.516p |

| | | | |
|-------|-----------|-----------|-----------|
| 0.30V | -16.468p | -745.765p | -10.874p |
| 0.40V | -13.353p | -683.799p | -8.234p |
| 0.50V | -10.247p | -622.802p | -5.595p |
| 0.60V | -7.147p | -562.404p | -2.956p |
| 0.70V | -4.050p | -502.414p | -318.962f |
| 0.80V | -955.896f | -442.712p | 2.318p |
| 0.90V | 2.136p | -383.217p | 4.954p |
| 1.10V | 8.315p | -264.634p | 10.227p |
| 1.20V | 11.404p | -205.467p | 12.862p |
| 1.30V | 14.492p | -146.346p | 15.498p |
| 1.40V | 17.579p | -87.245p | 18.133p |
| 1.50V | 20.666p | -28.141p | 20.768p |
| 1.60V | 23.754p | 30.987p | 23.404p |
| 1.70V | 26.841p | 90.164p | 26.039p |
| 1.80V | 29.929p | 149.414p | 28.674p |
| 1.90V | 33.018p | 208.769p | 31.310p |
| 2.10V | 39.198p | 327.949p | 36.581p |
| 2.20V | 42.291p | 387.873p | 39.216p |
| 2.30V | 45.385p | 448.012p | 41.852p |
| 2.40V | 48.483p | 507.296p | 44.489p |
| 2.50V | 51.583p | 563.856p | 47.125p |
| 2.60V | 54.673p | 619.785p | 49.762p |
| 2.70V | 57.468p | 676.156p | 52.401p |
| 2.80V | 59.647p | 733.868p | 55.040p |
| 2.90V | 61.717p | 807.258p | 57.675p |
| 3.10V | 65.859p | 5.906n | 61.928p |
| 3.20V | 68.003p | 59.801n | 63.585p |
| 3.30V | 72.601p | 620.266n | 65.236p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -27.709p | -598.098n | -10.874p |
| 3.40V | -92.071p | -6.086u | -13.516p |
| 3.50V | -1.699n | -53.601u | -16.163p |
| 3.60V | -37.668n | -397.909u | -18.939p |
| 3.70V | -780.351n | -3.288m | -29.683p |
| 3.80V | -14.514u | -16.226m | -411.332p |
| 3.90V | -156.838u | -45.305m | -15.437n |
| 4.10V | -3.535m | -142.138m | -18.044u |
| 4.20V | -19.457m | -198.614m | -271.662u |
| 4.30V | -69.631m | -257.221m | -1.613m |
| 4.40V | -153.494m | -317.129m | -4.650m |
| 4.50V | -252.314m | -377.904m | -11.215m |
| 4.60V | -357.354m | -439.297m | -43.562m |
| 4.70V | -465.583m | -501.149m | -127.373m |
| 4.80V | -575.715m | -563.357m | -240.395m |
| 4.90V | -687.103m | -625.847m | -363.667m |
| 5.10V | -912.311m | -751.475m | -621.897m |
| 5.20V | -1.026 | -814.544m | -753.859m |
| 5.30V | -1.140 | -877.750m | -886.904m |
| 5.40V | -1.254 | -941.073m | -1.021 |
| 5.50V | -1.368 | -1.004 | -1.155 |
| 5.60V | -1.483 | -1.068 | -1.290 |

| | | | |
|-------|--------|--------|--------|
| 5.70V | -1.598 | -1.132 | -1.425 |
| 5.80V | -1.713 | -1.195 | -1.561 |
| 5.90V | -1.828 | -1.259 | -1.697 |
| 6.10V | -2.059 | -1.387 | -1.969 |
| 6.20V | -2.174 | -1.451 | -2.105 |
| 6.30V | -2.290 | -1.514 | -2.242 |
| 6.40V | -2.406 | -1.578 | -2.378 |
| 6.50V | -2.521 | -1.642 | -2.515 |
| 6.60V | -2.637 | -1.706 | -2.652 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|---------------|---------------|--------------|
| dV/dt_f | 1.99/110.010p | 1.81/184.463p | 2.17/69.974p |
| dV/dt_r | 2.04/120.172p | 1.85/212.126p | 2.21/73.179p |

R_load=10000ohms

| R_load was connected to ground for Ramp_up test and power for Ramp_dn test

|

[End model

[Model] ipadd_io | ""

Model_type I/O

Vinl = 0.8

Vinh = 2

| variable | typ | min | max |
|----------|-------|-------|-------|
| C_comp | 2.34p | 2.21p | 2.52p |

| variable | typ | min | max |
|---------------------|------|-----|-------|
| [Temperature Range] | 40.0 | 0.0 | 120.0 |

| variable | typ | min | max |
|-----------------|-------|-------|-------|
| [Voltage Range] | 3.30V | 3.00V | 3.60V |

|

[Pulldown]

| pulldown in the table = pulldown subtract gnd_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -157.134u | -99.256u | -219.000u |
| -3.20V | -165.037u | -104.127u | -230.250u |
| -3.10V | -173.749u | -109.479u | -242.685u |
| -3.00V | -183.400u | -115.386u | -256.500u |
| -2.90V | -194.148u | -121.936u | -271.934u |
| -2.80V | -206.189u | -129.240u | -289.286u |
| -2.70V | -219.766u | -137.431u | -308.933u |
| -2.60V | -235.190u | -146.680u | -331.355u |
| -2.50V | -252.856u | -157.199u | -357.176u |
| -2.40V | -273.283u | -169.265u | -387.219u |
| -2.30V | -297.162u | -183.236u | -422.595u |
| -2.20V | -325.427u | -199.590u | -464.837u |
| -2.10V | -359.384u | -218.976u | -516.117u |
| -2.00V | -400.901u | -242.299u | -579.623u |
| -1.90V | -452.750u | -270.851u | -660.217u |
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |

| | | | |
|--------|------------|------------|----------|
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.871e-18 | 18.540e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 64.562m | 22.817m |
| 1.50V | 117.094m | 66.208m | 23.575m |
| 1.60V | 119.708m | 67.513m | 184.138m |
| 1.70V | 121.667m | 68.498m | 187.874m |
| 1.80V | 123.055m | 69.206m | 190.647m |
| 1.90V | 124.020m | 69.710m | 192.621m |
| 2.00V | 124.711m | 70.083m | 194.017m |
| 2.10V | 125.232m | 70.374m | 195.034m |
| 2.20V | 125.650m | 70.612m | 195.815m |
| 2.30V | 126.000m | 70.814m | 196.447m |
| 2.40V | 126.305m | 70.992m | 196.983m |
| 2.50V | 126.577m | 71.151m | 197.453m |
| 2.60V | 126.823m | 71.296m | 197.876m |
| 2.70V | 127.050m | 71.428m | 198.263m |
| 2.80V | 127.260m | 71.551m | 198.622m |
| 2.90V | 127.457m | 71.666m | 198.958m |
| 3.00V | 127.643m | 71.774m | 199.275m |
| 3.10V | 127.818m | 71.876m | 199.576m |
| 3.20V | 127.986m | 71.973m | 199.863m |
| 3.30V | 128.147m | 72.066m | 200.138m |
| 3.40V | 128.304m | 72.156m | 200.405m |
| 3.50V | 128.458m | 72.245m | 200.667m |
| 3.60V | 128.614m | 72.335m | 200.928m |
| 3.70V | 128.776m | 72.428m | 201.194m |
| 3.80V | 128.948m | 72.527m | 201.472m |
| 3.90V | 129.140m | 72.638m | 201.774m |
| 4.00V | 129.361m | 72.764m | 202.113m |
| 4.10V | 129.621m | 72.914m | 202.503m |

| | | | |
|-------|----------|----------|----------|
| 4.20V | 129.934m | 73.093m | 202.966m |
| 4.30V | 130.316m | 73.311m | 203.524m |
| 4.40V | 130.784m | 73.579m | 204.203m |
| 4.50V | 131.358m | 73.906m | 205.033m |
| 4.60V | 132.060m | 74.304m | 206.045m |
| 4.70V | 132.912m | 74.787m | 207.276m |
| 4.80V | 133.939m | 75.368m | 208.763m |
| 4.90V | 135.166m | 76.060m | 210.544m |
| 5.00V | 136.619m | 76.878m | 212.659m |
| 5.10V | 138.324m | 77.836m | 215.149m |
| 5.20V | 140.308m | 78.948m | 218.056m |
| 5.30V | 142.597m | 80.230m | 221.419m |
| 5.40V | 145.217m | 81.694m | 225.277m |
| 5.50V | 148.192m | 83.355m | 229.669m |
| 5.60V | 151.545m | 85.224m | 234.630m |
| 5.70V | 155.300m | 87.316m | 240.194m |
| 5.80V | 159.478m | 89.640m | 246.393m |
| 5.90V | 164.097m | 92.208m | 253.255m |
| 6.00V | 169.177m | 95.029m | 260.806m |
| 6.10V | 174.734m | 98.112m | 269.070m |
| 6.20V | 180.781m | 101.465m | 278.065m |
| 6.30V | 187.333m | 105.096m | 287.810m |
| 6.40V | 194.400m | 109.009m | 298.319m |
| 6.50V | 201.993m | 113.211m | 309.602m |
| 6.60V | 210.118m | 117.705m | 321.670m |

|
 [Pullup]
 | pullup in the table = pullup subtract power_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|----------|----------|----------|
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |
| -2.00V | 303.830u | 217.155u | 404.033u |
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |
| -1.30V | 960.395u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |

| | | | |
|--------|------------|------------|-------------|
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -65.539m | -13.798m |
| 1.40V | -110.103m | -67.611m | -154.438m |
| 1.50V | -113.807m | -69.311m | -170.370m |
| 1.60V | -117.010m | -70.713m | -176.323m |
| 1.70V | -119.783m | -71.893m | -181.647m |
| 1.80V | -122.195m | -72.910m | -186.387m |
| 1.90V | -124.297m | -73.804m | -190.581m |
| 2.00V | -126.131m | -74.599m | -194.261m |
| 2.10V | -127.733m | -75.311m | -197.468m |
| 2.20V | -129.139m | -75.954m | -200.255m |
| 2.30V | -130.384m | -76.540m | -202.683m |
| 2.40V | -131.498m | -77.077m | -204.814m |
| 2.50V | -132.504m | -77.575m | -206.704m |
| 2.60V | -133.423m | -78.037m | -208.399m |
| 2.70V | -134.270m | -78.470m | -209.937m |
| 2.80V | -135.057m | -78.877m | -211.346m |
| 2.90V | -135.792m | -79.261m | -212.650m |
| 3.00V | -136.483m | -79.625m | -213.864m |
| 3.10V | -137.136m | -79.971m | -215.004m |
| 3.20V | -137.756m | -80.302m | -216.079m |
| 3.30V | -138.345m | -80.617m | -217.098m |
| 3.40V | -138.908m | -80.920m | -218.067m |
| 3.50V | -139.447m | -81.210m | -218.993m |
| 3.60V | -139.964m | -81.490m | -219.880m |
| 3.70V | -140.462m | -81.761m | -220.732m |
| 3.80V | -140.943m | -82.022m | -221.552m |
| 3.90V | -141.408m | -82.277m | -222.344m |
| 4.00V | -141.860m | -82.525m | -223.112m |
| 4.10V | -142.300m | -82.769m | -223.858m |
| 4.20V | -142.733m | -83.010m | -224.586m |
| 4.30V | -143.159m | -83.250m | -225.300m |
| 4.40V | -143.585m | -83.493m | -226.006m |
| 4.50V | -144.013m | -83.740m | -226.709m |
| 4.60V | -144.449m | -83.996m | -227.417m |

| | | | |
|-------|-----------|-----------|-----------|
| 4.70V | -144.899m | -84.265m | -228.137m |
| 4.80V | -145.370m | -84.551m | -228.879m |
| 4.90V | -145.871m | -84.861m | -229.656m |
| 5.00V | -146.411m | -85.200m | -230.481m |
| 5.10V | -147.001m | -85.575m | -231.368m |
| 5.20V | -147.652m | -85.993m | -232.336m |
| 5.30V | -148.379m | -86.464m | -233.404m |
| 5.40V | -149.195m | -86.995m | -234.592m |
| 5.50V | -150.115m | -87.597m | -235.924m |
| 5.60V | -151.157m | -88.280m | -237.426m |
| 5.70V | -152.339m | -89.054m | -239.124m |
| 5.80V | -153.678m | -89.930m | -241.046m |
| 5.90V | -155.194m | -90.921m | -243.223m |
| 6.00V | -156.907m | -92.038m | -245.685m |
| 6.10V | -158.839m | -93.294m | -248.465m |
| 6.20V | -161.011m | -94.701m | -251.595m |
| 6.30V | -163.444m | -96.273m | -255.109m |
| 6.40V | -166.160m | -98.023m | -259.041m |
| 6.50V | -169.182m | -99.963m | -263.425m |
| 6.60V | -172.531m | -102.106m | -268.293m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -2.637 | -1.514 | -3.063 |
| -3.20V | -2.521 | -1.451 | -2.926 |
| -3.10V | -2.406 | -1.387 | -2.789 |
| -2.90V | -2.174 | -1.259 | -2.515 |
| -2.80V | -2.059 | -1.195 | -2.378 |
| -2.70V | -1.943 | -1.132 | -2.242 |
| -2.60V | -1.828 | -1.068 | -2.105 |
| -2.50V | -1.713 | -1.004 | -1.969 |
| -2.40V | -1.598 | -941.073m | -1.833 |
| -2.30V | -1.483 | -877.750m | -1.697 |
| -2.20V | -1.368 | -814.544m | -1.561 |
| -2.10V | -1.254 | -751.475m | -1.425 |
| -1.90V | -1.026 | -625.847m | -1.155 |
| -1.80V | -912.311m | -563.357m | -1.021 |
| -1.70V | -799.377m | -501.149m | -886.904m |
| -1.60V | -687.103m | -439.297m | -753.859m |
| -1.50V | -575.715m | -377.904m | -621.897m |
| -1.40V | -465.583m | -317.129m | -491.519m |
| -1.30V | -357.354m | -257.221m | -363.667m |
| -1.20V | -252.314m | -198.614m | -240.395m |
| -1.10V | -153.494m | -142.138m | -127.373m |
| -0.90V | -19.457m | -45.305m | -11.215m |
| -0.80V | -3.535m | -16.226m | -4.650m |
| -0.70V | -877.640u | -3.288m | -1.613m |
| -0.60V | -156.838u | -397.909u | -271.662u |
| -0.50V | -14.514u | -53.601u | -18.044u |
| -0.40V | -780.351n | -6.086u | -560.308n |
| -0.30V | -37.668n | -598.098n | -15.437n |
| -0.20V | -1.699n | -55.739n | -411.332p |
| -0.10V | -92.071p | -5.410n | -29.683p |

| | | | |
|-------|-----------|-----------|-----------|
| 0.00V | -27.709p | -1.212n | -18.939p |
| 0.10V | -22.802p | -890.771p | -16.163p |
| 0.20V | -19.598p | -810.054p | -13.516p |
| 0.30V | -16.468p | -745.765p | -10.874p |
| 0.40V | -13.353p | -683.799p | -8.234p |
| 0.50V | -10.247p | -622.802p | -5.595p |
| 0.60V | -7.147p | -562.404p | -2.956p |
| 0.70V | -4.050p | -502.414p | -318.962f |
| 0.80V | -955.896f | -442.712p | 2.318p |
| 0.90V | 2.136p | -383.217p | 4.954p |
| 1.10V | 8.315p | -264.634p | 10.227p |
| 1.20V | 11.404p | -205.467p | 12.862p |
| 1.30V | 14.492p | -146.346p | 15.498p |
| 1.40V | 17.579p | -87.245p | 18.133p |
| 1.50V | 20.666p | -28.141p | 20.768p |
| 1.60V | 23.754p | 30.987p | 23.404p |
| 1.70V | 26.841p | 90.164p | 26.039p |
| 1.80V | 29.929p | 149.414p | 28.674p |
| 1.90V | 33.018p | 208.769p | 31.310p |
| 2.10V | 39.198p | 327.949p | 36.581p |
| 2.20V | 42.291p | 387.873p | 39.216p |
| 2.30V | 45.385p | 448.012p | 41.852p |
| 2.40V | 48.483p | 507.296p | 44.489p |
| 2.50V | 51.583p | 563.856p | 47.125p |
| 2.60V | 54.673p | 619.785p | 49.762p |
| 2.70V | 57.468p | 676.156p | 52.401p |
| 2.80V | 59.647p | 733.868p | 55.040p |
| 2.90V | 61.717p | 807.258p | 57.675p |
| 3.10V | 65.859p | 5.906n | 61.928p |
| 3.20V | 68.003p | 59.801n | 63.585p |
| 3.30V | 72.601p | 620.266n | 65.236p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -27.709p | -598.098n | -10.874p |
| 3.40V | -92.071p | -6.086u | -13.516p |
| 3.50V | -1.699n | -53.601u | -16.163p |
| 3.60V | -37.668n | -397.909u | -18.939p |
| 3.70V | -780.351n | -3.288m | -29.683p |
| 3.80V | -14.514u | -16.226m | -411.332p |
| 3.90V | -156.838u | -45.305m | -15.437n |
| 4.10V | -3.535m | -142.138m | -18.044u |
| 4.20V | -19.457m | -198.614m | -271.662u |
| 4.30V | -69.631m | -257.221m | -1.613m |
| 4.40V | -153.494m | -317.129m | -4.650m |
| 4.50V | -252.314m | -377.904m | -11.215m |
| 4.60V | -357.354m | -439.297m | -43.562m |
| 4.70V | -465.583m | -501.149m | -127.373m |
| 4.80V | -575.715m | -563.357m | -240.395m |
| 4.90V | -687.103m | -625.847m | -363.667m |
| 5.10V | -912.311m | -751.475m | -621.897m |
| 5.20V | -1.026 | -814.544m | -753.859m |
| 5.30V | -1.140 | -877.750m | -886.904m |

| | | | |
|-------|--------|-----------|--------|
| 5.40V | -1.254 | -941.073m | -1.021 |
| 5.50V | -1.368 | -1.004 | -1.155 |
| 5.60V | -1.483 | -1.068 | -1.290 |
| 5.70V | -1.598 | -1.132 | -1.425 |
| 5.80V | -1.713 | -1.195 | -1.561 |
| 5.90V | -1.828 | -1.259 | -1.697 |
| 6.10V | -2.059 | -1.387 | -1.969 |
| 6.20V | -2.174 | -1.451 | -2.105 |
| 6.30V | -2.290 | -1.514 | -2.242 |
| 6.40V | -2.406 | -1.578 | -2.378 |
| 6.50V | -2.521 | -1.642 | -2.515 |
| 6.60V | -2.637 | -1.706 | -2.652 |

```

|
[Ramp]
|Voltage          I (typ)          I (min)          I (max)
|
dV/dt_f          1.99/104.603p 1.81/183.924p 2.18/69.643p
|
dV/dt_r          2.04/123.810p 1.85/215.062p 2.20/73.602p
R_load=10000ohms
| R_load was connected to ground for Ramp_up test and power for Ramp_dn test
|
|End model
[Model]          ipadex_i          | ""
Model_type          Input
Vinl = 0.8
Vinh = 2
| variable          typ          min          max
C_comp          2.92p          2.78p          2.96p
| variable          typ          min          max
[Temperature Range] 40.0          0.0          120.0
| variable          typ          min          max
[Voltage Range]    3.30V          3.00V          3.60V
|
[GND_clamp]
|
|Voltage          I (typ)          I (min)          I (max)
|
-3.30V          -831.819m -473.616m -909.150m
-3.20V          -796.528m -454.528m -869.534m
-3.10V          -761.255m -435.451m -829.938m
-2.90V          -690.773m -397.335m -750.811m
-2.80V          -655.569m -378.299m -711.286m
-2.70V          -620.391m -359.279m -671.789m
-2.60V          -585.244m -340.277m -632.324m
-2.50V          -550.131m -321.295m -592.895m
-2.40V          -515.057m -302.336m -553.507m
-2.30V          -480.027m -283.402m -514.167m
-2.20V          -445.047m -264.496m -474.880m
-2.10V          -410.126m -245.624m -435.657m
-1.90V          -340.501m -207.998m -357.451m
-1.80V          -305.826m -189.259m -318.503m
-1.70V          -271.273m -170.582m -279.692m
-1.60V          -236.871m -151.981m -241.057m
-1.50V          -202.665m -133.474m -202.657m

```

| | | | |
|--------|-----------|-----------|-----------|
| -1.40V | -168.722m | -115.088m | -164.583m |
| -1.30V | -135.151m | -96.861m | -126.991m |
| -1.20V | -102.140m | -78.852m | -90.181m |
| -1.10V | -70.064m | -61.160m | -54.834m |
| -0.90V | -14.097m | -27.650m | -2.799m |
| -0.80V | -1.307m | -13.160m | -53.501u |
| -0.70V | -36.639u | -3.159m | -768.589n |
| -0.60V | -903.944n | -256.975u | -10.997n |
| -0.50V | -22.242n | -13.934u | -172.415p |
| -0.40V | -567.014p | -730.372n | -16.888p |
| -0.30V | -32.976p | -38.990n | -13.767p |
| -0.20V | -18.575p | -2.810n | -12.822p |
| -0.10V | -16.945p | -867.431p | -11.909p |
| 0.00V | -15.630p | -713.428p | -10.996p |
| 0.10V | -14.322p | -652.886p | -10.084p |
| 0.20V | -13.014p | -597.227p | -9.171p |
| 0.30V | -11.707p | -541.823p | -8.258p |
| 0.40V | -10.399p | -486.432p | -7.345p |
| 0.50V | -9.092p | -431.043p | -6.432p |
| 0.60V | -7.784p | -375.653p | -5.520p |
| 0.70V | -6.477p | -320.263p | -4.607p |
| 0.80V | -5.169p | -264.873p | -3.694p |
| 0.90V | -3.862p | -209.483p | -2.781p |
| 1.10V | -1.246p | -98.704p | -955.508f |
| 1.20V | 61.165f | -43.314p | -42.711f |
| 1.30V | 1.369p | 12.076p | 870.085f |
| 1.40V | 2.676p | 67.466p | 1.783p |
| 1.50V | 3.984p | 122.856p | 2.696p |
| 1.60V | 5.291p | 178.246p | 3.609p |
| 1.70V | 6.599p | 233.635p | 4.521p |
| 1.80V | 7.906p | 289.025p | 5.434p |
| 1.90V | 9.214p | 344.415p | 6.347p |
| 2.10V | 11.829p | 455.195p | 8.173p |
| 2.20V | 13.137p | 510.585p | 9.085p |
| 2.30V | 14.444p | 565.974p | 9.998p |
| 2.40V | 15.752p | 621.364p | 10.911p |
| 2.50V | 17.059p | 676.754p | 11.824p |
| 2.60V | 18.367p | 732.144p | 12.736p |
| 2.70V | 19.674p | 787.535p | 13.649p |
| 2.80V | 20.982p | 842.946p | 14.562p |
| 2.90V | 22.290p | 898.735p | 15.475p |
| 3.10V | 24.905p | 1.163n | 17.301p |
| 3.20V | 26.212p | 4.019n | 18.213p |
| 3.30V | 27.520p | 57.671n | 19.126p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|----------|
| 3.30V | -15.630p | -38.990n | -8.258p |
| 3.40V | -16.945p | -730.372n | -9.171p |
| 3.50V | -18.575p | -13.934u | -10.084p |
| 3.60V | -32.976p | -256.975u | -10.996p |
| 3.70V | -567.014p | -3.159m | -11.909p |
| 3.80V | -22.242n | -13.160m | -12.822p |

```

3.90V      -903.944n  -27.650m  -13.767p
4.10V      -1.307m   -61.160m  -172.415p
4.20V      -14.097m  -78.852m  -10.997n
4.30V      -39.803m  -96.861m  -768.589n
4.40V      -70.064m  -115.088m -53.501u
4.50V      -102.140m -133.474m  -2.799m
4.60V      -135.151m -151.981m  -22.990m
4.70V      -168.722m -170.582m  -54.834m
4.80V      -202.665m -189.259m  -90.181m
4.90V      -236.871m -207.998m -126.991m
5.10V      -305.826m -245.624m -202.657m
5.20V      -340.501m -264.496m -241.057m
5.30V      -375.273m -283.402m -279.692m
5.40V      -410.126m -302.336m -318.503m
5.50V      -445.047m -321.295m -357.451m
5.60V      -480.027m -340.277m -396.509m
5.70V      -515.057m -359.279m -435.657m
5.80V      -550.131m -378.299m -474.880m
5.90V      -585.244m -397.335m -514.167m
6.10V      -655.569m -435.451m -592.895m
6.20V      -690.773m -454.528m -632.324m
6.30V      -726.003m -473.616m -671.789m
6.40V      -761.255m -492.715m -711.286m
6.50V      -796.528m -511.823m -750.811m
6.60V      -831.819m -530.941m -790.363m
|
|End model
[Model]          ipadm_3st          | ""
Model_type      3-state
| variable      typ          min          max
C_comp          1.99p          1.86p          2.15p
| variable      typ          min          max
[Temperature Range] 40.0          0.0          120.0
| variable      typ          min          max
[Voltage Range]   3.30V          3.00V          3.60V
|
[Pulldown]
| pulldown in the table = pulldown subtract gnd_clamp
|Voltage        I(typ)          I(min)          I(max)
|
-3.30V         -157.134u      -99.256u      -219.000u
-3.20V         -165.037u      -104.127u     -230.250u
-3.10V         -173.749u      -109.479u     -242.685u
-3.00V         -183.400u      -115.386u     -256.500u
-2.90V         -194.148u      -121.936u     -271.934u
-2.80V         -206.189u      -129.240u     -289.286u
-2.70V         -219.766u      -137.431u     -308.933u
-2.60V         -235.190u      -146.680u     -331.355u
-2.50V         -252.856u      -157.199u     -357.176u
-2.40V         -273.283u      -169.265u     -387.219u
-2.30V         -297.162u      -183.236u     -422.595u
-2.20V         -325.427u      -199.590u     -464.837u
-2.10V         -359.384u      -218.976u     -516.117u
-2.00V         -400.901u      -242.299u     -579.623u
-1.90V         -452.750u      -270.851u     -660.217u

```

| | | | |
|--------|------------|------------|-----------|
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.755e-18 | 18.548e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 47.725m | 22.817m |
| 1.50V | 86.564m | 48.943m | 23.575m |
| 1.60V | 88.497m | 49.908m | 136.139m |
| 1.70V | 89.946m | 50.637m | 138.902m |
| 1.80V | 90.974m | 51.160m | 140.954m |
| 1.90V | 91.689m | 51.534m | 142.415m |
| 2.00V | 92.200m | 51.810m | 143.449m |
| 2.10V | 92.586m | 52.024m | 144.201m |
| 2.20V | 92.895m | 52.201m | 144.779m |
| 2.30V | 93.154m | 52.351m | 145.246m |
| 2.40V | 93.380m | 52.482m | 145.642m |
| 2.50V | 93.581m | 52.600m | 145.990m |
| 2.60V | 93.764m | 52.706m | 146.303m |
| 2.70V | 93.931m | 52.804m | 146.590m |
| 2.80V | 94.087m | 52.895m | 146.855m |
| 2.90V | 94.233m | 52.980m | 147.104m |
| 3.00V | 94.370m | 53.060m | 147.338m |
| 3.10V | 94.500m | 53.135m | 147.560m |
| 3.20V | 94.624m | 53.207m | 147.772m |
| 3.30V | 94.744m | 53.276m | 147.976m |
| 3.40V | 94.859m | 53.343m | 148.174m |
| 3.50V | 94.974m | 53.408m | 148.367m |
| 3.60V | 95.089m | 53.475m | 148.560m |

| | | | |
|-------|----------|---------|----------|
| 3.70V | 95.208m | 53.543m | 148.757m |
| 3.80V | 95.336m | 53.617m | 148.963m |
| 3.90V | 95.478m | 53.699m | 149.186m |
| 4.00V | 95.641m | 53.792m | 149.436m |
| 4.10V | 95.833m | 53.902m | 149.725m |
| 4.20V | 96.065m | 54.035m | 150.067m |
| 4.30V | 96.347m | 54.196m | 150.479m |
| 4.40V | 96.693m | 54.394m | 150.981m |
| 4.50V | 97.117m | 54.635m | 151.594m |
| 4.60V | 97.636m | 54.930m | 152.342m |
| 4.70V | 98.266m | 55.287m | 153.252m |
| 4.80V | 99.024m | 55.716m | 154.350m |
| 4.90V | 99.931m | 56.227m | 155.666m |
| 5.00V | 101.005m | 56.831m | 157.230m |
| 5.10V | 102.264m | 57.539m | 159.070m |
| 5.20V | 103.730m | 58.361m | 161.218m |
| 5.30V | 105.422m | 59.308m | 163.704m |
| 5.40V | 107.357m | 60.391m | 166.555m |
| 5.50V | 109.556m | 61.618m | 169.801m |
| 5.60V | 112.034m | 63.000m | 173.468m |
| 5.70V | 114.809m | 64.545m | 177.581m |
| 5.80V | 117.897m | 66.263m | 182.163m |
| 5.90V | 121.311m | 68.160m | 187.235m |
| 6.00V | 125.066m | 70.245m | 192.816m |
| 6.10V | 129.172m | 72.524m | 198.924m |
| 6.20V | 133.642m | 75.002m | 205.573m |
| 6.30V | 138.485m | 77.685m | 212.776m |
| 6.40V | 143.709m | 80.578m | 220.544m |
| 6.50V | 149.320m | 83.683m | 228.885m |
| 6.60V | 155.326m | 87.004m | 237.805m |

|

[Pullup]

| pullup in the table = pullup subtract power_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|----------|----------|----------|
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |
| -2.00V | 303.830u | 217.155u | 404.033u |
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |

| | | | |
|--------|------------|------------|-------------|
| -1.30V | 960.396u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -47.451m | -13.837m |
| 1.40V | -79.705m | -48.954m | -118.519m |
| 1.50V | -82.391m | -50.187m | -123.324m |
| 1.60V | -84.713m | -51.203m | -127.640m |
| 1.70V | -86.724m | -52.057m | -131.501m |
| 1.80V | -88.472m | -52.794m | -134.939m |
| 1.90V | -89.996m | -53.442m | -137.982m |
| 2.00V | -91.327m | -54.017m | -140.655m |
| 2.10V | -92.489m | -54.533m | -142.987m |
| 2.20V | -93.511m | -54.999m | -145.014m |
| 2.30V | -94.415m | -55.424m | -146.781m |
| 2.40V | -95.224m | -55.814m | -148.333m |
| 2.50V | -95.955m | -56.174m | -149.709m |
| 2.60V | -96.623m | -56.510m | -150.943m |
| 2.70V | -97.238m | -56.824m | -152.063m |
| 2.80V | -97.809m | -57.119m | -153.088m |
| 2.90V | -98.343m | -57.398m | -154.036m |
| 3.00V | -98.846m | -57.662m | -154.920m |
| 3.10V | -99.320m | -57.913m | -155.749m |
| 3.20V | -99.770m | -58.152m | -156.531m |
| 3.30V | -100.198m | -58.381m | -157.272m |
| 3.40V | -100.607m | -58.601m | -157.977m |
| 3.50V | -100.998m | -58.812m | -158.650m |
| 3.60V | -101.374m | -59.015m | -159.295m |
| 3.70V | -101.735m | -59.211m | -159.914m |
| 3.80V | -102.084m | -59.401m | -160.510m |
| 3.90V | -102.422m | -59.585m | -161.086m |
| 4.00V | -102.750m | -59.766m | -161.644m |
| 4.10V | -103.070m | -59.942m | -162.186m |

| | | | |
|-------|-----------|----------|-----------|
| 4.20V | -103.384m | -60.117m | -162.715m |
| 4.30V | -103.694m | -60.291m | -163.234m |
| 4.40V | -104.002m | -60.467m | -163.747m |
| 4.50V | -104.313m | -60.647m | -164.257m |
| 4.60V | -104.629m | -60.832m | -164.770m |
| 4.70V | -104.955m | -61.027m | -165.293m |
| 4.80V | -105.296m | -61.234m | -165.831m |
| 4.90V | -105.659m | -61.459m | -166.394m |
| 5.00V | -106.050m | -61.704m | -166.991m |
| 5.10V | -106.477m | -61.975m | -167.634m |
| 5.20V | -106.949m | -62.278m | -168.334m |
| 5.30V | -107.474m | -62.619m | -169.106m |
| 5.40V | -108.064m | -63.003m | -169.965m |
| 5.50V | -108.730m | -63.439m | -170.928m |
| 5.60V | -109.483m | -63.932m | -172.012m |
| 5.70V | -110.337m | -64.492m | -173.239m |
| 5.80V | -111.305m | -65.126m | -174.627m |
| 5.90V | -112.401m | -65.843m | -176.199m |
| 6.00V | -113.640m | -66.651m | -177.978m |
| 6.10V | -115.036m | -67.560m | -179.986m |
| 6.20V | -116.606m | -68.578m | -182.247m |
| 6.30V | -118.365m | -69.715m | -184.785m |
| 6.40V | -120.329m | -70.981m | -187.626m |
| 6.50V | -122.513m | -72.384m | -190.793m |
| 6.60V | -124.935m | -73.935m | -194.311m |

| | | | |
|-------------|-----------|-----------|-----------|
| | | | |
| [GND_clamp] | | | |
| | | | |
| Voltage | I (typ) | I (min) | I (max) |
| | | | |
| -3.30V | -2.165 | -1.242 | -2.500 |
| -3.20V | -2.070 | -1.190 | -2.388 |
| -3.10V | -1.975 | -1.138 | -2.277 |
| -2.90V | -1.786 | -1.033 | -2.054 |
| -2.80V | -1.691 | -981.185m | -1.942 |
| -2.70V | -1.597 | -929.174m | -1.831 |
| -2.60V | -1.503 | -877.220m | -1.720 |
| -2.50V | -1.408 | -825.330m | -1.609 |
| -2.40V | -1.314 | -773.514m | -1.498 |
| -2.30V | -1.220 | -721.779m | -1.387 |
| -2.20V | -1.126 | -670.140m | -1.276 |
| -2.10V | -1.032 | -618.610m | -1.166 |
| -1.90V | -845.771m | -515.958m | -945.908m |
| -1.80V | -752.887m | -464.892m | -836.403m |
| -1.70V | -660.410m | -414.052m | -727.373m |
| -1.60V | -568.461m | -363.494m | -618.970m |
| -1.50V | -477.221m | -313.301m | -511.430m |
| -1.40V | -386.980m | -263.597m | -405.149m |
| -1.30V | -298.248m | -214.579m | -300.867m |
| -1.20V | -212.028m | -166.582m | -200.187m |
| -1.10V | -130.668m | -120.248m | -107.496m |
| -0.90V | -17.375m | -40.029m | -8.803m |
| -0.80V | -2.837m | -14.886m | -3.451m |
| -0.70V | -656.331u | -3.014m | -1.195m |
| -0.60V | -116.521u | -336.317u | -201.636u |

| | | | |
|--------|-----------|-----------|-----------|
| -0.50V | -10.789u | -41.964u | -13.420u |
| -0.40V | -580.051n | -4.632u | -416.799n |
| -0.30V | -27.994n | -450.005n | -11.484n |
| -0.20V | -1.269n | -41.862n | -311.158p |
| -0.10V | -74.463p | -4.218n | -27.092p |
| 0.00V | -26.215p | -1.078n | -18.737p |
| 0.10V | -22.114p | -826.325p | -16.303p |
| 0.20V | -19.278p | -754.146p | -13.966p |
| 0.30V | -16.497p | -694.188p | -11.632p |
| 0.40V | -13.726p | -635.953p | -9.300p |
| 0.50V | -10.963p | -578.437p | -6.968p |
| 0.60V | -8.203p | -521.365p | -4.637p |
| 0.70V | -5.446p | -464.595p | -2.307p |
| 0.80V | -2.691p | -408.039p | 22.980f |
| 0.90V | 62.079f | -351.636p | 2.353p |
| 1.10V | 5.566p | -239.133p | 7.011p |
| 1.20V | 8.316p | -182.975p | 9.340p |
| 1.30V | 11.067p | -126.851p | 11.669p |
| 1.40V | 13.817p | -70.743p | 13.998p |
| 1.50V | 16.567p | -14.634p | 16.327p |
| 1.60V | 19.317p | 41.493p | 18.656p |
| 1.70V | 22.067p | 97.654p | 20.985p |
| 1.80V | 24.817p | 153.868p | 23.313p |
| 1.90V | 27.568p | 210.159p | 25.642p |
| 2.10V | 33.072p | 323.083p | 30.300p |
| 2.20V | 35.825p | 379.789p | 32.629p |
| 2.30V | 38.581p | 436.650p | 34.958p |
| 2.40V | 41.339p | 492.867p | 37.288p |
| 2.50V | 44.098p | 547.026p | 39.618p |
| 2.60V | 46.849p | 600.695p | 41.948p |
| 2.70V | 49.356p | 654.682p | 44.279p |
| 2.80V | 51.378p | 709.650p | 46.611p |
| 2.90V | 53.315p | 776.122p | 48.939p |
| 3.10V | 57.193p | 4.552n | 52.772p |
| 3.20V | 59.183p | 44.522n | 54.319p |
| 3.30V | 62.959p | 466.732n | 55.861p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -26.215p | -450.005n | -11.632p |
| 3.40V | -74.463p | -4.632u | -13.966p |
| 3.50V | -1.269n | -41.964u | -16.303p |
| 3.60V | -27.994n | -336.317u | -18.737p |
| 3.70V | -580.051n | -3.014m | -27.092p |
| 3.80V | -10.789u | -14.886m | -311.158p |
| 3.90V | -116.521u | -40.029m | -11.484n |
| 4.10V | -2.837m | -120.248m | -13.420u |
| 4.20V | -17.375m | -166.582m | -201.636u |
| 4.30V | -60.888m | -214.579m | -1.195m |
| 4.40V | -130.668m | -263.597m | -3.451m |
| 4.50V | -212.028m | -313.301m | -8.803m |
| 4.60V | -298.248m | -363.494m | -37.420m |
| 4.70V | -386.980m | -414.052m | -107.496m |

| | | | |
|-------|-----------|-----------|-----------|
| 4.80V | -477.221m | -464.892m | -200.187m |
| 4.90V | -568.461m | -515.958m | -300.867m |
| 5.10V | -752.887m | -618.610m | -511.430m |
| 5.20V | -845.771m | -670.140m | -618.970m |
| 5.30V | -938.979m | -721.779m | -727.373m |
| 5.40V | -1.032 | -773.514m | -836.403m |
| 5.50V | -1.126 | -825.330m | -945.908m |
| 5.60V | -1.220 | -877.220m | -1.056 |
| 5.70V | -1.314 | -929.174m | -1.166 |
| 5.80V | -1.408 | -981.185m | -1.276 |
| 5.90V | -1.503 | -1.033 | -1.387 |
| 6.10V | -1.691 | -1.138 | -1.609 |
| 6.20V | -1.786 | -1.190 | -1.720 |
| 6.30V | -1.881 | -1.242 | -1.831 |
| 6.40V | -1.975 | -1.294 | -1.942 |
| 6.50V | -2.070 | -1.346 | -2.054 |
| 6.60V | -2.165 | -1.399 | -2.165 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|---------------|---------------|--------------|
| | | | |
| dV/dt_f | 1.99/116.478p | 1.81/206.384p | 2.17/80.687p |
| | | | |
| dV/dt_r | 2.02/147.722p | 1.84/253.853p | 2.19/93.030p |

R_load=10000ohms

| R_load was connected to ground for Ramp_up test and power for Ramp_dn test

|

|End model

[Model] ipadn_io | ""

Model_type I/O

Vinl = 0.8

Vinh = 2

| variable | typ | min | max |
|---------------------|-------|-------|-------|
| C_comp | 2.03p | 1.90p | 2.18p |
| variable | typ | min | max |
| [Temperature Range] | 40.0 | 0.0 | 120.0 |
| variable | typ | min | max |
| [Voltage Range] | 3.30V | 3.00V | 3.60V |

|

[Pulldown]

| pulldown in the table = pulldown subtract gnd_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| | | | |
| -3.30V | -157.134u | -99.256u | -219.000u |
| -3.20V | -165.037u | -104.127u | -230.250u |
| -3.10V | -173.749u | -109.479u | -242.685u |
| -3.00V | -183.400u | -115.386u | -256.500u |
| -2.90V | -194.148u | -121.936u | -271.934u |
| -2.80V | -206.189u | -129.240u | -289.286u |
| -2.70V | -219.766u | -137.431u | -308.933u |
| -2.60V | -235.190u | -146.680u | -331.355u |
| -2.50V | -252.856u | -157.199u | -357.176u |
| -2.40V | -273.283u | -169.265u | -387.219u |
| -2.30V | -297.162u | -183.236u | -422.595u |
| -2.20V | -325.427u | -199.590u | -464.837u |

| | | | |
|--------|------------|------------|-----------|
| -2.10V | -359.384u | -218.976u | -516.117u |
| -2.00V | -400.901u | -242.299u | -579.623u |
| -1.90V | -452.750u | -270.851u | -660.217u |
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.755e-18 | 18.548e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 47.725m | 22.817m |
| 1.50V | 86.564m | 48.943m | 23.575m |
| 1.60V | 88.497m | 49.908m | 136.139m |
| 1.70V | 89.946m | 50.637m | 138.902m |
| 1.80V | 90.974m | 51.160m | 140.954m |
| 1.90V | 91.689m | 51.534m | 142.415m |
| 2.00V | 92.200m | 51.810m | 143.449m |
| 2.10V | 92.586m | 52.024m | 144.201m |
| 2.20V | 92.895m | 52.201m | 144.779m |
| 2.30V | 93.154m | 52.351m | 145.246m |
| 2.40V | 93.380m | 52.482m | 145.642m |
| 2.50V | 93.581m | 52.600m | 145.990m |
| 2.60V | 93.764m | 52.706m | 146.303m |
| 2.70V | 93.931m | 52.804m | 146.590m |
| 2.80V | 94.087m | 52.895m | 146.855m |
| 2.90V | 94.233m | 52.980m | 147.104m |
| 3.00V | 94.370m | 53.060m | 147.338m |
| 3.10V | 94.500m | 53.135m | 147.560m |
| 3.20V | 94.624m | 53.207m | 147.772m |
| 3.30V | 94.744m | 53.276m | 147.976m |

| | | | |
|-------|----------|---------|----------|
| 3.40V | 94.859m | 53.343m | 148.174m |
| 3.50V | 94.974m | 53.408m | 148.367m |
| 3.60V | 95.089m | 53.475m | 148.560m |
| 3.70V | 95.208m | 53.543m | 148.757m |
| 3.80V | 95.336m | 53.617m | 148.963m |
| 3.90V | 95.478m | 53.699m | 149.186m |
| 4.00V | 95.641m | 53.792m | 149.436m |
| 4.10V | 95.833m | 53.902m | 149.725m |
| 4.20V | 96.065m | 54.035m | 150.067m |
| 4.30V | 96.347m | 54.196m | 150.479m |
| 4.40V | 96.693m | 54.394m | 150.981m |
| 4.50V | 97.117m | 54.635m | 151.594m |
| 4.60V | 97.636m | 54.930m | 152.342m |
| 4.70V | 98.266m | 55.287m | 153.252m |
| 4.80V | 99.024m | 55.716m | 154.350m |
| 4.90V | 99.931m | 56.227m | 155.666m |
| 5.00V | 101.005m | 56.831m | 157.230m |
| 5.10V | 102.264m | 57.539m | 159.070m |
| 5.20V | 103.730m | 58.361m | 161.218m |
| 5.30V | 105.422m | 59.308m | 163.704m |
| 5.40V | 107.357m | 60.391m | 166.555m |
| 5.50V | 109.556m | 61.618m | 169.801m |
| 5.60V | 112.034m | 63.000m | 173.468m |
| 5.70V | 114.809m | 64.545m | 177.581m |
| 5.80V | 117.897m | 66.263m | 182.163m |
| 5.90V | 121.311m | 68.160m | 187.235m |
| 6.00V | 125.066m | 70.245m | 192.816m |
| 6.10V | 129.172m | 72.524m | 198.924m |
| 6.20V | 133.642m | 75.002m | 205.573m |
| 6.30V | 138.485m | 77.685m | 212.776m |
| 6.40V | 143.709m | 80.578m | 220.544m |
| 6.50V | 149.320m | 83.683m | 228.885m |
| 6.60V | 155.326m | 87.004m | 237.805m |

|
 [Pullup]
 | pullup in the table = pullup subtract power_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|----------|----------|----------|
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |
| -2.00V | 303.830u | 217.155u | 404.033u |
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |

| | | | |
|--------|------------|------------|-------------|
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |
| -1.30V | 960.396u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -47.451m | -13.901m |
| 1.40V | -79.705m | -48.954m | -118.519m |
| 1.50V | -82.391m | -50.187m | -123.324m |
| 1.60V | -84.713m | -51.203m | -127.640m |
| 1.70V | -86.724m | -52.057m | -131.501m |
| 1.80V | -88.472m | -52.794m | -134.939m |
| 1.90V | -89.996m | -53.442m | -137.982m |
| 2.00V | -91.327m | -54.017m | -140.655m |
| 2.10V | -92.489m | -54.533m | -142.987m |
| 2.20V | -93.511m | -54.999m | -145.014m |
| 2.30V | -94.415m | -55.424m | -146.781m |
| 2.40V | -95.224m | -55.814m | -148.333m |
| 2.50V | -95.955m | -56.174m | -149.709m |
| 2.60V | -96.623m | -56.510m | -150.943m |
| 2.70V | -97.238m | -56.824m | -152.063m |
| 2.80V | -97.809m | -57.119m | -153.088m |
| 2.90V | -98.343m | -57.398m | -154.036m |
| 3.00V | -98.846m | -57.662m | -154.920m |
| 3.10V | -99.320m | -57.913m | -155.749m |
| 3.20V | -99.770m | -58.152m | -156.531m |
| 3.30V | -100.198m | -58.381m | -157.272m |
| 3.40V | -100.607m | -58.601m | -157.977m |
| 3.50V | -100.998m | -58.812m | -158.650m |
| 3.60V | -101.374m | -59.015m | -159.295m |
| 3.70V | -101.735m | -59.211m | -159.914m |
| 3.80V | -102.084m | -59.401m | -160.510m |

| | | | |
|-------|-----------|----------|-----------|
| 3.90V | -102.422m | -59.585m | -161.086m |
| 4.00V | -102.750m | -59.766m | -161.644m |
| 4.10V | -103.070m | -59.942m | -162.186m |
| 4.20V | -103.384m | -60.117m | -162.715m |
| 4.30V | -103.694m | -60.291m | -163.234m |
| 4.40V | -104.002m | -60.467m | -163.747m |
| 4.50V | -104.313m | -60.647m | -164.257m |
| 4.60V | -104.629m | -60.832m | -164.770m |
| 4.70V | -104.955m | -61.027m | -165.293m |
| 4.80V | -105.296m | -61.234m | -165.831m |
| 4.90V | -105.659m | -61.459m | -166.394m |
| 5.00V | -106.050m | -61.704m | -166.991m |
| 5.10V | -106.477m | -61.975m | -167.634m |
| 5.20V | -106.949m | -62.278m | -168.334m |
| 5.30V | -107.474m | -62.619m | -169.106m |
| 5.40V | -108.064m | -63.003m | -169.965m |
| 5.50V | -108.730m | -63.439m | -170.928m |
| 5.60V | -109.483m | -63.932m | -172.012m |
| 5.70V | -110.337m | -64.492m | -173.239m |
| 5.80V | -111.305m | -65.126m | -174.627m |
| 5.90V | -112.401m | -65.843m | -176.199m |
| 6.00V | -113.640m | -66.651m | -177.978m |
| 6.10V | -115.036m | -67.560m | -179.986m |
| 6.20V | -116.606m | -68.578m | -182.247m |
| 6.30V | -118.365m | -69.715m | -184.785m |
| 6.40V | -120.329m | -70.981m | -187.626m |
| 6.50V | -122.513m | -72.384m | -190.793m |
| 6.60V | -124.935m | -73.935m | -194.311m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -2.165 | -1.242 | -2.500 |
| -3.20V | -2.070 | -1.190 | -2.388 |
| -3.10V | -1.975 | -1.138 | -2.277 |
| -2.90V | -1.786 | -1.033 | -2.054 |
| -2.80V | -1.691 | -981.185m | -1.942 |
| -2.70V | -1.597 | -929.174m | -1.831 |
| -2.60V | -1.503 | -877.220m | -1.720 |
| -2.50V | -1.408 | -825.330m | -1.609 |
| -2.40V | -1.314 | -773.514m | -1.498 |
| -2.30V | -1.220 | -721.779m | -1.387 |
| -2.20V | -1.126 | -670.140m | -1.276 |
| -2.10V | -1.032 | -618.610m | -1.166 |
| -1.90V | -845.771m | -515.958m | -945.908m |
| -1.80V | -752.887m | -464.892m | -836.403m |
| -1.70V | -660.410m | -414.052m | -727.373m |
| -1.60V | -568.461m | -363.494m | -618.970m |
| -1.50V | -477.221m | -313.301m | -511.430m |
| -1.40V | -386.980m | -263.597m | -405.149m |
| -1.30V | -298.248m | -214.579m | -300.867m |
| -1.20V | -212.028m | -166.582m | -200.187m |
| -1.10V | -130.668m | -120.248m | -107.496m |
| -0.90V | -17.375m | -40.029m | -8.803m |

| | | | |
|--------|-----------|-----------|-----------|
| -0.80V | -2.837m | -14.886m | -3.451m |
| -0.70V | -656.331u | -3.014m | -1.195m |
| -0.60V | -116.521u | -336.317u | -201.636u |
| -0.50V | -10.789u | -41.964u | -13.420u |
| -0.40V | -580.051n | -4.632u | -416.799n |
| -0.30V | -27.994n | -450.005n | -11.484n |
| -0.20V | -1.269n | -41.862n | -311.158p |
| -0.10V | -74.463p | -4.218n | -27.092p |
| 0.00V | -26.215p | -1.078n | -18.737p |
| 0.10V | -22.114p | -826.325p | -16.303p |
| 0.20V | -19.278p | -754.146p | -13.966p |
| 0.30V | -16.497p | -694.188p | -11.632p |
| 0.40V | -13.726p | -635.953p | -9.300p |
| 0.50V | -10.963p | -578.437p | -6.968p |
| 0.60V | -8.203p | -521.365p | -4.637p |
| 0.70V | -5.446p | -464.595p | -2.307p |
| 0.80V | -2.691p | -408.039p | 22.980f |
| 0.90V | 62.079f | -351.636p | 2.353p |
| 1.10V | 5.566p | -239.133p | 7.011p |
| 1.20V | 8.316p | -182.975p | 9.340p |
| 1.30V | 11.067p | -126.851p | 11.669p |
| 1.40V | 13.817p | -70.743p | 13.998p |
| 1.50V | 16.567p | -14.634p | 16.327p |
| 1.60V | 19.317p | 41.493p | 18.656p |
| 1.70V | 22.067p | 97.654p | 20.985p |
| 1.80V | 24.817p | 153.868p | 23.313p |
| 1.90V | 27.568p | 210.159p | 25.642p |
| 2.10V | 33.072p | 323.083p | 30.300p |
| 2.20V | 35.825p | 379.789p | 32.629p |
| 2.30V | 38.581p | 436.650p | 34.958p |
| 2.40V | 41.339p | 492.867p | 37.288p |
| 2.50V | 44.098p | 547.026p | 39.618p |
| 2.60V | 46.849p | 600.695p | 41.948p |
| 2.70V | 49.356p | 654.682p | 44.279p |
| 2.80V | 51.378p | 709.650p | 46.611p |
| 2.90V | 53.315p | 776.122p | 48.939p |
| 3.10V | 57.193p | 4.552n | 52.772p |
| 3.20V | 59.183p | 44.522n | 54.319p |
| 3.30V | 62.959p | 466.732n | 55.861p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -26.215p | -450.005n | -11.632p |
| 3.40V | -74.463p | -4.632u | -13.966p |
| 3.50V | -1.269n | -41.964u | -16.303p |
| 3.60V | -27.994n | -336.317u | -18.737p |
| 3.70V | -580.051n | -3.014m | -27.092p |
| 3.80V | -10.789u | -14.886m | -311.158p |
| 3.90V | -116.521u | -40.029m | -11.484n |
| 4.10V | -2.837m | -120.248m | -13.420u |
| 4.20V | -17.375m | -166.582m | -201.636u |
| 4.30V | -60.888m | -214.579m | -1.195m |
| 4.40V | -130.668m | -263.597m | -3.451m |

| | | | |
|-------|-----------|-----------|-----------|
| 4.50V | -212.028m | -313.301m | -8.803m |
| 4.60V | -298.248m | -363.494m | -37.420m |
| 4.70V | -386.980m | -414.052m | -107.496m |
| 4.80V | -477.221m | -464.892m | -200.187m |
| 4.90V | -568.461m | -515.958m | -300.867m |
| 5.10V | -752.887m | -618.610m | -511.430m |
| 5.20V | -845.771m | -670.140m | -618.970m |
| 5.30V | -938.979m | -721.779m | -727.373m |
| 5.40V | -1.032 | -773.514m | -836.403m |
| 5.50V | -1.126 | -825.330m | -945.908m |
| 5.60V | -1.220 | -877.220m | -1.056 |
| 5.70V | -1.314 | -929.174m | -1.166 |
| 5.80V | -1.408 | -981.185m | -1.276 |
| 5.90V | -1.503 | -1.033 | -1.387 |
| 6.10V | -1.691 | -1.138 | -1.609 |
| 6.20V | -1.786 | -1.190 | -1.720 |
| 6.30V | -1.881 | -1.242 | -1.831 |
| 6.40V | -1.975 | -1.294 | -1.942 |
| 6.50V | -2.070 | -1.346 | -2.054 |
| 6.60V | -2.165 | -1.399 | -2.165 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|---------------|---------------|--------------|
| dV/dt_f | 2.00/112.556p | 1.82/199.937p | 2.17/74.356p |
| dV/dt_r | 2.02/146.245p | 1.84/252.851p | 2.20/93.872p |

R_load=10000ohms

| R_load was connected to ground for Ramp_up test and power for Ramp_dn test

|

|End model

[Model] ipadni_io | ""

Model_type I/O

Vinl = 0.8

Vinh = 2

| variable | typ | min | max |
|---------------------|-------|-------|-------|
| C_comp | 2.01p | 1.89p | 2.17p |
| [Temperature Range] | 40.0 | 0.0 | 120.0 |
| [Voltage Range] | 3.30V | 3.00V | 3.60V |

|

[Pulldown]

| pulldown in the table = pulldown subtract gnd_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -157.134u | -99.256u | -219.000u |
| -3.20V | -165.037u | -104.127u | -230.250u |
| -3.10V | -173.749u | -109.479u | -242.685u |
| -3.00V | -183.400u | -115.386u | -256.500u |
| -2.90V | -194.148u | -121.936u | -271.934u |
| -2.80V | -206.189u | -129.240u | -289.286u |
| -2.70V | -219.766u | -137.431u | -308.933u |
| -2.60V | -235.190u | -146.680u | -331.355u |
| -2.50V | -252.856u | -157.199u | -357.176u |

| | | | |
|--------|------------|------------|-----------|
| -2.40V | -273.283u | -169.265u | -387.219u |
| -2.30V | -297.162u | -183.236u | -422.595u |
| -2.20V | -325.427u | -199.590u | -464.837u |
| -2.10V | -359.384u | -218.976u | -516.117u |
| -2.00V | -400.901u | -242.299u | -579.623u |
| -1.90V | -452.750u | -270.851u | -660.217u |
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.755e-18 | 18.548e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 47.725m | 22.817m |
| 1.50V | 86.564m | 48.943m | 23.575m |
| 1.60V | 88.497m | 49.908m | 136.139m |
| 1.70V | 89.946m | 50.637m | 138.902m |
| 1.80V | 90.974m | 51.160m | 140.954m |
| 1.90V | 91.689m | 51.534m | 142.415m |
| 2.00V | 92.200m | 51.810m | 143.449m |
| 2.10V | 92.586m | 52.024m | 144.201m |
| 2.20V | 92.895m | 52.201m | 144.779m |
| 2.30V | 93.154m | 52.351m | 145.246m |
| 2.40V | 93.380m | 52.482m | 145.642m |
| 2.50V | 93.581m | 52.600m | 145.990m |
| 2.60V | 93.764m | 52.706m | 146.303m |
| 2.70V | 93.931m | 52.804m | 146.590m |
| 2.80V | 94.087m | 52.895m | 146.855m |
| 2.90V | 94.233m | 52.980m | 147.104m |
| 3.00V | 94.370m | 53.060m | 147.338m |

| | | | |
|-------|----------|---------|----------|
| 3.10V | 94.500m | 53.135m | 147.560m |
| 3.20V | 94.624m | 53.207m | 147.772m |
| 3.30V | 94.744m | 53.276m | 147.976m |
| 3.40V | 94.859m | 53.343m | 148.174m |
| 3.50V | 94.974m | 53.408m | 148.367m |
| 3.60V | 95.089m | 53.475m | 148.560m |
| 3.70V | 95.208m | 53.543m | 148.757m |
| 3.80V | 95.336m | 53.617m | 148.963m |
| 3.90V | 95.478m | 53.699m | 149.186m |
| 4.00V | 95.641m | 53.792m | 149.436m |
| 4.10V | 95.833m | 53.902m | 149.725m |
| 4.20V | 96.065m | 54.035m | 150.067m |
| 4.30V | 96.347m | 54.196m | 150.479m |
| 4.40V | 96.693m | 54.394m | 150.981m |
| 4.50V | 97.117m | 54.635m | 151.594m |
| 4.60V | 97.636m | 54.930m | 152.342m |
| 4.70V | 98.266m | 55.287m | 153.252m |
| 4.80V | 99.024m | 55.716m | 154.350m |
| 4.90V | 99.931m | 56.227m | 155.666m |
| 5.00V | 101.005m | 56.831m | 157.230m |
| 5.10V | 102.264m | 57.539m | 159.070m |
| 5.20V | 103.730m | 58.361m | 161.218m |
| 5.30V | 105.422m | 59.308m | 163.704m |
| 5.40V | 107.357m | 60.391m | 166.555m |
| 5.50V | 109.556m | 61.618m | 169.801m |
| 5.60V | 112.034m | 63.000m | 173.468m |
| 5.70V | 114.809m | 64.545m | 177.581m |
| 5.80V | 117.897m | 66.263m | 182.163m |
| 5.90V | 121.311m | 68.160m | 187.235m |
| 6.00V | 125.066m | 70.245m | 192.816m |
| 6.10V | 129.172m | 72.524m | 198.924m |
| 6.20V | 133.642m | 75.002m | 205.573m |
| 6.30V | 138.485m | 77.685m | 212.776m |
| 6.40V | 143.709m | 80.578m | 220.544m |
| 6.50V | 149.320m | 83.683m | 228.885m |
| 6.60V | 155.326m | 87.004m | 237.805m |

|
 [Pullup]
 | pullup in the table = pullup subtract power_clamp
 | Voltage I (typ) I (min) I (max)
 |

| | | | |
|--------|----------|----------|----------|
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |
| -2.00V | 303.830u | 217.155u | 404.033u |

| | | | |
|--------|------------|------------|-------------|
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |
| -1.30V | 960.396u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -47.451m | -13.901m |
| 1.40V | -79.705m | -48.954m | -118.519m |
| 1.50V | -82.391m | -50.187m | -123.324m |
| 1.60V | -84.713m | -51.203m | -127.640m |
| 1.70V | -86.724m | -52.057m | -131.501m |
| 1.80V | -88.472m | -52.794m | -134.939m |
| 1.90V | -89.996m | -53.442m | -137.982m |
| 2.00V | -91.327m | -54.017m | -140.655m |
| 2.10V | -92.489m | -54.533m | -142.987m |
| 2.20V | -93.511m | -54.999m | -145.014m |
| 2.30V | -94.415m | -55.424m | -146.781m |
| 2.40V | -95.224m | -55.814m | -148.333m |
| 2.50V | -95.955m | -56.174m | -149.709m |
| 2.60V | -96.623m | -56.510m | -150.943m |
| 2.70V | -97.238m | -56.824m | -152.063m |
| 2.80V | -97.809m | -57.119m | -153.088m |
| 2.90V | -98.343m | -57.398m | -154.036m |
| 3.00V | -98.846m | -57.662m | -154.920m |
| 3.10V | -99.320m | -57.913m | -155.749m |
| 3.20V | -99.770m | -58.152m | -156.531m |
| 3.30V | -100.198m | -58.381m | -157.272m |
| 3.40V | -100.607m | -58.601m | -157.977m |
| 3.50V | -100.998m | -58.812m | -158.650m |

| | | | |
|-------|-----------|----------|-----------|
| 3.60V | -101.374m | -59.015m | -159.295m |
| 3.70V | -101.735m | -59.211m | -159.914m |
| 3.80V | -102.084m | -59.401m | -160.510m |
| 3.90V | -102.422m | -59.585m | -161.086m |
| 4.00V | -102.750m | -59.766m | -161.644m |
| 4.10V | -103.070m | -59.942m | -162.186m |
| 4.20V | -103.384m | -60.117m | -162.715m |
| 4.30V | -103.694m | -60.291m | -163.234m |
| 4.40V | -104.002m | -60.467m | -163.747m |
| 4.50V | -104.313m | -60.647m | -164.257m |
| 4.60V | -104.629m | -60.832m | -164.770m |
| 4.70V | -104.955m | -61.027m | -165.293m |
| 4.80V | -105.296m | -61.234m | -165.831m |
| 4.90V | -105.659m | -61.459m | -166.394m |
| 5.00V | -106.050m | -61.704m | -166.991m |
| 5.10V | -106.477m | -61.975m | -167.634m |
| 5.20V | -106.949m | -62.278m | -168.334m |
| 5.30V | -107.474m | -62.619m | -169.106m |
| 5.40V | -108.064m | -63.003m | -169.965m |
| 5.50V | -108.730m | -63.439m | -170.928m |
| 5.60V | -109.483m | -63.932m | -172.012m |
| 5.70V | -110.337m | -64.492m | -173.239m |
| 5.80V | -111.305m | -65.126m | -174.627m |
| 5.90V | -112.401m | -65.843m | -176.199m |
| 6.00V | -113.640m | -66.651m | -177.978m |
| 6.10V | -115.036m | -67.560m | -179.986m |
| 6.20V | -116.606m | -68.578m | -182.247m |
| 6.30V | -118.365m | -69.715m | -184.785m |
| 6.40V | -120.329m | -70.981m | -187.626m |
| 6.50V | -122.513m | -72.384m | -190.793m |
| 6.60V | -124.935m | -73.935m | -194.311m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -2.165 | -1.242 | -2.500 |
| -3.20V | -2.070 | -1.190 | -2.388 |
| -3.10V | -1.975 | -1.138 | -2.277 |
| -2.90V | -1.786 | -1.033 | -2.054 |
| -2.80V | -1.691 | -981.185m | -1.942 |
| -2.70V | -1.597 | -929.174m | -1.831 |
| -2.60V | -1.503 | -877.220m | -1.720 |
| -2.50V | -1.408 | -825.330m | -1.609 |
| -2.40V | -1.314 | -773.514m | -1.498 |
| -2.30V | -1.220 | -721.779m | -1.387 |
| -2.20V | -1.126 | -670.140m | -1.276 |
| -2.10V | -1.032 | -618.610m | -1.166 |
| -1.90V | -845.771m | -515.958m | -945.908m |
| -1.80V | -752.887m | -464.892m | -836.403m |
| -1.70V | -660.410m | -414.052m | -727.373m |
| -1.60V | -568.461m | -363.494m | -618.970m |
| -1.50V | -477.221m | -313.301m | -511.430m |
| -1.40V | -386.980m | -263.597m | -405.149m |
| -1.30V | -298.248m | -214.579m | -300.867m |

| | | | |
|--------|-----------|-----------|-----------|
| -1.20V | -212.028m | -166.582m | -200.187m |
| -1.10V | -130.668m | -120.248m | -107.496m |
| -0.90V | -17.375m | -40.029m | -8.803m |
| -0.80V | -2.837m | -14.886m | -3.451m |
| -0.70V | -656.331u | -3.014m | -1.195m |
| -0.60V | -116.521u | -336.317u | -201.636u |
| -0.50V | -10.789u | -41.964u | -13.420u |
| -0.40V | -580.051n | -4.632u | -416.799n |
| -0.30V | -27.994n | -450.005n | -11.484n |
| -0.20V | -1.269n | -41.862n | -311.158p |
| -0.10V | -74.463p | -4.218n | -27.092p |
| 0.00V | -26.215p | -1.078n | -18.737p |
| 0.10V | -22.114p | -826.325p | -16.303p |
| 0.20V | -19.278p | -754.146p | -13.966p |
| 0.30V | -16.497p | -694.188p | -11.632p |
| 0.40V | -13.726p | -635.953p | -9.300p |
| 0.50V | -10.963p | -578.437p | -6.968p |
| 0.60V | -8.203p | -521.365p | -4.637p |
| 0.70V | -5.446p | -464.595p | -2.307p |
| 0.80V | -2.691p | -408.039p | 22.980f |
| 0.90V | 62.079f | -351.636p | 2.353p |
| 1.10V | 5.566p | -239.133p | 7.011p |
| 1.20V | 8.316p | -182.975p | 9.340p |
| 1.30V | 11.067p | -126.851p | 11.669p |
| 1.40V | 13.817p | -70.743p | 13.998p |
| 1.50V | 16.567p | -14.634p | 16.327p |
| 1.60V | 19.317p | 41.493p | 18.656p |
| 1.70V | 22.067p | 97.654p | 20.985p |
| 1.80V | 24.817p | 153.868p | 23.313p |
| 1.90V | 27.568p | 210.159p | 25.642p |
| 2.10V | 33.072p | 323.083p | 30.300p |
| 2.20V | 35.825p | 379.789p | 32.629p |
| 2.30V | 38.581p | 436.650p | 34.958p |
| 2.40V | 41.339p | 492.867p | 37.288p |
| 2.50V | 44.098p | 547.026p | 39.618p |
| 2.60V | 46.849p | 600.695p | 41.948p |
| 2.70V | 49.356p | 654.682p | 44.279p |
| 2.80V | 51.378p | 709.650p | 46.611p |
| 2.90V | 53.315p | 776.122p | 48.939p |
| 3.10V | 57.193p | 4.552n | 52.772p |
| 3.20V | 59.183p | 44.522n | 54.319p |
| 3.30V | 62.959p | 466.732n | 55.861p |

|
[POWER_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -26.215p | -450.005n | -11.632p |
| 3.40V | -74.463p | -4.632u | -13.966p |
| 3.50V | -1.269n | -41.964u | -16.303p |
| 3.60V | -27.994n | -336.317u | -18.737p |
| 3.70V | -580.051n | -3.014m | -27.092p |
| 3.80V | -10.789u | -14.886m | -311.158p |
| 3.90V | -116.521u | -40.029m | -11.484n |
| 4.10V | -2.837m | -120.248m | -13.420u |

| | | | |
|-------|-----------|-----------|-----------|
| 4.20V | -17.375m | -166.582m | -201.636u |
| 4.30V | -60.888m | -214.579m | -1.195m |
| 4.40V | -130.668m | -263.597m | -3.451m |
| 4.50V | -212.028m | -313.301m | -8.803m |
| 4.60V | -298.248m | -363.494m | -37.420m |
| 4.70V | -386.980m | -414.052m | -107.496m |
| 4.80V | -477.221m | -464.892m | -200.187m |
| 4.90V | -568.461m | -515.958m | -300.867m |
| 5.10V | -752.887m | -618.610m | -511.430m |
| 5.20V | -845.771m | -670.140m | -618.970m |
| 5.30V | -938.979m | -721.779m | -727.373m |
| 5.40V | -1.032 | -773.514m | -836.403m |
| 5.50V | -1.126 | -825.330m | -945.908m |
| 5.60V | -1.220 | -877.220m | -1.056 |
| 5.70V | -1.314 | -929.174m | -1.166 |
| 5.80V | -1.408 | -981.185m | -1.276 |
| 5.90V | -1.503 | -1.033 | -1.387 |
| 6.10V | -1.691 | -1.138 | -1.609 |
| 6.20V | -1.786 | -1.190 | -1.720 |
| 6.30V | -1.881 | -1.242 | -1.831 |
| 6.40V | -1.975 | -1.294 | -1.942 |
| 6.50V | -2.070 | -1.346 | -2.054 |
| 6.60V | -2.165 | -1.399 | -2.165 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|---------------|---------------|--------------|
| dV/dt_f | 2.00/113.266p | 1.82/197.371p | 2.17/74.028p |
| dV/dt_r | 2.02/147.014p | 1.84/251.849p | 2.20/93.411p |

R_load=10000ohms

| R_load was connected to ground for Ramp_up test and power for Ramp_dn test

|

|End model

[Model] ipado_3st | ""

| Model_type | typ | min | max |
|---------------------|-------|-------|-------|
| C_comp | 1.99p | 1.86p | 2.15p |
| [Temperature Range] | 40.0 | 0.0 | 120.0 |
| [Voltage Range] | 3.30V | 3.00V | 3.60V |

|

[Pulldown]

| pulldown in the table = pulldown subtract gnd_clamp

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -157.134u | -99.256u | -219.000u |
| -3.20V | -165.037u | -104.127u | -230.250u |
| -3.10V | -173.749u | -109.479u | -242.685u |
| -3.00V | -183.400u | -115.386u | -256.500u |
| -2.90V | -194.148u | -121.936u | -271.934u |
| -2.80V | -206.189u | -129.240u | -289.286u |
| -2.70V | -219.766u | -137.431u | -308.933u |
| -2.60V | -235.190u | -146.680u | -331.355u |

| | | | |
|--------|------------|------------|-----------|
| -2.50V | -252.856u | -157.199u | -357.176u |
| -2.40V | -273.283u | -169.265u | -387.219u |
| -2.30V | -297.162u | -183.236u | -422.595u |
| -2.20V | -325.427u | -199.590u | -464.837u |
| -2.10V | -359.384u | -218.976u | -516.117u |
| -2.00V | -400.901u | -242.299u | -579.623u |
| -1.90V | -452.750u | -270.851u | -660.217u |
| -1.80V | -519.217u | -306.549u | -765.681u |
| -1.70V | -607.277u | -352.346u | -909.270u |
| -1.60V | -729.045u | -413.024u | -1.115m |
| -1.50V | -907.407u | -496.811u | -1.434m |
| -1.40V | -1.191m | -619.011u | -1.987m |
| -1.30V | -1.699m | -811.079u | -3.133m |
| -1.20V | -2.799m | -1.146m | -6.243m |
| -1.10V | -5.689m | -1.822m | -12.974m |
| -1.00V | -10.416m | -3.302m | -17.948m |
| -0.90V | -12.342m | -5.449m | -17.964m |
| -0.80V | -11.672m | -6.479m | -16.692m |
| -0.70V | -10.528m | -6.146m | -15.152m |
| -0.60V | -9.204m | -5.387m | -13.338m |
| -0.50V | -7.770m | -4.535m | -11.313m |
| -0.40V | -6.286m | -3.652m | -9.190m |
| -0.30V | -4.766m | -2.754m | -6.999m |
| -0.20V | -3.214m | -1.846m | -4.740m |
| -0.10V | -1.627m | -928.990u | -2.410m |
| 0.00V | 32.755e-18 | 18.548e-18 | -1.607f |
| 0.10V | 1.604m | 910.814u | 2.391m |
| 0.20V | 3.124m | 1.775m | 4.661m |
| 0.30V | 4.566m | 2.595m | 6.817m |
| 0.40V | 5.928m | 3.372m | 8.858m |
| 0.50V | 7.210m | 4.105m | 10.784m |
| 0.60V | 8.411m | 4.792m | 12.593m |
| 0.70V | 9.529m | 5.432m | 14.284m |
| 0.80V | 10.562m | 6.023m | 15.855m |
| 0.90V | 11.508m | 6.563m | 17.306m |
| 1.00V | 12.367m | 7.051m | 18.639m |
| 1.10V | 13.138m | 7.486m | 19.856m |
| 1.20V | 13.821m | 7.865m | 20.957m |
| 1.30V | 14.417m | 8.189m | 21.944m |
| 1.40V | 14.930m | 47.725m | 22.817m |
| 1.50V | 86.564m | 48.943m | 23.575m |
| 1.60V | 88.497m | 49.908m | 136.139m |
| 1.70V | 89.946m | 50.637m | 138.902m |
| 1.80V | 90.974m | 51.160m | 140.954m |
| 1.90V | 91.689m | 51.534m | 142.415m |
| 2.00V | 92.200m | 51.810m | 143.449m |
| 2.10V | 92.586m | 52.024m | 144.201m |
| 2.20V | 92.895m | 52.201m | 144.779m |
| 2.30V | 93.154m | 52.351m | 145.246m |
| 2.40V | 93.380m | 52.482m | 145.642m |
| 2.50V | 93.581m | 52.600m | 145.990m |
| 2.60V | 93.764m | 52.706m | 146.303m |
| 2.70V | 93.931m | 52.804m | 146.590m |
| 2.80V | 94.087m | 52.895m | 146.855m |
| 2.90V | 94.233m | 52.980m | 147.104m |

| | | | |
|-------|----------|---------|----------|
| 3.00V | 94.370m | 53.060m | 147.338m |
| 3.10V | 94.500m | 53.135m | 147.560m |
| 3.20V | 94.624m | 53.207m | 147.772m |
| 3.30V | 94.744m | 53.276m | 147.976m |
| 3.40V | 94.859m | 53.343m | 148.174m |
| 3.50V | 94.974m | 53.408m | 148.367m |
| 3.60V | 95.089m | 53.475m | 148.560m |
| 3.70V | 95.208m | 53.543m | 148.757m |
| 3.80V | 95.336m | 53.617m | 148.963m |
| 3.90V | 95.478m | 53.699m | 149.186m |
| 4.00V | 95.641m | 53.792m | 149.436m |
| 4.10V | 95.833m | 53.902m | 149.725m |
| 4.20V | 96.065m | 54.035m | 150.067m |
| 4.30V | 96.347m | 54.196m | 150.479m |
| 4.40V | 96.693m | 54.394m | 150.981m |
| 4.50V | 97.117m | 54.635m | 151.594m |
| 4.60V | 97.636m | 54.930m | 152.342m |
| 4.70V | 98.266m | 55.287m | 153.252m |
| 4.80V | 99.024m | 55.716m | 154.350m |
| 4.90V | 99.931m | 56.227m | 155.666m |
| 5.00V | 101.005m | 56.831m | 157.230m |
| 5.10V | 102.264m | 57.539m | 159.070m |
| 5.20V | 103.730m | 58.361m | 161.218m |
| 5.30V | 105.422m | 59.308m | 163.704m |
| 5.40V | 107.357m | 60.391m | 166.555m |
| 5.50V | 109.556m | 61.618m | 169.801m |
| 5.60V | 112.034m | 63.000m | 173.468m |
| 5.70V | 114.809m | 64.545m | 177.581m |
| 5.80V | 117.897m | 66.263m | 182.163m |
| 5.90V | 121.311m | 68.160m | 187.235m |
| 6.00V | 125.066m | 70.245m | 192.816m |
| 6.10V | 129.172m | 72.524m | 198.924m |
| 6.20V | 133.642m | 75.002m | 205.573m |
| 6.30V | 138.485m | 77.685m | 212.776m |
| 6.40V | 143.709m | 80.578m | 220.544m |
| 6.50V | 149.320m | 83.683m | 228.885m |
| 6.60V | 155.326m | 87.004m | 237.805m |

|
 [Pullup]
 | pullup in the table = pullup subtract power_clamp
 | Voltage I (typ) I (min) I (max)

| | | | |
|--------|----------|----------|----------|
| -3.30V | 132.979u | 100.794u | 170.075u |
| -3.20V | 138.984u | 105.115u | 178.000u |
| -3.10V | 145.559u | 109.825u | 186.702u |
| -3.00V | 152.789u | 114.981u | 196.300u |
| -2.90V | 160.778u | 120.648u | 206.941u |
| -2.80V | 169.651u | 126.906u | 218.803u |
| -2.70V | 179.562u | 133.852u | 232.110u |
| -2.60V | 190.706u | 141.605u | 247.141u |
| -2.50V | 203.326u | 150.317u | 264.253u |
| -2.40V | 217.736u | 160.174u | 283.910u |
| -2.30V | 234.344u | 171.418u | 306.723u |
| -2.20V | 253.692u | 184.362u | 333.513u |
| -2.10V | 276.513u | 199.421u | 365.415u |

| | | | |
|--------|------------|------------|-------------|
| -2.00V | 303.830u | 217.155u | 404.033u |
| -1.90V | 337.102u | 238.340u | 451.722u |
| -1.80V | 378.494u | 264.081u | 512.067u |
| -1.70V | 431.351u | 296.004u | 590.810u |
| -1.60V | 501.113u | 336.601u | 697.730u |
| -1.50V | 597.240u | 389.880u | 850.877u |
| -1.40V | 737.641u | 462.700u | 1.087m |
| -1.30V | 960.396u | 567.748u | 1.497m |
| -1.20V | 1.361m | 731.012u | 2.348m |
| -1.10V | 2.237m | 1.013m | 4.712m |
| -1.00V | 4.644m | 1.583m | 10.148m |
| -0.90V | 8.090m | 2.907m | 12.062m |
| -0.80V | 8.032m | 4.727m | 11.029m |
| -0.70V | 7.118m | 4.754m | 9.778m |
| -0.60V | 6.128m | 4.128m | 8.443m |
| -0.50V | 5.109m | 3.441m | 7.052m |
| -0.40V | 4.082m | 2.746m | 5.644m |
| -0.30V | 3.056m | 2.053m | 4.233m |
| -0.20V | 2.033m | 1.363m | 2.821m |
| -0.10V | 1.014m | 678.856u | 1.410m |
| -0.00V | 58.687e-18 | 58.622e-18 | 117.504e-18 |
| 0.10V | -987.106u | -655.604u | -1.381m |
| 0.20V | -1.928m | -1.274m | -2.709m |
| 0.30V | -2.828m | -1.859m | -3.988m |
| 0.40V | -3.685m | -2.412m | -5.216m |
| 0.50V | -4.499m | -2.931m | -6.392m |
| 0.60V | -5.269m | -3.416m | -7.516m |
| 0.70V | -5.994m | -3.866m | -8.587m |
| 0.80V | -6.673m | -4.280m | -9.602m |
| 0.90V | -7.306m | -4.658m | -10.561m |
| 1.00V | -7.890m | -4.999m | -11.461m |
| 1.10V | -8.424m | -5.301m | -12.302m |
| 1.20V | -8.907m | -5.563m | -13.081m |
| 1.30V | -9.339m | -47.451m | -13.837m |
| 1.40V | -79.705m | -48.954m | -118.519m |
| 1.50V | -82.391m | -50.187m | -123.324m |
| 1.60V | -84.713m | -51.203m | -127.640m |
| 1.70V | -86.724m | -52.057m | -131.501m |
| 1.80V | -88.472m | -52.794m | -134.939m |
| 1.90V | -89.996m | -53.442m | -137.982m |
| 2.00V | -91.327m | -54.017m | -140.655m |
| 2.10V | -92.489m | -54.533m | -142.987m |
| 2.20V | -93.511m | -54.999m | -145.014m |
| 2.30V | -94.415m | -55.424m | -146.781m |
| 2.40V | -95.224m | -55.814m | -148.333m |
| 2.50V | -95.955m | -56.174m | -149.709m |
| 2.60V | -96.623m | -56.510m | -150.943m |
| 2.70V | -97.238m | -56.824m | -152.063m |
| 2.80V | -97.809m | -57.119m | -153.088m |
| 2.90V | -98.343m | -57.398m | -154.036m |
| 3.00V | -98.846m | -57.662m | -154.920m |
| 3.10V | -99.320m | -57.913m | -155.749m |
| 3.20V | -99.770m | -58.152m | -156.531m |
| 3.30V | -100.198m | -58.381m | -157.272m |
| 3.40V | -100.607m | -58.601m | -157.977m |

| | | | |
|-------|-----------|----------|-----------|
| 3.50V | -100.998m | -58.812m | -158.650m |
| 3.60V | -101.374m | -59.015m | -159.295m |
| 3.70V | -101.735m | -59.211m | -159.914m |
| 3.80V | -102.084m | -59.401m | -160.510m |
| 3.90V | -102.422m | -59.585m | -161.086m |
| 4.00V | -102.750m | -59.766m | -161.644m |
| 4.10V | -103.070m | -59.942m | -162.186m |
| 4.20V | -103.384m | -60.117m | -162.715m |
| 4.30V | -103.694m | -60.291m | -163.234m |
| 4.40V | -104.002m | -60.467m | -163.747m |
| 4.50V | -104.313m | -60.647m | -164.257m |
| 4.60V | -104.629m | -60.832m | -164.770m |
| 4.70V | -104.955m | -61.027m | -165.293m |
| 4.80V | -105.296m | -61.234m | -165.831m |
| 4.90V | -105.659m | -61.459m | -166.394m |
| 5.00V | -106.050m | -61.704m | -166.991m |
| 5.10V | -106.477m | -61.975m | -167.634m |
| 5.20V | -106.949m | -62.278m | -168.334m |
| 5.30V | -107.474m | -62.619m | -169.106m |
| 5.40V | -108.064m | -63.003m | -169.965m |
| 5.50V | -108.730m | -63.439m | -170.928m |
| 5.60V | -109.483m | -63.932m | -172.012m |
| 5.70V | -110.337m | -64.492m | -173.239m |
| 5.80V | -111.305m | -65.126m | -174.627m |
| 5.90V | -112.401m | -65.843m | -176.199m |
| 6.00V | -113.640m | -66.651m | -177.978m |
| 6.10V | -115.036m | -67.560m | -179.986m |
| 6.20V | -116.606m | -68.578m | -182.247m |
| 6.30V | -118.365m | -69.715m | -184.785m |
| 6.40V | -120.329m | -70.981m | -187.626m |
| 6.50V | -122.513m | -72.384m | -190.793m |
| 6.60V | -124.935m | -73.935m | -194.311m |

|
[GND_clamp]

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| -3.30V | -2.165 | -1.242 | -2.500 |
| -3.20V | -2.070 | -1.190 | -2.388 |
| -3.10V | -1.975 | -1.138 | -2.277 |
| -2.90V | -1.786 | -1.033 | -2.054 |
| -2.80V | -1.691 | -981.185m | -1.942 |
| -2.70V | -1.597 | -929.174m | -1.831 |
| -2.60V | -1.503 | -877.220m | -1.720 |
| -2.50V | -1.408 | -825.330m | -1.609 |
| -2.40V | -1.314 | -773.514m | -1.498 |
| -2.30V | -1.220 | -721.779m | -1.387 |
| -2.20V | -1.126 | -670.140m | -1.276 |
| -2.10V | -1.032 | -618.610m | -1.166 |
| -1.90V | -845.771m | -515.958m | -945.908m |
| -1.80V | -752.887m | -464.892m | -836.403m |
| -1.70V | -660.410m | -414.052m | -727.373m |
| -1.60V | -568.461m | -363.494m | -618.970m |
| -1.50V | -477.221m | -313.301m | -511.430m |
| -1.40V | -386.980m | -263.597m | -405.149m |

| | | | |
|--------|-----------|-----------|-----------|
| -1.30V | -298.248m | -214.579m | -300.867m |
| -1.20V | -212.028m | -166.582m | -200.187m |
| -1.10V | -130.668m | -120.248m | -107.496m |
| -0.90V | -17.375m | -40.029m | -8.803m |
| -0.80V | -2.837m | -14.886m | -3.451m |
| -0.70V | -656.331u | -3.014m | -1.195m |
| -0.60V | -116.521u | -336.317u | -201.636u |
| -0.50V | -10.789u | -41.964u | -13.420u |
| -0.40V | -580.051n | -4.632u | -416.799n |
| -0.30V | -27.994n | -450.005n | -11.484n |
| -0.20V | -1.269n | -41.862n | -311.158p |
| -0.10V | -74.463p | -4.218n | -27.092p |
| 0.00V | -26.215p | -1.078n | -18.737p |
| 0.10V | -22.114p | -826.325p | -16.303p |
| 0.20V | -19.278p | -754.146p | -13.966p |
| 0.30V | -16.497p | -694.188p | -11.632p |
| 0.40V | -13.726p | -635.953p | -9.300p |
| 0.50V | -10.963p | -578.437p | -6.968p |
| 0.60V | -8.203p | -521.365p | -4.637p |
| 0.70V | -5.446p | -464.595p | -2.307p |
| 0.80V | -2.691p | -408.039p | 22.980f |
| 0.90V | 62.079f | -351.636p | 2.353p |
| 1.10V | 5.566p | -239.133p | 7.011p |
| 1.20V | 8.316p | -182.975p | 9.340p |
| 1.30V | 11.067p | -126.851p | 11.669p |
| 1.40V | 13.817p | -70.743p | 13.998p |
| 1.50V | 16.567p | -14.634p | 16.327p |
| 1.60V | 19.317p | 41.493p | 18.656p |
| 1.70V | 22.067p | 97.654p | 20.985p |
| 1.80V | 24.817p | 153.868p | 23.313p |
| 1.90V | 27.568p | 210.159p | 25.642p |
| 2.10V | 33.072p | 323.083p | 30.300p |
| 2.20V | 35.825p | 379.789p | 32.629p |
| 2.30V | 38.581p | 436.650p | 34.958p |
| 2.40V | 41.339p | 492.867p | 37.288p |
| 2.50V | 44.098p | 547.026p | 39.618p |
| 2.60V | 46.849p | 600.695p | 41.948p |
| 2.70V | 49.356p | 654.682p | 44.279p |
| 2.80V | 51.378p | 709.650p | 46.611p |
| 2.90V | 53.315p | 776.122p | 48.939p |
| 3.10V | 57.193p | 4.552n | 52.772p |
| 3.20V | 59.183p | 44.522n | 54.319p |
| 3.30V | 62.959p | 466.732n | 55.861p |

|
[POWER_clamp]
|

| Voltage | I (typ) | I (min) | I (max) |
|---------|-----------|-----------|-----------|
| 3.30V | -26.215p | -450.005n | -11.632p |
| 3.40V | -74.463p | -4.632u | -13.966p |
| 3.50V | -1.269n | -41.964u | -16.303p |
| 3.60V | -27.994n | -336.317u | -18.737p |
| 3.70V | -580.051n | -3.014m | -27.092p |
| 3.80V | -10.789u | -14.886m | -311.158p |
| 3.90V | -116.521u | -40.029m | -11.484n |

| | | | |
|-------|-----------|-----------|-----------|
| 4.10V | -2.837m | -120.248m | -13.420u |
| 4.20V | -17.375m | -166.582m | -201.636u |
| 4.30V | -60.888m | -214.579m | -1.195m |
| 4.40V | -130.668m | -263.597m | -3.451m |
| 4.50V | -212.028m | -313.301m | -8.803m |
| 4.60V | -298.248m | -363.494m | -37.420m |
| 4.70V | -386.980m | -414.052m | -107.496m |
| 4.80V | -477.221m | -464.892m | -200.187m |
| 4.90V | -568.461m | -515.958m | -300.867m |
| 5.10V | -752.887m | -618.610m | -511.430m |
| 5.20V | -845.771m | -670.140m | -618.970m |
| 5.30V | -938.979m | -721.779m | -727.373m |
| 5.40V | -1.032 | -773.514m | -836.403m |
| 5.50V | -1.126 | -825.330m | -945.908m |
| 5.60V | -1.220 | -877.220m | -1.056 |
| 5.70V | -1.314 | -929.174m | -1.166 |
| 5.80V | -1.408 | -981.185m | -1.276 |
| 5.90V | -1.503 | -1.033 | -1.387 |
| 6.10V | -1.691 | -1.138 | -1.609 |
| 6.20V | -1.786 | -1.190 | -1.720 |
| 6.30V | -1.881 | -1.242 | -1.831 |
| 6.40V | -1.975 | -1.294 | -1.942 |
| 6.50V | -2.070 | -1.346 | -2.054 |
| 6.60V | -2.165 | -1.399 | -2.165 |

|

[Ramp]

| Voltage | I (typ) | I (min) | I (max) |
|--|---------------|---------------|--------------|
| | | | |
| dV/dt_f | 1.99/130.331p | 1.81/220.000p | 2.17/83.712p |
| | | | |
| dV/dt_r | 2.03/153.657p | 1.84/260.814p | 2.20/92.663p |
| R_load=10000ohms | | | |
| R_load was connected to ground for Ramp_up test and power for Ramp_dn test | | | |
| | | | |
| End model | | | |
| [End] | | | |



NOTES

Index

A

ac electrical characteristics 4

B

Boundary Scan (JTAG Port) timing diagram 54

bus

external address 4

external data 4

C

Clock 4

clock

external 4

operation 6

clocks

internal 4

configuration 3

D

dc electrical characteristics 3

design considerations

electrical 3

PLL 4

power consumption 3

thermal 1

DRAM

out of page

wait states selection guide 27

out of page and refresh timings

11 wait states 31

15 wait states 33

4 wait states 27

8 wait states 29

Page mode

read accesses 26

wait states selection guide 17

write accesses 25

Page mode timings

1 wait state 17

2 wait states 20

3 wait states 22

4 wait states 23

refresh access 37

E

electrical design considerations 3

emory 3

Enhanced Serial Audio Interface 9

ESAI 9

receiver timing 51, 52

timings 47

transmitter timing 50

EXTAL jitter 4

external address bus 4

external bus control 4, 5

external clock operation 4

external data bus 4

external interrupt timing (negative edge-triggered)

11

external level-sensitive fast interrupt timing 10

external memory access (DMA Source) timing 12

External Memory Expansion Port 4, 12

F

functional signal groups 1

G

GPIO timing 52

Ground 3
PLL 3

I

internal clocks 4
interrupt and mode control 6
interrupt control 6
interrupt timing 7
 external level-sensitive fast 10
 external negative edge-triggered 11

J

Jitter 4
JTAG 12
JTAG Port
 timing 53, 54

M

maximum ratings 1, 2
Memory 3
Memory Configuration 3
mode control 6
Mode select timing 7

O

OnCE module 12
operating mode select timing 11

P

package
 TQFP description 1, 3
Peripheral modules 3
Phase Lock Loop 6
PLL 4, 6
 Characteristics 6
 performance issues 4
PLL design considerations 4
PLL performance issues 4
Port A 4
Port C 9
Power 2
power consumption design considerations 3

R

recovery from Stop state using IRQA 11, 12
RESET 6
Reset timing 7, 10

S

Serial Audio Interface (ESAI) 3
Serial Host Interface 7
Serial Host Interface (SHI) 3
SHI 7
signal groupings 1
signals 1
SRAM

read and write accesses 12
Stop state
 recovery from 11, 12
Stop timing 7
supply voltage 2

T

Test Access Port timing diagram 55
Test Clock (TCLK) input timing diagram 54
thermal characteristics 2
thermal design considerations 1
Timing
 Enhanced Serial Audio Interface (ESAI) 50
 General Purpose I/O (GPIO) Timing 47
 OnCE™ (On Chip Emulator) Timing 47
 Serial Host Interface (SHI) SPI Protocol Tim-
 ing 37
 Serial Host Interface (SHI) Timing 37
timing
 interrupt 7
 mode select 7
 Reset 7
 Stop 7
TQFP
 pin list by number 3
 pin-out drawing (top) 1

How to Reach Us:

Home Page:
www.freescale.com

E-mail:
support@freescale.com

USA/Europe or Locations Not Listed:
Freescale Semiconductor
Technical Information Center, CH370
1300 N. Alma School Road
Chandler, Arizona 85224
+1-800-521-6274 or +1-480-768-2130
support@freescale.com

Europe, Middle East, and Africa:
Freescale Halbleiter Deutschland GmbH
Technical Information Center
Schatzbogen 7
81829 Muenchen, Germany
+44 1296 380 456 (English)
+46 8 52200080 (English)
+49 89 92103 559 (German)
+33 1 69 35 48 48 (French)
support@freescale.com

Japan:
Freescale Semiconductor Japan Ltd.
Headquarters
ARCO Tower 15F
1-8-1, Shimo-Meguro, Meguro-ku,
Tokyo 153-0064, Japan
0120 191014 or +81 3 5437 9125
support.japan@freescale.com

Asia/Pacific:
Freescale Semiconductor Hong Kong Ltd.
Technical Information Center
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T., Hong Kong
+800 2666 8080
support.asia@freescale.com

For Literature Requests Only:
Freescale Semiconductor Literature Distribution Center
P.O. Box 5405
Denver, Colorado 80217
1-800-521-6274 or 303-675-2140
Fax: 303-675-2150
LDCForFreescaleSemiconductor@hibbertgroup.com

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners.

© Freescale Semiconductor, Inc. 2006. All rights reserved.

RoHS-compliant and/or Pb-free versions of Freescale products have the functionality and electrical characteristics of their non-RoHS-compliant and/or non-Pb-free counterparts. For further information, see <http://www.freescale.com> or contact your Freescale sales representative.

For information on Freescale's Environmental Products program, go to <http://www.freescale.com/epp>.