


**3A 200A Axial**
**SBD Type: 30PHA20**

OUTLINE DRAWING

**FEATURES**

- \* High VRM SBD
- \* Low Forward Voltage Drop
- \* Low Power Loss, High Efficiency
- \* High Surge Capability


**Maximum Ratings**

Apporox Net Weight:1.19g


Rating	Symbol	30PHA20		Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	200		V
Average Rectified Output Current	$I_O$	3.0	50Hz Half Sine Wave Resistive Load	A
		1.4		
RMS Forward Current	$I_{F(RMS)}$	4.71		A
Surge Forward Current	$I_{FSM}$	60	50Hz Half Sine Wave, 1cycle, Non-repetitive	A
Operating Junction Temperature Range	$T_{jw}$	- 40 to + 150		°C
Storage Temperature Range	$T_{stg}$	- 40 to + 150		°C

**Electrical/Thermal • Characteristics**



Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	$I_{RM}$	$T_j = 25^\circ\text{C}$ , $V_{RM} = V_{RRM}$	-	-	200	$\mu\text{A}$
Peak Forward Voltage	$V_{FM}$	$T_j = 25^\circ\text{C}$ , $I_{FM} = 3\text{ A}$	-	-	0.90	V
Thermal Resistance	$R_{th(j-l)}$	Junction to Lead	-	-	8	°C/W
	$R_{th(j-a)}$	Junction to Ambient *			80	

\*: Print Lands 5x5mm, Both sides


30PHA\_ OUTLINE DRAWING (Dimensions in mm)



### FORWARD CURRENT VS. VOLTAGE




### AVERAGE FORWARD POWER DISSIPATION





### PEAK REVERSE CURRENT VS. PEAK REVERSE VOLTAGE

$T_j = 150\text{ }^\circ\text{C}$





### AVERAGE REVERSE POWER DISSIPATION






### AVERAGE FORWARD CURRENT VS. LEAD TEMPERATURE

$V_{RM}=200V$



### AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE


Without Fin or P.C. Board,  $V_{RM}=200V$



### SURGE CURRENT RATINGS

f=50Hz, Half Sine Wave, Non-Repetitive, No Load

30PHA20



### JUNCTION CAPACITANCE VS. REVERSE VOLTAGE

T<sub>j</sub>=25°C, V<sub>m</sub>=20mV<sub>RMS</sub>, f=100kHz, Typical Value

30PHA20

