TOSHIBA 5VHZ52

TOSHIBA RECTIFIER SILICON DIFFUSED TYPE

5 V H Z 5 2

MOST SUITABLE FOR COLOR T.V. DAMPER

Repetitive Peak Reverse Voltage: VRRM=1700V


Average Forward Current $: I_{F(AV)} = 5A$

Reverse Recovery Time $: t_{rr} = 1.5 \mu s$

High Reliability

MAXIMUM RATINGS (Ta = 25°C)

| CHARACTERISTIC | SYMBOL | RATING | UNIT | |
|----------------------------------|--------------------|-----------|------|--|
| Repetitive Peak Reverse Voltage | v_{RRM} | 1700 | V | |
| Average Output Rectified Current | IO | 5 | A | |
| Peak One Cycle Surge Forward | Tenana | 50 (50Hz) | A | |
| Current (Non-Repetitive) | $_{ m IFSM}$ | 60 (60Hz) | | |
| Junction Temperature | $T_{\rm j}$ | -40~150 | °C | |
| Storage Temperature Range | $\mathrm{T_{stg}}$ | -40~150 | °C | |
| Screq Torque | _ | 0.6 | N⋅m | |



Unit in mm


3-16C2(1) **TOSHIBA**

Weight: 5.5g (Typ.)

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

| CHARACTERISTIC | SYMBOL | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|------------------------------------|----------------------|-------------------------------|------|------|------|----------------|
| Peak Forward Voltage | $V_{	extbf{FM}}$ | I _{FM} =5A | _ | _ | 1.5 | V |
| Repetitive Peak Reverse Current | I_{RRM} | $V_{RRM} = 1700V$ | _ | _ | 100 | μ A |
| Reverse Recovery Time | t _{rr} | I_{F} =0.1A, I_{DC} =0.1A | _ | _ | 1.5 | μs |
| Thermal Resistance | $R_{	ext{th (j-c)}}$ | DC | _ | _ | 2.5 | °C/W |

MARKING



| %1 | TYPE | 5VHZ52 | | | |
|-----------|---|--------|--|--|--|
| %2 | Polarity Mark | + | | | |
| *3 | Lot Number —Month (Starting from Alphabet A) Year (Last Number of the Christian Er | | | | |

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

 The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

 The information contained herein is subject to change without notice.

