



## AOU456 N-Channel Enhancement Mode Field Effect Transistor




### General Description

The AOU456 uses advanced trench technology and design to provide excellent  $R_{DS(ON)}$  with low gate charge. This device is suitable for use in PWM, load switching and general purpose applications. Standard Product AOU456 is Pb-free (meets ROHS & Sony 259 specifications). AOU456L is a Green Product ordering option. AOU456 and AOU456L are electrically identical.


### Features

$V_{DS} (V) = 25V$   
 $I_D = 50A (V_{GS} = 10V)$   
 $R_{DS(ON)} < 7 m\Omega (V_{GS} = 10V)$   
 $R_{DS(ON)} < 10 m\Omega (V_{GS} = 4.5V)$

TO-251



Top View  
Drain Connected to Tab



### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	25	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>G</sup>	$I_D$	50	A
$T_C=100^\circ C$		50	
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	150	
Avalanche Current <sup>C</sup>	$I_{AR}$	30	A
Repetitive avalanche energy $L=0.1mH$ <sup>C</sup>	$E_{AR}$	45	mJ
Power Dissipation <sup>B</sup>	$P_D$	50	W
$T_C=25^\circ C$		25	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 175	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	41	50	°C/W
Maximum Junction-to-Case <sup>B</sup>	$R_{\theta JC}$	2.1	3	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	25			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=20\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$	0.01	1	5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm20\text{V}$			100	nA
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1	1.74	3	V
$I_{D(\text{ON})}$	On state drain current	$V_{GS}=10\text{V}, V_{DS}=5\text{V}$	100			A
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=20\text{A}$		5.5	7	$\text{m}\Omega$
			$T_J=125^\circ\text{C}$	8		
		$V_{GS}=4.5\text{V}, I_D=20\text{A}$		8.5	10	
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=20\text{A}$		45		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.74	1	V
$I_S$	Maximum Body-Diode Continuous Current				50	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=12.5\text{V}, f=1\text{MHz}$		1850	2220	pF
$C_{oss}$	Output Capacitance			472		pF
$C_{rss}$	Reverse Transfer Capacitance			275		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.86	1.2	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=12.5\text{V}, I_D=20\text{A}$		31.7	38	nC
$Q_g(4.5\text{V})$	Total Gate Charge			15.7	19	nC
$Q_{gs}$	Gate Source Charge			5.8		nC
$Q_{gd}$	Gate Drain Charge			8.2		nC
$t_{D(\text{on})}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=12.5\text{V}, R_L=0.625\Omega, R_{\text{GEN}}=3\Omega$		7.5		ns
$t_r$	Turn-On Rise Time			14		ns
$t_{D(\text{off})}$	Turn-Off Delay Time			30		ns
$t_f$	Turn-Off Fall Time			11.5		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=20\text{A}, dI/dt=100\text{A}/\mu\text{s}$		30.9	37	ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=20\text{A}, dI/dt=100\text{A}/\mu\text{s}$		20.3		nC

A: The value of  $R_{\text{JJA}}$  is measured with the device in a still air environment with  $T_A=25^\circ\text{C}$ .

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=175^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C: Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=175^\circ\text{C}$ .

D. The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to case  $R_{\text{JJC}}$  and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using  $<300\ \mu\text{s}$  pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of  $T_{J(\text{MAX})}=175^\circ\text{C}$ .

G. The maximum current rating is limited by bond-wires. Rev1: August 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

Figure 12: Single Pulse Avalanche capability




Figure 13: Power De-rating (Note B)




Figure 14: Current De-rating (Note B)