


STEREO AUDIO AMPLIFIER

DESCRIPTION

The AV2025 is a monolithic integrated circuit consisting of a 2 channel power amplifier. It is suitable for stereo and bridge amplifier application of radio cassette tape recorders.


FEATURES

Bridge or stereo configuration.
Few External components
High Channel isolation
Voltage range : 3V to 12V
Power on/off no noise
Voltage gain up to 45dB(Adjustable with external resistor)
Soft clipping
Internal Thermal protection
Working Voltage down to 3V




DIP-16

BLOCK DIAGRAM



PIN CONFIGURATION



ORDERING INFORMATION

PIN	SYMBOL	PIN	SYMBOL
1	AUX _{BTL}	9	GND
2	2OUT	10	1IN
3	2BS	11	1FB
4	2GND _p	12	1GND _p
5	2GND _p	13	1GND _p
6	2FB	14	1BS
7	2IN	15	1OUT
8	FIL	16	VCC

ABSOLUTE MAXIMUM RATINGS (T_{amb}=25°C)


PARAMETER	SYMBOL	VALUE	UNIT
Supply	V _{cc}	15	V
Output Peak Current	I _{op}	1.5	A
Junction Temperature	T _j	150°C	°C
Storage Temperature	T _s	-40°C ~+150°C	°C

ELECTRICAL CHARACTERISTICS(T_A=+25°C, V_{cc}=9V, f=1KHz, R_L=8Ω, unless otherwise specified).


PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Supply Voltage	V _{cc}			3	-	12	V
Quiescent Current	I _{cc}	V _i =0, Stereo		-	40	50	mA
Quiescent Output Voltage	V _o (DC)			4.0	4.5	5.0	V
Closed Loop Voltage Gain	A _v	Stereo	V _i =-45dBm	43	45	47	dB
		Bridge		49	51	53	
Channel Balance	CB	Stereo		-1	0	+1	dB
Total Harmonic Distortion	THD	Stereo	P _o =250mW, f=1kHz, R _L =4Ω, V _{cc} =9V	-	0.3	1.5	%
		Bridge		-	0.5	-	

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT	
Input Resistance	Zi				30		K Ω	
Channel Separation	CSR	Rg=10K Ω ,f=1kHz, RL=4 Ω ,Po=1W		40	55	-	dB	
Ripple Rejection	Srip	Rg=0,frip=100Hz, Vrip=150mV,Av=45dB		40	46	-	dB	
Input Noise Voltage	VNI	BW:20Hz- 20kHz,Av=200	Rg=0 Ω	-	1.5	3	uV	
			Rg=10K Ω	-	3	6		
Output Power	Po	THD= 10%,f= 1kHz	Stereo	Vcc=9V,RL=4 Ω	1.7	2.3	-	W
				Vcc=6V,RL=8 Ω	-	1.3	-	
				Vcc=6V,RL=4 Ω	0.7	1.0	-	
				Vcc=6V,RL=8 Ω	-	0.6	-	
				Vcc=3V,RL=4 Ω	-	0.1	-	
			Bridge	Vcc=9V,RL=8 Ω	-	4.7	-	
				Vcc=6V,RL=4 Ω	-	2.8	-	

APPLICATION CIRCUIT



(1.STEREO)



(2.BRIDGE)

TYPICAL PERFORMANCE CHARACTERISTICS

