


E-Series Surface Mount Mixer 5 – 1000 MHz




Features

- LO Power +7 dBm
- Up to +1 dBm RF
- Surface Mount
- Low Profile



SM-89 Package

Note: Non Hermetic Package



Description

M/A-COM's ELCM-2 is a Low Cost, Broadband, high performance Double Balanced Mixer designed for use in high volume wireless applications. The device has been optimized by careful selection of the Schottky Diode and Balun Transformer for excellent performance. ELCM-2 is available in an SM-89 surface mount package and reflows using standard soldering reflow profiles.

Electrical Specifications @ +25°C, Z₀ = 50 Ohms, LO = +7dBm

Parameter	Units	Minimum	Typical	Maximum
Frequency Range				
RF	5 - 1000	—	—	—
LO	5 - 1000	—	—	—
IF	DC - 1000	—	—	—
Conversion Loss				
10 - 500	dB	—	6.5	8.0
5 - 1000	dB	—	7.0	9.5
Isolation (LO - RF)				
5 - 50	MHz	40	60	—
50 - 500	MHz	20	40	—
500 - 1000	MHz	18	25	—
Isolation (LO - IF)				
5 - 50	MHz	30	55	—
50 - 500	MHz	20	30	—
500 - 1000	MHz	12	20	—
RF Input for 1dB Compression	dBm	—	—	+1


V3.00 S 1352



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks.
Specifications subject to change without notice.



Absolute Maximum Ratings


Parameter	Absolute Maximum
RF Power	50 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to +100°C
Operating Temperature	-55°C to +100°C
Pin Temperature (10 Seconds)	260°C

Functional Configuration


Function	Pin No.
LO	1
RF	4
IF	5
Ground	2, 3, 6
Case Ground	—
Unconnected	—

Typical Performance @ +25°C


Conversion Loss



L-R Isolation



L-I Isolation



V3.00 S 1352



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks. Specifications subject to change without notice.

