



MBRS1035CT THRU MBRS10100CT

10.0 AMPS. Schottky Barrier Rectifiers



Voltage Range
35 to 100 Volts
Current
10.0 Amperes



Features

- ✧ Plastic material used carries Underwriters Laboratory Classifications 94V-0
- ✧ Metal silicon junction, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ Guardring for overvoltage protection
- ✧ High temperature soldering guaranteed: 260°C/10 seconds, 0.25"(6.35mm) from case

Mechanical Data

- ✧ Cases: JEDEC D2PAK molded plastic body
- ✧ Terminals: Lead solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in. - lbs. max
- ✧ Weight: 0.08 ounce, 2.24 grams

D2PAK



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	MBSR 1035 CT	MBSR 1045 CT	MBSR 1050 CT	MBSR 1060 CT	MBSR 1090 CT	MBSR 10100 CT	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	35	45	50	60	90	100	V
Maximum RMS Voltage	V_{RMS}	24	31	35	42	63	70	V
Maximum DC Blocking Voltage	V_{DC}	35	45	50	60	90	100	V
Maximum Average Forward Rectified Current See Fig. 1	$I_{(AV)}$	10						A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	150						A
Peak Repetitive Reverse Surge Current (Note 1)	I_{RRM}	0.5						A
Maximum Instantaneous Forward Voltage at (Note 2) $I_F=5.0A, T_c=25^\circ C$ $I_F=5.0A, T_c=125^\circ C$ $I_F=10A, T_c=25^\circ C$ $I_F=10A, T_c=125^\circ C$	V_F	0.70 0.57		0.80 0.65		0.85 0.75 0.95 0.85		V
Maximum Instantaneous Reverse Current @ $T_c=25^\circ C$ at Rated DC Blocking Voltage (Note 2) @ $T_c=125^\circ C$	I_R			0.1 6.0				mA mA
Maximum Thermal Resistance, Junction to Case	$R_{\theta JC}$	2.0						°C/W
Operating Junction Temperature Range	T_J	-65 to +150						°C
Storage Temperature Range	T_{STG}	-65 to +175						°C

- Notes: 1. 2.0us Pulse Width, f=1.0 KHz
2. Pulse Test: 300us Pulse Width, 1% Duty Cycle
3. Thermal Resistance from Junction to Case Per Leg.



RATINGS AND CHARACTERISTIC CURVES (MBRS1035CT THRU MBRS10100CT)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS PER LEG

