

ELLIPSE (4.7 X 5.7) High Performance AlInGaP LED Lamps

MVL-663UOLK-S

Description

The MVL-663UOLK-S , utilizes the latest absorbing substrate Aluminum Indium Gallium Phosphide (AlInGaP) LED technology. This LED material has outstanding light output efficiency over a wide range of drive current. The package is ellipse transparent red color plastic type.


Applications

- Full color displays & moving message signs
- Solid state incandescent replacement bulbs
- High ambient panel indicators
- Color printers & scanners
- Medical & Analytical instruments

Features

- Ultra - brightness
- Low power consumption
- TTL compatible
- Reliable
- Stopper

Package Dimensions



Notes :

1. Tolerance is ± 0.25 mm (.010") unless otherwise noted.
2. Protruded resin under flange is 1.5 mm (.059") max.
3. Lead spacing is measured where the leads emerge from the package.

Absolute Maximum Ratings

@ $T_A=25^\circ\text{C}$

Parameter	Symbol	Maximum Rating	Unit
Power Dissipation	P_{ad}	110	mW
Peak Forward Current(1/10 Duty Cycle 100 μ s pulse width)	I_{pf}	100	mA
Continuous Forward Current	I_{af}	50	mA
Reverse Voltage	V_R	5	V
Operating Temperature Range	T_{opr}	-40 $^\circ\text{C}$ to +100 $^\circ\text{C}$	
Storage Temperature Range	T_{stg}	-40 $^\circ\text{C}$ to +100 $^\circ\text{C}$	
Lead Soldering Temperature 1.6 mm from body for 5 seconds at 260 $^\circ\text{C}$			

UNI

Unity Opto Technology Co., Ltd.

12/16/2000

Optical-Electrical Characteristics

@ T_A=25°C

Parameter	Test Conditions	Symbol	Min .	Typ .	Max .	Unit .
Luminous Intensity	I _F =20mA	I _V	-	850	-	mcd
Forward Voltage	I _F =20mA	V _F	-	2.0	2.4	V
Reverse Current	V _R =5V	I _R	-		100	μA
Peak /Dominant Wavelength	I _F =20mA	λ _p /λ _d	-	630/625	-	nm
Spectral Line Half Width	I _F =20mA	Δλ	-	18	-	nm
Viewing Angle	I _F =20mA	2θ _{1/2}	-	35/65	-	deg.

Typical Optical-Electrical Characteristic Curves




FIG.1 SPECTRAL DISTRIBUTION




FIG.2 FORWARD CURRENT VS. FORWARD VOLTAGE




FIG.3 FORWARD CURRENT VS. AMBIENT TEMPERATURE




FIG.4 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




FIG.5 RADIATION DIAGRAM