

## NTE1317 Integrated Circuit Module, 2 Power, 2 Channel, AF Power Amplifier, 50W Min.

**Features:**

- Muting Circuit
- Reduced Heat Sink due to Case Temperature Dissipation up to +125°C

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage, $V_{CC\text{max}}$ .....	±53.0V
Operating Junction Temperature, $T_J$ .....	+150°C
Substrate Temperature, $T_C$ .....	+125°C
Storage Temperature Range, $T_{\text{stg}}$ .....	-30° to +125°C
Thermal Resistance, Junction-to-Case, $R_{\text{thJC}}$ .....	1.8°C/W
Turn-on Time ( $V_{CC} = \pm 35\text{V}$ , $R_L = 8\Omega$ , $f = 50\text{Hz}$ , $P_O = 50\text{W}$ ), $t_s$ .....	2sec

**Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage, $V_{CC}$ .....	±35V
Load Resistance, $R_L$ .....	8Ω

**Electrical Characteristics:** ( $T_A = 25^\circ\text{C}$ ,  $V_{CC} = \pm 35\text{V}$ ,  $R_L = 8\Omega$ ,  $R_g = 600\Omega$ ,  $V_G = 40\text{dB}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Idle Current	$I_{CCO}$	$V_{CC} = \pm 42.5\text{V}$	20	40	100	mA
Power Out	$P_O$	THD = 0.8%, $f = 20\text{Hz}$ to $20\text{kHz}$	50	-	-	W
		$V_{CC} = \pm 32\text{V}$ , THD = 0.2%, $R_L = 4\Omega$ , $f = 1\text{kHz}$	55	-	-	W
Total Harmonic Distortion	THD	$P_O = 1.0\text{W}$ , $f = 1\text{kHz}$	-	-	0.08	%
Breakpoints	$f_L, f_H$	$P_O = 1.0\text{W}$ , +0 -3dB	20 to 50k			Hz
Source Impedance	$r_i$	$P_O = 1.0\text{W}$ , $f = 1\text{kHz}$	-	55	-	kΩ
Input Noise Voltage	$V_{NO}$	$V_{CC} = \pm 42.5\text{V}$ , $R_g = 10\text{k}\Omega$	-	-	1.2	mV <sub>rms</sub>
Transient Noise Voltage	$V_N$	$V_{CC} = \pm 42.5\text{V}$	-70	0	70	mV
Muting Voltage	$V_M$		-2	-5	-10	V

**Pin Connection Diagram**  
(Front View)

18	Rt Ch Input (-)
17	Rt Ch Input (+)
16	GND
15	Compensation
14	(-) V <sub>CC</sub>
13	Rt Ch Output
12	Bypass
11	(+) V <sub>CC</sub>
10	Lt Ch Output
9	(-) V <sub>CC</sub>
8	Compensation
7	Compensation
6	Muting
5	Compensation
4	Compensation
3	Compensation
2	Lt Ch Input (+)
1	Lt Ch Input (-)

