



NTE2547 (NPN) & NTE2548 (PNP) **Silicon Complementary Transistors** **Darlington Driver**

Features:

- High DC Current Gain
- High Current Capacity and Wide ASO
- Low Saturation Voltage

Applications:

- Motor Drivers
- Printer Hammer Drivers
- Relay Drivers
- Voltage Regulator Control

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector to Base Voltage, V_{CBO}	110V
Collector to Emitter Voltage, V_{CEO}	100V
Emitter to Base Voltage, V_{EBO}	6V
Collector Current, I_C	
Continuous	8A
Peak	12A
Collector Dissipation, P_C	
$T_A = +25^\circ\text{C}$	2.0W
$T_C = +25^\circ\text{C}$	30W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = 80\text{V}$, $I_E = 0$	-	-	0.1	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5\text{V}$, $I_C = 0$	-	-	3.0	mA
DC Current Gain	h_{FE}	$V_{CE} = 3\text{V}$, $I_C = 4\text{A}$	1500	4000		
Gain Bandwidth Product	f_T	$V_{CE} = 5\text{V}$, $I_C = 4\text{A}$	-	20	-	MHz

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Saturation Voltage NTE2547	$V_{CE(\text{sat})}$	$I_C = 4\text{A}, I_B = 8\text{mA}$	—	0.9	1.5	V
NTE2548			—	1.0	—	V
Base to Emitter Saturation Voltage	$V_{BE(\text{sat})}$	$I_C = 4\text{A}, I_B = 8\text{mA}$	—	—	2.0	V
Collector–Base Breakdown Voltage	$V_{(BR)\text{CBO}}$	$I_C = 5\text{mA}, I_E = 0$	110	—	—	V
Collector–Emitter Breakdown Voltage	$V_{(BR)\text{CEO}}$	$I_C = 50\text{mA}, R_{BE} = \infty$	100	—	—	V
Turn-On Time NTE2547	t_{on}	$I_C = 4\text{A}, I_{B1} = 500\text{mA},$ $I_{B2} = -500\text{mA},$ Pulse Width = 50 μs , Duty Cycle $\leq 1\%$, Note 1	—	0.6	—	μs
NTE2548			—	0.7	—	μs
Storage Time NTE2547	t_{stg}		—	4.8	—	μs
NTE2548			—	1.4	—	μs
Fall Time NTE2547	t_f		—	1.6	—	μs
NTE2548			—	1.5	—	μs

Note 1. For NTE2548 (PNP), the polarity is reversed.

