



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE3144 thru NTE3147 Light Emitting Diode – 5mm

Features:

- All Plastic Mold Type w/Water Clear Lens:
 NTE3144 (High Efficiency Red, AlGaP/GaAs)
 NTE3145 (Yellow Green, GaInN/GaN)
 NTE3146 (Yellow, AlInGaP/GaAs)
 NTE3147 (Orange, AlInGaP/GaAs)

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Dissipation, P_D			
NTE3144, NTE3146, NTE3147	90mW	
NTE3145	84mW	
Continuous Forward Current, I_F			
NTE3144, NTE3147	30mA	
NTE3145, NTE3146	25mA	
Peak Forward Current (0.1 ms pulse width, 1/10 duty cycle), I_{FM}	50mA	
Reverse Voltage, V_R	5V	
LED Junction Temperature, T_j	+100°C	
Operating Temperature Range, T_{opr}	-25° to +85°C	
Storage Temperature Range, T_{stg}	-40° to +100°C	
Lead Temperature (During Soldering, 5sec max, 1.6mm below package base)	260°C	

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
View Angle of Half Power	201/2	$I_F = 20\text{mA}$	–	30	–	Degree
Forward Voltage NTE3144, NTE3147	V_F	$I_F = 20\text{mA}$	–	2.05	2.80	V
			–	2.15	2.80	V
			–	2.10	2.80	V
Reverse Current	I_R	$V_R = 5\text{V}$	–	–	10	uA
Luminous Intensity NTE3144, NTE3147	I_V	$I_F = 20\text{mA}$, Note 1	40	60	–	mcd
			50	80	–	mcd
			35	50	–	mcd

Note 1. Tolerance: 30%, measured using Exeltron 2001.

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Peak Emission Wavelength NTE3144, NTE3147	λ_p	$I_F = 20\text{mA}$	-	625	-	nm
NTE3145			-	570	-	nm
NTE3146			-	589	-	nm
Dominant Wave Length NTE3144, NTE3147	$\lambda_d(\text{HUE})$	$I_F = 20\text{mA}$, Note 2	-	618	-	nm
NTE3145			-	567	-	nm
NTE3146			-	585	-	nm
Spectrum Width of Half Valve NTE3144, NTE3147	$\Delta\lambda$	$I_F = 20\text{mA}$	-	45	-	nm
NTE3145			-	30	-	nm
NTE3146			-	35	-	nm
Terminal Capacitance NTE3144, NTE3147	C_t	$V = 0\text{V}$, $F = 1\text{MHz}$	-	6	-	pF
NTE3145, NTE3146			-	7	-	pF
Response Frequency	F_C		-	4	-	MHz

Note 2. The dominate wavelength, λ_d , is derived from the CIE Chromaticity Diagram and represents the color of the device.

