


Audio Clock Generator

FEATURES

- Supports the following output frequencies
 - 12.288MHz audio clock output
 - 24.576MHz audio clock output
 - 27MHz reference output
- Accepts Crystal or reference clock inputs
 - Fundamental crystal: 27MHz
 - Reference input: 27MHz
- On-the-fly switching of the two audio frequencies (12.288MHz, and 24.576MHz).
- Accepts <1.0V reference signal input voltage
- Single 2.5V or 3.3V ± 10% power supply
- Available in 8-Pin SOIC GREEN/RoHS compliant Package.

PACKAGE PIN CONFIGURATION



Note: ^: Internal pull-up resistor. The internal pull-up resistor results in a default high value when no pull-down resistor is connected to this pin.


DESCRIPTION

The PLL601-26 is a low cost integrated XO IC designed to work with a fundamental 27MHz crystal or a clock input. In addition to a 27MHz clock reference output, it provides two selectable audio frequencies (12.288MHz, and 24.576MHz), making the chip ideal for handheld, STB and MPEG Video applications. Additional system frequencies can also be supported by cascading the PLL601-26 with PhaseLink's QTC programmable clock family.

AUDIO CLOCK SELECTION

FSEL	ACLK (MHz)
0	12.288
1(Default)	24.576

BLOCK DIAGRAM



Audio Clock Generator
PIN DESCRIPTIONS

Name	Pin #	Type	Description
XIN/FIN	1	I	27Mhz Crystal or Reference input.
VDD	2	P	Power supply connection.
GND	3	P	Ground connection.
27MHz	4	O	27MHz reference output.
ACLK	5	O	Audio clock output (see selection table on page 1).
DNC	6	I	Do Not Connect.
FSEL	7	I	On-The-Fly audio frequency Switching (selector) Input. This pin has an internal 60 K Ω pull up resistor.
XOUT	8	I	Crystal output. Do Not Connect if reference input is used.

Notes: I – Input pin; O – Output pin; P – power supply/ground pin.

ELECTRICAL SPECIFICATIONS
ABSOLUTE MAXIMUM RATINGS

PARAMETERS	SYMBOL	MIN.	MAX.	UNITS
Supply Voltage Range	V _{DD}	-0.5	4.6	V
Input Voltage Range	V _I	-0.5	V _{DD} +0.5	V
Output Voltage Range	V _O	-0.5	V _{DD} +0.5	V
Soldering Temperature (Green package)			260	°C
Storage Temperature	T _S	-65	150	°C
Ambient Operating Temperature		0	+70	°C

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

* Note: Operating Temperature is guaranteed by design for all parts (COMMERCIAL and INDUSTRIAL), but tested for COMMERCIAL grade only.

AC SPECIFICATIONS

PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Crystal Input Frequency(XIN)	Fundamental Crystal		27		MHz
Input (FIN) Frequency			27		MHz
Input (FIN) Signal Amplitude	Internally AC coupled	0.9		V _{DD}	V _{pp}
Output Rise Time	15pF Load, 10/90%V _{DD}		2.5	3.5	ns
Output Fall Time	15pF Load, 90/10%V _{DD}		2.5	3.5	ns
Duty Cycle	At V _{DD} /2	45	50	55	%

Audio Clock Generator
DC SPECIFICATIONS

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current, Dynamic, with Loaded Outputs	I_{DD}	At 27MHz, load=15pF			15	mA
Operating Voltage	V_{DD}		2.25		3.63	V
Output Low Voltage	V_{OL}	$I_{OL} = +4mA$			0.4	V
Output High Voltage	V_{OH}	$I_{OH} = -4mA$	$V_{DD} - 0.4$			V
Output Current	I_{OSD}	$V_{OL} = 0.4V, V_{OH} = 2.4V$			10	mA
Short-circuit Current	I_S			± 50		mA

CRYSTAL SPECIFICATIONS


PARAMETERS	SYMBOL	MIN.	TYP.	MAX.	UNITS
Fundamental Crystal Resonator Frequency	F_{XIN}		27		MHz
Crystal Loading Rating	$C_L (xtal)$		16		pF
Maximum Sustainable Drive Level				500	μW
Operating Drive Level			100		μW
Crystal Shunt Capacitance	C_0			6	pF
Effective Series Resistance, Fundamental, 27MHz	ESR			30	Ω

Note: A detailed crystal specification document is also available for this part

JITTER SPECIFICATIONS

PARAMETERS	CONDITIONS	FREQUENCY	MIN.	TYP.	MAX.	UNITS
Cycle to Cycle Jitter	$T_{cyc-cyc}$	27MHz		300		ps
Cycle to Cycle Jitter	$T_{cyc-cyc}$	Audio Clock		150		ps

PACKAGE DRAWINGS (GREEN PACKAGE COMPLIANT)




ORDERING INFORMATION

For part ordering, please contact our Sales Department:
 47745 Fremont Blvd., Fremont, CA 94538, USA
 Tel: (510) 492-0990 Fax: (510) 492-0991

PART NUMBER

The order number for this device is a combination of the following:
 Device number, Package type and Operating temperature range



Part / Order Number	Marking	Package Option
PLL601-26SC	P601-26SC	8-Pin SOIC (Tube)
PLL601-26SC-R	P601-26SC	8-Pin SOIC (Tape and Reel)
PLL601-26SCL	P601-26SCL	8-Pin SOIC (Tube), GREEN
PLL601-26SCL-R	P601-26SCL	8-Pin SOIC (Tape and Reel), GREEN

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

LIFE SUPPORT POLICY: PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.