

TLT-8-2014


# Temperature Compensated Low Noise Amplifier 2 GHz - 8 GHz

This Low Noise Amplifier offers low Noise figure performance of 3.2 dB over the band 2 GHz to 8 GHz with 33 dB Gain.

Teledyne Microwave amplifiers are balanced or feedback designs and manufactured with the latest MIC & MMIC technology. The GaAs FET's used in these amplifiers are well established proven devices from multiple sources.

Teledyne Microwave offers a complete line of Narrow and broadband Amplifiers covering the frequency range 500 MHz to 40 GHz. These products are available in either connectorized packages or as modules. For a complete list of these products and more, please visit our website.

Other products from Teledyne Microwave include: Transceivers, Synthesizers, and YIG Products



---

## Specifications:

Model Number: TLT-8-2014  
Frequency Range: 2 GHz - 8 GHz  
Gain (min): 33 dB  
Gain Vs Temp at any Frequency: +/-1.00 dB  
Noise Figure (max): 3.2 dB  
Output Power @ 1dB Compression: 18 dBm  
Gain Flatness Vs Frequency: +/-1.5 dB  
3<sup>rd</sup> Order Intercept (Typ): 27 dBm  
Power Supply:  
    Input Voltage: 11.5 to 15 VDC  
    Current @ 12 VDC (typ): 310 mA  
    Current @ 12 VDC (max): 350 mA  
Case Type (See attached Outline): SC6  
Temperature Range: -54 to +90C




ISO 9001:2000

1274 Terra Bella Avenue, Mountain View, CA 94043 • PHN# 800.832.6869 or +1.650.962.6944 • FAX# 650.962.6845  
www.teledynemicrowave.com • microwave@teledyne.com

TLT-8-2014

# Temperature Compensated Low Noise Amplifier 2 GHz - 8 GHz



ISO 9001:2000

1274 Terra Bella Avenue, Mountain View, CA 94043 • PHN# 800.832.6869 or +1.650.962.6944 • FAX# 650.962.6845  
www.teledynemicrowave.com • microwave@teledyne.com