



PC Board Layout

ORDERING INFORMATION

FJ 260S--P\_C-- --  
 a b c d

- a: No. of position (8,10)
- b: No. of contact (8,10)
- c: Plating 6u" 15u" 30u" 50u"
- d: Option (K,N)



K:With keyway (8p&10p only)



N:No flangestop

MATERIAL: HOUSING-PBT POLYESTER UL94V-0  
 COLOR-BLACK

CONTACTS-0.35mm THICKNESS ALLOY  
 C5210 SELECTIVE GOLD PLATING

SHIELD-0.25mm THICKNESS COPPER  
 ALLOY WITH TIN/NICKEL PLATED

TOLERANCE .x ±0.3  
 .xx ±0.20

UL.CUL File NO.: E166003

<b>XMULTIPLE</b>		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 27, Min. Shi, Johnson St., Taipei, Taiwan 10496, R.O.C.	XMULTIPLE USA 2800 Old Country Road, Fountain Valley, CA 92708	DATE	REV
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: Top Entry Shielded Modular Jack 180°		DRAWN	BY
PART NO: XRJ-FJ-260S		CHKD	DATE
	(mm)	1 of 1	A
			06/18/04