

## Surface mount diode

## Schottky barrier rectifiers diodes

### SK 22...SK210

**Forward Current: 2 A**

**Reverse Voltage: 20 to 100 V**

## Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0

## Mechanical Data

- Plastic case DO-214AA / SMB
- Weight approx.: 0,1 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 3000 pieces per reel

1) Max. temperature of the terminals  $T_T = 100^\circ\text{C}$

2)  $I_F = 2\text{A}$ ,  $T_J = 25^\circ\text{C}$

3)  $T_A = 25^\circ\text{C}$

4) Mounted on P.C. board with 50 mm<sup>2</sup> copper pads at each terminal

Type	Polarity color band	Repetitive peak reverse voltage $V_{RRM}$ V	Surge peak reverse voltage $V_{RSM}$ V	Maximum forward voltage $T_j = 25^\circ\text{C}$ $I_F = 2\text{A}$	Maximum reverse recovery time $I_F = -\text{A}$ $I_R = -\text{A}$ $I_{RR} = -\text{A}$ $t_{rr}$ ns
SK 22	-	20	20	0,5	-
SK 23	-	30	30	0,5	-
SK 24	-	40	40	0,5	-
SK 25	-	50	50	0,7	-
SK 26	-	60	60	0,7	-
SK 28	-	80	80	0,85	-
SK 210	-	100	100	0,85	-

## Absolute Maximum Ratings


$T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_{FAV}$	Max. averaged fwd. current, R-load, $T_T = 100^\circ\text{C}$	2	A
$I_{FRM}$	Repetitive peak forward current $f > 15\text{ Hz}^1)$	12	A
$I_{FSM}$	Peak fwd. surge current 50 Hz half sinus-wave <sup>3)</sup>	50	A
$I_{rt}$	Rating for fusing, $t < 10\text{ ms}^3)$	12,5	A <sup>2</sup> s
$R_{thA}$	Max. thermal resistance junction to ambient <sup>4)</sup>	60	K/W
$R_{thT}$	Max. thermal resistance junction to terminals	15	K/W
$T_j$	Operating junction temperature	-50...+150	°C
$T_s$	Storage temperature	-50...+150	°C

## Characteristics

$T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_R$	Maximum leakage current, $T_j = 25^\circ\text{C}$ ; $V_R = V_{RRM}$ $T_j = 100^\circ\text{C}$ ; $V_R = V_{RRM}$	<0,5 <10	mA mA
$C_J$	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
$Q_{rr}$	Reverse recovery charge ( $U_R = V$ ; $I_F = A$ ; $dI_F/dt = A/\text{ms}$ )	-	μC
$E_{RSM}$	Non repetitive peak reverse avalanche energy ( $I_R = \text{mA}$ ; $T_j = {}^\circ\text{C}$ ; inductive load switched off)	-	mJ



case: SMB / DO-214AA

# SK 22 ... SK 210




Fig. 1 Forward characteristic ( typical values )




Fig. 2 Rated forward current vs. temp. of the terminals <sup>4)</sup>