

# M3A & MAH Series


## 8 pin DIP, 5.0 or 3.3 Volt, AC MOS/TTL, Clock Oscillators



### Ordering Information

	M3A/MAH	1	3	F	A	D	-R	00.0000	MHz
<b>Product Series</b>	M3A = 3.3 Volt MAH = 5.0 Volt								
<b>Temperature Range</b>	1: 0°C to +70°C      2: -40°C to +85°C 6: -20°C to +70°C      7: 0°C to +85°C								
<b>Stability</b>	1: ±1000 ppm      2: ±500 ppm 3: ±100 ppm      4: ±50 ppm 5: ±35 ppm      6: ±25 ppm *8: ±20 ppm								
<b>Output Type</b>	F: Fixed      T: Tristate								
<b>Symmetry/Logic Compatibility</b>	A: 40/60 AC MOS/TTL      B: 45/55 TTL C: 45/55 AC MOS								
<b>Package/Lead Configurations</b>	A: DIP; Gold Flash Header      D: DIP; Nickel Header G: Gull Wing; Nickel Header      X: Gull Wing; Gold Flash Header								
<b>RoHS Compliance</b>	Blank: non-RoHS compliant part -R: RoHS compliant part								
<b>Frequency (customer specified)</b>									

\*Contact factory for availability.



### Pin Connections

PIN	FUNCTION
1	N/C or Tri-state
4	Circuit/Case Ground
5	Output
8	+Vdd

	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition
Electrical Specifications	Frequency Range	F	30		133	MHz	
	Frequency Stability	$\Delta F/F$	(See Ordering Information)				
	Operating Temperature	T <sub>A</sub>	(See Ordering Information)				
	Storage Temperature	T <sub>s</sub>	-55		+125	°C	
	Input Voltage	V <sub>dd</sub>	3.135	3.3	3.465	V	M3A
			4.75	5.0	5.25	V	MAH
	Input Current	I <sub>dd</sub>		30	50	mA	M3A
				70	90	mA	MAH
	Symmetry (Duty Cycle)		(See Ordering Information)				
	Load				50	Ω	See Note 2
	Rise/Fall Time	Tr/Tf		1	2.5	ns	See Note 3
					2	ns	See Note 3
	Logic "1" Level	V <sub>oh</sub>	90% V <sub>dd</sub>			V	AC MOS Load
			V <sub>dd</sub> -0.5			V	TTL Load
Logic "0" Level	V <sub>ol</sub>			10% V <sub>dd</sub>	V	AC MOS Load	
				0.5	V	TTL Load	
Cycle to Cycle Jitter			5	15	ps RMS	1 Sigma	
Tri-State Function		Input Logic "1" or floating; output active Input Logic "0"; output to high-Z					
Environmental	Mechanical Shock	Per MIL-STD-202, Method 213, Condition C					
	Vibration	Per MIL-STD-202, Method 201 & 204					
	Wave Solder Conditions	+260°C for 10 secs. max.					
	Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 <sup>-5</sup> atm.cc/s of helium)					
Solderability	Per EIAJ-STD-002						

1. Symmetry is measured at 1.4 V with TTL load, and at 50% V<sub>dd</sub> with AC MOS load.
2. See load circuit diagram #6.
3. Rise/Fall times are measured between 0.5 V and 2.4 V with TTL load, and between 10% V<sub>dd</sub> and 90% V<sub>dd</sub> with AC MOS load.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see [www.mtronpti.com](http://www.mtronpti.com) for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.