

## N-Channel 150-V (D-S) MOSFET

PRODUCT SUMMARY			
V <sub>(BR)DSS</sub> (V)	R <sub>DS(on)</sub> ( $\Omega$ )	I <sub>D</sub> (A)	Q <sub>g</sub> (Typ.)
150	0.018 at V <sub>GS</sub> = 10 V	75 <sup>d</sup>	64

### FEATURES


- TrenchFET® Power MOSFET
- 100 % R<sub>g</sub> and UIS Tested




### APPLICATIONS

- Primary Side Switch
- Power Supplies

TO-263



Top View



Ordering Information: SUM75N15-18P-E3 (Lead (Pb)-free)

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T <sub>C</sub> = 25 °C, unless otherwise noted			
Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V <sub>DS</sub>	150	V
Gate-Source Voltage	V <sub>GS</sub>	± 20	
Continuous Drain Current (T <sub>J</sub> = 150 °C)	T <sub>C</sub> = 25 °C	75 <sup>d</sup>	A
	T <sub>C</sub> = 70 °C	70	
Pulsed Drain Current	I <sub>DM</sub>	180	
Avalanche Current	I <sub>AS</sub>	50	
Single Avalanche Energy <sup>a</sup>	E <sub>AS</sub>	125	mJ
Maximum Power Dissipation <sup>a</sup>	T <sub>C</sub> = 25 °C	312.5 <sup>b</sup>	W
	T <sub>A</sub> = 25 °C <sup>c</sup>	3.12	
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	- 55 to 150	°C

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Junction-to-Ambient (PCB Mount) <sup>c</sup>	R <sub>thJA</sub>	40	°C/W
Junction-to-Case (Drain)	R <sub>thJC</sub>	0.4	

Notes:

- Duty cycle ≤ 1 %.
- See SOA curve for voltage derating.
- When Mounted on 1" square PCB (FR-4 material).
- Package limited.

# SUM75N15-18P

Vishay Siliconix









## SPECIFICATIONS $T_J = 25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{DS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	150			V
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	2.5		4.5	
Gate-Body Leakage	$I_{\text{GSS}}$	$V_{\text{DS}} = 0 \text{ V}, V_{\text{GS}} = \pm 20 \text{ V}$			$\pm 250$	nA
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}} = 150 \text{ V}, V_{\text{GS}} = 0 \text{ V}$		1		$\mu\text{A}$
		$V_{\text{DS}} = 150 \text{ V}, V_{\text{GS}} = 0 \text{ V}, T_J = 125^\circ\text{C}$		50		
		$V_{\text{DS}} = 150 \text{ V}, V_{\text{GS}} = 0 \text{ V}, T_J = 150^\circ\text{C}$		250		
On-State Drain Current <sup>a</sup>	$I_{\text{D}(\text{on})}$	$V_{\text{DS}} \geq 10 \text{ V}, V_{\text{GS}} = 10 \text{ V}$	120			A
Drain-Source On-State Resistance <sup>a</sup>	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10 \text{ V}, I_D = 20 \text{ A}$		0.0148	0.018	$\Omega$
		$V_{\text{GS}} = 10 \text{ V}, I_D = 20 \text{ A}, T_J = 125^\circ\text{C}$		0.0296	0.036	
Forward Transconductance <sup>a</sup>	$g_{\text{fs}}$	$V_{\text{DS}} = 15 \text{ V}, I_D = 20 \text{ A}$		55		S
<b>Dynamic<sup>b</sup></b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{GS}} = 0 \text{ V}, V_{\text{DS}} = 75 \text{ V}, f = 1 \text{ MHz}$		4180		pF
Output Capacitance	$C_{\text{oss}}$			235		
Reverse Transfer Capacitance	$C_{\text{rss}}$			83		
Total Gate Charge <sup>c</sup>	$Q_g$	$V_{\text{DS}} = 75 \text{ V}, V_{\text{GS}} = 10 \text{ V}, I_D = 85 \text{ A}$		64	100	nC
Gate-Source Charge <sup>c</sup>	$Q_{\text{gs}}$			23		
Gate-Drain Charge <sup>c</sup>	$Q_{\text{gd}}$			16		
Gate Resistance	$R_g$	$f = 1 \text{ MHz}$		2.1	4.2	$\Omega$
Turn-On Delay Time <sup>c</sup>	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = 75 \text{ V}, R_L = 0.88 \Omega$ $I_D \geq 85 \text{ A}, V_{\text{GEN}} = 10 \text{ V}, R_g = 1 \Omega$		15	25	ns
Rise Time <sup>c</sup>	$t_r$			10	15	
Turn-Off Delay Time <sup>c</sup>	$t_{\text{d}(\text{off})}$			25	40	
Fall Time <sup>c</sup>	$t_f$			8	15	
<b>Source-Drain Diode Ratings and Characteristics <math>T_C = 25^\circ\text{C}</math><sup>b</sup></b>						
Continuous Current	$I_S$				75	A
Pulsed Current	$I_{\text{SM}}$				180	
Forward Voltage <sup>a</sup>	$V_{\text{SD}}$	$I_F = 30 \text{ A}, V_{\text{GS}} = 0 \text{ V}$		1.0	1.5	V
Reverse Recovery Time	$t_{rr}$	$I_F = 50 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}$		130	200	ns
Peak Reverse Recovery Current	$I_{\text{RM}(\text{REC})}$			8	12	A
Reverse Recovery Charge	$Q_{rr}$			520	1200	nC

Notes:

- a. Pulse test; pulse width  $\leq 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ .
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.







**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted


# SUM75N15-18P




Vishay Siliconix



**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted



\*  $V_{GS} >$  minimum  $V_{GS}$  at which  $R_{DS(\text{on})}$  is specified

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted


\* The power dissipation  $P_D$  is based on  $T_{J(max)} = 150$  °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?69995>.



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.