


## Power Switching Applications

### 2SC4541



#### ■ Features

- Low Saturation Voltage:  $V_{CE(sat)} = 0.5V$  (max) ( $I_c = 1.5A$ )
- High Speed Switching Time:  $t_{stg} = 0.5\mu s$ (typ.)
- Small Flat Package
- $P_c = 1$  to  $2W$  (mounted on ceramic substrate)
- Complementary to 2SA1736


#### ■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Collector-Base Voltage	$V_{CBO}$	80	V
Collector-Emitter Voltage	$V_{CEO}$	50	V
Emitter-Base Voltage	$V_{EBO}$	6	V
Collector Current	$I_c$	3	A
Base Current	$I_b$	0.6	A
Collector Power Dissipation	$P_c$	500	mW
	$P_c^*$	1000	
Junction temperature	$T_j$	150	°C
Storage temperature Range	$T_{stg}$	-55 to +150	°C

\* Mounted on a ceramic substrate (250 mm<sup>2</sup> x 0.8 t)

#### ■ Electrical Characteristics $T_a = 25^\circ C$





Parameter	Symbol	Testconditons	Min	Typ	Max	Unit
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = 80V$ , $I_E = 0$			0.1	μA
Emitter Cut-off Current	$I_{EBO}$	$V_{EB} = 6V$ , $I_C = 0$			0.1	μA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10mA$ , $I_B = 0$	50			V
DC Current Gain	$h_{FE}$	$V_{CE} = 2V$ , $I_C = 100mA$	120		400	
		$V_{CE} = 2V$ , $I_C = 2A$	40			
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 1.5A$ , $I_B = 75mA$			0.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 1.5A$ , $I_B = 75mA$			1.2	V
Transition Frequency	$f_T$	$V_{CE} = 2V$ , $I_C = 100mA$	100			MHz
Collector Output Capacitance	$C_{ob}$	$V_{CB} = 10V$ , $I_E = 0$ , $f = 1MHz$	20			pF
Turn-On Time	$t_{on}$	See Test Circuit.		0.1		
Storage Time	$t_{stg}$			0.5		μs
Fall Time	$t_f$			0.1		

**2SC4541****■ Test Circuit**

$|IB1| = -|IB2| = 75\text{mA}$ , DUTY CYCLE  $\leqslant 1\%$

**■ Marking**

Marking	KD
---------	----

**■ Electrical Characteristics Curves**

## 2SC4541

