



RLO Series

Precision compensated low pressure sensors

FEATURES


- Ranges from 1 to 30 inch H₂O gage or differential
- Precision temperature compensated
- Calibrated offset and span
- Extremely low position sensitivity
- Excellent long term stability
- Sensortech PRO services

MEDIA COMPATIBILITY


To be used with non-corrosive, non-ionic working fluids such as clean dry air, dry gases and the like.

The media wetted materials are:


- silicon
- glass filled nylon
- silicone
- ceramic (Al₂O₃)
- gold



EQUIVALENT CIRCUIT



ELECTRICAL CONNECTION





RLO Series

Precision compensated low pressure sensors

SPECIFICATIONS

Maximum ratings

Supply voltage V_s	0 to 16 V
Common-mode pressure	50 psig
Lead temperature (soldering 5 seconds)	315 °C

Environmental specifications

Temperature range	
Compensated	0 to 50°C
Operating	-25 to 85°C
Storage	-40 to 125°C
Humidity limits (non-condensing)	0 to 95 %RH

PRESSURE SENSOR CHARACTERISTICS

Part no.	Operating pressure	Max. over pressure ¹
RLOH001D	1 "H ₂ O	5 psi
RLOH005D	5 "H ₂ O	5 psi
RLOH010D	10 "H ₂ O	5 psi
RLOH020D	20 "H ₂ O	5 psi
RLOH030D	30 "H ₂ O	5 psi

PERFORMANCE CHARACTERISTICS

($V_s = 12\text{ V}$, $T_A = 25\text{ °C}$, common-mode pressure = 0 psig, pressure applied to port 2)

RLOH001D

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset	-0.5	0	+0.5	mV
Full scale span (FSS) ²	9	10	11	
Combined non-linearity and hysteresis ³			±0.25	%FSS
Temperature effects (0 to 50°C) ⁴	Span		±200	μV
	Offset		±250	
Offset warm-up shift ⁵		±100		
Offset position sensitivity (±1 g)		±50		
Input resistance		4.5		kΩ
Output resistance		1.5		
Common mode voltage ⁶		6		V



RLO Series

Precision compensated low pressure sensors

PERFORMANCE CHARACTERISTICS (cont.)

($V_s = 12\text{ V}$, $T_A = 25\text{ °C}$, common-mode pressure = 0 psig, pressure applied to port 2)

RLOH005D

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset	-0.5	0	+0.5	mV
Full scale span (FSS) ²	19	20	21	
Combined non-linearity and hysteresis ³			±0.25	%FSS
Temperature effects (0 to 50°C) ⁴	Span		±200	μV
	Offset		±150	
Offset warm-up shift ⁵		±50		
Offset position sensitivity (±1 g)		±10		
Input resistance		10		kΩ
Output resistance		1.5		
Common mode voltage ⁶		6		V

RLOH010D

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset	-0.5	0	+0.5	mV
Full scale span (FSS) ²	19	20	21	
Combined non-linearity and hysteresis ³			±0.25	%FSS
Temperature effects (0 to 50°C) ⁴	Span		±200	μV
	Offset		±150	
Offset warm-up shift ⁵		±50		
Offset position sensitivity (±1 g)		±10		
Input resistance		13		kΩ
Output resistance		1.5		
Common mode voltage ⁶		6		V



RLO Series

Precision compensated low pressure sensors

PERFORMANCE CHARACTERISTICS (cont.)

($V_s = 12\text{ V}$, $T_A = 25\text{ °C}$, common-mode pressure = 0 psig, pressure applied to port 2)

RLOH020D

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset	-0.5	0	+0.5	mV
Full scale span (FSS) ²	19	20	21	
Combined non-linearity and hysteresis ³			±0.25	%FSS
Temperature effects (0 to 50°C) ⁴	Span		±200	µV
	Offset		±150	
Offset warm-up shift ⁵		±50		
Offset position sensitivity (±1 g)		±5		
Input resistance		10		kΩ
Output resistance		2		
Common mode voltage ⁶		6		V

RLOH030D

Characteristics	Min.	Typ.	Max.	Unit
Zero pressure offset	-0.5	0	+0.5	mV
Full scale span (FSS) ²	19	20	21	
Combined non-linearity and hysteresis ³			±0.25	%FSS
Temperature effects (0 to 50°C) ⁴	Span		±200	µV
	Offset		±150	
Offset warm-up shift ⁵		±50		
Offset position sensitivity (±1 g)		±5		
Input resistance		12		kΩ
Output resistance		1.5		
Common mode voltage ⁶		6		V

Notes


- ¹ The maximum over pressure may be applied without causing durable shifts of the electrical parameters of the sensing element.
- ² Full scale span (FSS) is the algebraic difference between the output voltage at full-scale pressure and the output at zero pressure.
- ³ Non-linearity refers to the **Best Straight Line** fit measured for offset pressure, full-scale pressure and ½ full-scale pressure.
- ⁴ Shift is relative to 25°C.
- ⁵ Shift within the first hour of excitation applied to the sensor.
- ⁶ This is the common mode voltage of the output arms (pin 3 and 5) for $V_s = 12\text{ V}$



RLO Series

Precision compensated low pressure sensors

OUTLINE DRAWING



mass: approx. 10 g

third angle projection

dimensions in mm (inches)

ORDERING INFORMATION - AVAILABLE LISTINGS

Note: Preferred listings are highlighted in grey

Pressure range	Gage/differential devices
1 "H ₂ O	RLOH001D
5 "H ₂ O	RLOH005D
10 "H ₂ O	RLOH010D
20 "H ₂ O	RLOH020D
30 "H ₂ O	RLOH030D

Sensortech PRO services:

- Extended guarantee period of 2 years
- Improved performance characteristics
- Custom product modifications and adaptations even for small quantities
- Advanced logistics models for supply inventory and short delivery times
- Technical support through application engineers on the phone or at your site
- Fastest possible technical response for design and QA engineers
- ... plus other services on request

Sensortech reserves the right to make changes to any products herein. Sensortech does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.