


Diode Modules

PSKD 310

$$\begin{aligned} I_{FRMS} &= 2 \times 480 \text{ A} \\ I_{FAVM} &= 2 \times 305 \text{ A} \\ V_{RRM} &= 800-1800 \text{ V} \end{aligned}$$

Preliminary Data Sheet

V_{RSM} V	V_{RRM} V	Type
900	800	PSKD 310/08
1300	1200	PSKD 310/12
1500	1400	PSKD 310/14
1700	1600	PSKD 310/16
1900	1800	PSKD 310/18



Symbol	Test Conditions	Maximum Ratings
I_{FRMS}	$T_{VJ} = T_{VJM}$	480 A
I_{FAVM}	$T_C = 100^\circ\text{C}; 180^\circ \text{ sine}$	305 A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}; V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$ 11 500 A
		$t = 8.3 \text{ ms (60 Hz), sine}$ 12 200 A
	$T_{VJ} = T_{VJM}; V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$ 9 600 A
		$t = 8.3 \text{ ms (60 Hz), sine}$ 10 200 A
Ji^2dt	$T_{VJ} = 45^\circ\text{C}; V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$ 662 000 A ² s
		$t = 8.3 \text{ ms (60 Hz), sine}$ 620 000 A ² s
	$T_{VJ} = T_{VJM}; V_R = 0$	$t = 10 \text{ ms (50 Hz), sine}$ 460 000 A ² s
		$t = 8.3 \text{ ms (60 Hz), sine}$ 430 000 A ² s
T_{VJ}		-40...+150 °C
T_{VJM}		150 °C
T_{stg}		-40...+125 °C
V_{ISOL}	50/60 Hz, RMS $t = 1 \text{ min}$	3000 V~
	$I_{ISOL} \leq 1 \text{ mA}$ $t = 1 \text{ s}$	3600 V~
M_d	Mounting torque (M5)	2.5-5/22-44 Nm/lb.in.
	Terminal connection torque (M8)	12-15/106-132 Nm/lb.in.
Weight	Typical including screws	320 g

Features

- Direct copper bonded Al_2O_3 -ceramic base plate
- Planar passivated chips
- Isolation voltage 3600 V~
- UL registered, E 148688

Applications




- Supplies for DC power equipment
- DC supply for PWM inverter
- Field supply for DC motors
- Battery DC power supplies

Advantages

- Space and weight savings
- Simple mounting
- Improved temperature and power cycling
- Reduced protection circuits

Dimensions in mm (1 mm = 0.0394")

Symbol	Test Conditions	Characteristic Values
I_{RRM}	$T_{VJ} = T_{VJM}; V_R = V_{RRM}$	40 mA
V_F	$I_F = 600 \text{ A}; T_{VJ} = 25^\circ\text{C}$	1.2 V
V_{TO}	For power-loss calculations only	0.75 V
r_T	$T_{VJ} = T_{VJM}$	0.63 mΩ
R_{thJC}	per diode; DC current	0.129 K/W
R_{thJK}	per module	0.065 K/W
	per diode; DC current	0.169 K/W
	per module	0.0845 K/W
Q_s	$T_{VJ} = 125^\circ\text{C}; I_F = 400 \text{ A}; -di/dt = 50 \text{ A}/\mu\text{s}$	760 μC
I_{RM}		275 A
d_s	Creepage distance on surface	12.7 mm
d_A	Strike distance through air	9.6 mm
a	Maximum allowable acceleration	50 m/s ²



Threaded spacer for higher Anode/Cathode construction: Type ZY 250, material brass

Data according to IEC 60747 and refer to a single thyristor/diode unless otherwise stated.




Fig. 1 Surge overload current
 I_{FSM} : Crest value, t : duration




Fig. 2 j^2dt versus time (1-10 ms)




Fig. 2a Maximum forward current
 at case temperature




Fig. 3 Power dissipation versus
 forward current and ambient
 temperature (per diode)




Fig. 4 Single phase rectifier bridge:
 Power dissipation versus direct
 output current and ambient
 temperature
 R = resistive load
 L = inductive load




Fig. 5 Three phase rectifier bridge:
Power dissipation versus direct
output current and ambient
temperature




Fig. 6 Transient thermal impedance
junction to case (per diode)

R_{thJC} for various conduction angles d:

d	R_{thJC} (K/W)
DC	0.129
180°	0.131
120°	0.132
60°	0.132
30°	0.133

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.0035	0.0099
2	0.0165	0.168
3	0.1091	0.456




Fig. 7 Transient thermal impedance
junction to heatsink (per diode)

R_{thJK} for various conduction angles d:

d	R_{thJK} (K/W)
DC	0.169
180°	0.171
120°	0.172
60°	0.172
30°	0.173

Constants for Z_{thJK} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.0035	0.0099
2	0.0165	0.168
3	0.1091	0.456
4	0.04	1.36