



Polystyrene and Foil Capacitors





(All dimensions in inches)

1906TC

Tubular Wrap and Fill

Lead Specs.
Tinned Copperweld
Under .250D = 24 AWG
.250 - .440D = 22 AWG
Above .440D = 20 AWG

DIMENSIONS and RATINGS

| Сар. | 1906TC-2 50 VDC | | 1906TC-3 100 VDC | | 1906TC-3 200 VDC | | 1906TC-3 400 VDC | | 1906TC-3 600 VDC | | | |
|--------------|--------------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|-------|--|
| μF | D | L | D | L | D | L | D | L | D | L | | |
| .001 | .160 | .406 | .180 | .406 | .180 | .406 | .230 | .406 | .240 | .531 | | |
| .0012 | .160 | .406 | .180 | .406 | .180 | .406 | .250 | .406 | .260 | .531 | | |
| .0015 | .160 | .406 | .180 | .406 | .180 | .406 | .170 | .531 | .290 | .531 | | |
| .0022 | .160 | .406 | .180 | .406 | .220 | .406 | .200 | .531 | .250 | .656 | | |
| .0027 | .160 | .406 | .180 | .406 | .240 | .406 | .220 | .531 | .270 | .656 | | |
| .0039 | .190 | .406 | .210 | .406 | .190 | .531 | .260 | .531 | .320 | .656 | | |
| .0047 | .200 | .406 | .220 | .406 | .210 | .531 | .280 | .531 | .350 | .656 | | |
| .0056 | .220 | .406 | .240 | .406 | .230 | .531 | .240 | .656 | .320 | .781 | | |
| .0068 | .240 | .406 | .180 | .531 | .250 | .531 | .270 | .656 | .350 | .781 | - 110 | |
| .0082 | .180 | .531 | .200 | .531 | .270 | .531 | .290 | .656 | .390 | .781 | | |
| .01 | .190 | .531 | .220 | .531 | .300 | .531 | .320 | .656 | .370 | .906 | 17179 | |
| .012 | .210 | .531 | .230 | .531 | .260 | .656 | .350 | .656 | .400 | .906 | | |
| .015 | .230 | .531 | .260 | .531 | .290 | .656 | .340 | .781 | .450 | .906 .906 | | |
| .018 | .250 | .531 | .280 | .531 | .320 | .656 | .370 .400 | .781 .781 | .490 .450 | 1.190 | | |
| .022 .027 | .280 .250 | .531 .656 | .250 | .656 .656 | .350 | .656 .781 | .390 | .906 | .500 | 1.190 | | |
| .027 | .250 .270 | .656 | .300 | .656 | .340 | .781 | .390 | .906 | .550 | 1.190 | | |
| .033 | .300 | .656 | .330 | .656 | .400 | .781 | .430 | .906 | .590 | 1.190 | | |
| .039 | .320 | .656 | .310 | .781 | .440 | .781 | .510 | .906 | .650 | 1.190 | | |
| .056 | .350 | .656 | .340 | .781 | .430 | .906 | .470 | 1.190 | .610 | 1.440 | | |
| .068 | .340 | .781 | .370 | .781 | .470 | .906 | .520 | 1.190 | .670 | 1.440 | | |
| .082 | .370 | .781 | .410 | .781 | .510 | .906 | .570 | 1.190 | .740 | 1.440 | | |
| .1 | .410 | .781 | .400 | .906 | .480 | 1.190 | .630 | 1.190 | .730 | 1.690 | | |
| .12 | .440 | .781 | .440 | .906 | .530 | 1.190 | .600 | 1.440 | .800 | 1.690 | | |
| .15 | .440 | .906 | .490 | .906 | .580 | 1.190 | .670 | 1.440 | .890 | 1.690 | | |
| .18 | .480 | .906 | .450 | 1.190 | .640 | 1.190 | .730 | 1.440 | .970 | 1.690 | | |
| .22 | .530 | .906 | .500 | 1.190 | .620 | 1.440 | .730 | 1.690 | 1.070 | 1.690 | | |
| .27 | .500 | 1.190 | .550 | 1.190 | .680 | 1.440 | .810 | 1.690 | | | | |
| .33 | .550 | 1.190 | .610 | 1.190 | .750 | 1.440 | .890 | 1.690 | | | | |
| .39 | .590 | 1.190 | .590 | 1.440 | .740 | 1.690 | .970 | 1.690 | | | | |
| .47 | .650 | 1.190 | .640 | 1.440 | .810 | 1.690 | 1.060 | 1.690 | | | | |
| .56 | .620 | 1.440 | .700 | 1.440 | .890 | 1.690 | | | | | | |
| .68 | .690 | 1.440 | .690 | 1.690 | .980 | 1.690 | | | | | | |
| .82 | .750 | 1.440 | .760 | 1.690 | | | | | | | | |
| 1.0 | .750 | 1.690 | .840 | 1.690 | | | | | | | | |
| 1.25 | .840 | 1.690 | .930 | 1.690 | | | | | | | | |
| 1.5 | .920 | 1.690 | 1.020 | 1.690 | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | l | | l | | I | I | I | I | I | | |

ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park * 41 Interstate Lane * WATERBURY, CONNECTICUT 06705 Phone (203) 755-5629 FAX (203) 755-0659