

59036 Clamp Sensor Features and Benefits



Features

- Sensor with integral clamping feature
- Suitable for mounting on 15mm Ø pipework
- Choice of contacts
- Choice of connector
- Customer defined cable length


Benefits

- No standby power required
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination
- Quick and simple clip fit feature

Applications

- Position and limit sensing
- Linear actuators
- Industrial Process Control
- Liquid level control

DIMENSIONS (in) mm



CUSTOMER OPTIONS - Switching Specifications


TABLE I			Normally Open	Normally Open High Voltage	Change Over	Normally Closed
Contact Type			1	2	3	4
Switch Type						
Power	Power	Watt - max.	10	10	5	5
	Switching	Vdc - max.	200	300	175	175
Voltage	Breakdown	Vdc - min.	250	450	200	200
	Switching	A - max.	0.5	0.5	0.25	0.25
Current	Carry	A - max.	1.2	1.5	1.5	1.5
	Contact, Initial	Ω - max.	0.2	0.2	0.2	0.2
Resistance	Insulation	Ω - min.	10 ¹⁰	10 ¹⁰	10 ⁷	10 ⁷
	Contact	pF - typ.	0.3	0.2	0.3	0.3
Capacitance	Operating	°C	-40 to +105	-20 to +105	-40 to +105	-40 to +105
	Storage	°C	-65 to +105	-65 to +105	-65 to +105	-65 to +105
Temperature	Operate	ms - max.	1.0	1.0	3.0	3.0
	Release	ms - max.	1.0	1.0	3.0	3.0
Time	11ms 1/2 sine	G - max.	100	100	50	50
Shock	50-2000 Hz	G - max.	30	30	30	30
Vibration						

CUSTOMER OPTIONS - Cable Length and Termination Specification

TABLE 2	TABLE 3	ACTIVATION
Cable Type:- 24 AWG 7/32 PVC 105°C ULI1430/UL1569 Standard Lengths SELECT OPTION CABLE LENGTH (in) mm 01 (3,94) 100 02 (11,81) 300 03 (19,69) 500 04 (29,53) 750 05 (39,37) 1000	Termination Options:- SELECT OPTION DESCRIPTION (2 WIRE VERSIONS ILLUSTRATED) A or F Tinned or untinned leads C 6.35mm fastons D AMP MTE 2.54mm pitch E JST XHP 2.5mm pitch	Using Hamlin 57025 actuator as illustrated below

ORDERING INFORMATION

N.B. 57025 actuator sold separately



Hamlin USA Tel: +1 920 648 3000 • Fax: +1 920 648 3001 • Email: sales.us@hamlin.com
 Hamlin UK Tel: +44 (0)1379 649700 • Fax: +44 (0)1379 649702 • Email: sales.uk@hamlin.com
 Hamlin Germany Tel: +49 (0) 6181 953660 • Fax: +49 (0) 6181 953666 • Email: sales.de@hamlin.com
 Hamlectrol France Tel: +33 (0) 1 4687 0202 • Fax: +33 (0) 1 4686 6786 • Email: sales.fr@hamlin.com

DETAILS PROVIDED ON THIS DATA SHEET ARE PROVIDED FOR INFORMATION PURPOSES ONLY AND SHOULD NOT BE RELIED UPON AS BEING ACCURATE FOR ANY PARTICULAR PURPOSE. Product performance may be affected by the application to which the product is put. Upon request, HAMLIN will assist purchasers by providing information specific to any particular application. HAMLIN disclaims any and all liability whatsoever for any purchaser's reliance upon the information contained on this data sheet without further consultation with authorised representatives of HAMLIN.