

GLASS PASSIVATED SUPER FAST RECTIFIERS

PRODUCT SUMMARY

Reverse Voltage 50 to 600 Volts
 Forward Current 8.0 Amperes




FEATURES

Superfast switching time for high efficiency
 Low reverse leakage current
 High surge capacity

MECHANICAL DATA

Case: TO-220AB full molded plastic package
 Terminals: Lead solderable per MIL-STD-202, Method 208
 Polarity: As marked
 Standard packaging: Any
 Weight: 0.08 ounces, 2.24 grams

TO-220AB



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified.)


Parameter	Symbol	MUR805CT	MUR810CT	MUR820CT	MUR840CT	MUR860CT	Unit	
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	Volts	
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	Volts	
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	Volts	
Maximum average forward rectified current at $T_c=120^\circ\text{C}$	$I_{F(AV)}$	8.0						Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	100.0						Amps
Maximum instantaneous forward voltage at 4.0A per element	V_F	2.2				2.8		Volts
Maximum DC reverse current at rated DC blocking voltage	I_R	10.0 800						μA
Maximum reverse recovery time at $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_T=0.25\text{A}$	t_{rr}	30			50			nS
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150						$^\circ\text{C}$

Notes: 1. Pulse test: Pulse width 300 usec, Duty cycle 2%

RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Figure 1
Typical Forward Characteristics



Instantaneous Forward Current - Amperes *versus*
Instantaneous Forward Voltage - Volts

Figure 2
Typical Reverse Characteristics






Figure 3
Forward Derating Curve



Average Forward Rectified Current - Amperes *versus*
Ambient Temperature - $^\circ\text{C}$

Figure 4
Maximum Non-Repetitive Forward Surge Current



Peak Forward Surge Current - Amperes *versus*
Number Of Cycles At 60Hz - Cycles

Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, expressed or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.