



#### General ordering data

|                  |   |
|------------------|---|
| Order No.        | 1630500000  |
| Part designation | SL 5.00/4/135B3.2SN OR  |
| Version          | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 4, 135°, Box |
| EAN              | 4008190203924   |
| Qty.             | 100 pc(s).  |

#### System parameters

|                             |                     |
|-----------------------------|---------------------|
| Fitted to PCB               | Soldered connection |
| Outgoing elbow              | 135°                |
| Pitch                       | 5 mm                |
| Pitch in inch               | 0.197 inch          |
| No. of poles                | 4                   |
| Solder pin length           | 3.2 mm              |
| Can be coded                | Yes                 |
| No. of rows                 | 1                   |
| No. of solder pins per pole | 1                   |
| Dia. of fitting hole        | 1.3 mm              |
| Fitting hole tolerance      | + 0.1 mm            |
| L1 in mm                    | 15 mm               |
| L1 in inch                  | 0.591 inch          |
| Insulation resistance       | 1 MΩ                |

#### System parameters

|   |  |
|---|--|
| Electric shock protection to DIN VDE 0470 | Finger-safe plugged/ back-of-hand-safe unplugged |
|---|--|

#### Material data

|                                       |                     |
|---------------------------------------|---------------------|
| Insulating material                   | PBT                 |
| Colour                                | orange              |
| colour chart                          | Similar to RAL 2000 |
| Insulating material group             | IIIa                |
| Flammability class UL 94              | V-0                 |
| CTI                                   | >= 200              |
| Contact base material                 | CuSn                |
| Contact surface                       | tinned              |
| Constant operating temp., min.        | -25 °C              |
| Constant operating temp., max.        | 100 °C              |
| Storage temperature, min.             | -25 °C              |
| Storage temperature, max.             | 55 °C               |
| Max. relative humidity during storage | 80 %                |

#### DIN IEC rating data

|  |                   |
|--|-------------------|
| Rated current, min. No. pins (Tu=20°C)   | 17 A              |
| Rated current, max. No. pins (Tu=20°C)   | 13 A              |
| Rated current, min. No. pins (Tu=40°C)   | 15 A              |
| Rated current, max. No. pins (Tu=40°C)   | 11 A              |
| Rated voltage for overvoltage class/pollution severity III/3                   | 250 V             |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV              |
| Rated voltage for overvoltage class/pollution severity III/2                   | 320 V             |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV              |
| Rated voltage for overvoltage class/pollution severity II/2                    | 400 V             |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2  | 4 kV              |
| Short-time withstand current resistance  | 3 x 1s with 120 A |

#### CSA rating data

|                             |       |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A  |

#### UL 1059 rating data

|                             |       |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A  |

## Approvals

Approvals institutes



## Classifications

|            |             |
|------------|-------------|
| ETIM 2.0   | NK          |
| ETIM 3.0   | EC001284    |
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |
| eClass 5.1 | 27-26-07-04 |

## Similar products

| Order No.  | Part designation        | Version  |
|------------|-------------------------|--|
| 1630480000 | SL 5.00/2/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 2, 135°, Box  |
| 1630490000 | SL 5.00/3/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 3, 135°, Box  |
| 1630510000 | SL 5.00/5/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 5, 135°, Box  |
| 1630520000 | SL 5.00/6/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 6, 135°, Box  |
| 1630530000 | SL 5.00/7/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 7, 135°, Box  |
| 1630540000 | SL 5.00/8/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 8, 135°, Box  |
| 1630550000 | SL 5.00/9/135B3.2SN OR  | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 9, 135°, Box  |
| 1630560000 | SL 5.00/10/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 10, 135°, Box |
| 1630570000 | SL 5.00/11/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 11, 135°, Box |
| 1630580000 | SL 5.00/12/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 12, 135°, Box |
| 1630590000 | SL 5.00/13/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 13, 135°, Box |

|           |                         |  |
|-----------|-------------------------|--|
| 163060000 | SL 5.00/14/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 14, 135°, Box |
| 163061000 | SL 5.00/15/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 15, 135°, Box |
| 163062000 | SL 5.00/16/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 16, 135°, Box |
| 163063000 | SL 5.00/17/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 17, 135°, Box |
| 163064000 | SL 5.00/18/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 18, 135°, Box |
| 163065000 | SL 5.00/19/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 19, 135°, Box |
| 163066000 | SL 5.00/20/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 20, 135°, Box |
| 163067000 | SL 5.00/21/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 21, 135°, Box |
| 163068000 | SL 5.00/22/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 22, 135°, Box |
| 163069000 | SL 5.00/23/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 23, 135°, Box |
| 163070000 | SL 5.00/24/135B3.2SN OR | PCB plug-in connector, Male connectors, Soldered connection, Pitch: 5.00 mm, No. of poles: 24, 135°, Box |