


# SAW Bandpass Filter 203403B



## 1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

## 2. Package Dimension



### Package : D3512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

| Pin Configuration |             |
|-------------------|-------------|
| 1                 | Input       |
| 5                 | Output      |
| 2, 4              | Ground      |
| 3, 6              | Case ground |

|  |   |           |             |     |
|--|---|-----------|-------------|-----|
|  | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 203403B     |     |
|  |   | Rev. Date | 2004-04-26  |     |
|  |   | Rev.      | NI0026-CS02 | 1/5 |

# SAW Bandpass Filter 203403B



## 3. Specifications

Fo = 80.85 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

|  |        | Minimum | Typical | Maximum |
|--|--------|---------|---------|---------|
| Center Frequency                       | MHz    | 80.82   | 80.85   | 80.88   |
| Insertion Loss                         | dB     | -       | 21.5    | 23.5    |
| 1dB Bandwidth                          | MHz    | -       | 10.84   | -       |
| 3dB Bandwidth                          | MHz    | 11.2    | 11.25   | 11.3    |
| 40dB Bandwidth                         | MHz    | -       | 12.65   | 12.8    |
| Amplitude Ripple (Fo +/- 5.2 MHz)      | dB     | -       | 1.0     | 1.5     |
| Group Delay Variation (Fo +/- 5.2 MHz) | nsec   | -       | 70      | 150     |
| Absolute Delay                         | usec   | -       | 2.5     | -       |
| Ultimate Rejection                     | dB     | 50      | 55      | -       |
| Temperature Coefficient of Frequency   | ppm/°C | -       | -72     | -       |

### Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss

|   |   |           |             |     |
|---|---|-----------|-------------|-----|
| <br>Integrated Technology Future | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 203403B     |     |
|   |   | Rev. Date | 2004-04-26  |     |
|   |   | Rev.      | NI0026-CS02 | 2/5 |

# SAW Bandpass Filter 203403B



## 4. Matching Schematic

( Actual matching values may vary due to PCB layout and parasitics )



## 5. Marking Configuration

ITF<sup>1)</sup>04A001<sup>2)</sup>  
203403B<sup>3)</sup>



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

|  |   |           |             |     |
|--|---|-----------|-------------|-----|
|  | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 203403B     |     |
|  |   | Rev. Date | 2004-04-26  |     |
|  |   | Rev.      | NI0026-CS02 | 3/5 |

# SAW Bandpass Filter 203403B



## 6. Typical Performance ( at +25°C )







**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No. 203403B

Rev. Date 2004-04-26

Rev. NI0026-CS02 4/5

# SAW Bandpass Filter 203403B



**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No. 203403B

Rev. Date 2004-04-26

Rev. NI0026-CS02 5/5