

NTS500 Series

500 Watts

Total Power: 200 - 500 Watts
Input Voltage: 85 - 264 Vac
120 - 300 Vdc
of Outputs: Single



Special Features

- Active power factor correction
- IEC EN61000-3-2 compliance
- Remote sense
- Power fail and remote inhibit
- Single wire current sharing
- Built-in EMI filter
- Low output ripple
- 5V standby
- 12V fan output
- Overvoltage protection
- Overload protection
- Thermal overload protection
- DC power good
- Built in OR-ing diode / FET
- Optional fan cover (-CF suffix)
- PM Bus compliant
- Digital I²C interface
- 2 year warranty
- POE isolation on NTS508

Safety

TUV: 60950
cCSAus: 60601-1
NEMKO: 60950
AUSTEL: 60950
CB: Certificate and report
CE: Mark (LVD)

Electrical Specifications

Input

Input range: 85 - 264 Vac (wide range)
Frequency: 47-63 Hz
Inrush current: 50 A max., cold start @ 25°C
Efficiency: 85% typical at full load, nominal line
EMI filter: FCC Class B conducted and radiated; CISPR22 Class B conducted and radiated; EN55022 Class B conducted and radiated; VDE0878PT3 Class B conducted and radiated.
Safety ground leakage current: <0.5 mA @ 50/60 Hz, 264 Vac input

Output

Maximum power: 200 W for convection; 500 W with 30 CFM forced air
Adjustment range: ±5%
Standby output: 5 V @ 1 A regulated, ±5%
Fan output: 12 V @ 0.5 A, -5 %, +7%, 0.5 A for -CF version
Hold-up time: 20 ms @ 500 W load, 115 VAC nominal line at factory voltage setting
Overload protection: Short circuit protection on all outputs. Case overload protected @ 115-130% above peak rating
Overvoltage protection: 20-35% above nominal output



Logic Control

Power failure:	TTL logic signal goes high 100-500 msec after main output. It goes low at least 4 msec before loss of regulation
Remote on/off:	Requires an external contact closure to inhibit outputs
DC OK:	TTL logic goes high after the output is in regulation. It goes low when there is loss of regulation.
Remote sense:	Compensates for 0.5 V lead drop min. Will operate without remote sense connected. Reverse connection protected.

Environmental Specifications

Operating temperature:	0° to 50 °C ambient derate each output as 2.5% per degree from 50° to 70 °C.
Storage temperature:	-40°C to +85°C
Electromagnetic susceptibility:	Designed to meet EN61000-4; -2, -3, -4, -5, -6, -8, -11 Level 3
Humidity:	Operating; non-condensing 10% to 90% RH
Vibration:	Three orthogonal axes, sweep at 1 oct/min, 5 min. dwell at four major resonances 2 G peak 8 Hz to 500 Hz, operational
MTBF demonstrated:	1M hours at full load and 25 °C ambient conditions

Ordering Information

Model Number	Output Voltage	Minimum Load	Maximum Load with Convection Cooling	Maximum Load with 30CFM Forced Air	Peak Load ¹	Regulation ²	Ripple P/P (PARD) ³
NTS503	12 V	0 A	16.6 A	41.7 A	47 A	±2%	120 mV
NTS505	24 V	0 A	8.3 A	20.8 A	23.4 A	±2%	240 mV
NTS508	48 V	0 A	4.2 A	10.4 A	11.7 A	±2%	480 mV

- Peak current lasting <30 seconds with a maximum 10% duty cycle.
- At 25°C including initial tolerance, line voltage, load currents and output voltages adjusted to factory settings.
- Peak-to-peak with 20 MHz bandwidth and 10 µF (tantalum capacitor) in parallel with a 0.1 µF capacitor at rated line voltage and load ranges.
- 5 V standby and 12 V fan output cannot be used above 50 °C with convection cooling.

Pin Assignments

Connector

CN1	PIN 1	Line
	PIN 3	Neutral
	PIN 5	Ground
SK7	PIN 1	V1 swp
	PIN 2	- Remote Sense
	PIN 3	+ Remote Sense
	PIN 4	5 VSB (standby)
	PIN 5	5 VSB return
	PIN 6	+12 V
	PIN 7	Common
	PIN 8	Inhibit
	PIN 9	DC power good (DC OK)
	PIN 10	Power Fail (POK)



CN403

PIN 1	Ground
PIN 2	A2_out
PIN 3	A1_out
PIN 4	A0_out
PIN 6	I ² C_sda_out
PIN 7	5 V_I ² C
PIN 8	n/c
PIN 9	n/c
PIN 10	n/c



Adjustment Potentiometers

P1	+V1 Output adjust
P3	+5 VSB adjust

Mating Connectors

SK4,5,6	Molex 19141-0058
----------------	------------------

SK7 Control signals	Molex 90142-0010 PINS: 90119-2110
----------------------------	--------------------------------------

or

Amp: 87977-3
PINS: 87309-8

SK8	Molex 22-01-2025 Pins: 08-52-0123
------------	--------------------------------------


CN403	JST PHDR-10VS Pins: JST 5PHD-002T-PO.5-L/P or Landwin 2050 S1000 Pins: 2053T011P
--------------	---

Astec Connector Kit #70-841-024 includes all of the above

Notes:

- Specifications subject to change without notice.
- All dimensions in inches (mm), tolerance is ±.02".
- Specifications are at factory settings
- Mounting maximum insertion depth is 0.12".
- Warranty: 2 year
- Weight: 3.016 lb. / 1.18 kg.

Mechanical Drawing



Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 (760) 930 4600
Facsimile: +1 (760) 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.powerconversion.com
techsupport.embeddedpower@emerson.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Emerson Network Power.
The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- **Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
©2008 Emerson Electric Co.