


TOSHIBA LED LAMP InGaAlP RED LIGHT EMISSION

TLRMH265P

- 5 mm DIAMETER
- InGaAlP RED LED
- Diffused Milky White Lens
- Low Drive Current, High Intensity Red Light Emission
- All Plastic Molded Lens, Provides an Excellent ON-OFF Contrast Ratio.
- Fast Response Time, Capable of Pulse Operation.
- Straight Lead Type
- Application : Exit Sign, Security Equipment

Unit in mm



Weight : 0.31 g

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Forward Current (DC)	I_F	50	mA
Reverse Voltage	V_R	4	V
Power Dissipation	P_D	125	mW
Operating Temperature Range	T_{opr}	-40~100	°C
Storage Temperature Range	T_{stg}	-40~120	°C

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP.	MAX	UNIT
Forward Voltage	V_F	$I_F = 20$ mA	—	2.05	2.5	V
Reverse Current	I_R	$V_R = 4$ V	—	—	50	μ A
Luminous Intensity	I_V	$I_F = 20$ mA	272	650	—	mcd
Peak Emission Wavelength	λ_p	$I_F = 20$ mA	—	636	—	nm
Spectral Line Half Width	$\Delta\lambda$	$I_F = 20$ mA	—	20	—	nm
Dominant Wavelength	λ_d	$I_F = 20$ mA	—	626	—	nm







For part availability and ordering information please call Toll Free: 800.984.5337
 Website: www.marktechopto.com | Email: info@marktechopto.com

PRECAUTION

Please be careful of the followings

- Soldering temperature : 260°C max Soldering time : 3 s max
(Soldering portion of lead : up to 2 mm from the body of the device)
- If the lead is formed, the lead should be formed up to 5 mm from the body of the device without forming stress to the resin. Soldering should be performed after lead forming.
- This visible LED lamp also emits some IR light. If a photodetector is located near the LED lamp, please ensure that it will not be affected by this IR light.



RADIATION PATTERN

