



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

N-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 30 Volts CURRENT 8.9 Ampere

CHM3172JPT

Lead free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (SO-8)
- * Super High density cell design for extremely low R_{DS(ON)}.
- * High saturation current capability.


CONSTRUCTION

- * N-Channel Enhancement

CIRCUIT



SO-8



Dimensions in millimeters

SO-8

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM3172JPT	Units
V _{DSS}	Drain-Source Voltage	30	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	8.9	A
	- Pulsed (Note 3)	30	
P _D	Maximum Power Dissipation	2500	mW
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
2006-01			

RATING CHARACTERISTIC CURVES (CHM3172JPT)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	30			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 30 \text{ V}, V_{\text{GS}} = 0 \text{ V}$			1	μA
I_{GSSF}	Gate-Body Leakage	$V_{\text{GS}} = 20\text{V}, V_{\text{DS}} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{\text{GS}} = -20\text{V}, V_{\text{DS}} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	1		3	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}, I_D=6.3\text{A}$		16	20	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_D=5.0\text{A}$		22	28	

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{\text{DS}} = 15\text{V}, V_{\text{GS}} = 0\text{V}, f = 1.0 \text{ MHz}$		1080		pF
C_{oss}	Output Capacitance			220		
C_{rss}	Reverse Transfer Capacitance			140		

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{\text{DS}}=15\text{V}, I_D=6\text{A}$ $V_{\text{GS}}=5\text{V}$		10.4	13	nC
Q_{gs}	Gate-Source Charge			3.5		
Q_{gd}	Gate-Drain Charge			3.8		
t_{on}	Turn-On Time	$V_{\text{DD}}= 15\text{V}$ $I_D = 1.0\text{A}, V_{\text{GS}} = 10 \text{ V}$ $R_{\text{GEN}} = 6 \Omega$		16	30	nS
t_r	Rise Time			9	20	
t_{off}	Turn-Off Time			31	60	
t_f	Fall Time			10	20	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current	(Note 1)			2.3	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = 2.3\text{A}, V_{\text{GS}} = 0 \text{ V}$ (Note 2)			1.2	V