

FEATURES

4-input, 1-output multiplexed HDMI transceiver
HDMI 1.4 support
Audio return channel (ARC)
3D TV support
Content type bits
CEC 1.4-compatible (CEC_CPD and CEC_HPDP)

Xpressview™ fast switching on all HDMI input ports
Character- and icon-based on-screen display (OSD)
High-Bandwidth Digital Content Protection (HDCP 1.4)
HDCP repeater support
225 MHz HDMI Rx and Tx support 36-/30-/24-bit Deep Color
Supports DVI RGB graphics up to 1600 × 1200 at 60 Hz
Ultralow jitter digital PLL (100% deskew)

Quad HDMI Rx input
Format details available on all unselected ports
Adaptive equalizer for cable lengths up to 30 meters
Internal extended display identification data (EDID) RAM
EDID replication (512 bytes per port)
EDID with HDMI cable 5 V power support
5 V detect inputs
Hot plug assertion control pins

Single HDMI Tx output
EDID data extraction
Hot plug detect (HPD) input

Audio support
HDMI 1.4-compatible audio interface
Dedicated flexible audio input/output port
S/PDIF (IEC 60958-compatible) digital audio input/output
Super audio CD (SACD) with DSD input/output interface
High bit rate (HBR) audio
Dolby® TrueHD
DTS-HD Master Audio™
Full audio input and output support

General
Interrupt controller with 3 interrupt outputs
STDI (standard identification circuit)
Software libraries, driver, and application available
2-layer PCB design supported

APPLICATIONS

AVRs
HTiB
Sound bar with HDMI repeater support
HBR enabled TVs
Other repeater applications

GENERAL DESCRIPTION

The ADV7623 is a high performance, four-input, one-output, High-Definition Multimedia Interface (HDMI™) transceiver that integrates HDMI 1.4 receiver and transmitter functions with digital audio I/Os onto one chip. It supports all HDCP repeater functions through fully tested Analog Devices, Inc., repeater software libraries and drivers.

The ADV7623 incorporates Xpressview fast switching on all input HDMI ports. Using an Analog Devices hardware-based HDCP engine that minimizes software overhead, Xpressview technology allows fast switching between any HDMI input ports in less than 1 second.

The ADV7623 supports all mandatory HDMI 1.4 3D TV formats in addition to all HDTV formats up to 1080p 36-bit Deep Color. The ADV7623 also features an integrated HDMI 1.4 CEC controller, which supports capability, discovery, and control (CDC).

The ADV7623 has an integrated on-screen display (OSD) feature that allows generation and control of high quality character- and icon-based system status and control displays. Customers interested in using OSD are provided with Analog Devices OSD SDK.

The ADV7623 offers a dedicated flexible audio output port and a dedicated audio input port to allow for easy extraction and insertion of audio data into and out of the HDMI stream. HDMI audio formats, including SACD via DSD and compressed high bit rate audio via HBR, are supported. The ADV7623 also features an audio return channel (ARC) receiver. ARC simplifies cabling by combining upstream audio capability in a conventional HDMI cable.

Fabricated in an advanced CMOS process, the ADV7623 is provided in a 144-lead, 20 mm × 20 mm, Pb-free LQFP and is specified over the 0°C to 70°C temperature range.

For more information on the ADV7623, contact a local Analog Devices sales office or email ATV_VIDEORX_INFO@analog.com.

Advantiv
Advanced Television Solutions
by Analog Devices

Xpressview
Fast Switching Technology
by Analog Devices

Rev. SpA

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113 ©2010 Analog Devices, Inc. All rights reserved.

ADV7623

NOTES