

TABLE II: SHELL SIZE

Shell Size		E ± .06	F ± .09	G Max	H ± .03	J	K
F	H						
08	09	.72 (18.3)	.87 (22.1)	.63 (16.0)	1.042 (26.5)	.304 (7.7)	.160 (4.1)
10	11	.75 (19.1)	.93 (23.6)	.66 (16.8)	1.107 (28.1)	.432 (11.0)	.174 (4.4)
12	13	.75 (19.1)	1.00 (25.4)	.72 (18.3)	1.174 (29.8)	.546 (13.9)	.195 (5.0)
14	15	.76 (19.3)	1.03 (26.2)	.83 (21.1)	1.241 (31.5)	.670 (17.0)	.315 (8.0)
16	17	.78 (19.8)	1.05 (26.7)	.91 (23.1)	1.305 (33.1)	.796 (20.2)	.385 (9.8)
18	19	.79 (20.1)	1.06 (26.9)	.93 (23.6)	1.371 (34.8)	.902 (22.9)	.445 (11.3)
20	21	.82 (20.8)	1.09 (27.7)	1.04 (26.4)	1.438 (36.5)	1.027 (26.1)	.525 (13.3)
22	23	.86 (21.8)	1.13 (28.7)	1.12 (28.4)	1.505 (38.2)	1.152 (29.3)	.595 (15.1)
24	25	.89 (22.6)	1.16 (29.5)	1.18 (30.0)	1.572 (39.9)	1.276 (32.4)	.655 (16.6)

TABLE III: FINISH

Symbol	Finish Description
XM	2000 Hour Corrosion Resistant Electroless Nickel
XMT	2000 Hour Corrosion Resistant Ni-PTFE, Nickel-Fluorocarbon Polymer. <i>1000 Hour Grey™</i>
XW	2000 Hour Corrosion Resistant Cadmium Olive Drab Over Electroless Nickel

TABLE IV: BRAID TYPE

Symbol	Braid Type
A	100% AmberStrand®
B	75%/25% AmberStrand® Blend
L	100% ArmorLite™
Standard	Nickel/Copper 34awg
T	Tin/Copper 34awg

NOTES

1. 770-001S**-0 shrink boot supplied with T option. See shrink boot product page for more details.
2. Coupling nut supplied unplated.
3. See Table I in Intro for front end dimensional details.