


CL-194S (Rタイプ) シリーズ

Mono-Color Upward-Lighting Type CL-194S(R type) Series



● 小型・薄型の広指向性青色LEDです。

● Compact, thin, and wide-directivity blue LED

●絶対最大定格/Absolute Maximum Rating

(Ta 25°C)

Series	Pd (mW)	I _F (mA)	I _{FP} (mA)	V _R (V)	T _{op} (°C)	T _{st} (°C)
CL-194S (R type)	35	10	100*1	4	-25~+80	-30~+85

※1 I_{FP}の条件はduty 1/10、パルス巾30msecです。

※1 Condition for I_{FP} is pulse of 1/10 duty and 30msec width.

●電氣的光学的特性/Electro-optical Characteristics


(Ta 25°C)

Product code	Lighting color	V _F			λ _p typ (nm)	Δλ typ (nm)	I _v * (mcd)		
		I _F (mA)	typ (V)	max (V)			I _F (mA)	min (mcd)	typ (mcd)
CL-194S(R type)-HB8-R	Blue	5	2.9	3.15	470	26	5	45	65

※NIST規格に準拠

※Per NIST standards


●外形寸法図/Outline drawing



推奨はんだ付けパターン

The following soldering patterns are recommended for reflow-soldering:

リフローはんだ用
For reflow soldering



■ 諸特性 / Characteristics

