



## PL008 Series SMD LED PLCC-2 Package Yellow

### Features

- \*PLCC-2 Package 3.2 x 2.7 x 1.9 mm
- \*High Luminous Output
- \*Very Wide Viewing Angle
- \*For use as Optical Indicator, Backlighting
- \*For Optical Coupling into Light Pipes/Lenses
- \*12mm Tape, 2000pc Reels
- \*RoHS Compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to + 85°C
Storage Temperature Range.....	-40°C to + 100°C
Reflow Soldering Temperature.....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Water Clear Lens			nm	nm	Deg				
PL008-WCY01	Yellow	GaAsP	585	590	120°	2.1	2.6	4.0	10.0

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

