


PROJ	LOC	DIST	REV	ZONE	LTR	DESCRIPTION	DATE	APPD
4092	DF	50			P	REDRAM & ADD 5--11, NPR 90-486 & DF-4147	12-90	DO
					R	REV PER DF-4804	9-91	SG

PART NO.	A Δ	B	
830637-1	11.00 [279.4]	-	
830637-2	24.00 [609.6]	-	
830637-3	6.50 [165.1]	.50 [12.7]	OBSOLETE
830637-4	9.00 [228.6]	-	
830637-5	36.00 [914.4]	.38 [9.7]	OBSOLETE
830637-6	30.00 [762.0]	-	
830637-7	72.00 [1828.8]	-	
830637-8	47.25 [1200.1]	.50 [12.7]	
830637-9	20.25 [514.3]	.50 [12.7]	
1-830637-0	8.00 [203.2]	.50 [12.7]	OBSOLETE
1-830637-1	36.00 [914.4]	-	
1-830637-2	12.00 [304.8]	.38 [9.7]	
1-830637-3	18.00 [457.2]	.38 [9.7]	
1-830637-4	108.00 [2743.2]	-	
1-830637-5	180.00 [4572.0]	-	OBSOLETE
1-830637-6	60.00 [1524.0]	.38 [9.7]	
1-830637-7	26.00 [660.4]	.38 [9.7]	OBSOLETE
1-830637-8	42.00 [1066.8]	.38 [9.7]	
1-830637-9	54.00 [1371.6]	.38 [9.7]	OBSOLETE
2-830637-0	5.00 [127.0]	.38 [9.7]	OBSOLETE
2-830637-1	6.00 [152.4]	.38 [9.7]	
2-830637-2	264.00 [6705.6]	.38 [9.7]	OBSOLETE
2-830637-3	17.00 [431.8]	.50 [12.7]	
2-830637-4	48.00 [1219.2]	.38 [9.7]	
2-830637-5	15.75 [400.0]	-	
2-830637-6	10.25 [260.3]	.38 [9.7]	
2-830637-7	14.00 [355.6]	.38 [9.7]	
2-830637-8	24.00 [609.6]	.38 [9.7]	
2-830637-9	240.00 [6096.0]	.38 [9.7]	OBSOLETE
3-830637-0	84.00 [2133.6]	.38 [9.7]	
3-830637-1	120.00 [3048.0]	.38 [9.7]	OBSOLETE
3-830637-2	96.00 [2438.4]	.38 [9.7]	OBSOLETE
3-830637-3	20.00 [508.0]	.38 [9.7]	
3-830637-4	15.00 [381.0]	.38 [9.7]	
3-830637-5	4.00 [101.6]	.38 [9.7]	OBSOLETE
3-830637-6	118.00 [2997.2]	.38 [9.7]	
3-830637-7	25.00 [635.0]	.38 [9.7]	OBSOLETE
3-830637-8	300.00 [7620.0]	.38 [9.7]	OBSOLETE
3-830637-9	196.88 [5000.8]	.38 [9.7]	
4-830637-0	144.00 [3657.6]	.38 [9.7]	OBSOLETE
4-830637-1	591.00 [15011.4]	.38 [9.7]	OBSOLETE
4-830637-2	30.00 [762.0]	.38 [9.7]	OBSOLETE
4-830637-3	16.00 [406.4]	.38 [9.7]	OBSOLETE
4-830637-4	158.00 [4013.2]	.38 [9.7]	
4-830637-5	237.00 [6019.8]	.38 [9.7]	
4-830637-6	19.75 [501.6]	.38 [9.7]	
4-830637-7	9.00 [228.6]	.38 [9.7]	OBSOLETE
4-830637-8	13.00 [330.2]	.38 [9.7]	OBSOLETE
4-830637-9	315.00 [8001.0]	-	
5-830637-0	12.25 [311.15]	-	
5-830637-1	59.00 [1498.6]	.38 [9.7]	



- Δ TOLERANCE OF LEAD LENGTH:
 UP TO 24 INCHES [609.6] = \pm .12 [\pm 3.0]
 24 INCHES [609.6] & UP = \pm 1%
- MARKED PER MIL-STD-130.
 - PIGTAIL IS SOLDER DIPPED.
 - TO MATE WITH AMP LGH-1L
 - RECEPTACLE WITH 1.69 [42.93] BARREL DEPTH.
 - OPERATING VOLTAGE: 25 KVDC AT 0 TO 70,000 FEET; -55°C TO 125°C.
 - MIN LEAD LENGTH IS 5.00 [127.0].

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN INCHES (mm) TOLERANCES ON: 2 PLC DEC \pm .02 (0.51) 3 PLC DEC \pm -	DR 12-5-90 C.C. THOMAS	NAME	AMP INCORPORATED Mortonsburg, Pa. 17105
MATERIAL SEE CALLOUTS	CHK 12-12-91 D. OPLINGER	LEAD ASSY, SGL. END, LGH-1L	
FINISH SEE CALLOUTS	APPD 12-12-91 D. EBY	SIZE CAGE CODE C 00779	DRAWING NO 830637
	PRODUCT SPEC	SCALE 2:1	SHEET 1 OF 1
	APPLICATION SPEC		
	WEIGHT		