

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free

## FEATURES

- Low Diode Capacitance
- Low Diode Forward Resistance


## PACKAGING INFORMATION

Weight: 0.0039 g (Approximate)

## MARKING CODE

A81

SOD-323



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	1.05 REF.		E	0.080	0.180
B	0.20 REF.		F	1.15	1.45
C	0.80	1.00	G	1.60	1.80
D	0.25	0.40	H	2.30	2.70

## MAXIMUM RATINGS (Single diode @ $T_A = 25^\circ\text{C}$ )


Parameter	Symbol	Ratings	Unit
Continuous Reverse Voltage	$V_R$	50	V
Continuous Forward Current	$I_F$	50	mA
Power Dissipation ( $T_A = 90^\circ\text{C}$ )	$P_D$	200	mW
Junction, Storage Temperature	$T_J, T_{STG}$	-55 ~ +150	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS (at $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameters	Symbol	Min.	Max.	Unit	Test Conditions
Continuous Reverse Voltage	$V_R$	50	-	V	$I_R = 10 \mu\text{A}$
Forward Voltage	$V_F$	-	1.1	V	$I_F = 50 \text{ mA}$
Reverse Current	$I_R$	-	100	nA	$V_R = 50 \text{ V}$
Diode Capacitance	$C_{D1A}$	-	0.91	pF	$V_R = 0, f = 1\text{MHz}$
	$C_{D1B}$	-	1.11		$V_R = 0, f = 1\text{MHz}$
	$C_{D2}$	-	0.55		$V_R = 1 \text{ V}, f = 1\text{MHz}$
	$C_{D3}$	-	0.35		$V_R = 5 \text{ V}, f = 1\text{MHz}$
Diode Forward Resistance	$r_D$	-	40	$\Omega$	$I_F = 0.5 \text{ mA}, f = 100 \text{ MHz}$
		-	25		$I_F = 1 \text{ mA}, f = 100 \text{ MHz}$
		-	5		$I_F = 10 \text{ mA}, f = 100 \text{ MHz}$


**RATINGS AND CHARACTERISTIC CURVES**

**BAP50-03**




f = 100 MHz; T<sub>J</sub> = 25 °C.

Fig.1 Forward resistance as a function of forward current; typical values.



f = 1 MHz; T<sub>J</sub> = 25 °C.


Fig.2 Diode capacitance as a function of reverse voltage; typical values.



(1) I<sub>F</sub> = 10 mA. (2) I<sub>F</sub> = 1 mA. (3) I<sub>F</sub> = 0.5 mA.

Diode inserted in series with a 50 Ω stripline circuit and biased via the analyzer Tee network.  
T<sub>amb</sub> = 25 °C.

Fig.3 Insertion loss ( $|S_{21}|^2$ ) of the diode as a function of frequency; typical values.



Diode zero biased and inserted in series with a 50 Ω stripline circuit.  
T<sub>amb</sub> = 25 °C.

Fig.4 Isolation ( $|S_{21}|^2$ ) of the diode as a function of frequency; typical values.