

CLEARTUBE

Clear P.V.C. Tubing

Construction

Cleartube is made from a clear P.V.C. material: its smooth inner surface minimizes flow-resistance whilst the P.V.C. material offers excellent resistance to abrasion and chemicals, it is available in two grades—food grade or industrial.

Applications

Cleartube is designed to provide a light weight, highly flexible tubing specifically for liquids and low-pressure gases.

Details

Cleartube is available in four different wall thicknesses; for sizes and wall thicknesses, see table.

Longth:

30m Coils (100ft)-other

lengths are available to order.

Temperatures:


-0°C to +60°C.

Colour:

Clear: other colours are

available to order.

The state of the s



2	Wall Thickness; Japan (Xila)
	UPUA Inches
	6
1	10 % 12 %
	18 %
	28 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	32 1X 36 1X

	Thi	ckne (*/=i	na:	
	IAD		-chai	18
32 38			1 % 1 %	

Well Thickness:	
FOR Inches	
50 2 60 216	
75	

Other sizes are available to order.

-5% +0% -5% +0%

Important Note: Please note that the information is to the best of our knowledge, true and accurate. We reserve the right to alter the specifications without notice. Since conditions under which the products may be used are beyond our control, our recommendations are made without warranty or guarantee and we cannot be held responsible for misuse of products or information. However, our experienced technical staff would be happy to advise you on the uses for which our products are suitable.

Southern Division & Headquerters: FLEXIBLE MOSE SUPPLIES LTD., 140 EDINBURGH AVENUE, SLOUGH, BERKS, SL1 4UA TEL: 01753 570863 FAX: 01753 824141 TELEX: 849182

Midland Division & Manufacturing Plant: FLEX-METALLIC INDUSTRIES. CASWELL ROAD, BRACKMILLS INDUSTRIAL ESTATE, NORTHAMPTON, NN4 OPW TEL: 01604 762176 FAX: 01604 769915 Northern Division: FLEXIBLE HOSE SUPPLIES LTD., SPRINGFIELD ROAD, KEARSLEY. BOLTON, LANCS, BL4 8NB TEL: 01204 796736 FAX: 01204 796767

0 1984