



# PD500


## 500 $\mu$ m InGaAs Photodiode

### FEATURES


- Planar Structure
- Dielectric Passivation
- High Shunt Resistance
- High Responsivity

### APPLICATIONS

- High Sensitivity Instrumentation
- Laser Back Facet Monitoring



PD500-0xx  
Ceramic Sub-Mount



PD500-1xx  
TO can Package

### PRODUCT DESCRIPTION

The PD500 is an InGaAs photodiode with a photosensitive region 500 $\mu$ m in diameter. It is intended for use in high sensitivity instrumentation, laser back-facet monitoring and low bit rate communication systems.

Planar semiconductor design and dielectric passivation provide superior noise performance. The device can be assembled on a ceramic sub-mount or in an hermetic TO46 can. Custom packages are an option.

### ELECTRICAL CHARACTERISTICS

Table 1: Electrical Specifications

PARAMETER	MIN	TYP	MAX	UNIT
Dark Current ( $I_D$ ) <sup>(1)</sup>	-	25	-	nA
Capacitance <sup>(2)</sup>	-	20	-	pF
Responsivity at 1310nm	0.80	0.90	-	A/W
Responsivity at 1550nm	0.85	0.95	-	A/W
Rise/Fall time	-	3	-	ns
Shunt Resistance (Class A) <sup>(2)</sup>	50	-	-	M $\Omega$

(1) 5V reverse bias

(2) 0V reverse bias

# PD500



## ELECTRICAL CHARACTERISTICS (cont)

**Table 2: Absolute Maximum Ratings**

PARAMETER	MIN	MAX	UNIT
Forward Current	-	50	mA
Reverse Current	-	5	mA
Reverse Voltage	-	15	V
Optical input power	-	5	mW
Operating Case Temperature	-40	+85	°C
Storage Temperature	-40	+85	°C
Soldering temperature (10 seconds)	-	+250	°C

Stresses in excess of the absolute ratings may cause permanent damage. Functional operation is not implied under these conditions. Exposure to absolute ratings for extended periods of time may adversely affect reliability.

## ORDERING INFORMATION

Part Number	Options
PD500-0xx	Custom defined size and electrical layout
PD500-1xx	Package: TO46 Number of pins: 2, 3 Cap: Window, AR / Non-AR coated. Cap plating: Gold or nickel

Please contact Anadigics for the specific part number and pinout that suits your needs

**ANADIGICS, Inc.**  
829 Flynn Road  
Camarillo, California 93012, U.S.A.  
Tel: +1 (805) 445-4500  
Fax: +1 (805) 445-4502  
URL: <http://www.anadigics.com>  
E-mail: [Mktg@anadigics.com](mailto:Mktg@anadigics.com)

### IMPORTANT NOTICE

ANADIGICS, Inc. reserves the right to make changes to its products or discontinue any product at any time without notice. The product specifications contained in Advanced Product Information sheets and Preliminary Data sheets are subject to change prior to a product's formal introduction. Information in Data Sheets have been carefully checked and are assumed to be reliable; however, ANADIGICS assumes no responsibility for inaccuracies. ANADIGICS strongly urges customers to verify that the information they are using is current before placing orders.

### WARNING

ANADIGICS products are not intended for use in life support appliances, devices, or systems. Use of an ANADIGICS product in any such application without written consent is prohibited.