

InGaAs PIN PHOTODIODE

PD-1190

2 mm InGaAs PIN Photodiode with TO-5 Package

FEATURES

- 2 High responsivity for dual windows at 1310 nm and 1550 nm
- 2 Low dark current
- 2 Hermetically sealed TO-5 3-pin metal case
- 2 Active diameter 2 mm
- 2 Flat Window Cap Package




DESCRIPTION

PD-1190 InGaAs Photodiode are suited to receive the light at the wavelength range from 800 nm to 1650 nm. With high reliability, PD-1190 series are the best choice for power monitor application.

ELECTRICAL AND OPTICAL CHARACTERISTICS (T _C =25°C)						
Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
	Active Area			2		mm
	Detection Range		800		1650	nm
R	Responsivity	V _R =3V, λ=1300 nm	0.85	0.9		A/W
		V _R =3V, λ=1550 nm	0.90	1.0		
I _{dark}	Dark Current	V _R =3V		5	30	nA
C	Capacitance	V _R =3V		400	1000	pF
	Shunt Resistance	V _R =10mV	5	10		MΩ

ABSOLUTE MAXIMUM RATINGS (T _C =25 °C)			
Symbol	Parameter	Ratings	Unit
P _o	Input Optical Power	10	mW
V _{RD}	Reverse Voltage	5	V
I _{FD}	Forward Current	10	mA
T _{opr}	Operating Temperature	-40~+85	°C
T _{stg}	Storage Temperature	-40~+85	°C

MECHANICAL DIMENSION (mm) and PIN ASSIGNMENT



Note: 1. Specifications subject to change without notice.

ORDER INFORMATION

Part No.: P D - 1 1 9 0