



## Holder / No. 562 PC Mount, for TR5®/TE5® Fuses



Holes in PCB



### Specifications

- Packaging**  
100                      bulk (1000 pcs.)
- Mounting**  
PC Board, 5.08mm pin spacing
- Materials**  
Holder:                Black Thermoplastic, UL94 V-0  
                             Nylon 46  
Terminals:            Copper alloy; solderable  
                             tinned
- Electrical Data (23°C)**  
Rated Voltage:        250V  
Max. Current/Power: 6.3A/1.6W
- Minimum Cross Section**  
Conducting path - 0.1mm<sup>2</sup>
- Unit Weight**  
0.12g




Order Information


Qty.	Order-Number	Series	Packaging
		562	0000
			100

Specifications are subject to change without notice

## Holder / No. 564 Surface Mount, for TR5®/TE5® Fuses



recommended Pad Layout (mm)



- Packaging**  
100                      Tape/Reel (1500 pcs.)  
                             Carrier tape width 16 mm  
                             Reel diameter 33 cm
- Order Number**  
Holder                 No. 564 0000 100
- Mounting**  
PC Board, 5.08mm pad spacing
- Materials**  
Holder:                Black Thermoplastic, UL94 V-0  
                             Nylon 46  
Terminals:            Copper alloy; solderable  
                             tinned
- Electrical Data (23°C)**  
Rated Voltage:        250V  
Max. Current/Power: 6.3A/1.6W
- Minimum Cross Section**  
Conducting path - 0.1mm<sup>2</sup>
- Unit Weight**  
0.44g



Order Information

Qty.	Order-Number	Series	Packaging
		564	0000
			100

Specifications are subject to change without notice

Note: 1.00 means the number one with two decimal places. 1,000 means the number one thousand.