

PULSEJACK™

1X1 Tab-DOWN RJ45

Description:

10/100 Base-TX RJ45 1X1 Tab-DOWN with LEDs 8-pin (J0 series) integrated magnetics connector (ICM), designed to support applications, such as SOHO (ADSL modems), LAN-on-Motherboard (LOM), Hub and Switches.



Features and Benefits:

- 1X1 Tab-DOWN RJ45 with internal magnetics
- Available with or without LEDs
- Suitable for CAT 5 & 6 Fast Ethernet Cable or better UTP
- Internal magnetics are 100% electrically tested for HI-POT and functionality

Electrical Performance Summary:

- Internal magnetics options available
- Meets or exceeds IEEE 802.3 standard for 100Base-T
- 350 μ H minimum OCL with 8 mA bias current
- High performance for maximum EMI suppression
- Minimum 1500 Vrms isolation per IEEE 802.3 requirement



Electrical Specifications @ 25°C — Operating Temperature 0°C to +70°C

Part Number	Turns ^{1,2} Ratios		LEDs ³ L/R	Insertion Loss (dB TYP) 1-65 MHz	Return Loss (dB TYP) 100 Ω ±15 Ω				Crosstalk (dB TYP)			Common Mode Rejection (dB TYP)		Hipot (Vrms)
	TX	RX			L/R	1-10 MHz	10-30 MHz	30-60 MHz	60-80 MHz	1-30 MHz	30-60 MHz	60-100 MHz	1-50 MHz	
J0006D01B	1CT:1	1CT:1	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0006D21	1CT:1	1CT:1	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0006D21B	1CT:1	1CT:1	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0011D01 ⁶	1CT:1CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0011D01B ⁶	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0011D21	1CT:1CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0011D21B	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0011D21E	1CT:1CT	1CT:1CT	G/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0018D21	1CT:1.414CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0018D21E	1CT:1.414CT	1CT:1CT	G/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0024D21	1CT:2	1CT:1	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0024D21B	1CT:2	1CT:1	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D01 ⁶	1CT:1CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D01B ⁶	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D01E ⁶	1CT:1CT	1CT:1CT	G/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D01F ^{4,6}	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D21	1CT:1CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D21B	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D21E	1CT:1CT	1CT:1CT	G/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D21F ⁴	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0026D21G ⁵	1CT:1CT	1CT:1CT	YG/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0033D21	1.25CT:1CT	1CT:1CT	N/A	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0035D21B	1CT:1CT	1CT:1CT	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0048D21M	1CT:1	1CT:1	G/G	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500
J0073D01B ⁶	1CT:2.5CT	1CT:1	G/Y	-1	-20	-16	-12	-10	-40	-35	-30	-30	-20	1500

Notes: 1. Both transmit and receive channels meet IEEE 802.3 specifications.

2. Different electrical and mechanical specifications can be accommodated.

3. LEDs Left/Right: G=green, Y=yellow, N/A=none, YG=Bi-color LED Yellow Green.

4. LEDs with internal resistor.

5. Bi-color Left LED.

6. Part numbers ending "D01" do not have external EMI fingers. See mechanical drawings section for explanation of EMI fingers.

RJ45 Durability Testing Rating

Part Number	Mating Force (MAX)	Unmating Force (MAX)	Durability	Plug to Jack Retention (MIN)
J0 Series	5 lbs./2.268 kgs.	5 lbs./2.268 kgs.	750 Insertions	20 lbs./9.072 kgs.



RJ45 Material Specification

Part Number	Shield		Contact			Housing	
	Material	Finish	Material	Plating Area	Solder Area	Material	Specification
J0 Series	Cartridge Brass	10-20m inches Nickel over 10-20m inches Nickel	Phosphor Bronze	Nickel underplating and selective gold plating 30 μ inches	120 μ inches Sn90/Pb10 over 50 μ inches nickel	Thermoplastic	UL 94 V-0

Notes: 1. All connector part numbers starting with the series prefix J0 comply to the above limits. 2. Connector dimensions comply with FCC dimension requirements.


US 619 674 8100 • UK 44 1483 401 700 • France 33 3 84 35 04 04 • Singapore 65 6287 8998 • Taiwan 886 2 2698 0228 • Hong Kong 852 2788 6588 • <http://www.pulseeng.com>

J0 Series Mechanicals




J0 Series Electrical Schematics


J0006



J0011




J0012




J0 Series Electrical Schematics (continued)


J0018




J0024




J0026




J0033




J0035



J0048




J0073




LED Configuration


LED = "B & E" Specification
(LEDs without internal resistors)




LED = "M" Specification
(LEDs without internal resistors)



LED = "F" Specification
(LEDs with internal resistors)



LED = "G" Specification
(Bi-color LED option with internal resistors)



Standard LED	Wavelength	Forward* V(MAX)	(TYP)
Yellow	585 nm	2.5 V	2.1 V
Green	565 nm	2.5 V	2.2 V

* Using an internal resistor within the LED increases the voltage rating of the diode from 2.5 V to 5.0 V (assumes bias current = 20 mA).

Application Notes

Advantages of the PulseJack Modules

Increased Reliability

Pulse developed a patented method for ensuring the quality, consistency, and connection integrity of encapsulated coils and other three-dimensional electronic components. The InterLock Base consists of an internal plastic carrier that holds the coil firmly in place and provides precisely engineered "lead-channels" to lock together the lead wires and the leadframe pins. All of the InterLock Base interconnections are then simultaneously dip soldered, providing for both efficiency and uniformity for best common mode rejection and crosstalk.

Higher Manufacturing Yields

Because of this Pulse patented higher reliability method, there is less of a chance of opens and shorts, thus providing higher yields.

Consistent Electrical and Magnetic Performance

- With internal magnetics specifically oriented on all parts, there are more consistent readings on all functional tests. This is optimized for best crosstalk, common mode rejection and return loss.
- With the selection of common mode material and winding techniques, common mode noise rejection maintains integrity at higher frequencies.
- Multiple tabs around shield-to-ground, shield-to-chassis, and shunt noise to ground improves EMI suppression.

For More Information :

UNITED STATES (Worldwide)	UNITED KINGDOM (Northern Europe)	FRANCE (Southern Europe)	SINGAPORE (Southern Asia)	TAIWAN, R.O.C. (Northern Asia)	HONG KONG (China/Hong Kong)	DISTRIBUTOR
12220 World Trade Drive San Diego, CA 92128 U.S.A. http://www.pulseeng.com TEL: 858 674 8100 FAX: 858 674 8262	1 & 2 Huxley Road The Surrey Research Park Guildford, Surrey GU2 5RE United Kingdom TEL: 44 1483 401700 FAX: 44 1483 401701	Zone Industrielle F-39270 Orgelet France TEL: 33 3 84 35 04 04 FAX: 33 3 84 25 46 41	150 Kampong Ampat #07-01/02 KA Centre Singapore 368324 TEL: 65 6287 8998 FAX: 65 6280 0080	3F-4, No. 81, Sec. 1 HsinTai Wu Road Hsi-Chih, Taipei Hsien Taiwan, R.O.C. Tel: 886 2 2698 0228 FAX: 886 2 2698 0948	19/F, China United Plaza 1008 Tai Nan West Street Cheung Sha Wan, Kowloon Hong Kong, China TEL: 852 2788 6588 FAX: 852 2776 1055	

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.